

Trenco
818 Soundside Rd
Edenton, NC 27932

Re: J0620-2664
Lot 2 Properties of BC

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Comtech, Inc - Fayetteville.

Pages or sheets covered by this seal: E14497252 thru E14497276

My license renewal date for the state of North Carolina is December 31, 2020.

North Carolina COA: C-0844



June 10, 2020

Gilbert, Eric

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497252
J0620-2664	A1-GE	GABLE	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:26:52 2020 Page 1
ID:2GNsYO62BI49KgBFP3SImayOXVO-I4RGsmxybQBO7LqEkCT1gxcgppbziHvSqCF9wz7fW1




Plate Offsets (X,Y)--	[6:0-5-4,0-3-0], [24:0-5-0,0-3-0], [30:0-9-3,0-2-12]
-----------------------	--

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.35	Vert(LL) -0.09	34-35	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.38	Vert(CT) -0.17	34-35	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.40	Horz(CT) 0.06	27	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.07	35-37	>999	240	Weight: 425 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 4-7-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 6-11, 7-30.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 31-32,30-31.
WEBS 2x4 SP No.2	WEBS 1 Row at midpt 4-35, 6-34
OTHERS 2x4 SP No.2	JOINTS 1 Brace at Jt(s): 17, 24, 9, 10, 12, 21

REACTIONS. All bearings 0-3-8 except (jt=length) 29=6-3-8, 27=6-3-8, 30=6-3-8.
 (lb) - Max Horz 2=340(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) except 2=304(LC 12), 30=357(LC 22), 31=248(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 29, 30 except 2=1645(LC 1), 27=261(LC 1), 31=1849(LC 1), 31=1849(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2891/739, 3-4=-2528/697, 4-6=-1873/613, 6-7=-1389/578, 7-8=-329/212, 8-11=-322/211, 11-13=-332/200, 13-15=-329/164, 15-18=-300/77, 18-22=-293/0, 22-23=-340/0, 23-25=-299/0, 25-26=-345/25, 26-27=-311/33, 7-9=-1364/452, 9-10=-1362/449, 10-12=-1358/438, 12-16=-1380/458, 16-17=-1458/530, 17-19=-1227/440, 19-21=-1300/508, 21-24=-1326/530, 24-30=0/396
 BOT CHORD 2-38=-588/2477, 37-38=-593/2478, 35-37=-440/2082, 34-35=-264/1438, 32-34=-130/1298
 WEBS 3-37=-416/174, 4-37=0/423, 4-35=-855/401, 17-32=-346/201, 24-32=-303/1430, 24-31=-1704/535, 6-35=-96/710, 6-34=-284/156, 7-34=-13/408, 23-24=-281/184

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 304 lb uplift at joint 2, 357 lb uplift at joint 30 and 248 lb uplift at joint 31.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.




June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497253
J0620-2664	A2	PIGGYBACK BASE	6	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:26:53 2020 Page 1

ID:2GNsYO62BI49KgBFP3SImayOXVO-7G?f36ybjvY20Hv0oSkiZtU1lCAti7U2hUxohNz7fW0



Scale = 1:72.5




Plate Offsets (X,Y)-- [2:0-5-4,0-2-12], [4:0-5-2,Edge]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.50	Vert(LL)	-0.14 13-15	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.31	Vert(CT)	-0.22 13-15	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.55	Horz(CT)	0.01 10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL)	0.06 13	>999	240		
							Weight: 312 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 2-4.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except* 1-16: 2x6 SP No.1	WEBS 1 Row at midpt 2-15, 3-13

REACTIONS. (size) 16=0-3-8, 10=0-3-8
 Max Horz 16=-261(LC 8)
 Max Uplift 16=-29(LC 12), 10=-86(LC 13)
 Max Grav 16=1257(LC 2), 10=1870(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1092/299, 2-3=-897/353, 3-4=-897/353, 4-5=-1043/338, 5-7=-827/148,
 7-8=-354/523, 1-16=-1193/323
 BOT CHORD 15-16=-203/277, 13-15=-91/882, 11-13=0/603, 10-11=-347/370, 8-10=-347/370
 WEBS 3-13=-261/179, 5-13=-127/446, 1-15=-90/895, 5-11=-557/271, 7-11=-228/1125,
 7-10=-1763/582

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-12 to 4-7-9, Interior(1) 4-7-9 to 8-11-13, Exterior(2) 8-11-13 to 15-2-7, Interior(1) 15-2-7 to 21-10-6, Exterior(2) 21-10-6 to 28-1-1, Interior(1) 28-1-1 to 38-8-7 zone; cantilever right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 29 lb uplift at joint 16 and 86 lb uplift at joint 10.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.




Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497254
J0620-2664	A3	PIGGYBACK BASE	3	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:26:54 2020 Page 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-bSZ1HSzDUDgveRUDL9Fxf651yvcWVRbgCv8hMDpz7fW?

Job Reference (optional)



Scale = 1:72.5




Plate Offsets (X,Y)-- [2:0-5-4,0-2-12], [4:0-4-0,0-0-10]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.36	Vert(LL) -0.10	13-15	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.29	Vert(CT) -0.14	13-15	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.49	Horz(CT) 0.01	8	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.03	13-15	>999	240		
							Weight: 312 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 2-4.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except* 1-16: 2x6 SP No.1	WEBS 1 Row at midpt 2-15, 2-13, 3-13, 5-11

REACTIONS. (size) 16=0-3-8, 11=0-3-8, 8=0-3-0
 Max Horz 16=-261(LC 8)
 Max Uplift 16=-25(LC 12), 11=-137(LC 8), 8=-96(LC 25)
 Max Grav 16=973(LC 1), 11=2001(LC 2), 8=301(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-811/243, 2-3=-479/265, 3-4=-479/265, 4-5=-596/256, 5-7=-117/554, 7-8=-168/409,
 1-16=-905/266
 BOT CHORD 15-16=-202/277, 13-15=-83/664, 11-13=-462/330, 10-11=-291/76, 8-10=-291/76
 WEBS 2-13=-258/84, 3-13=-407/208, 5-13=-204/1142, 5-11=-1420/439, 1-15=-36/623,
 7-11=-475/423

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-12 to 4-7-9, Interior(1) 4-7-9 to 8-11-13, Exterior(2) 8-11-13 to 15-2-7, Interior(1) 15-2-7 to 21-10-6, Exterior(2) 21-10-6 to 28-1-1, Interior(1) 28-1-1 to 38-8-7 zone; porch right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 25 lb uplift at joint 16, 137 lb uplift at joint 11 and 96 lb uplift at joint 8.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497255
J0620-2664	B1-GE	PIGGYBACK BASE SUPPO	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:26:55 2020 Page 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-4e6PUo_sFWoIFb3PvtmAelZCW0vmA8dL8oQvIFz7FW_




Plate Offsets (X,Y)-- [12:0-4-0,0-2-13], [18:0-4-0,0-2-13]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.05	Vert(LL) 0.00	27	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.03	Vert(CT) 0.00	27	n/r	120		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.13	Horz(CT) 0.01	27	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S						
							Weight: 410 lb	FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except 2'-0" oc purlins (6'-0" max.): 12-18.
 Rigid ceiling directly applied or 10'-0" oc bracing.
 BOT CHORD T-Brace: 2x4 SPF No.2 - 17-37, 16-38, 15-39, 14-40, 13-41, 11-42, 10-44, 19-36, 20-34
 WEBS Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
 Brace must cover 90% of web length.

REACTIONS. All bearings 41-11-0.
 (lb) - Max Horz 2=340(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) 27, 38, 39, 40, 41, 42, 44, 45, 46, 47, 48, 49, 36, 33, 32, 31, 30, 2 except 34=101(LC 13), 29=134(LC 13)
 Max Grav All reactions 250 lb or less at joint(s) 27, 37, 38, 39, 40, 41, 42, 44, 45, 46, 47, 48, 36, 34, 33, 32, 31, 30, 29, 2 except 49=270(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-316/243, 3-4=-302/250, 10-11=-244/292, 11-12=-271/312, 12-13=-251/296, 13-14=-251/296, 14-15=-251/296, 15-16=-251/296, 16-17=-251/296, 17-18=-251/297, 18-19=-271/312, 19-20=-244/277, 26-27=-251/175

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) All plates are 2x4 MT20 unless otherwise indicated.
 - 6) Gable requires continuous bottom chord bearing.
 - 7) Gable studs spaced at 2'-0" oc.
 - 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 9) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-6" tall by 2'-0" wide will fit between the bottom chord and any other members.
 - 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 27, 38, 39, 40, 41, 42, 44, 45, 46, 47, 48, 49, 36, 33, 32, 31, 30, 2 except (jt=lb) 34=101, 29=134.
 - 11) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 27.
 - 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 13) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.



Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497257
J0620-2664	C1-GE	PIGGYBACK BASE SUPPO	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:26:58 2020 Page 1
ID:2GNsYO62BI49KgBFP3SmayOXVO-UDoX7p0kYRBK62o_a?JtGxBjnDxmNUknqfZLaz7fVx




Plate Offsets (X,Y)-- [11:0-3-0,0-3-8], [23:0-4-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.05	Vert(LL)	0.00	15	n/r	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.01	Vert(CT)	0.00	15	n/r		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.17	Horz(CT)	-0.00	18	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S					Weight: 264 lb	FT = 20%


LUMBER-
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x6 SP No.1
OTHERS 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 11-16.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS T-Brace: 2x4 SPF No.2 - 15-18, 14-19, 13-20, 12-21, 11-22, 10-23
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
Brace must cover 90% of web length.

REACTIONS. All bearings 23-11-8.
(lb) - Max Horz 2=523(LC 12)
Max Uplift All uplift 100 lb or less at joint(s) 18, 2, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28 except 29=161(LC 12)
Max Grav All reactions 250 lb or less at joint(s) 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29 except 2=344(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-617/495, 3-4=-498/395, 4-5=-421/335, 5-6=-346/277, 6-8=-271/218

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Gable studs spaced at 2-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18, 2, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28 except (jt=lb) 29=161.
 - 10) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 11) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.



June 10, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497258
J0620-2664	C2	Piggyback Base	4	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:26:58 2020 Page 1

ID:2GNsYO62BI49KgBFP3SmayOXVO-UDoX7p0kYRBK62o_a?JtGxBf1Du?NLynqIfZLaz7fVx



Scale = 1:67.0

Plate Offsets (X,Y)-- [13:0-3-12,0-2-0]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.29	Vert(LL)	-0.10 10-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.25	Vert(CT)	-0.20 10-12	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.76	Horz(CT)	0.01 9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL)	0.08 10-12	>999	240		
							Weight: 234 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-3-14 oc purlins, except end verticals, and 2-0-0 oc purlins (5-11-2 max.): 5-7.
BOT CHORD 2x6 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except*	WEBS 1 Row at midpt 9-14, 3-10
6-9: 2x6 SP No.1	JOINTS 1 Brace at Jt(s): 13, 14

REACTIONS. (size) 9=0-3-8, 2=0-3-8
 Max Horz 2=364(LC 12)
 Max Uplift 9=116(LC 9), 2=15(LC 12)
 Max Grav 9=1163(LC 2), 2=1062(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1444/106, 3-5=-2054/499, 5-6=-1666/510, 9-14=-866/324, 6-14=-866/324
 BOT CHORD 2-12=-420/1199, 10-12=-422/1192
 WEBS 3-12=0/360, 3-10=-1308/474, 10-13=-87/938, 5-13=-28/704, 6-13=-539/1834,
 3-13=-513/1628

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-7 to 3-7-6, Interior(1) 3-7-6 to 15-11-13, Exterior(2) 15-11-13 to 22-2-7, Interior(1) 22-2-7 to 23-11-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Provide adequate drainage to prevent water ponding.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2 except (jt=lb) 9=116.
 - 6) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.




June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497259
J0620-2664	C3	PIGGYBACK BASE	4	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:26:59 2020 Page 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-yQMwK91MJJBkCNA8iq6p8kqmd8p6lx3PO6t0z7fVw



Scale = 1:68.7

Plate Offsets (X,Y)-- [2:0-5-8,Edge], [10:0-3-8,0-2-8], [11:Edge,0-2-0], [11:0-3-4,0-2-0], [13:Edge,0-2-0], [14:0-2-8,0-2-4]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.29	Vert(LL) -0.11	10-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.60	Vert(CT) -0.22	10-12	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.87	Horz(CT) 0.05	9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.11	10-12	>999	240	Weight: 252 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-3-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-10-6 max.): 5-7.
BOT CHORD 2x10 SP No.1 *Except* 2-10: 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except* 6-9: 2x6 SP No.1	WEBS 1 Row at midpt 9-15, 3-10
	JOINTS 1 Brace at Jt(s): 14, 15

REACTIONS. (size) 9=0-3-8, 2=0-3-8
 Max Horz 2=363(LC 12)
 Max Uplift 9=114(LC 9), 2=18(LC 12)
 Max Grav 9=1123(LC 2), 2=996(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1559/210, 3-5=-2108/586, 5-6=-1717/586, 9-15=-829/332, 6-15=-829/332
 BOT CHORD 2-12=-509/1355, 10-12=-510/1339
 WEBS 3-10=-1419/561, 10-14=-108/891, 5-14=-78/739, 3-12=-30/491, 6-14=-611/1863,
 3-14=-581/1586

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-7 to 3-7-6, Interior(1) 3-7-6 to 15-11-13, Exterior(2) 15-11-13 to 22-2-7, Interior(1) 22-2-7 to 23-11-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Provide adequate drainage to prevent water ponding.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2 except (jt=lb) 9=114.
 - 6) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



June 10, 2020



Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497260
J0620-2664	C4	PIGGYBACK BASE	2	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:00 2020 Page 1

ID:2GNsYO62BI49KgBFP3SImayOXVO-QcwIXV1_33R2MMYMiQMLLMGs71S?qBw4l38gQTz7fVv

Job Reference (optional)



Scale = 1:168.8

Plate Offsets (X,Y)-- [2:0-5-8,Edge], [5:0-3-0,0-3-4], [10:0-3-8,0-2-8], [11:0-3-1,0-1-11], [11:0-3-0,0-2-0], [13:0-2-12,0-1-11], [14:0-3-12,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.89	Vert(LL) -0.20	10-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.73	Vert(CT) -0.42	10-12	>664	240	M18SHS	244/190
BCLL 0.0 *	Rep Stress Incr NO	WB 0.96	Horz(CT) 0.09	9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.20	10-12	>999	240		
							Weight: 252 lb	FT = 20%

LUMBER-

TOP CHORD 2x6 SP No.1
 BOT CHORD 2x10 SP No.1 *Except*
 2-10: 2x6 SP 2400F 2.0E
 WEBS 2x4 SP No.2 *Except*
 6-9: 2x6 SP No.1

BRACING-

TOP CHORD 2-0-0 oc purlins (2-11-4 max.), except end verticals
 (Switched from sheeted: Spacing > 2-8-0).
 Rigid ceiling directly applied or 9-9-0 oc bracing.
 BOT CHORD
 WEBS 1 Row at midpt 9-15, 6-14, 3-14
 2 Rows at 1/3 pts 3-10
 JOINTS 1 Brace at Jt(s): 5, 14, 15

REACTIONS.


(size) 9=0-3-8, 2=0-3-8
 Max Horz 2=726(LC 12)
 Max Uplift 9=229(LC 9), 2=36(LC 12)
 Max Grav 9=2247(LC 2), 2=1991(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-3124/422, 3-5=-4185/1161, 5-6=-3408/1161, 9-15=-1646/661, 6-15=-1646/661
 BOT CHORD 2-12=-1019/2711, 10-12=-1021/2680
 WEBS 3-10=-2842/1123, 10-14=-209/1762, 5-14=-150/1460, 3-12=-68/1003, 6-14=-1212/3697,
 3-14=-1152/3148

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-7 to 3-7-6, Interior(1) 3-7-6 to 15-11-13, Exterior(2) 15-11-13 to 22-2-7, Interior(1) 22-2-7 to 23-11-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Provide adequate drainage to prevent water ponding.
- 3) All plates are MT20 plates unless otherwise indicated.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2 except (jt=lb) 9=229.
- 7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



June 10, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497261
J0620-2664	C5	PIGGYBACK BASE	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:01 2020 Page 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-uouUglr2cqMZvzWXZG7tauZpAERwiZhHEWjtDyvz7fVU




Plate Offsets (X,Y)-- [12:0-3-12,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.29	Vert(LL) -0.10	9-11	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.25	Vert(CT) -0.20	9-11	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.76	Horz(CT) 0.01	8	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.08	9-11	>999	240	Weight: 232 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-3-15 oc purlins, except end verticals, and 2-0-0 oc purlins (5-11-1 max.): 4-6.
BOT CHORD 2x6 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except*	WEBS 1 Row at midpt 8-13, 2-9
5-8: 2x6 SP No.1	JOINTS 1 Brace at Jt(s): 12, 13

REACTIONS. (size) 8=0-3-8, 1=0-3-8
 Max Horz 1=358(LC 12)
 Max Uplift 8=116(LC 9), 1=2(LC 12)
 Max Grav 8=1164(LC 2), 1=1009(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1425/112, 2-4=-2057/501, 4-5=-1668/511, 8-13=-867/324, 5-13=-867/324
 BOT CHORD 1-11=-421/1203, 9-11=-424/1197
 WEBS 2-11=0/362, 2-9=-1313/475, 9-12=-89/941, 4-12=-30/707, 5-12=-540/1837,
 2-12=-514/1630

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-1-12 to 4-6-9, Interior(1) 4-6-9 to 15-11-13, Exterior(2) 15-11-13 to 22-2-7, Interior(1) 22-2-7 to 23-11-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Provide adequate drainage to prevent water ponding.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=116.
 - 6) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.




June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497262
J0620-2664	C6	Monopitch	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:01 2020 Page 1

ID:2GNsYO62B149KgBFP3SlmayOXVO-uoUglr2cqMZvzWXZG7tauZpBeRuHZLEWjtDyvyz7fVU



Scale = 1:59.2

Plate Offsets (X,Y)-- [2:0-5-8,Edge], [7:Edge,0-2-0], [9:Edge,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.20	Vert(LL)	-0.02	2-8	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.34	Vert(CT)	-0.06	2-8	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.88	Horz(CT)	0.02	6	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.03	2-8	>999	Weight: 129 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x10 SP No.1 *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except*	WEBS 1 Row at midpt
5-6: 2x6 SP No.1	5-6

REACTIONS. (size) 6=0-3-8, 2=0-3-8
 Max Horz 2=319(LC 12)
 Max Uplift 6=176(LC 12)
 Max Grav 6=606(LC 19), 2=594(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-735/0
 BOT CHORD 2-8=-241/622, 6-8=-233/622
 WEBS 3-8=0/384, 3-6=-779/288

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-7 to 3-7-6, Interior(1) 3-7-6 to 14-0-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 4) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 6=176.




June 10,2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497263
J0620-2664	D1-GE	GABLE	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:02 2020 Page 1

ID:2GNsYO62B149KgBFP3SmayOXVO-N?12yB3Fbghmbg5lprOpRnMGTr4slGpNINdnULz7Vt
 0-11-0 4-8-12 9-5-5 11-11-8 14-5-11 19-2-4 23-11-0 24-10-0
 0-11-0 4-8-12 4-8-9 2-6-3 2-6-3 7 4-8-9 4-8-12 0-11-0



Scale = 1:57.3

Plate Offsets (X,Y)-- [2:0-2-0,0-1-12], [5:0-4-2,0-2-0], [7:0-4-2,0-2-0], [10:0-2-0,0-1-12], [13:0-5-0,0-7-8], [15:0-5-0,0-7-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.58	Vert(LL) -0.35	13-15	>814	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.96	Vert(CT) -0.55	13-15	>508	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.23	Horz(CT) 0.01	12	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.10	13-15	>999	240		
							Weight: 265 lb	FT = 20%

LUMBER-

TOP CHORD 2x6 SP 2400F 2.0E *Except*
 5-7: 2x6 SP No.1
 BOT CHORD 2x10 SP No.1
 WEBS 2x6 SP No.1 *Except*
 6-17,2-15,10-13: 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-7.
 BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 17

REACTIONS.


(size) 16=0-3-8, 12=0-3-8
 Max Horz 16=-376(LC 10)
 Max Grav 16=1656(LC 2), 12=1656(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1899/0, 3-4=-1135/199, 8-9=-1135/199, 9-10=-1899/0, 5-6=-26/441, 6-7=-26/441,
 2-16=-1879/17, 10-12=-1880/17
 BOT CHORD 15-16=-341/581, 13-15=0/1187, 12-13=-91/311
 WEBS 3-15=0/948, 9-13=0/948, 4-17=-1455/160, 8-17=-1455/160, 2-15=-27/989,
 10-13=-35/995

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 3-4, 8-9, 4-17, 8-17; Wall dead load (5.0psf) on member(s).3-15, 9-13
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 13-15
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Attic room checked for L/360 deflection.



June 10,2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road
 Edenton, NC 27932

Job J0620-2664	Truss D2	Truss Type PIGGYBACK ATTIC	Qty 10	Ply 1	Lot 2 Properties of BC E14497264
-------------------	-------------	-------------------------------	-----------	----------	-------------------------------------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:04 2020 Page 1



Scale = 1:57.8

Plate Offsets (X,Y)-- [1:0-1-0,0-2-0], [4:0-4-2,0-2-0], [6:0-4-2,0-2-0], [9:0-1-0,0-2-0], [11:0-5-0,0-7-4], [13:0-4-0,0-5-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.98	Vert(LL)	-0.35 11-13	>797	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.60	Vert(CT)	-0.57 11-13	>491	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.24	Horz(CT)	0.01 10	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.08 11-13	>999	240	Weight: 236 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-6.
BOT CHORD 2x10 SP 2400F 2.0E *Except* 10-12: 2x10 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x6 SP No.1 *Except* 5-15,1-13,9-11: 2x4 SP No.2	JOINTS 1 Brace at Jt(s): 15

REACTIONS. (size) 14=0-3-8, 10=0-3-8
 Max Horz 14=-265(LC 10)
 Max Grav 14=1604(LC 2), 10=1604(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1855/0, 2-3=-1119/176, 7-8=-1120/178, 8-9=-1848/0, 4-5=-20/444, 5-6=-20/444,
 1-14=-1804/0, 9-10=-1802/0
 BOT CHORD 13-14=-236/429, 11-13=0/1136
 WEBS 2-13=0/880, 8-11=0/876, 3-15=-1431/119, 7-15=-1431/119, 1-13=0/1000, 9-11=0/1014

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-12 to 4-8-12, Interior(1) 4-8-12 to 9-6-7, Exterior(2) 9-6-7 to 20-7-4, Interior(1) 20-7-4 to 23-8-4 zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Ceiling dead load (10.0 psf) on member(s). 2-3, 7-8, 3-15, 7-15; Wall dead load (5.0psf) on member(s).2-13, 8-11
 - 7) Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 11-13
 - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 9) Attic room checked for L/360 deflection.



June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497265
J0620-2664	E1-GE	GABLE	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:05 2020 Page 1

ID:2GNsYO62BI49KgBFP3SlmayOXVO-najBbC57ub3LS7qKVzxW2P_sG2FwVaUpRLrR5gz7fVq



Scale = 1:42.3




Plate Offsets (X,Y)-- [2:Edge,0-2-12], [12:Edge,0-2-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.23	Vert(LL) -0.07	21-22	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.36	Vert(CT) -0.11	21-22	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.42	Horz(CT) 0.01	12	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.10	21-22	>999	240	Weight: 142 lb	FT = 20%


LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 9-8-11 oc bracing.

REACTIONS. (size) 12=0-3-0, 2=0-3-0
 Max Horz 2=200(LC 10)
 Max Uplift 12=-165(LC 13), 2=-165(LC 12)
 Max Grav 12=785(LC 1), 2=785(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-892/777, 3-4=-806/744, 4-5=-762/759, 5-6=-731/784, 6-7=-724/824, 7-8=-724/824,
 8-9=-731/784, 9-10=-762/759, 10-11=-806/744, 11-12=-892/777
 BOT CHORD 2-23=-488/615, 22-23=-488/615, 21-22=-488/615, 20-21=-488/615, 19-20=-488/615,
 18-19=-488/615, 16-18=-488/615, 15-16=-488/615, 14-15=-488/615, 12-14=-488/615
 WEBS 7-19=-625/493

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; porch left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable studs spaced at 2-0-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 12=165, 2=165.



June 10, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497266
J0620-2664	E2	COMMON	1	1		

Comtech, Inc., Fayetteville, NC - 28314,


8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:05 2020 Page 1

ID:2GNsYO62B149KgBFP3SlmayOXVO-najBbC57ub3LS7qKVzxW2P_pO2ERVbJpRLrR5gz7fVq

0-11-0 9-3-0 18-6-0 19-5-0
 0-11-0 9-3-0 9-3-0 0-11-0

5x8 =

Scale = 1:43.5



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.41	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.39	Vert(LL) -0.05 2-7 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.37	Vert(CT) -0.10 2-7 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.01 4 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.10 4-7 >999 240	Weight: 110 lb	FT = 20%

LUMBER-

TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 4=0-3-0, 2=0-3-0
 Max Horz 2=-160(LC 10)
 Max Uplift 4=-115(LC 8), 2=-115(LC 9)
 Max Grav 4=849(LC 2), 2=849(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1032/758, 3-4=-1032/758
 BOT CHORD 2-7=-457/742, 4-7=-457/742
 WEBS 3-7=-547/632

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-7 to 3-7-6, Interior(1) 3-7-6 to 9-3-0, Exterior(2) 9-3-0 to 13-7-13, Interior(1) 13-7-13 to 19-3-7 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 4=115, 2=115.



June 10, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497267
J0620-2664	E3	COMMON	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:06 2020 Page 1
 ID:2GNsYO62BI49KgBFP3SlmayOXVO-FmHZoY6lfvBC4HPW2hSldW_ISakE2Zzg?b_d6z7fVp



5x8 =

Scale = 1:42.1




Plate Offsets (X,Y)-- [4:Edge,0-2-8]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.44	Vert(LL)	-0.05	2-6	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.39	Vert(CT)	-0.10	2-6	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.37	Horz(CT)	0.01	4	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.10	2-6	>999	Weight: 108 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

REACTIONS. (size) 4=0-3-0, 2=0-3-0
 Max Horz 2=159(LC 11)
 Max Uplift 4=111(LC 8), 2=115(LC 9)
 Max Grav 4=803(LC 2), 2=850(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1034/758, 3-4=-1031/761
 BOT CHORD 2-6=-470/744, 4-6=-470/744
 WEBS 3-6=-546/633

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-9-7 to 3-7-6, Interior(1) 3-7-6 to 9-3-0, Exterior(2) 9-3-0 to 13-7-13, Interior(1) 13-7-13 to 18-4-8 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 4=111, 2=115.



June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497268
J0620-2664	E4	COMMON	3	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:07 2020 Page 1
 ID:2GNsYO62B149KgBFP3SlmayOXVO-jyrx?u7NQCJ3hR_icO__7q39Vsx1zVr6vfkYAZz7fVo




Plate Offsets (X,Y)-- [1:Edge,0-2-8], [3:Edge,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.44	Vert(LL) -0.05	1-5	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.38	Vert(CT) -0.10	1-5	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.37	Horz(CT) 0.01	3	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL) 0.10	1-5	>999	240	Weight: 105 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

REACTIONS. (size) 1=0-3-0, 3=0-3-0
 Max Horz 1=155(LC 9)
 Max Uplift 1=111(LC 9), 3=111(LC 8)
 Max Grav 1=804(LC 2), 3=804(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1033/761, 2-3=-1033/761
 BOT CHORD 1-5=-471/745, 3-5=-471/745
 WEBS 2-5=-544/633

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-1-8 to 4-6-5, Interior(1) 4-6-5 to 9-3-0, Exterior(2) 9-3-0 to 13-7-13, Interior(1) 13-7-13 to 18-4-8 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=111, 3=111.




June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497269
J0620-2664	PB1	GABLE	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:08 2020 Page 1
 ID:2GNsYO62BI49KgBFP3SlmayOXVO-B9PJDE8?BWRvJbZvA5VDg1cQWFLxi1SF7J45i?z7fVn



Scale = 1:26.7

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.03	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 8 n/a n/a		
	Code IRC2015/TPI2014			Weight: 55 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 12-11-7.
 (lb) - Max Horz 1=124(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 9, 2, 8, 13, 14, 11, 10
 Max Grav All reactions 250 lb or less at joint(s) 1, 9, 2, 8, 12, 13, 14, 11, 10

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 9, 2, 8, 13, 14, 11, 10.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



June 10, 2020


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497270
J0620-2664	PB2	PIGGYBACK	9	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:09 2020 Page 1
 ID:2GNsYO62BI49KgBFP3SlmayOXVO-fLziQa8eyqZmxI85kp0SDF8WbfnRTuPMzpeERz7fVm



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.33	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.24	Vert(LL) 0.01 5 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.08	Vert(CT) 0.02 5 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 4 n/a n/a	Weight: 45 lb	FT = 20%
	Code IRC2015/TPI2014				

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 2=11-5-3, 4=11-5-3, 6=11-5-3
 Max Horz 2=99(LC 10)
 Max Uplift 2=35(LC 12), 4=45(LC 13)
 Max Grav 2=257(LC 1), 4=257(LC 1), 6=461(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 3-6=284/113

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-3-2 to 4-7-15, Interior(1) 4-7-15 to 6-5-11, Exterior(2) 6-5-11 to 10-10-8, Interior(1) 10-10-8 to 12-8-5 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



June 10, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497271
J0620-2664	PB3	GABLE	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:10 2020 Page 1
 ID:2GNsYO62BI49KgBFP3SlmayOXVO-8XW4ew9Gj7hdYujHHWXhShm_31OAXyYbdZCmuz7VI
 8-11-7
 4-5-11 4-5-11 4-5-12

Scale = 1:20.4



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.04	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 6 n/a n/a	Weight: 33 lb	FT = 20%
	Code IRC2015/TPI2014				

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

All bearings 8-11-7.
 (lb) - Max Horz 1=84(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 2, 6, 10, 8
 Max Grav All reactions 250 lb or less at joint(s) 1, 7, 2, 6, 9, 10, 8

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 2, 6, 10, 8.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



June 10, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497272
J0620-2664	PB4	PIGGYBACK	6	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:11 2020 Page 1
ID:2GNsYO62BI49KgBFP3SmayOXVO-cj4SrGAuURpUA2IUrE2wlgEvNTMMvO9ipHIIJKz7fV/k



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.19	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.10	Vert(LL) 0.01 5 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.03	Vert(CT) 0.01 5 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 30 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 2=7-5-3, 4=7-5-3, 6=7-5-3
Max Horz 2=67(LC 11)
Max Uplift 2=-34(LC 12), 4=-40(LC 13)
Max Grav 2=193(LC 1), 4=193(LC 1), 6=267(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



June 10, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497273
J0620-2664	PB5	GABLE	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:11 2020 Page 1
ID:2GNsYO62BI49KgBFP3SImayOXVO-cj4SrGAuURpUA2IUrE2wigExcTNeVOCipHIJKz7fVk



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.04	Vert(LL) n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.02	Vert(CT) n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.02	Horz(CT) -0.00	7	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P					Weight: 42 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x6 SP No.1
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

All bearings 7-11-11.
 (lb) - Max Horz 1=171(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 7, 2, 8, 10 except 9=102(LC 12)
 Max Grav All reactions 250 lb or less at joint(s) 1, 7, 2, 8, 9, 10

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 1, 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7, 2, 8, 10 except (jt=lb) 9=102.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



June 10, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497274
J0620-2664	PB6	PIGGYBACK	9	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:12 2020 Page 1
 ID:2GNsYO62BI49KgBFP3SImayOXVO-4weq3cBWFlyLoCsgPxZ9qtm?Utg_erwr2x2lrmz7fVj



Scale = 1:24.4

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.48	Vert(LL) 0.00	1	n/r	120		MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.21	Vert(CT) 0.02	1	n/r	120			
BCLL 0.0 *	Lumber DOL 1.15	WB 0.06	Horz(CT) 0.00		n/a	n/a			
BCDL 10.0	Rep Stress Incr YES	Matrix-P						Weight: 37 lb	FT = 20%
	Code IRC2015/TPI2014								


LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x6 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 5=7-2-10, 2=7-2-10, 6=7-2-10
 Max Horz 2=116(LC 12)
 Max Uplift 5=69(LC 3), 2=-8(LC 12), 6=-8(LC 12)
 Max Grav 5=1(LC 20), 2=248(LC 1), 6=355(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-3-2 to 4-7-15, Interior(1) 4-7-15 to 6-5-11, Exterior(2) 6-5-11 to 7-8-15 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 2, 6.
 - 7) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.




June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC	E14497275
J0620-2664	PB7	PIGGYBACK	2	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:13 2020 Page 1

ID:2GNsYO62BI49KgBFP3SmayOXVO-Y6CCGyC8?24CPMRszf5ON5JCNGzANHq?HbnsNCz7Vi



Scale = 1:24.8

Plate Offsets (X,Y)-- [2:0-6-11,Edge]


LOADING (psf)	SPACING-	4-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.35	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.40	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.08	Horz(CT)	-0.00	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 45 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD 2-0-0 oc purlins (6-0-0 max.), except end verticals
BOT CHORD 2x4 SP No.1	(Switched from sheeted: Spacing > 2-8-0).
WEBS 2x6 SP No.1	Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.2	

REACTIONS. All bearings 7-2-10.
 (lb) - Max Horz 1=229(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) except 1=671(LC 19), 5=114(LC 3), 2=516(LC 12)
 Max Grav All reactions 250 lb or less at joint(s) 5 except 1=463(LC 12), 2=1239(LC 19), 6=611(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=552/586
 WEBS 3-6=344/212

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-15 to 4-9-12, Interior(1) 4-9-12 to 6-5-11, Exterior(2) 6-5-11 to 7-8-15 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 1, 2 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 671 lb uplift at joint 1, 114 lb uplift at joint 5 and 516 lb uplift at joint 2.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.




June 10, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 2 Properties of BC
J0620-2664	PB8	PIGGYBACK	11	1	E14497276

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s May 6 2020 MiTek Industries, Inc. Wed Jun 10 14:27:14 2020 Page 1

ID:2GNsYO62BI49KgBFP3SImayOXVO-0lmbUHCmmMC31W03WWMcdwlsSZgOD6IA8WFXPvfz7fVh



4x4 =

Scale = 1:17.5




Plate Offsets (X,Y)-- [2:0-2-6,0-1-8], [4:0-2-6,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.06	Vert(LL)	0.00	4	n/r	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.03	Vert(CT)	0.00	5	n/r		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.01	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 19 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-6 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 2=3-10-12, 4=3-10-12, 6=3-10-12
 Max Horz 2=-69(LC 10)
 Max Uplift 2=-39(LC 13), 4=-46(LC 13)
 Max Grav 2=118(LC 1), 4=118(LC 1), 6=121(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 39 lb uplift at joint 2 and 46 lb uplift at joint 4.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



June 10,2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road
 Edenton, NC 27932

Symbols

PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- $\frac{1}{16}$ " from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.


* Plate location details available in MITrak 20/20 software or upon request.

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TPI 1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-89: Design Standard for Bracing.
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

Numbering System



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TPI 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITTEK® All Rights Reserved



MITek Engineering Reference Sheet: MI-7473 rev. 10/03/2015



General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TPI 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TPI 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TPI 1 Quality Criteria.