Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit			
PROPERTY LOCATION: 1631 Main Street (SR 1532)			
ISSUED TO: Signature Hones 81ds SUBDIVISION Prop. of BC LLC 2019 LOT # 6			
NEW REPAIR EXPANSION Site Improvements required prior to Construction Authorization Issuance:			
Type of Structure: 3-12edroom GO'XST' SFD			
Proposed Wastewater System Type: 25% reduction 35.			
Projected Daily Flow: 360 GPD			
Number of bedrooms:3 Number of Occupants: max			
Basement I'es INO			
Pump Required: Yes Mo May be required based on final location and elevations of facilities			
Type of Water Supply: Community Public Well Distance from well 100 + feet Permit valid for: Permit valid for:			
Permit conditions: No expiration			
The second of th			
Authorized State Agent:: COCOMM, Date: 02/27/2020 SEE ATTACHED SITE SKETCH			
The issuance of this permit by the Health Department in no way guarantees the issuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of			
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.			
AND			
Constitution Authoritation			
<u>Construction Authorization</u>			
(Required for Building Permit)			
The construction and installation requirements of Rules 1950, 1952, 1954, 1955, 1956, 1957, 1958, and 1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance			
with the attached system layout.			
ISSUED TO: Signature Home Blds PROPERTY LOCATION: 1631 Main Street (Sr. 1532)			
SUBDITISION FIGO. OF DE CEE ACT LOT #			
Facility Type: 361601x5515 New Expansion Repair			
Basement? Yes Sk No Basement Fixtures? Yes No			
Type of Wastewater System** 25% reduction 35km (Initial) Wastewater Flow: 365 GPD			
(See note below, if applicable)			
25% reduction 35 - (Repair)			
Installation Requirements/Conditions Number of trenches			
Septic Tank Size 1000 gallons Exact length of each trench 55 feet Trench Spacing: 7 Feet on Center			
Pump Tank Size gallons			
Butter state of control of contro			
(Trench bottoms shall be level to $\pm 1/4$ " 36" above the trench bottom)			
in all directions)			
Pump Requirements:ft. TDH vsGPMinches below pipe			
Aggregate Depth: inches above pipe			
Conditions: Gravity to D-Box Equival Distribution regioned NA inches total			
WATER LINES (INCLUDING IRRIGATION) MILET DE JOET, EROM ANY RART OF SERTIS SYSTEM OR REDAIR AREA			
WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR REPAIR AREA.			
NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA.			
**If applicable: 1 understand the system type specified is different from the type specified on the application. I accept the specifications of this permit.			
- Apprendix of another type specimes is different from the type specimes on the appreciation. I accept the specime atoms of this period.			
Ourse/Lead Beauty-tails Simple			
Owner/Legal Representative Signature: Date:			
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This			
Construction Authorization is subject to compliance with the provisions of the Laws and Rules for Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH			
- Hard Land Che 11 h			
Authorized State Agent: Call College Date: 62/27/2020			

Harnett County Department of Public Health Site Sketch

	Main Street (SN 1532)		
Issued To: Signature	Home Blds Subdivision Prop. of	BCLL 2019 Lot# 6	
		-11.119	
Authorized State Agent:	ANDRAW CURA	Date: 02/24/2020	
	CLORELL CLORELL		
	100.08		
	15		
	15 -0 -6 -		
	we sell		
	1		
	T.	XICOFT WELL SETBACK	
	m.>		
	50' M.S	[JNITIAL SEPTIC]	
	1	* SOFT WELL SETBACK	
* POWER SHALL BE		[REPAIR SEPTIC]	
		* GRAVITT TO DASEX	
ROUTED PLONE		EQUAL DISTAISUTION	
PROPERTY LINE		neavines	
	PUMP TO	2001/425	
	25% 12000100		
	ream area	X FIVE (5) 55#T	
		LINES W/	
	7	0 25% NEOUCEION	
	2	000	
		14	
	302 500	X SHALLOW TO DEEC	
	(65×52)	INSTALL MAT BE	
	11.6	NEW WITELD	
		[xan 450>]	
	T		
		1	
	1	* OR FOUR (4)	
		10 FT 110 F	
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	FOFT LINES	
	88' /	w/ 25% NEOUGION	
	E		
This drawing is for illustrati	ive purposes only. System installation must mee	et all pertinent laws, rules, and regulations.	
The state of the s			
MAIN STREET (SRI532)			