

Trenco  
818 Soundside Rd  
Edenton, NC 27932

Re: J0420-1863  
Weaver / Sonnenburg Res. / Harnett

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Comtech, Inc - Fayetteville.

Pages or sheets covered by this seal: E14364916 thru E14364928

My license renewal date for the state of North Carolina is December 31, 2020.

North Carolina COA: C-0844



May 4, 2020

---

Gilbert, Eric

**IMPORTANT NOTE:** The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job J0420-1863	Truss F1	Truss Type Floor	Qty 3	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364916
-------------------	-------------	---------------------	----------	----------	------------------------------------	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:46 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-mA\_FZr8Xla37zE0uikfF1xhaX4h6CW4xVZP0bGzJvBR




Plate Offsets (X,Y)--	[4:0-1-8,Edge], [5:0-1-8,Edge], [13:0-1-8,Edge], [14:0-1-8,Edge]
-----------------------	--

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSL</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>	
TCLL 40.0	Plate Grip DOL	1.00	TC 0.75	Vert(LL)	-0.26	19-20	>809	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 1.00	Vert(CT)	-0.35	19-20	>607	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.79	Horz(CT)	0.06	18	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014		Matrix-S							
									Weight: 171 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1 (flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1 (flat)	BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 2x4 SP No.3 (flat)	

**REACTIONS.** (size) 30=Mechanical, 24=0-3-8, 18=0-3-0  
Max Grav 30=794(LC 3), 24=2230(LC 1), 18=859(LC 4)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**TOP CHORD** 2-3=-2252/0, 3-4=-2252/0, 4-5=-2367/0, 5-6=-1680/345, 6-8=-1680/345, 8-9=0/2343, 9-10=0/2343, 10-11=-1865/276, 11-13=-1865/276, 13-14=-2749/0, 14-15=-2562/0, 15-16=-2562/0

**BOT CHORD** 29-30=0/1462, 28-29=0/2367, 27-28=0/2367, 26-27=0/2367, 24-26=-878/413, 22-24=-821/491, 21-22=0/2749, 20-21=0/2749, 19-20=0/2749, 18-19=0/1598

**WEBS** 9-24=-281/0, 2-30=-1604/0, 2-29=0/874, 3-29=-298/0, 8-24=-2190/0, 8-26=0/1548, 6-26=-266/15, 5-26=-1103/0, 4-29=-216/353, 10-24=-2307/0, 10-22=0/1652, 11-22=-261/33, 16-18=-1753/0, 16-19=0/1067, 15-19=-339/0, 14-19=-274/324, 13-22=-1277/0

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.



May 4, 2020

<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information</b> available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.</p>	<p>ENGINEERING BY <b>TRENCO</b> A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
---	---

Job J0420-1863	Truss F1A	Truss Type GABLE	Qty 1	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364917
-------------------	--------------	---------------------	----------	----------	------------------------------------	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:47 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-ENYdnB99WuB\_aOb4FRAUa9EmvT7Nx\_M4kd8Z7izJvBQ




Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge], [13:0-1-8,Edge], [14:0-1-8,Edge], [18:0-1-8,Edge], [19:Edge,0-1-8]


<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.64	Vert(LL)	-0.15	30-31	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.61	Vert(CT)	-0.21	30-31	>962		
BCLL 0.0	Rep Stress Incr	YES	WB 0.72	Horz(CT)	0.04	27	n/a		
BCDL 5.0	Code	IRC2015/TPI2014	Matrix-S						
								Weight: 179 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1 (flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1 (flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3 (flat)	
OTHERS 2x4 SP No.3 (flat)	

**REACTIONS.** All bearings 2-3-0 except (jt=length) 33=Mechanical, 27=0-3-8.  
 (lb) - Max Uplift All uplift 100 lb or less at joint(s) 20 except 19=-753(LC 4)  
 Max Grav All reactions 250 lb or less at joint(s) 20 except 33=796(LC 3), 27=1998(LC 1), 21=1833(LC 4), 21=1750(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 18-19=0/766, 2-3=-2259/0, 3-4=-2259/0, 4-5=-2378/0, 5-6=-1696/145, 6-8=-1696/145, 8-9=0/2109, 9-10=0/2109, 10-11=-1188/447, 11-13=-1188/447, 13-14=-1414/168, 14-15=-1135/36, 15-16=-1135/36, 16-17=0/1334, 17-18=0/1334  
 BOT CHORD 32-33=0/1466, 31-32=0/2378, 30-31=0/2378, 29-30=0/2378, 27-29=-640/432, 25-27=-898/287, 24-25=-168/1414, 23-24=-168/1414, 22-23=-168/1414  
 WEBS 9-27=-278/0, 17-21=-263/0, 2-33=-1608/0, 2-32=0/877, 8-27=-2153/0, 8-29=0/1513, 6-29=-250/0, 5-29=-925/0, 10-27=-1805/0, 10-25=0/1159, 16-21=-1694/0, 16-22=0/1029, 13-25=-479/0, 14-22=-371/175, 21-38=-1515/0, 18-38=-1537/0

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Gable studs spaced at 1-4-0 oc.
  - 5) Refer to girder(s) for truss to truss connections.
  - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 20 except (jt=lb) 19=753.
  - 7) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 8) CAUTION, Do not erect truss backwards.



May 4, 2020

Job J0420-1863	Truss F2	Truss Type Floor	Qty 4	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364918
-------------------	-------------	---------------------	----------	----------	------------------------------------	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:48 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-iZ60\_XAnHBjRCYAGp8hj7MnxbtQLgRbEztu7g9zJvBP




Plate Offsets (X,Y)--	[4:0-1-8,Edge], [5:0-1-8,Edge], [13:0-1-8,Edge], [14:0-1-8,Edge]
-----------------------	--


<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.65	Vert(LL) -0.16 28-29 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.82	Vert(CT) -0.22 28-29 >916 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.72	Horz(CT) 0.05 18 n/a n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S			
				Weight: 163 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1 (flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1 (flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 24-26,22-24.
WEBS 2x4 SP No.3 (flat)	

**REACTIONS.** (size) 30=Mechanical, 24=0-3-8, 18=0-3-0  
Max Grav 30=795(LC 3), 24=2108(LC 1), 18=755(LC 4)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**TOP CHORD** 2-3=-2257/0, 3-4=-2257/0, 4-5=-2375/0, 5-6=-1691/160, 6-8=-1691/160, 8-9=0/2126, 9-10=0/2126, 10-12=-1625/335, 12-13=-1625/335, 13-14=-2126/0, 14-15=-2092/0, 15-16=-2092/0  
**BOT CHORD** 29-30=0/1465, 28-29=0/2375, 27-28=0/2375, 26-27=0/2375, 24-26=-656/427, 22-24=-842/507, 21-22=0/2126, 20-21=0/2126, 19-20=0/2126, 18-19=0/1379  
**WEBS** 9-24=-278/0, 2-30=-1607/0, 2-29=0/876, 3-29=-288/0, 8-24=-2154/0, 8-26=0/1514, 6-26=-271/10, 5-26=-1038/0, 4-29=-265/296, 10-24=-2062/0, 10-22=0/1395, 16-18=-1512/0, 16-19=0/788, 15-19=-302/0, 14-19=-112/404, 13-22=-949/0

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.




May 4, 2020

<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information</b> available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.</p>	<p>ENGINEERING BY <b>TRENCO</b> A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
---	---

Job J0420-1863	Truss F3	Truss Type Floor	Qty 3	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364919
					Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:49 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-AlgOCtBP2VRiqilSNsCyfaJ7IHozPwsNBXdgCbzJvBO



	9-10-4	25-8-0
	9-10-4	15-9-12
Plate Offsets (X,Y)--	[10:0-1-8,Edge], [11:0-1-8,Edge], [22:0-1-8,Edge], [23:0-1-8,Edge]	

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>	
TCLL 40.0	Plate Grip DOL	1.00	TC 0.62	Vert(LL)	-0.14	16-17	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.69	Vert(CT)	-0.19	17	>988	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.59	Horz(CT)	0.04	15	n/a	n/a		
BCDL 5.0	Code	IRC2015/TPI2014	Matrix-S							
								Weight: 130 lb	FT = 20%F, 11%E	

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1 (flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1 (flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3 (flat)	

**REACTIONS.** (size) 24=Mechanical, 21=0-3-8, 15=0-3-0  
Max Grav 24=471(LC 3), 21=1629(LC 1), 15=785(LC 7)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**TOP CHORD** 2-3=-825/200, 3-4=-825/200, 4-5=-825/200, 5-6=0/1163, 6-7=0/1163, 7-9=-1888/0, 9-10=-1888/0, 10-11=-2310/0, 11-12=-2213/0, 12-13=-2213/0  
**BOT CHORD** 23-24=-41/756, 22-23=-200/825, 21-22=-491/543, 19-21=0/815, 18-19=0/2310, 17-18=0/2310, 16-17=0/2310, 15-16=0/1442  
**WEBS** 6-21=-297/0, 2-24=-826/46, 5-21=-1217/0, 5-22=0/664, 4-22=-359/0, 7-21=-1888/0, 7-19=0/1242, 13-15=-1581/0, 13-16=0/853, 12-16=-259/11, 11-16=-349/170, 10-19=-700/0

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 6) CAUTION, Do not erect truss backwards.



May 4, 2020

<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information</b> available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.</p>	<p>818 Soundside Road Edenton, NC 27932</p>
---	---

Job J0420-1863	Truss F5	Truss Type Floor	Qty 2	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364920
					Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:50 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-fyDmPDB1ppZZRrKfxZJBcnsJdh598MgXQBNDk1zJvBN






Plate Offsets (X,Y)--	[4:0-1-8,Edge], [5:0-1-8,Edge]				
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.55	Vert(LL) -0.26 11-12 >829 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.86	Vert(CT) -0.34 13-15 >625 360	M18SHS	244/190
BCLL 0.0	Rep Stress Incr YES	WB 0.62	Horz(CT) 0.06 10 n/a n/a	Weight: 90 lb FT = 20%F, 11%E	
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S			

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (size) 16=0-3-8, 10=0-3-0  
Max Grav 16=968(LC 1), 10=968(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-3009/0, 3-4=-3009/0, 4-5=-3543/0, 5-7=-3009/0, 7-8=-3009/0  
BOT CHORD 15-16=0/1833, 13-15=0/3543, 12-13=0/3543, 11-12=0/3543, 10-11=0/1833  
WEBS 8-10=-2012/0, 8-11=0/1301, 7-11=-303/4, 5-11=-858/0, 2-16=-2012/0, 2-15=0/1301, 3-15=-303/4, 4-15=-858/0

- NOTES-**
- Unbalanced floor live loads have been considered for this design.
  - All plates are MT20 plates unless otherwise indicated.
  - All plates are 1.5x3 MT20 unless otherwise indicated.
  - Plates checked for a plus or minus 1 degree rotation about its center.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.





<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information</b> available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.</p>	<p>ENGINEERING BY <b>TRENCO</b> A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
---	---



Job J0420-1863	Truss F5A	Truss Type GABLE	Qty 1	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364921
-------------------	--------------	---------------------	----------	----------	------------------------------------	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:51 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-78n8cZCga6hQ3?vrUHEQk?PSd5OWtqdgfr6nHUzJvBM



9-3-8	10-7-0	15-8-8	15-10-0	17-11-8
9-3-8	1-3-8	5-1-8	0-1-8	2-1-8


Plate Offsets (X,Y)--	[4:0-1-8,Edge], [5:0-1-8,Edge], [10:0-1-8,Edge]				
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.60	Vert(LL) -0.21 15-17 >873 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.98	Vert(CT) -0.29 15-17 >644 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.57	Horz(CT) 0.03 12 n/a n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S		Weight: 94 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1 (flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1 (flat)	BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 2x4 SP No.3 (flat)	

**REACTIONS.** (size) 18=0-3-8, 11=2-3-0, 12=2-3-0, 12=2-3-0  
Max Uplift 11=518(LC 1)  
Max Grav 18=770(LC 1), 12=1683(LC 1), 12=1683(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 10-11=0/515, 2-3=-2194/0, 3-4=-2194/0, 4-5=-2127/0, 5-6=-1743/0, 6-8=-1743/0, 8-9=0/1009, 9-10=0/992  
BOT CHORD 17-18=0/1407, 15-17=0/2127, 14-15=0/2127, 13-14=0/2127, 12-13=0/651  
WEBS 9-12=-263/0, 2-18=-1542/0, 2-17=0/871, 3-17=-309/0, 8-12=-1837/0, 8-13=0/1207, 5-13=-837/0, 5-14=0/317, 10-12=-1126/0

- NOTES-**
- Plates checked for a plus or minus 1 degree rotation about its center.
  - Gable studs spaced at 1-4-0 oc.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 11=518.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.



May 4, 2020

Job J0420-1863	Truss F6	Truss Type Floor	Qty 2	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364922
					Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:51 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-78n8cZCga6hQ3?vrUHEQk?PUw5Shtrygfr6nHUzJvBM





Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge]

<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.45	Vert(LL) -0.17 12-13 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.72	Vert(CT) -0.23 12-13 >837 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.49	Horz(CT) 0.04 9 n/a n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S		Weight: 81 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1 (flat)  
BOT CHORD 2x4 SP No.1 (flat)  
WEBS 2x4 SP No.3 (flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 14=0-3-8, 9=0-3-0  
Max Grav 14=858(LC 1), 9=858(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-2528/0, 3-4=-2528/0, 4-5=-2770/0, 5-6=-2516/0, 6-0, 5P CHORD



**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.



818 Soundside Road  
Edenton, NC 27932



Job J0420-1863	Truss F7	Truss Type Floor	Qty 6	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364923
-------------------	-------------	---------------------	----------	----------	------------------------------------	-----------

Comtech, Inc, Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:52 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-bKLWqvDILQpGh9U12\_mfHCxhoUpsclQqtVsKpwzJvBL





Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge]


<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.38	Vert(LL)	-0.15	12	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.66	Vert(CT)	-0.21	12	>890		
BCLL 0.0	Rep Stress Incr	YES	WB 0.48	Horz(CT)	0.04	9	n/a		
BCDL 5.0	Code IRC2015/TP12014		Matrix-S						
								Weight: 80 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1 (flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1 (flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3 (flat)	

**REACTIONS.** (size) 14=Mechanical, 9=0-3-0  
Max Grav 14=842(LC 1), 9=842(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-2460/0, 3-4=-2460/0, 4-5=-2674/0, 5-6=-2449/0, 6-7=-2449/0  
BOT CHORD 13-14=0/1564, 12-13=0/2674, 11-12=0/2674, 10-11=0/2674, 9-10=0/1565  
WEBS 2-14=-1716/0, 2-13=0/991, 3-13=-261/1, 7-9=-1717/0, 7-10=0/978, 4-13=-508/62, 5-10=-546/55

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 3) Plates checked for a plus or minus 1 degree rotation about its center.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.





May 4, 2020

Job J0420-1863	Truss F8	Truss Type Floor	Qty 6	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364924
					Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:53 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-3Wvu1FEw6kx7IJ2EciHuqQUuDuBfLnwz69buLMzJvBK



11-8-0  
11-8-0

Plate Offsets (X,Y)-- [4:0-1-8,Edge], [11:0-1-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	2-0-0	TC 0.46	Vert(LL) -0.10	9-10	>999	480	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.56	Vert(CT) -0.13	9-10	>999	360		
BCLL 0.0	Lumber DOL 1.00	WB 0.33	Horz(CT) 0.02	8	n/a	n/a		
BCDL 5.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2015/TPI2014						Weight: 61 lb	FT = 20%F, 11%E


**LUMBER-**  
TOP CHORD 2x4 SP No.1 (flat)  
BOT CHORD 2x4 SP No.1 (flat)  
WEBS 2x4 SP No.3 (flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 12=0-3-0, 8=0-3-8  
Max Grav 12=622(LC 1), 8=622(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1426/0, 3-4=-1426/0, 4-5=-1359/0, 5-6=-1359/0  
BOT CHORD 11-12=0/1092, 10-11=0/1426, 9-10=0/1426, 8-9=0/1089  
WEBS 2-12=-1196/0, 2-11=0/564, 3-11=-278/0, 6-8=-1193/0, 6-9=0/367, 4-9=-310/75

**NOTES-**  
1) Unbalanced floor live loads have been considered for this design.  
2) Plates checked for a plus or minus 1 degree rotation about its center.  
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



May 4, 2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.**  
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.





818 Soundside Road  
Edenton, NC 27932

Job J0420-1863	Truss F9	Truss Type GABLE	Qty 1	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364925
					Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:53 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-3Wvu1FEw6kx7IJ2EciHuqQUkuASLIDz69buLMzJvBK



1-0-0	2-4-0	3-8-0	5-0-0	7-8-0	9-0-0	10-4-0	11-8-0
1-0-0	1-4-0	1-4-0	1-4-0	2-8-0	1-4-0	1-4-0	1-4-0
Plate Offsets (X,Y)-- [6:0-3-0,0-0-8], [11:0-1-8,Edge], [12:0-1-8,Edge], [18:0-0-10,0-1-4], [19:0-0-10,0-3-0]							

LOADING (psf)	SPACING-	CSL	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.56	Vert(LL) -0.09	12	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.63	Vert(CT) -0.12	12	>999	360		
BCLL 0.0	Rep Stress Incr NO	WB 0.50	Horz(CT) 0.04	9	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S						
							Weight: 72 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1 (flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1 (flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3 (flat)	
OTHERS 2x4 SP No.3 (flat)	

**REACTIONS.** (size) 14=0-3-0, 9=0-3-8  
Max Grav 14=1327(LC 1), 9=1327(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-2176/0, 3-4=-3140/0, 4-5=-3140/0, 5-6=-3140/0, 6-7=-2176/0  
BOT CHORD 13-14=0/1414, 12-13=0/2908, 11-12=0/3140, 10-11=0/2908, 9-10=0/1414  
WEBS 2-14=-1877/0, 2-13=0/1060, 3-13=-1018/0, 3-12=0/316, 7-9=-1877/0, 7-10=0/1060, 6-10=-1018/0, 6-11=0/316

- NOTES-**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 2) Plates checked for a plus or minus 1 degree rotation about its center.
  - 3) Gable studs spaced at 1-4-0 oc.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 9-14=-10, 1-8=-225



May 4, 2020

<p><b>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.</b></p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see <b>ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information</b> available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.</p>	<p>ENGINEERING BY <b>TRENCO</b> A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
---	---

Job J0420-1863	Truss KW3	Truss Type GABLE	Qty 1	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364926
					Job Reference (optional)	


Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:54 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-XjTHFbEYs13\_wTdQAPo7Md16GIIT4Jr6LpLrtozJvBJ

0-1/8

0-1/8

Scale = 1:42.8



0-10-0	2-2-0	3-6-0	4-10-0	6-2-0	7-6-0	8-10-0	10-2-0	11-6-0	12-10-0	14-2-0	15-6-0	16-10-0	18-2-0	19-6-0	20-10-0	22-2-0	23-6-0	24-10-0	25-8-0
0-10-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	0-10-0

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	23	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014		Matrix-R						Weight: 113 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.1(flat)  
BOT CHORD 2x4 SP No.1(flat)  
WEBS 2x4 SP No.3(flat)  
OTHERS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 25-8-0.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 44, 23, 33, 35, 36, 37, 38, 39, 40, 41, 42, 43, 32, 31, 30, 29, 28, 27, 26, 25, 24

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 2) Plates checked for a plus or minus 1 degree rotation about its center.
  - 3) Gable requires continuous bottom chord bearing.
  - 4) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - 5) Gable studs spaced at 1-4-0 oc.
  - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



May 4, 2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.**  
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.

ENGINEERING BY  
**TRENCO**  
A MiTek Affiliate  
818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Weaver / Sonnenburg Res. / Harnett	E14364927
J0420-1863	KW7	GABLE	1	1	Job Reference (optional)	


Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:55 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-?v1fSwFAdLBrYdCcJ7JMvrZH1i?ipm5GaT4\_QFzJvBI

0-1-8

0-1-8

Scale = 1:25.9



1-2-0	2-6-0	3-10-0	5-2-0	6-6-0	7-10-0	9-2-0	10-6-0	11-10-0	13-2-0	14-6-0	15-8-0
1-2-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-2-0
<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>		
TCLL 40.0	Plate Grip DOL	1.00	TC 0.06	Vert(LL)	n/a	-	n/a	MT20	244/190		
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a				
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	14	n/a				
BCDL 5.0	Code	IRC2015/TPI2014	Matrix-R								
								Weight: 70 lb	FT = 20%F, 11%E		


**LUMBER-**  
 TOP CHORD 2x4 SP No.1(flat)  
 BOT CHORD 2x4 SP No.1(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 15-8-0.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 26, 14, 20, 21, 22, 23, 24, 25, 19, 18, 17, 16, 15

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 2) Plates checked for a plus or minus 1 degree rotation about its center.
  - 3) Gable requires continuous bottom chord bearing.
  - 4) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - 5) Gable studs spaced at 1-4-0 oc.
  - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



May 4, 2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.**  
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road  
 Edenton, NC 27932

Job J0420-1863	Truss KW8	Truss Type GABLE	Qty 1	Ply 1	Weaver / Sonnenburg Res. / Harnett	E14364928
					Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

8.330 s Mar 23 2020 MiTek Industries, Inc. Mon May 4 10:47:55 2020 Page 1  
ID:z9tQeuaeEwTQ6FgPNEM81tzKtIE-?v1fSwFAdLBrYdCcJ7JMvrZGti?gpm3GaT4\_QFzJvBl



0-1-8  
Scale = 1:21.9





Plate Offsets (X,Y)-- [19:0-1-8,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.07	Vert(LL)	0.00	13	****	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	-0.00	20	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	12	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014		Matrix-S							
									Weight: 71 lb	FT = 20%F, 11%E


**LUMBER-**  
TOP CHORD 2x4 SP No.1 (flat)  
BOT CHORD 2x4 SP No.1 (flat)  
WEBS 2x4 SP No.3 (flat)  
OTHERS 2x4 SP No.3 (flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 13-3-4.  
(lb) - Max Grav All reactions 250 lb or less at joint(s) 22, 12, 12, 20, 21, 19, 18, 17, 16, 15, 14, 13

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 2) Plates checked for a plus or minus 1 degree rotation about its center.
  - 3) Gable studs spaced at 1-4-0 oc.
  - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 5) CAUTION, Do not erect truss backwards.



May 4, 2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 10/03/2015 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 218 N. Lee Street, Suite 312, Alexandria, VA 22314.




818 Soundside Road  
Edenton, NC 27932




# Symbols

## PLATE LOCATION AND ORIENTATION



For 4 x 2 orientation, locate plates 0-  $\frac{1}{16}$ " from outside edge of truss.



\* Plate location details available in **MITrak 20/20 software** or upon request.

## PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

## BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

## Industry Standards:

ANSI/TPI 1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-89: Design Standard for Bracing.  
BCSI: Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System



**JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.**

**CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.**

## PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988  
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TPI 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITTEK® All Rights Reserved



MITek Engineering Reference Sheet: MII-7473 rev. 10/03/2015



# General Safety Notes

**Failure to Follow Could Cause Property Damage or Personal Injury**

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TPI 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TPI 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TPI 1 Quality Criteria.