



ROOF & FLOOR TRUSSES & BEAMS

Reilly Road Industrial Park
Fayetteville, N.C. 28309
Phone: (910) 864-8787
Fax: (910) 864-4444

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.


Signature Curtis Quick
Curtis Quick

LOAD CHART FOR JACK STUDS

(BASED ON TABLES ROEHLIC 6 (3))

NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADERS/GIRDERS

END REACTION (IP / FT)	REQ'D STUDS FOR 10' HEADERS	END REACTION (IP / FT)	REQ'D STUDS FOR 10' HEADERS
1700	1	2550	1
3400	2	5100	2
5100	3	7650	3
6800	4	10200	4
8500	5	12750	5
10200	6	15300	6
11900	7		
13600	8		
15300	9		



**Bonus Room
40lbs. Live Load**

Hatch Legend

	2nd Floor Bearing Walls @ 8' 1-1/2"
	7-1/4" Tray Ceiling

▲ = Denotes Left End of Truss
(Reference Engineered Truss Drawing)
Do Not Erect Trusses Backwards

Truss Placement Plan
SCALE: 1/4" = 1'

HANGER LEGEND

	= USP HUS26 / Single 2x Hanger
--	--------------------------------

Beam Legend

PlotID	Length	Product	Plies	Net Qty
BM1	11' 0"	1-3/4"x 9-1/4" LVL Kerto-S	2	2

BUILDER	Benjamin Stout	CITY / CO.	Bunnlevel / Harnett Co
JOB NAME	Lot 38 Blackberry Manor	ADDRESS	38 Kotata Ave
PLAN	The Reedsville	MODEL	Roof
SEAL DATE	N/A	DATE REV.	06/03/20
QUOTE #	Quote #	DRAWN BY	Curtis Quick
JOB #	J0320-1195	SALES REP.	Marshall Naylor

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BC3-B1 and BC3-B3 provided with the truss delivery package or online @ sbcindustry.com.