



**HDR-2 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED**

Level: Level



**Member Information**

|                     |               |
|---------------------|---------------|
| Type:               | Girder        |
| Plies:              | 2             |
| Moisture Condition: | Dry           |
| Deflection LL:      | 480           |
| Deflection TL:      | 360           |
| Importance:         | Normal        |
| Temperature:        | Temp <= 100°F |

|                |              |
|----------------|--------------|
| Application:   | Floor        |
| Design Method: | ASD          |
| Building Code: | IBC/IRC 2015 |
| Load Sharing:  | No           |
| Deck:          | Not Checked  |

**Reactions UNPATTERNED lb (Uplift)**

| Brg | Live | Dead | Snow | Wind | Const |
|-----|------|------|------|------|-------|
| 1   | 0    | 1498 | 1386 | 0    | 0     |
| 2   | 0    | 1498 | 1386 | 0    | 0     |

**Bearings**

| Bearing           | Length | Cap. React | D/L lb      | Total | Ld. Case | Ld. Comb. |
|-------------------|--------|------------|-------------|-------|----------|-----------|
| 1 - SPF End Grain | 3.000" | 32%        | 1498 / 1386 | 2884  | L        | D+S       |
| 2 - SPF End Grain | 3.000" | 32%        | 1498 / 1386 | 2884  | L        | D+S       |

**Analysis Results**

| Analysis     | Actual         | Location | Allowed       | Capacity    | Comb. | Case |
|--------------|----------------|----------|---------------|-------------|-------|------|
| Moment       | 3802 ft-lb     | 3'       | 14423 ft-lb   | 0.264 (26%) | D+S   | L    |
| Unbraced     | 3802 ft-lb     | 3'       | 10944 ft-lb   | 0.347 (35%) | D+S   | L    |
| Shear        | 1962 lb        | 5' 1/2"  | 7943 lb       | 0.247 (25%) | D+S   | L    |
| LL Defl inch | 0.029 (L/2324) | 3'       | 0.141 (L/480) | 0.210 (21%) | S     | L    |
| TL Defl inch | 0.060 (L/1117) | 3'       | 0.188 (L/360) | 0.320 (32%) | D+S   | L    |

**Design Notes**

- 1 Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 2 Refer to last page of calculations for fasteners required for specified loads.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on single ply width.

| ID | Load Type   | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1  | Uniform     |          |            | Top  | 462 PLF  | 0 PLF  | 462 PLF   | 0 PLF    | 0 PLF       | B2 TRUSS |
| 2  | Uniform     |          |            | Top  | 30 PLF   | 0 PLF  | 0 PLF     | 0 PLF    | 0 PLF       | WALL     |
|    | Self Weight |          |            |      | 7 PLF    |        |           |          |             |          |

**Notes**  
 Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**  
 1. Dry service conditions, unless noted otherwise  
 2. LVL not to be treated with fire retardant or corrosive chemicals

**Handling & Installation**  
 1. LVL beams must not be cut or drilled  
 2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals  
 3. Damaged Beams must not be used  
 4. Design assumes top edge is laterally restrained  
 5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023


**Manufacturer Info**  
 Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
 www.metsawood.com/us  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**HDR-2 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED**

Level: Level



**Multi-Ply Analysis**

Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6"

|                          |           |
|--------------------------|-----------|
| Capacity                 | 0.0 %     |
| Load                     | 0.0 PLF   |
| Yield Limit per Foot     | 163.7 PLF |
| Yield Limit per Fastener | 81.9 lb.  |
| Yield Mode               | IV        |
| Edge Distance            | 1 1/2"    |
| Min. End Distance        | 3"        |
| Load Combination         |           |
| Duration Factor          | 1.00      |

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

**Manufacturer Info**



Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
 www.metsawood.com/us  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**HDR-1 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED**

Level: Level



**Member Information**

|                     |               |                |              |
|---------------------|---------------|----------------|--------------|
| Type:               | Girder        | Application:   | Floor        |
| Plies:              | 2             | Design Method: | ASD          |
| Moisture Condition: | Dry           | Building Code: | IBC/IRC 2015 |
| Deflection LL:      | 480           | Load Sharing:  | No           |
| Deflection TL:      | 360           | Deck:          | Not Checked  |
| Importance:         | Normal        |                |              |
| Temperature:        | Temp <= 100°F |                |              |

**Reactions UNPATTERNED lb (Uplift)**

| Brg | Live | Dead | Snow | Wind | Const |
|-----|------|------|------|------|-------|
| 1   | 0    | 1576 | 1464 | 0    | 0     |
| 2   | 0    | 1576 | 1464 | 0    | 0     |

**Bearings**

| Bearing           | Length | Cap. | React D/L   | Ib   | Total | Ld. Case | Ld. Comb. |
|-------------------|--------|------|-------------|------|-------|----------|-----------|
| 1 - SPF End Grain | 3.000" | 33%  | 1576 / 1464 | 3040 | L     | D+S      |           |
| 2 - SPF End Grain | 3.000" | 33%  | 1576 / 1464 | 3040 | L     | D+S      |           |

**Analysis Results**

| Analysis     | Actual         | Location | Allowed       | Capacity    | Comb. | Case |
|--------------|----------------|----------|---------------|-------------|-------|------|
| Moment       | 4007 ft-lb     | 3'       | 14423 ft-lb   | 0.278 (28%) | D+S   | L    |
| Unbraced     | 4007 ft-lb     | 3'       | 10944 ft-lb   | 0.366 (37%) | D+S   | L    |
| Shear        | 2069 lb        | 11 1/2"  | 7943 lb       | 0.260 (26%) | D+S   | L    |
| LL Defl inch | 0.031 (L/2200) | 3'       | 0.141 (L/480) | 0.220 (22%) | S     | L    |
| TL Defl inch | 0.064 (L/1060) | 3'       | 0.188 (L/360) | 0.340 (34%) | D+S   | L    |

**Design Notes**

- 1 Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 2 Refer to last page of calculations for fasteners required for specified loads.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on single ply width.

| ID | Load Type   | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1  | Uniform     |          |            | Top  | 488 PLF  | 0 PLF  | 488 PLF   | 0 PLF    | 0 PLF       | B2 TRUSS |
| 2  | Uniform     |          |            | Top  | 30 PLF   | 0 PLF  | 0 PLF     | 0 PLF    | 0 PLF       | WALL     |
|    | Self Weight |          |            |      | 7 PLF    |        |           |          |             |          |

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

**Manufacturer Info**


Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
 www.metsawood.com/us  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**HDR-1 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED**

Level: Level



**Multi-Ply Analysis**

Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6"

|                          |           |
|--------------------------|-----------|
| Capacity                 | 0.0 %     |
| Load                     | 0.0 PLF   |
| Yield Limit per Foot     | 163.7 PLF |
| Yield Limit per Fastener | 81.9 lb.  |
| Yield Mode               | IV        |
| Edge Distance            | 1 1/2"    |
| Min. End Distance        | 3"        |
| Load Combination         |           |
| Duration Factor          | 1.00      |

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

**Manufacturer Info**



Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
 www.metsawood.com/us  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**HDR-3 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED**

Level: Level



**Member Information**

|                     |               |
|---------------------|---------------|
| Type:               | Girder        |
| Plies:              | 2             |
| Moisture Condition: | Dry           |
| Deflection LL:      | 480           |
| Deflection TL:      | 360           |
| Importance:         | Normal        |
| Temperature:        | Temp <= 100°F |

|                |              |
|----------------|--------------|
| Application:   | Floor        |
| Design Method: | ASD          |
| Building Code: | IBC/IRC 2015 |
| Load Sharing:  | No           |
| Deck:          | Not Checked  |

**Reactions UNPATTERNED lb (Uplift)**

| Brg | Live | Dead | Snow | Wind | Const |
|-----|------|------|------|------|-------|
| 1   | 0    | 2044 | 1932 | 0    | 0     |
| 2   | 0    | 2044 | 1932 | 0    | 0     |

**Bearings**

| Bearing           | Length | Cap. React | D/L lb      | Total | Ld. Case | Ld. Comb. |
|-------------------|--------|------------|-------------|-------|----------|-----------|
| 1 - SPF End Grain | 3.000" | 44%        | 2044 / 1932 | 3976  | L        | D+S       |
| 2 - SPF End Grain | 3.000" | 44%        | 2044 / 1932 | 3976  | L        | D+S       |

**Analysis Results**

| Analysis     | Actual         | Location | Allowed       | Capacity    | Comb. | Case |
|--------------|----------------|----------|---------------|-------------|-------|------|
| Moment       | 5241 ft-lb     | 3'       | 14423 ft-lb   | 0.363 (36%) | D+S   | L    |
| Unbraced     | 5241 ft-lb     | 3'       | 10944 ft-lb   | 0.479 (48%) | D+S   | L    |
| Shear        | 2706 lb        | 11 1/2"  | 7943 lb       | 0.341 (34%) | D+S   | L    |
| LL Defl inch | 0.040 (L/1667) | 3'       | 0.141 (L/480) | 0.290 (29%) | S     | L    |
| TL Defl inch | 0.083 (L/810)  | 3'       | 0.188 (L/360) | 0.440 (44%) | D+S   | L    |

**Design Notes**

- 1 Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 2 Refer to last page of calculations for fasteners required for specified loads.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on single ply width.

| ID | Load Type   | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1  | Uniform     |          |            | Top  | 644 PLF  | 0 PLF  | 644 PLF   | 0 PLF    | 0 PLF       | A2 TRUSS |
| 2  | Uniform     |          |            | Top  | 30 PLF   | 0 PLF  | 0 PLF     | 0 PLF    | 0 PLF       | WALL     |
|    | Self Weight |          |            |      | 7 PLF    |        |           |          |             |          |

**Notes**  
 Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**  
 1. Dry service conditions, unless noted otherwise  
 2. LVL not to be treated with fire retardant or corrosive chemicals

**Handling & Installation**  
 1. LVL beams must not be cut or drilled  
 2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals  
 3. Damaged Beams must not be used  
 4. Design assumes top edge is laterally restrained  
 5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023


**Manufacturer Info**  
 Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
 www.metsawood.com/us  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**HDR-3 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED**

Level: Level



**Multi-Ply Analysis**

Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6"

|                          |           |
|--------------------------|-----------|
| Capacity                 | 0.0 %     |
| Load                     | 0.0 PLF   |
| Yield Limit per Foot     | 163.7 PLF |
| Yield Limit per Fastener | 81.9 lb.  |
| Yield Mode               | IV        |
| Edge Distance            | 1 1/2"    |
| Min. End Distance        | 3"        |
| Load Combination         |           |
| Duration Factor          | 1.00      |

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

**Manufacturer Info**


Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
 www.metsawood.com/us  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**GDH-18 Kerto-S LVL 1.750" X 14.000" 2-Ply - PASSED**

Level: Level



**Member Information**

|                     |               |                |              |
|---------------------|---------------|----------------|--------------|
| Type:               | Girder        | Application:   | Floor        |
| Plies:              | 2             | Design Method: | ASD          |
| Moisture Condition: | Dry           | Building Code: | IBC/IRC 2015 |
| Deflection LL:      | 480           | Load Sharing:  | No           |
| Deflection TL:      | 360           | Deck:          | Not Checked  |
| Importance:         | Normal        |                |              |
| Temperature:        | Temp <= 100°F |                |              |

**Reactions UNPATTERNED lb (Uplift)**

| Brg | Live | Dead | Snow | Wind | Const |
|-----|------|------|------|------|-------|
| 1   | 377  | 2504 | 377  | 0    | 0     |
| 2   | 377  | 2504 | 377  | 0    | 0     |

**Bearings**

| Bearing           | Length | Cap. React | D/L lb     | Total | Ld. Case | Ld. Comb.   |
|-------------------|--------|------------|------------|-------|----------|-------------|
| 1 - SPF End Grain | 3.500" | 29%        | 2504 / 565 | 3069  | L        | D+0.75(L+S) |
| 2 - SPF End Grain | 3.500" | 29%        | 2504 / 565 | 3069  | L        | D+0.75(L+S) |

**Analysis Results**

| Analysis     | Actual         | Location  | Allowed       | Capacity     | Comb.       | Case |
|--------------|----------------|-----------|---------------|--------------|-------------|------|
| Moment       | 12910 ft-lb    | 9'5"      | 26999 ft-lb   | 0.478 (48%)  | D+L         | L    |
| Unbraced     | 13754 ft-lb    | 9'5"      | 13758 ft-lb   | 1.000 (100%) | D+0.75(L+S) | L    |
| Shear        | 2453 lb        | 1'4 3/4"  | 10453 lb      | 0.235 (23%)  | D+L         | L    |
| LL Defl inch | 0.102 (L/2160) | 9'5 1/16" | 0.459 (L/480) | 0.220 (22%)  | 0.75(L+S)   | L    |
| TL Defl inch | 0.555 (L/398)  | 9'5 1/16" | 0.612 (L/360) | 0.910 (91%)  | D+0.75(L+S) | L    |

**Design Notes**

- 1 Fasten all plies using 3 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 2 Refer to last page of calculations for fasteners required for specified loads.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top loads must be supported equally by all plies.
- 5 Top must be laterally braced at a maximum of 7'5 5/8" o.c.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on single ply width.

| ID | Load Type   | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1  | Uniform     |          |            | Top  | 55 PLF   | 40 PLF | 40 PLF    | 0 PLF    | 0 PLF       | R + F    |
| 2  | Uniform     |          |            | Top  | 200 PLF  | 0 PLF  | 0 PLF     | 0 PLF    | 0 PLF       | WALL     |
|    | Self Weight |          |            |      | 11 PLF   |        |           |          |             |          |

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

**Manufacturer Info**


Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
[www.metsawood.com/us](http://www.metsawood.com/us)  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**GDH-18 Kerto-S LVL 1.750" X 14.000" 2-Ply - PASSED**

Level: Level



**Multi-Ply Analysis**

Fasten all plies using 3 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6"

|                          |           |
|--------------------------|-----------|
| Capacity                 | 0.0 %     |
| Load                     | 0.0 PLF   |
| Yield Limit per Foot     | 245.6 PLF |
| Yield Limit per Fastener | 81.9 lb.  |
| Yield Mode               | IV        |
| Edge Distance            | 1 1/2"    |
| Min. End Distance        | 3"        |
| Load Combination         |           |
| Duration Factor          | 1.00      |

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

**Manufacturer Info**

Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
 www.metsawood.com/us  
 ICC-ES: ESR-3633



Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS





**GDH-9 Kerto-S LVL 1.750" X 11.875" 2-Ply - PASSED**

Level: Level



**Member Information**

|                            |                             |
|----------------------------|-----------------------------|
| Type: Girder               | Application: Floor          |
| Plies: 2                   | Design Method: ASD          |
| Moisture Condition: Dry    | Building Code: IBC/IRC 2015 |
| Deflection LL: 480         | Load Sharing: No            |
| Deflection TL: 360         | Deck: Not Checked           |
| Importance: Normal         |                             |
| Temperature: Temp <= 100°F |                             |

**Reactions UNPATTERNED lb (Uplift)**

| Brg | Live | Dead | Snow | Wind | Const |
|-----|------|------|------|------|-------|
| 1   | 0    | 517  | 0    | 0    | 0     |
| 2   | 0    | 517  | 0    | 0    | 0     |

**Bearings**

| Bearing           | Length | Cap. React | D/L lb  | Total | Ld. Case | Ld. Comb. |
|-------------------|--------|------------|---------|-------|----------|-----------|
| 1 - SPF End Grain | 3.500" | 5%         | 517 / 0 | 517   | Uniform  | D         |
| 2 - SPF End Grain | 3.500" | 5%         | 517 / 0 | 517   | Uniform  | D         |

**Analysis Results**

| Analysis     | Actual         | Location | Allowed       | Capacity    | Comb. | Case    |
|--------------|----------------|----------|---------------|-------------|-------|---------|
| Moment       | 1156 ft-lb     | 4'11"    | 17919 ft-lb   | 0.065 (6%)  | D     | Uniform |
| Unbraced     | 1156 ft-lb     | 4'11"    | 9664 ft-lb    | 0.120 (12%) | D     | Uniform |
| Shear        | 389 lb         | 8'7 3/8" | 7980 lb       | 0.049 (5%)  | D     | Uniform |
| LL Defl inch | 0.000 (L/999)  | 0        | 999.000 (L/0) | 0.000 (0%)  |       |         |
| TL Defl inch | 0.022 (L/5130) | 4'11"    | 0.312 (L/360) | 0.070 (7%)  | D     | Uniform |

**Design Notes**

- 1 Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 2 Refer to last page of calculations for fasteners required for specified loads.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on single ply width.

| ID | Load Type   | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1  | Uniform     |          |            | Top  | 96 PLF   | 0 PLF  | 0 PLF     | 0 PLF    | 0 PLF       | Wall     |
|    | Self Weight |          |            |      | 9 PLF    |        |           |          |             |          |

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

**Manufacturer Info**


Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
[www.metsawood.com/us](http://www.metsawood.com/us)  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**GDH-9 Kerto-S LVL 1.750" X 11.875" 2-Ply - PASSED**

Level: Level



**Multi-Ply Analysis**

Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6"

|                          |           |
|--------------------------|-----------|
| Capacity                 | 0.0 %     |
| Load                     | 0.0 PLF   |
| Yield Limit per Foot     | 163.7 PLF |
| Yield Limit per Fastener | 81.9 lb.  |
| Yield Mode               | IV        |
| Edge Distance            | 1 1/2"    |
| Min. End Distance        | 3"        |
| Load Combination         |           |
| Duration Factor          | 1.00      |

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

**Manufacturer Info**

Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
 www.metsawood.com/us  
 ICC-ES: ESR-3633

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS

