


Job	Truss	Truss Type	Qty	Ply	Lamco_Sullivan
20020029	A	Piggyback Base	2	1	Job Reference (optional)

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:49

Page: 1

ID:qhi9wEnjkTRG9Acc7QsZ3Szna1_TOCLGIAKAfN2a81JzVruL11BjdpezBm6ZTFQ8hznYl8



Scale = 1:86.9

Plate Offsets (X, Y): [2:Edge,0-0-13], [4:0-3-0,Edge], [5:0-3-12,0-2-0], [7:0-3-12,0-2-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.83	Vert(LL)	-0.18	13-16	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.72	Vert(CT)	-0.31	13-16	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.98	Horz(CT)	0.02	12	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 326 lb	FT = 20%

LUMBER	
TOP CHORD	2x4 SP 2400F 2.0E *Except* T3:2x4 SP No.2, T5:2x4 SP No.1
BOT CHORD	2x6 SP No.2
WEBS	2x4 SP No.2 *Except* W8:2x4 SP No.3
WEDGE	Left: 2x4 SP No.3
REACTIONS	(lb/size)
	12=1959/0-3-8, (min. 0-2-10), 19=1542/0-3-8, (min. 0-2-3)
	Max Horiz 19=213 (LC 13)
	Max Uplift 12=58 (LC 12)
	Max Grav 12=2248 (LC 2), 19=1844 (LC 40)

BRACING	
TOP CHORD	Structural wood sheathing directly applied or 5-9-10 oc purlins, except
	2-0-0 oc purlins (5-3-2 max.): 5-7.
BOT CHORD	Rigid ceiling directly applied or 4-3-10 oc bracing.
WEBS	1 Row at midpt 5-18, 7-13, 6-16, 8-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-25=-304/459, 25-26=-225/571, 3-26=-224/600, 3-27=-477/105, 4-27=-377/111, 4-5=-376/131, 5-28=-924/128, 6-28=-924/128, 6-7=-924/128, 7-8=-869/585, 8-29=-916/1830, 29-30=-936/1779, 30-31=-937/1771, 9-31=-958/1731, 9-32=-1042/1886, 10-32=-1047/1790
BOT CHORD	2-19=-382/329, 18-19=-159/296, 18-33=0/691, 17-33=0/691, 17-34=0/691, 16-34=0/691, 16-35=0/693, 15-35=0/693, 15-36=0/693, 14-36=0/693, 13-14=0/693, 12-13=-452/562, 10-12=-1769/1070
WEBS	5-18=-759/133, 7-13=-933/404, 9-12=-142/336, 7-16=-112/587, 6-16=-650/187, 5-16=-47/658, 3-18=0/983, 8-12=-2384/810, 8-13=-137/929, 3-19=-1757/226

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 12 and 19. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 20020029	Truss AA	Truss Type Piggyback Base	Qty 6	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	------------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:50

Page: 1

ID:qhi9wEnjkTRG9Acc7QsZ3Szna1_xaljUeAyx9VvBHcVXDM7uFaLJ06vi5uFn7?zg7znY17



Scale = 1:86.9

Plate Offsets (X, Y): [2:Edge,0-0-13], [4:0-4-0,Edge], [5:0-3-12,0-2-0], [7:0-3-12,0-2-0]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.84	Vert(LL)	-0.26	16-18	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.91	Vert(CT)	-0.44	16-18	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.77	Horz(CT)	0.08	12	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 317 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP 2400F 2.0E *Except* T3,T5:2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.2 *Except* W7:2x4 SP No.3
WEDGE Left: 2x4 SP No.3

REACTIONS (lb/size) 2=1540/0-3-8, (min. 0-2-4), 12=1961/0-3-8, (min. 0-2-10)
Max Horiz 2=-213 (LC 13)
Max Grav 2=1881 (LC 50), 12=2247 (LC 2)

BRACING
TOP CHORD Structural wood sheathing directly applied or 3-6-8 oc purlins, except
2-0-0 oc purlins (3-3-5 max.): 5-7.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
5-6-9 oc bracing: 10-12.
WEBS 1 Row at midpt 6-16

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-24=-2811/413, 24-25=-2623/434, 3-25=-2619/440, 3-26=-2751/562, 4-26=-2583/567, 4-5=-2580/588, 5-27=-1930/456, 6-27=-1930/456, 6-7=-1930/456, 7-8=-2729/541, 8-28=-2407/336, 28-29=-2529/311, 29-30=-2531/311, 9-30=-2611/308, 9-31=-794/1373, 10-31=-803/1269
BOT CHORD 2-32=-209/2370, 32-33=-209/2370, 18-33=-209/2370, 18-34=-49/1728, 17-34=-49/1728, 17-35=-49/1728, 16-35=-49/1728, 16-36=-23/1665, 15-36=-23/1665, 15-37=-23/1665, 14-37=-23/1665, 13-14=-23/1665, 12-13=0/1967, 10-12=-1281/836
WEBS 5-18=-187/1045, 7-13=-129/1066, 9-12=-3131/921, 7-16=-79/650, 6-16=-644/184, 5-16=-74/593, 3-18=-589/296, 9-13=-186/500, 8-13=-662/302

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 12. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

Job 20020029	Truss AA	Truss Type Piggyback Base	Qty 6	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	------------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:50

Page: 2

ID:qhi9wEnjkTRG9Acc7QsZ3Szna1_-xaljUeAyx9VvBHcVXDM7uFaLJ06vi5uFn7?zg7znY17

11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 20020029	Truss BA	Truss Type Piggyback Base	Qty 6	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	------------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:50

Page: 1

ID:OilCs50uMIeEmaqAUWyaG93znZsL-xaljiUeAyx9VvBHcVXDM7uFaLq08ni6Ffn?zg7znY17



Scale = 1:75.1

Plate Offsets (X, Y): [2:Edge,0-0-13], [5:0-3-12,0-2-0], [7:0-3-12,0-2-0], [11:Edge,0-0-13]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.87	Vert(LL)	-0.21	12-14	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.79	Vert(CT)	-0.36	12-14	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.72	Horz(CT)	0.04	11	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 291 lb	FT = 20%	

LUMBER
 TOP CHORD 2x4 SP No.2 *Except* T4,T5:2x4 SP No.1
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.2
 WEDGE Left: 2x4 SP No.3
 SLIDER Right 2x4 SP No.3 -- 2-4-3

BRACING
 TOP CHORD Structural wood sheathing directly applied, except 2-0-0 oc purlins (4-9-4 max.): 5-7.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS 1 Row at midpt 3-17, 5-16, 6-14, 7-14

REACTIONS (lb/size) 11=1213/ Mechanical, (min. 0-1-8), 17=1871/0-3-8, (min. 0-2-8)
 Max Horiz 17=210 (LC 10)
 Max Grav 11=1483 (LC 26), 17=2144 (LC 3)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-292/583, 3-4=-503/91, 4-5=-425/112, 5-6=-1242/323, 6-7=-1242/323, 7-8=-1932/473, 8-9=-2069/451, 9-10=-2103/334, 10-11=-860/0
 BOT CHORD 2-17=-372/322, 16-25=-46/819, 15-25=-46/819, 15-26=-46/819, 14-26=-46/819, 14-27=0/1212, 13-27=0/1212, 13-28=0/1212, 12-28=0/1212, 12-29=-159/1687, 29-30=-159/1687, 11-30=-159/1687
 WEBS 3-17=-2024/362, 3-16=0/1230, 5-16=-1071/265, 5-14=-118/920, 6-14=-415/176, 7-12=-184/921, 9-12=-445/289

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 20020029	Truss BE	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	--	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:51

Page: 1

ID:eEpoDsRRIUAFJEG4kllisznqUO-PmJ5hzBbiSdmpRBh5wtMRS6YcQVVrHkP0nkXDaznY16



Scale = 1:75.2

Plate Offsets (X, Y): [11:0-4-8,0-2-8], [19:0-4-8,0-2-8], [28:Edge,0-3-8]

Loading	(psf)	Spacing	2-0-0	CSI	0.74	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.76	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.22	Horz(CT)	-0.02	29	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 361 lb	FT = 20%

LUMBER	BRACING
TOP CHORD	TOP CHORD
BOT CHORD	BOT CHORD
WEBS	WEBS
OTHERS	
SLIDER	

REACTIONS All bearings 35-10-8.
 (lb) - Max Horiz 49=222 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 30, 31, 32, 33, 34, 35, 36, 39, 40, 41, 42, 43, 46, 47 except 29=-452 (LC 26), 48=-276 (LC 2), 49=-145 (LC 13)
 Max Grav All reactions 250 (lb) or less at joint(s) 29, 31, 32, 33, 34, 35, 36, 39, 40, 41, 42, 43, 46, 48 except 30=393 (LC 26), 37=402 (LC 2), 45=408 (LC 29), 47=255 (LC 2), 49=833 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-314/255, 3-4=-288/488, 4-5=-264/530, 5-6=-233/571, 6-7=-50/411, 7-8=-68/511, 8-9=0/436, 9-10=0/496, 10-11=-5/469, 11-12=-11/383, 12-13=-11/383, 13-14=-11/383, 14-15=-11/383, 15-16=-11/383, 16-17=-11/383, 17-18=-11/383, 18-19=-11/383, 19-20=-6/468, 20-21=-17/499, 21-22=-25/469, 22-23=-56/493, 23-24=-114/494, 24-25=-172/507, 25-26=-232/523, 26-27=-285/530, 27-28=-377/599, 28-29=-237/350
 BOT CHORD 2-52=-383/329, 51-52=-383/329, 50-51=-383/329, 49-50=-383/329, 48-49=-447/311, 47-48=-447/311, 46-47=-447/311, 45-46=-447/311, 44-45=-447/311, 43-44=-447/311, 42-43=-447/311, 41-42=-447/311, 40-41=-447/311, 39-40=-447/311, 38-39=-447/311, 37-38=-447/311, 36-37=-447/311, 35-36=-447/311, 34-35=-447/311, 33-34=-447/311, 32-33=-447/311, 31-32=-447/311, 30-31=-447/311, 29-30=-447/311
 WEBS 12-45=-362/17, 6-49=-409/307, 18-37=-361/17

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.

Job	Truss	Truss Type	Qty	Ply	Lamco_Sullivan
20020029	BE	Piggyback Base Supported Gable	1	1	Job Reference (optional)

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:51

Page: 2

ID:eEpoDsRRIUAFJEJG4klilsznqUO-PmJ5hzBbiSdmpRBh5wtMRS6YcQVVVRhkP0nkXDaznYI6

- 9) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 10) One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 29, 41, 42, 43, 45, 46, 47, 48, 49, 40, 39, 37, 36, 35, 34, 33, 32, 31, and 30. This connection is for uplift only and does not consider lateral forces.
- 11) Non Standard bearing condition. Review required.
- 12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- 14) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 20020029	Truss CE	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	--	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:52

Page: 1

ID:MbAQRBqGmai7NHHb7TAwrEznqRr-tzITuJCDTmldRbmufdObzgfK9qxcAAiYFRU4I0znY15



Scale = 1:58.8

Plate Offsets (X, Y): [11:0-2-8,0-1-13], [18:Edge,0-1-8], [19:Edge,0-1-8], [25:0-2-4,0-1-4]

Loading	(psf)	Spacing	2-0-0	CSI	0.69	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.69	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.32	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	0.00	19	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 255 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.2
OTHERS	2x4 SP No.2 *Except* ST3,ST2,ST1:2x4 SP No.3
SLIDER	Left 2x4 SP No.3 -- 1-11-1

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 11-18.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	1 Row at midpt 18-19, 10-27, 8-28, 12-26, 13-24, 14-23, 15-22, 16-21, 17-20

REACTIONS All bearings 27-4-8.

- (lb) - Max Horiz 2=332 (LC 12), 34=332 (LC 12)
- Max Uplift All uplift 100 (lb) or less at joint(s) 2, 19, 20, 21, 22, 23, 24, 26, 27, 28, 29, 30, 31, 32, 33, 34
- Max Grav All reactions 250 (lb) or less at joint(s) 2, 19, 20, 21, 22, 23, 24, 26, 27, 28, 29, 30, 31, 32, 33, 34

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 3-4=-490/452, 4-5=-434/405, 5-6=-375/356, 6-7=-316/307, 7-8=-258/258

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 19, 2, 27, 28, 29, 30, 31, 32, 33, 26, 24, 23, 22, 21, and 20. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 20020029	Truss D	Truss Type Piggyback Base	Qty 4	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	------------	------------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:52

Page: 1

ID:0AQNWVmsXUM?Mk?AK3BjXLznqRO-tzTuJCDTmIdRbmufdObzgfQq1A09YFRU4I0znY15




Job 20020029	Truss EA	Truss Type Attic	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	---------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:52

Page: 1

ID:RZhoszQkp4ALq17YUP90JkznqQY-tztTuJCDTmldRbmufdObzgfjrqwzAyFYFRU4I0znYI5



Scale = 1:65.1

Plate Offsets (X, Y): [5:0-3-0,Edge], [11:0-5-0,Edge], [12:0-5-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.71	Vert(LL)	-0.22	11-12	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	-0.33	11-12	>774	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.97	Horz(CT)	0.01	10	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.10	11-12	>999	360		
BCDL	10.0											
											Weight: 184 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.2 *Except* B2:2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.2 *Except* W1:2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 10=871/0-3-8, (min. 0-1-8), 13=871/0-3-8, (min. 0-1-8)
 Max Horiz 13=232 (LC 12)
 Max Grav 10=1229 (LC 27), 13=1229 (LC 26)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-509/215, 3-4=-852/175, 4-5=-76/575, 5-6=-77/575, 6-7=-852/175, 7-8=-509/215, 2-13=-587/215, 8-10=-587/214
 BOT CHORD 12-13=0/830, 11-12=0/858, 10-11=0/821
 WEBS 7-11=0/622, 3-12=0/622, 4-6=-1505/335, 3-13=-1009/0, 7-10=-1009/0

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 3-4, 6-7, 4-6; Wall dead load (5.0psf) on member(s).7-11, 3-12
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 11-12
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at j(s) 13 and 10. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.

LOAD CASE(S) Standard


Job 20020029	Truss EC	Truss Type Attic	Qty 3	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	---------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:52

Page: 1

ID:RZhoszQkp4ALq17YUP9QjknqQY-tzTtUJCDTmldRbmufdObzgfjrQwzAyxYFRU4I0znYI5



Scale = 1:65.1

Plate Offsets (X, Y): [10:0-5-0,Edge], [11:0-5-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	0.71	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.71	Vert(LL)	-0.22 10-11	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	-0.33 10-11	>771	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.99	Horz(CT)	0.01 9	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.10 10-11	>999	360		
BCDL	10.0									Weight: 184 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.2 *Except* B2:2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.2 *Except* W5,W1:2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 9=872/0-3-8, (min. 0-1-8), 12=830/0-3-8, (min. 0-1-8)
 Max Horiz 12=-228 (LC 11)
 Max Grav 9=1230 (LC 27), 12=1183 (LC 26)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-469/183, 2-3=-854/174, 3-4=-72/503, 4-5=-73/504, 5-6=-853/174, 6-7=-508/215, 1-12=-509/176, 7-9=-586/215
 BOT CHORD 11-12=0/831, 10-11=0/860, 9-10=0/822
 WEBS 6-10=0/623, 2-11=0/621, 3-13=-1456/330, 5-13=-1456/330, 2-12=-1032/0, 6-9=-1011/0

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 2-3, 5-6, 3-13, 5-13; Wall dead load (5.0psf) on member(s).6-10, 2-11
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 10-11
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at j(s) 12 and 9. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.

LOAD CASE(S) Standard


Job 20020029	Truss ED	Truss Type Attic	Qty 3	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	---------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:53

Page: 1

ID:KRzDCQmz6DW8gvxOqV2iaUznp6A-L9Rr6fDrE4tU2L4CLvqWtCuBE9UvVqhT5DeHSznY4



Scale = 1:64.1

Plate Offsets (X, Y): [3:0-2-1,0-2-0], [4:0-3-0,Edge], [5:0-2-1,0-2-0], [9:0-5-0,Edge], [12:0-5-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.67	Vert(LL)	-0.11	12-13	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.79	Vert(CT)	-0.20	12-13	>650	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.63	Horz(CT)	-0.02	11	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.11	11-12	>999	360		
BCDL	10.0											
											Weight: 172 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2 *Except* B2,B3:2x10 SP 2400F 2.0E
WEBS 2x4 SP No.2 *Except* W2,W7,W1:2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 0-3-8, except 8=0-3-8, 15=0-3-8
(lb) - Max Horiz 15=212 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) except 10=-125 (LC 9)
Max Grav All reactions 250 (lb) or less at joint(s) except 8=773 (LC 26), 10=378 (LC 27), 11=637 (LC 20), 15=842 (LC 26)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-540/201, 2-3=-564/152, 5-6=-609/159, 6-7=-283/175, 13-15=0/390, 1-15=0/390, 7-8=-302/160
BOT CHORD 12-13=-6/529, 11-12=0/529, 10-11=0/528, 9-10=-9/529, 8-9=0/522
WEBS 3-5=-732/262, 2-13=-282/0, 6-8=-654/10, 1-15=-898/37

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 2-3, 5-6, 3-5; Wall dead load (5.0psf) on member(s).2-12, 6-9
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 11-12, 10-11, 9-10
 - Refer to girder(s) for truss to truss connections.
 - Bearing at joint(s) 15 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8 and 15. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Attic room checked for L/360 deflection.

LOAD CASE(S) Standard


Job 20020029	Truss EE	Truss Type Attic	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	---------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:53

Page: 1

ID:RZhoszQkp4ALq17YUP90jknqQY-L9Rr6fDrE4tU2L4CLvqWICiFEDEvWvhT5DeHSznY14



Scale = 1:65.1

Plate Offsets (X, Y): [2:0-3-0,0-1-12], [4:0-2-8,0-2-12], [8:0-2-8,0-2-12], [10:0-3-0,0-1-12], [15:0-3-8,0-4-8], [16:0-3-8,0-4-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.73	Vert(LL)	-0.24	15-16	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.55	Vert(CT)	-0.37	15-16	>697	180	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.56	Horz(CT)	0.01	12	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH		Attic	0.03	17-18	>787	360		
BCDL	10.0											
											Weight: 210 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.2 *Except* B2:2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing.
 JOINTS 1 Brace at Jt(s): 22, 25

REACTIONS (lb/size) 12=885/0-3-8, (min. 0-1-8), 19=932/0-3-8, (min. 0-1-11)
 Max Horiz 19=232 (LC 12)
 Max Grav 12=1275 (LC 27), 19=1428 (LC 26)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-711/57, 3-4=-785/154, 4-5=-902/160, 5-6=-46/576, 6-7=-52/551, 7-8=-922/154, 8-9=-616/202, 9-10=-486/125,
 2-19=-679/73, 10-12=-459/139
 BOT CHORD 18-19=0/907, 17-18=0/907, 16-17=0/907, 15-16=0/940, 14-15=0/867, 13-14=0/867, 12-13=0/867
 WEBS 8-15=-53/1085, 4-16=-116/883, 5-20=-1615/277, 7-20=-1615/277, 19-23=-876/6, 22-23=-755/0, 21-22=-836/0,
 4-21=-951/140, 8-24=-1321/27, 24-25=-960/0, 25-26=-871/0, 12-26=-1057/0, 14-24=-442/93, 9-26=-252/71

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- All plates are MT20 plates unless otherwise indicated.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2'-0" oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 4-5, 7-8, 5-20, 7-20; Wall dead load (5.0psf) on member(s). 8-15, 4-16, 17-21, 18-22
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 17-18, 16-17, 15-16
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 19 and 12. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- NOTE: DUE TO THE OVERALL LENGTH TO DEPTH RATIO OF THE ROOM, THE FLOOR MAY EXHIBIT OBJECTIONABLE VIBRATION AND OR BOUNCE. BUILDING DESIGNER TO CONSIDER PROVIDING MEANS TO DAMPEN THESE EFFECTS. TRUSS DESIGN SHALL BE REVIEWED AND APPROVED PRIOR TO MANUFACTURING.
- Attic room checked for L/360 deflection.

Job 20020029	Truss EE	Truss Type Attic	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	---------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:53

Page: 2

ID:RZhoszQkp4ALq17YUP9OjknqQY-L9Rr6fDrE4tU2IL4CLvqWICiFEDEvWvhT5DeHSznYI4

LOAD CASE(S) Standard


Job 20020029	Truss EF	Truss Type Attic	Qty 4	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	---------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:54

Page: 1

ID:Cxz075ZsH0h5ZY2VxO97IXznZZZ-pL?EJ?DT?N?LgwwGm2R325k5WecHeu0rlzBqvznY13



Scale = 1:68.1

Plate Offsets (X, Y): [3:0-2-1,0-2-0], [5:0-2-1,0-2-0], [9:0-5-0,Edge], [10:0-5-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.57	Vert(LL)	-0.22	9-10	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.37	Vert(CT)	-0.33	9-10	>778	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.89	Horz(CT)	0.01	8	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.10	9-10	>999	360		
BCDL	10.0											
											Weight: 181 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP 2400F 2.0E
BOT CHORD 2x6 SP No.2 *Except* B2:2x10 SP 2400F 2.0E
WEBS 2x4 SP No.2 *Except* W6,W9,W1:2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 8=833/0-3-8, (min. 0-1-8), 14=810/0-3-8, (min. 0-1-8)
Max Horiz 14=212 (LC 12)
Max Grav 8=1200 (LC 27), 14=1157 (LC 26)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-686/202, 2-3=-837/177, 3-4=-66/475, 4-5=-69/470, 5-6=-866/174, 6-7=-455/175, 7-8=-499/168, 11-14=0/546, 1-14=0/546
BOT CHORD 10-11=0/816, 9-10=0/843, 8-9=0/805
WEBS 2-10=0/621, 6-9=0/615, 3-12=-1451/329, 5-12=-1451/329, 6-8=-1031/0, 2-11=-659/0, 1-14=-1237/49

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 2-3, 5-6, 3-12, 5-12; Wall dead load (5.0psf) on member(s). 2-10, 6-9
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 9-10
 - Bearing at joint(s) 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8 and 14. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Attic room checked for L/360 deflection.

LOAD CASE(S) Standard


Job 20020029	Truss F	Truss Type Common	Qty 2	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	------------	----------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:54

Page: 1

ID:TiEE9NwIYKk2zKJw02ANFznZOm-pL?EJ?DT?N?LgwwGm2R325kBSefte4prlizBqvznYI3



Scale = 1:41.2

Plate Offsets (X, Y): [2:Edge,0-0-12], [4:Edge,0-0-12]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	0.01	5-11	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.14	Vert(CT)	-0.02	5-11	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 77 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE Left: 2x4 SP No.3
 Right: 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6'-0" oc purlins.
 Rigid ceiling directly applied or 10'-0" oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 2=443/0-3-8, (min. 0-1-8), 4=408/0-3-8, (min. 0-1-8)
 Max Horiz 2=107 (LC 10)
 Max Grav 2=526 (LC 2), 4=482 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-514/127, 3-4=-513/127
 BOT CHORD 2-5=-144/309, 4-5=0/309

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4 and 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 20020029	Truss FE	Truss Type Common Supported Gable	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	--------------------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:54

Page: 1

ID:?mnZDHkKmwBXV1?BLalubOznZnj-pL?EJ?DT?N?LgwwGm2R325kC?ehHe4LrlizBqvznY13



Scale = 1:42.1

Loading	(psf)	Spacing	2-0-0	CSI	0.09	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.10	Horz(CT)	0.00	9	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 70 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3 *Except* ST3:2x4 SP No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 6'-0'-0" oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6'-0'-0" oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 12-1-0.
(lb) - Max Horiz 15=129 (LC 10)
Max Uplift All uplift 100 (lb) or less at joint(s) 9, 10, 11, 13, 14, 15
Max Grav All reactions 250 (lb) or less at joint(s) 9, 10, 11, 12, 13, 14, 15

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 2'-0" oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15, 9, 12, 13, 14, 11, and 10. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 20020029	Truss FG	Truss Type Common Girder	Qty 1	Ply 2	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	-----------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:55

Page: 1

ID:TEsN?RycXSS_goNeOM46KAznZNR-HYZcXLE5mh7CI3VTkmylhl11vYNjr_xPikMLznY12



Scale = 1:45.6

Plate Offsets (X, Y): [2:Edge,0-4-0], [4:Edge,0-4-0]

Loading	(psf)	Spacing	2-0-0	CSI	0.20	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.20	Vert(LL)	-0.05	5-11	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.56	Vert(CT)	-0.10	5-11	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.98	Horz(CT)	0.01	2	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 167 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP 2400F 2.0E
 WEBS 2x4 SP No.3
 WEDGE Left: 2x10 SP 2400F 2.0E
 Right: 2x10 SP 2400F 2.0E

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=3417/0-3-8, (min. 0-1-11), 4=3398/0-3-8, (min. 0-1-11)
 Max Horiz 2=107 (LC 30)
 Max Grav 2=4039 (LC 3), 4=4022 (LC 3)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-4041/0, 3-4=-4040/0
 BOT CHORD 2-12=-228/3061, 12-13=0/3061, 5-13=0/3061, 5-14=0/3061, 14-15=0/3061, 4-15=0/3061
 WEBS 3-5=0/4747

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.
 Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load; Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4 and 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- Use USP THD26 (With 18-16d nails into Girder & 12-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 2-0-12 from the left end to 10-0-12 to connect truss(es) BA (1 ply 2x6 SP) to back face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Job	Truss	Truss Type	Qty	Ply	Lamco_Sullivan
20020029	FG	Common Girder	1	2	Job Reference (optional)

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:55

Page: 2

ID:TEsN?RycXSS_goNeOM46KAznZNR-HYZcXLE5mh7CI3VTKmylbiHL11vYnJr_xPikMLznYI2

Uniform Loads (lb/ft)

Vert: 1-3=-48, 3-4=-48, 6-9=-20

Concentrated Loads (lb)

Vert: 5=-1193, 12=-1193, 13=-1193, 14=-1193, 15=-1193


Job 20020029	Truss PB	Truss Type Piggyback	Qty 14	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	-------------------------	-----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:55

Page: 1

ID:Q600IDkrRY3hlt1SIJsrPzna11-HYZcXLE5mh7CI3VTKmylbiHML10uNYE_xPikMLznY12



Scale = 1:32.4

Plate Offsets (X, Y): [2:0-2-9,0-1-8], [6:0-2-9,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.09	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	6	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 46 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 10-11-4.
 (lb) - Max Horiz 2=-78 (LC 11), 11=-78 (LC 11)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 6, 8, 10, 11, 15
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 6, 11, 15 except
 8=298 (LC 26), 9=268 (LC 2), 10=299 (LC 25)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-10=-260/179, 5-8=-260/179

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 6, 9, 10, and 8. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 20020029	Truss PBA	Truss Type Piggyback	Qty 8	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	--------------	-------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:55

Page: 1

ID:es_MekgPkq0nYv6t29actMznqSo-HYZcXLE5mh7Ct3VTkmylbIHMC10uNYE_xPikMLznYl2



Scale = 1:34.6

Loading	(psf)	Spacing	2-0-0	CSI	0.19	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.09	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH							Weight: 47 lb	FT = 20%
BCDL	10.0											

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6'-0" oc purlins.
 Rigid ceiling directly applied or 10'-0" oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 12-4-12.
 (lb) - Max Horiz 1=-79 (LC 9)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 6, 8
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 5 except 6=310 (LC 25), 7=267 (LC 2), 8=317 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-8=-260/173

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - Gable requires continuous bottom chord bearing.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7, 8, and 6. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 20020029	Truss PBB	Truss Type Piggyback	Qty 4	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	--------------	-------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:55

Page: 1

ID:Y_s?JAIEmAE9kaQzmMgU_8znqRP-HYZcXLE5mh7Ci3VTkmyblHGP1?eNXw_xPikMLznYI2



Scale = 1:31.8

Plate Offsets (X, Y): [3:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.56	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 34 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6'-0-0 oc purlins, except end verticals.

Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=88/8-6-6, (min. 0-1-8), 5=84/8-6-6, (min. 0-1-8), 6=396/8-6-6, (min. 0-1-8)
 Max Horiz 1=104 (LC 10)
 Max Uplift 1=-11 (LC 9), 5=-9 (LC 9), 6=-14 (LC 10)
 Max Grav 1=126 (LC 25), 5=113 (LC 25), 6=481 (LC 24)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-6=-381/208

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06"-00 tall by 2'-00"-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 6. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 20020029	Truss PBE	Truss Type Piggyback	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	--------------	-------------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:55

Page: 1

ID:hsi1pAQADtwX4wAtyKjEfRznqUQ-HYZcXLE5mh7Ci3VTKmylbiHML10uNYE_xPikMLznY12



Scale = 1:32.4

Plate Offsets (X, Y): [2:0-2-9,0-1-8], [6:0-2-9,0-1-8]

Loading	(psf)	Spacing	2-0-0	CSI	0.18	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.09	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horz(CT)	0.00	6	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 46 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 10-11-4.
(lb) - Max Horiz 2=-78 (LC 11), 11=-78 (LC 11)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 6, 8, 10, 11, 15
Max Grav All reactions 250 (lb) or less at joint(s) 2, 6, 11, 15 except
8=298 (LC 26), 9=268 (LC 2), 10=299 (LC 25)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-10=-260/179, 5-8=-260/179

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 6, 9, 10, and 8. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 20020029	Truss V	Truss Type Valley	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	------------	----------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:56

Page: 1

ID:SJDrRP?dq5_w7W06PXo4eznZsN-mk7_khFjX?F3vC4fuTTX8WqWARLj6?T8A3SlunznY11



Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.24	Vert(LL)	n/a	-	n/a	999	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.18	Vert(TL)	n/a	-	n/a	999	
TCDL	10.0	Rep Stress Incr	YES	WB	0.06	Horiz(TL)	0.00	3	n/a	n/a	
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-SH							
BCDL	10.0									Weight: 36 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=148/9-5-3, (min. 0-1-8), 3=150/9-5-3, (min. 0-1-8),
 4=290/9-5-3, (min. 0-1-8)
 Max Horiz 1=-72 (LC 9)
 Max Uplift 1=-5 (LC 14), 3=-11 (LC 14)
 Max Grav 1=177 (LC 2), 3=179 (LC 2), 4=337 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 3, and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 20020029	Truss VA	Truss Type Valley	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	----------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:56

Page: 1

ID: ?1l_n5x_m8K72eoSqfYtnzznZNS-mk7_khFjX?F3vC4fuTTX8WqXjRNI6?x8A3SlunznY11



Scale = 1:30.1

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.14	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.05	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	n/a	-	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-P								
BCDL	10.0										Weight: 23 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=103/6-2-13, (min. 0-1-8), 3=105/6-2-13, (min. 0-1-8),
4=163/6-2-13, (min. 0-1-8)
Max Horiz 1=45 (LC 12)
Max Uplift 1=-10 (LC 14), 3=-14 (LC 14)
Max Grav 1=125 (LC 2), 3=127 (LC 2), 4=187 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 3, and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 20020029	Truss VB	Truss Type Valley	Qty 1	Ply 1	Lamco_Sullivan Job Reference (optional)
-----------------	-------------	----------------------	----------	----------	--

Carter Components - Sanford, Sanford, NC, user

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Fri Feb 07 11:47:56

Page: 1

ID: ?1l_n5x_m8K72eoSqfYtnzznZNS-mk7_khFjX?F3vC4fuTTX8WqZcRNw6?O8A3SlunznY11



Scale = 1:25.1

Plate Offsets (X, Y): [2:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.02	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.04	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	n/a	-	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-P							Weight: 9 lb	FT = 20%
BCDL	10.0											

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 3-1-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=77/3-0-6, (min. 0-1-8), 3=77/3-0-6, (min. 0-1-8)
Max Horiz 1=-19 (LC 9)
Max Grav 1=91 (LC 2), 3=91 (LC 2)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 3. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard