

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	A	ATTIC	8	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:18 2020 Page 1
 ID:qVvPb7bITNTQeBoz4CnhCwycNjr-EwLXLyAPCsPQ1g_sUB9onna8P43gEfbC1Hn?iAybTPl




Plate Offsets (X,Y)-- [2:0-1-0,0-2-0], [8:0-2-2,Edge], [10:0-2-2,Edge], [16:0-1-0,0-2-0]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.70	Vert(LL) -0.25 20-24 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.98	Vert(CT) -0.48 20-24 >616 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.64	Horz(CT) 0.05 18 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS	Attic -0.09 20-24 660 360		
				Weight: 228 lb	FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.2 *Except*
 T3: 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 *Except*
 B2: 2x4 SP No.2 or 2x4 SPF No.2, B3: 2x4 SP No.1
 WEBS 2x4 SP No.3 *Except*
 W5,W1: 2x4 SP No.2 or 2x4 SPF No.2, W7: 2x6 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 8-10, 6-7, 12-13.
 BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
 WEBS 3 Rows at 1/4 pts 21-26
 JOINTS 1 Brace at Jt(s): 6, 7, 12, 13, 29

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 28=1203/0-3-8 (min. 0-1-15), 18=1203/0-3-8 (min. 0-1-15)
 Max Horz 28=-341(LC 10)
 Max Uplift 28=-8(LC 12), 18=-8(LC 13)
 Max Grav 28=1220(LC 2), 18=1220(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1140/101, 3-4=-955/122, 4-5=-900/317, 8-9=-73/433, 9-10=-73/433, 11-14=-903/316, 14-15=-955/121, 15-16=-1140/101, 2-28=-1169/166, 16-18=-1169/166, 6-7=-281/343, 12-13=-284/347
 BOT CHORD 27-28=-329/483, 25-27=0/2191, 24-25=0/2191, 20-24=0/2191, 19-20=0/2191, 18-19=-110/278
 WEBS 26-27=0/378, 6-26=0/386, 4-6=-76/430, 23-26=-189/278, 22-23=-1662/0, 21-22=-197/287, 19-21=0/379, 13-21=0/387, 13-14=-80/433, 5-7=-1238/417, 7-29=-1171/354, 12-29=-1171/354, 11-12=-1235/413, 2-27=-41/607, 16-19=-50/609, 23-24=0/332, 20-22=0/332, 23-27=-1824/0, 19-22=-1823/0

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) All plates are 1.5x4 MT20 unless otherwise indicated.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 7) Ceiling dead load (5.0 psf) on member(s). 23-26, 22-23, 21-22, 5-7, 7-29, 12-29, 11-12; Wall dead load (5.0psf) on member(s).23-24, 20-22
 - 8) Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 20-24
 - 9) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 28 and 18. This connection is for uplift only and does not consider lateral forces.
 - 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 12) Attic room checked for L/360 deflection.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	A	ATTIC	8	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:18 2020 Page 2
ID:qVyPb7bITNTQeBoz4CnhCwycNrx-EwLXLyAPCsPQ1g_sUB9onna8P43gEfbC1Hn?!AybTpi

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	A1	ATTIC	3	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:22 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjrj-7hb2BJDvG5wsWHldj1EkYdIp8iQBATYnxvIDSybtPth




Plate Offsets (X,Y)-- [1:0-1-12,0-2-0], [7:0-2-2,Edge], [9:0-2-2,Edge], [15:0-1-0,0-2-0]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.71	Vert(LL) -0.25 19-23 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.98	Vert(CT) -0.48 19-23 >611 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.64	Horz(CT) 0.04 17 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS	Attic -0.09 19-23 660 360		Weight: 224 lb FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.2 *Except*
 T3: 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 *Except*
 B2: 2x4 SP No.2 or 2x4 SPF No.2, B3: 2x4 SP No.1
 WEBS 2x4 SP No.3 *Except*
 W5,W1: 2x4 SP No.2 or 2x4 SPF No.2, W7: 2x6 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-11-9 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 7-9, 5-6, 11-12.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 19-23.
 WEBS 3 Rows at 1/4 pts 20-25
 JOINTS 1 Brace at Jt(s): 5, 6, 11, 12, 28

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 27=1114/0-3-8 (min. 0-1-13), 17=1206/0-3-8 (min. 0-1-15)
 Max Horz 27=-329(LC 8)
 Max Uplift 17=-7(LC 13)
 Max Grav 27=1146(LC 2), 17=1222(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1131/88, 2-3=-956/108, 3-4=-919/318, 7-8=-77/445, 8-9=-77/445,
 10-13=-899/317, 13-14=-958/119, 14-15=-1143/99, 1-27=-1094/105,
 15-17=-1172/165, 5-6=-280/351, 11-12=-286/344
 BOT CHORD 26-27=-299/430, 24-26=0/2203, 23-24=0/2203, 19-23=0/2203, 18-19=0/2203,
 17-18=-110/278
 WEBS 25-26=0/362, 5-25=0/372, 3-5=-86/409, 22-25=-200/279, 21-22=-1667/0,
 20-21=-196/290, 18-20=0/381, 12-20=0/388, 12-13=-79/439, 4-6=-1266/420,
 6-28=-1183/356, 11-28=-1183/356, 10-11=-1245/414, 1-26=-23/618,
 15-18=-49/612, 22-23=0/331, 19-21=0/333, 22-26=-1817/0, 18-21=-1830/0

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are 1.5x4 MT20 unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 22-25, 21-22, 20-21, 4-6, 6-28, 11-28, 10-11; Wall dead load (5.0psf) on member(s). 22-23, 19-21
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 19-23
 - One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 27 and 17. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Continued on page 2

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	A1	ATTIC	3	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:22 2020 Page 2
 ID:qVyPb7bITNTQeBoz4CnhCwycNrx-7hb2BJDvG5wsWHldj1Ekydlp8iQbATYnxvIDSxybTph

NOTES-

12) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	AE	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:27 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNri-TfOXe0H24dY8c2AaVaqwfhSg717nrjpW5BS_79ybTpc




Plate Offsets (X,Y)-- [2:0-1-0,0-2-0], [8:0-2-2,Edge], [10:0-2-2,Edge], [16:0-1-0,0-2-0]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.70	Vert(LL) -0.25 20-24 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.98	Vert(CT) -0.48 20-24 >616 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.64	Horz(CT) 0.05 18 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS	Attic -0.09 20-24 660 360		
				Weight: 251 lb	FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.2 *Except*
 T3: 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 *Except*
 B2: 2x4 SP No.2 or 2x4 SPF No.2, B3: 2x4 SP No.1
 WEBS 2x4 SP No.3 *Except*
 W5,W1: 2x4 SP No.2 or 2x4 SPF No.2, W7: 2x6 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 8-10, 6-7, 12-13.
 BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
 WEBS 3 Rows at 1/4 pts 21-26
 JOINTS 1 Brace at Jt(s): 6, 7, 12, 13, 29

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 28=1203/0-3-8 (min. 0-1-15), 18=1203/0-3-8 (min. 0-1-15)
 Max Horz 28=-341(LC 10)
 Max Uplift 28=-8(LC 12), 18=-8(LC 13)
 Max Grav 28=1220(LC 2), 18=1220(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1140/101, 3-4=-955/122, 4-5=-900/317, 8-9=-73/433, 9-10=-73/433, 11-14=-903/316, 14-15=-955/121, 15-16=-1140/101, 2-28=-1169/166, 16-18=-1169/166, 6-7=-281/343, 12-13=-284/347
 BOT CHORD 27-28=-329/483, 25-27=0/2191, 24-25=0/2191, 20-24=0/2191, 19-20=0/2191, 18-19=-110/278
 WEBS 26-27=0/378, 6-26=0/386, 4-6=-76/430, 23-26=-189/278, 22-23=-1662/0, 21-22=-197/287, 19-21=0/379, 13-21=0/387, 13-14=-80/433, 5-7=-1238/417, 7-29=-1171/354, 12-29=-1171/354, 11-12=-1235/413, 2-27=-41/607, 16-19=-50/609, 23-24=0/332, 20-22=0/332, 23-27=-1824/0, 19-22=-1823/0

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) All plates are 1.5x4 MT20 unless otherwise indicated.
 - 6) Gable studs spaced at 2-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 9) Ceiling dead load (5.0 psf) on member(s). 23-26, 22-23, 21-22, 5-7, 7-29, 12-29, 11-12; Wall dead load (5.0psf) on member(s).23-24, 20-22
 - 10) Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 20-24
 - 11) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 28 and 18. This connection is for uplift only and does not consider lateral forces.
 - 12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	AE	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:27 2020 Page 2
 ID:qVyPb7bITNTQeBoz4CnhCwycNrx-TfOxE0H24dY8c2AaVaqwfhSg7i7nrjpW5BS_79ybTpc

NOTES-

- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 14) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	B	Roof Special	10	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:30 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjr-uD44s2KwNYwjTWv9BiNdGJ48kwJm27Ezn9hekUybTpZ




Plate Offsets (X,Y)-- [2-0-2-14,0-3-0]					
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.86	Vert(LL) -0.03 10-12 >999 240	MT20	197/144
TCDL 10.0	Lumber DOL 1.15	BC 0.32	Vert(CT) -0.07 10-12 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.47	Horz(CT) -0.01 7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-MS			Weight: 120 lb FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 6-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=140/Mechanical, 12=481/0-3-8 (min. 0-1-8), 9=987/0-3-8 (min. 0-1-9)
 Max Horz 12=350(LC 9)
 Max Uplift 7=-137(LC 9), 12=-137(LC 8), 9=-169(LC 8)
 Max Grav 7=224(LC 19), 12=481(LC 1), 9=987(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-499/102, 3-4=-402/114, 4-5=-227/363, 2-12=-424/198
 BOT CHORD 11-12=-585/551, 10-11=-585/551, 9-10=-421/484
 WEBS 4-10=0/264, 4-9=-792/304, 5-9=-576/154



- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 137 lb uplift at joint 7.
 - 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 12 and 9. This connection is for uplift only and does not consider lateral forces.
 - 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	BE	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:37 2020 Page 1
 ID:qVyPb7blTNTQeBoz4CnhCwycNrx-Aa?JKRPJkipjpbxV5g?G2osLzkiPBiz?OktWTaybTpS



Scale = 1:51.7

Plate Offsets (X,Y)-- [2:0-2-14,0-3-0], [24:0-1-15,0-0-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.86	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.32	Vert(LL) -0.03 10-12 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.47	Vert(CT) -0.07 10-12 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) -0.01 7 n/a n/a		
	Code IRC2015/TPI2014			Weight: 156 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS 1 Row at midpt 6-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=140/Mechanical, 12=481/0-3-8 (min. 0-1-8), 9=987/0-3-8 (min. 0-1-9)

Max Horz 12=350(LC 9)
 Max Uplift 7=-137(LC 9), 12=-137(LC 8), 9=-169(LC 8)
 Max Grav 7=224(LC 19), 12=481(LC 1), 9=987(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-499/102, 3-4=-402/114, 4-5=-227/363, 2-12=-424/198
 BOT CHORD 11-12=-585/551, 10-11=-585/551, 9-10=-421/484
 WEBS 4-10=0/264, 4-9=-792/304, 5-9=-576/154

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 3) All plates are 1.5x4 MT20 unless otherwise indicated.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 137 lb uplift at joint 7.
- 9) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 12 and 9. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	C	Common	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:41 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjr-3LEEApsqnwJ9ICFHkW4CDe167M2P7AiaJMrdLybTpO



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.53	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.45	Vert(LL) -0.08 8-9 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.17	Vert(CT) -0.16 8-9 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.01 8 n/a n/a		
	Code IRC2015/TPI2014			Weight: 67 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 10=670/0-3-8 (min. 0-1-8), 8=670/0-3-8 (min. 0-1-8)
 Max Horz 10=-94(LC 10)
 Max Uplift 10=-95(LC 12), 8=-95(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 3-4=-621/202, 4-5=-621/202
 BOT CHORD 9-10=-55/474, 8-9=-55/474
 WEBS 4-9=0/308, 3-10=-772/243, 5-8=-772/243

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 10 and 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	C1	COMMON	5	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:45 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNri-x6UI0AVLr9pbmpY2ZM88NUCnfzOH3_gAE_pxm6ybTpK



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.56	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.45	Vert(LL) -0.08 7-8 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.17	Vert(CT) -0.16 7-8 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.01 7 n/a n/a		
	Code IRC2015/TPI2014			Weight: 65 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 9=673/0-3-8 (min. 0-1-8), 7=585/0-3-8 (min. 0-1-8)
 Max Horz 9=98(LC 9)
 Max Uplift 9=95(LC 12), 7=66(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 3-4=-630/202, 4-5=-627/203
 BOT CHORD 8-9=-103/481, 7-8=-103/481
 WEBS 4-8=0/309, 3-9=-782/244, 5-7=-762/283

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9 and 7. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	C2	COMMON	4	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:49 2020 Page 1
ID:qVyPb7bITNTQeBoz4CnhCwycNjr-qtjFsYYrvOJ0FRspoCD4YKMTkamA?ohm9cn8vtybTpG



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.56	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.45	Vert(LL) -0.08 6-7 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.17	Vert(CT) -0.16 6-7 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.01 6 n/a n/a		
	Code IRC2015/TPI2014			Weight: 63 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=588/0-3-8 (min. 0-1-8), 6=588/0-3-8 (min. 0-1-8)
 Max Horz 8=86(LC 9)
 Max Uplift 8=66(LC 12), 6=66(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-636/204, 3-4=-636/204
 BOT CHORD 7-8=-104/489, 6-7=-104/489
 WEBS 3-7=0/310, 2-8=-772/284, 4-6=-772/283

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8 and 6. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	CE	Common Supported Gable	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:53 2020 Page 1
ID:qVyPb7bITNTQeBoz4CnhCwycNnj-ifzmhvbMycqSk29a110iAXGUBEZxeNL4EIM2eybTpC



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.12	Vert(LL)	-0.01 11	n/r	120	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.04	Vert(CT)	-0.01 11	n/r	90		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.06	Horz(CT)	0.00 12	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-R					Weight: 84 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 15-0-0.
 (lb) - Max Horz 20=-94(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 20, 12, 17, 18, 19, 15, 14, 13
 Max Grav All reactions 250 lb or less at joint(s) 20, 12, 16, 17, 18, 19, 15, 14, 13

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 20, 12, 17, 18, 19, 15, 14, and 13. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	D	Common	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:56 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjrj-7EevKxeEFC1bVu9iArjKo9ltPDb8_SomC_0ezybTtp9



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.24	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.21	Vert(LL) -0.02 9-10 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.10	Vert(CT) -0.05 9-10 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.00 8 n/a n/a		
	Code IRC2015/TPI2014			Weight: 52 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 10=496/0-3-8 (min. 0-1-8), 8=496/0-3-8 (min. 0-1-8)
 Max Horz 10=-81(LC 10)
 Max Uplift 10=-75(LC 12), 8=-75(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 3-4=-384/162, 4-5=-384/162
 BOT CHORD 9-10=-43/287, 8-9=-43/287
 WEBS 3-10=-468/144, 5-8=-468/143

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 10 and 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	D1	Common	4	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:57 2020 Page 1
ID:qVyPb7bITNTQeBoz4CnhCwycNjrj-bQCHXHes0rKuDFTLGtMys0hwooZmtRgx?sjZBQybTp8



Scale = 1:24.9



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.23	Vert(LL)	-0.02	7-8	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.21	Vert(CT)	-0.05	7-8	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.10	Horz(CT)	0.01	6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS							
									Weight: 48 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=415/0-3-8 (min. 0-1-8), 6=415/0-3-8 (min. 0-1-8)
 Max Horz 8=73(LC 9)
 Max Uplift 8=46(LC 12), 6=46(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-402/165, 3-4=-402/165
 BOT CHORD 7-8=-93/306, 6-7=-93/306
 WEBS 2-8=-474/187, 4-6=-474/187

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8 and 6. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	DE	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:33:59 2020 Page 1
ID:qVyPb7bITNTQeBoz4CnhCwycNnj-XpK1yzg7YSacSzdkNIPQyRnHzcH4LLAES9CgFlybTp6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.12	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) -0.01 9 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Vert(CT) -0.01 9 n/r 90		
BCDL 10.0	Rep Stress Incr YES	Matrix-R	Horz(CT) 0.00 10 n/a n/a		
	Code IRC2015/TPI2014			Weight: 58 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 10-8-0.
 (lb) - Max Horz 16=-81(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 16, 10, 14, 15, 12, 11
 Max Grav All reactions 250 lb or less at joint(s) 16, 10, 13, 14, 15, 12, 11

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 1.5x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 16, 10, 14, 15, 12, and 11. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	J1	Jack-Open	6	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:01 2020 Page 1

ID:qVyPb7bITNTQeBoz4CnhCwycNnj-TBSofNfiN44qJhHm7VjRu1ssbCQyipFyXvThnKBybTp4



Scale = 1:13.9

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.21	Vert(LL) -0.00	5	>999	240	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.09	Vert(CT) -0.00	5	>999	180		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Horz(CT) 0.00		n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS						
	Code IRC2015/TPI2014						Weight: 12 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=182/0-3-8 (min. 0-1-8), 4=36/Mechanical
 Max Horz 5=56(LC 9)
 Max Uplift 5=-17(LC 12), 4=-37(LC 12)
 Max Grav 5=182(LC 1), 4=41(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	J1A	Monopitch	8	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:03 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNnj-QaZYokJdch41xawVc8TM6HxpxDeAH9lqNnAuO3ybTp2



Scale = 1:13.9

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.20	Vert(LL)	-0.00	5	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.09	Vert(CT)	-0.00	5	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	-0.00	4	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MR						Weight: 12 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 4=36/Mechanical, 5=182/0-3-8 (min. 0-1-8)
 Max Horz 5=87(LC 11)
 Max Uplift 4=47(LC 9), 5=-39(LC 12)
 Max Grav 4=49(LC 19), 5=182(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4 and 5. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	M2	Monopitch	7	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:06 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjrj-q9FhQMIWucSco2f4IG13kvZR_RToURsG3IPY?OybTp?



Scale = 1:55.6

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.27	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.86	Vert(LL) -0.23 7-8 >404 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.36	Vert(CT) -0.47 7-8 >202 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) -0.00 7 n/a n/a		
	Code IRC2015/TPI2014			Weight: 69 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 8-5-9 oc bracing.
 WEBS 1 Row at midpt 4-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 7=321/Mechanical, 8=405/0-3-8 (min. 0-1-8)

Max Horz 8=336(LC 12)
 Max Uplift 7=-294(LC 12)
 Max Grav 7=428(LC 19), 8=405(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-8=-272/253
 WEBS 3-7=-327/306, 3-8=-409/245

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 7=294.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	M3	MONOPITCH	6	1	Job Reference (optional)


84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:08 2020 Page 1

ID:qVyPb7bITNTQeBoz4CnhCwycNjr-mXNRr2nmQDiK1LpTPh3XpkfgFEGXyN2ZW3uf3HybToz



Scale = 1:42.8



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.73	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.39	Vert(LL) -0.06 5-6 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.25	Vert(CT) -0.12 5-6 >578 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) -0.00 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 45 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=314/0-3-8 (min. 0-1-8), 5=219/Mechanical
 Max Horz 6=237(LC 12)
 Max Uplift 5=216(LC 12)
 Max Grav 6=314(LC 1), 5=276(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-6=-259/0
 BOT CHORD 5-6=-320/254
 WEBS 2-5=-267/336

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=216.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	M3A	GABLE	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:10 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNnj-jwUCGkp0yrz2GfyrX65?ulk_22x0QHyr_NNI79ybTos



Scale = 1:45.4



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.84	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.46	Vert(LL) 0.08 5-6 >892 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.25	Vert(CT) -0.12 5-6 >547 180		
BCDL 10.0	Rep Stress Incr NO	Matrix-MP	Horz(CT) -0.00 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 57 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 9-8-9 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=349/0-3-8 (min. 0-1-8), 5=239/Mechanical
 Max Horz 6=237(LC 12)
 Max Uplift 6=-19(LC 8), 5=-276(LC 12)
 Max Grav 6=349(LC 1), 5=303(LC 41)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-6=-259/0
 BOT CHORD 6-11=-320/254, 11-12=-320/254, 12-13=-320/254, 5-13=-320/254
 WEBS 2-5=-267/336

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=276.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 31 lb down and 50 lb up at 0-5-8, and 26 lb down and 51 lb up at 2-5-8, and 26 lb down and 51 lb up at 4-5-8 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-2=-60, 2-3=-60, 4-6=-20

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	M3A	GABLE	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334


8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:10 2020 Page 2
ID:qVyPb7bITNTQeBoz4CnhCwycNrx-jwUCGkp0yrz2GfyrX65?ulk_22x0QHyr_NNI79ybTox

LOAD CASE(S) Standard
Concentrated Loads (lb)
Vert: 11=-23(F) 12=-16(F) 13=-16(F)


Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	M5	MONOPITCH	4	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:13 2020 Page 1
 ID:qVyPb7blTNTQeBoz4CnhCwycNri-7VAKulrvFmLc77hQCEfiWOMYxFy_dc0IgLbQkUybTou



Scale = 1:46.3



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.67	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.50	Vert(LL) -0.09 5-6 >823 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.33	Vert(CT) -0.18 5-6 >412 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) -0.00 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 50 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 9-8-9 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=340/0-3-8 (min. 0-1-8), 5=247/Mechanical
 Max Horz 6=263(LC 12)
 Max Uplift 5=233(LC 12)
 Max Grav 6=340(LC 1), 5=306(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-6=-278/0
 BOT CHORD 5-6=-343/274
 WEBS 2-5=-285/357, 3-5=-273/214

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Refer to girder(s) for truss to truss connections.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=233.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	M5E	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:16 2020 Page 1
 ID:qVvYp7blTTNTQeBoz4CnhCwycNri-X4sTWntnYhjB_aQ?tNCP80_2BT_hqzmkMj4LpybTor



Scale = 1:46.3



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.67	Vert(LL)	-0.09	5-6	>823	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.50	Vert(CT)	-0.18	5-6	>412		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.33	Horz(CT)	-0.00	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP						
								Weight: 61 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 9-8-9 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=340/0-3-8 (min. 0-1-8), 5=247/Mechanical
 Max Horz 6=263(LC 12)
 Max Uplift 5=233(LC 12)
 Max Grav 6=340(LC 1), 5=306(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-6=-278/0
 BOT CHORD 5-6=-343/274
 WEBS 2-5=-285/357, 3-5=-273/214

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=233.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	M6	MONOPITCH	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:18 2020 Page 1
 ID:qVyPb7blTNTQeBoz4CnhCwycNnj-USzDxTv14IzvEuaO?nEtDR3O1Ghelu31qdJBPybTop



Scale = 1:40.7



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.65	Vert(LL)	-0.05	5-6	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.34	Vert(CT)	-0.09	5-6	>696		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.22	Horz(CT)	-0.00	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP						
								Weight: 43 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-8-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 6=302/0-3-8 (min. 0-1-8), 5=205/Mechanical
 Max Horz 6=224(LC 12)
 Max Uplift 5=207(LC 12)
 Max Grav 6=302(LC 1), 5=261(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 BOT CHORD 5-6=-307/244
 WEBS 2-5=-258/324

NOTES-



- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 5=207.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	PB2	Piggyback	12	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:19 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNrj-yfXb8ovfqc5ms28aYVl6fciieg6c1OTA2H2kx8ybToo



LOADING (psf)		SPACING-		CSI.		DEFL.			PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.08	Vert(LL)	0.00	5	n/r	120	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	0.00	5	n/r	90		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.02	Horz(CT)	0.00	4	n/a	n/a		
BCDL	10.0	Code IRC2015/TPI2014		Matrix-P							Weight: 19 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-1-10 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=120/4-0-4 (min. 0-1-8), 4=120/4-0-4 (min. 0-1-8), 6=124/4-0-4 (min. 0-1-8)
 Max Horz 2=-58(LC 10)
 Max Uplift 2=-28(LC 13), 4=-33(LC 13)
 Max Grav 2=120(LC 1), 4=120(LC 1), 6=125(LC 3)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T1	Common	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:21 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNrj-u1fMZUxwMDLU5Lizgwoar4hyYUdhVGyTWaXr00ybTom





Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.50	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.71	Vert(LL) 0.26 6-9 >955 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.14	Vert(CT) -0.50 6-9 >501 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.72 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 151 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP DSS
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-0-9 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

(lb/size) 1=867/0-3-8 (min. 0-1-8), 5=858/0-3-8 (min. 0-1-8)
 Max Horz 1=262(LC 9)
 Max Uplift1=-42(LC 12), 5=-53(LC 12)
 Max Grav 1=867(LC 1), 5=863(LC 19)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-721/219, 2-3=-926/149, 3-4=-1056/184, 4-5=-592/150
 BOT CHORD 2-13=0/951, 6-13=0/951, 6-14=0/951, 4-14=0/951
 WEBS 3-6=0/373

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T1A	Roof Special	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:23 2020 Page 1
 ID:qVvPb7bITNTQeBoz4CnhCwycNrx-qQn6_AzAubCKfSLnLq2wVmCYHcz83mzu0y5yvbTok



Scale = 1:55.0

Plate Offsets (X,Y)-- [7:0-4-5,0-5-1], [9:0-5-8,0-2-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.85	Vert(LL)	-0.29 10-18	>749	240	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.74	Vert(CT)	-0.58 10-18	>381	180		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.30	Horz(CT)	0.31 9	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS						
	Code IRC2015/TPI2014							
							Weight: 124 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP No.2 *Except*
 T2: 2x6 SP DSS, T3: 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2 *Except*
 B2: 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-5-11 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-8.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 8, 10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=762/0-3-8 (min. 0-1-8), 9=805/Mechanical
 Max Horz 1=232(LC 11)
 Max Uplift1=-51(LC 13), 9=-98(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-634/170, 2-3=-757/141, 3-4=-881/237, 4-5=-974/195, 5-6=-387/106,
 6-19=-597/119, 8-19=-597/119
 BOT CHORD 2-20=-6/597, 10-20=-6/597, 5-10=-57/925, 7-9=-124/640
 WEBS 3-10=-102/729, 4-10=-602/219

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T1B	Roof Special	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:25 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNri-mpusPs_QQSsvazckvlsW?wscE5?3RuW3RCV29oybToi



Scale: 1/4"=1'




Plate Offsets (X,Y)-- [3:Edge,0-3-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.58	Vert(LL)	0.11 9-12	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.68	Vert(CT)	-0.20 9-12	>999	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.94	Horz(CT)	0.11 6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 122 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2 *Except*
 T1: 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-9-4 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5. Rigid ceiling directly applied or 9-10-14 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

(lb/size) 6=736/Mechanical, 1=755/0-3-8 (min. 0-1-8)
 Max Horz 1=229(LC 9)
 Max Uplift6=-77(LC 13), 1=-41(LC 12)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-616/78, 2-3=-729/142, 3-4=-848/187
 BOT CHORD 2-13=-34/557, 9-13=-34/557, 8-9=-351/1706, 7-8=-351/1706, 6-7=-343/1712
 WEBS 3-9=-10/496, 4-9=-1239/346, 4-6=-1744/340

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T1C	Roof Special	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:26 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNrf-F?SFdC?2BL_mB6BwTTOIY7OpMV0eAMOCfsFchEybtOh



8x8

Scale: 1/4"=1'




Plate Offsets (X,Y)-- [3:Edge,0-3-8], [4:0-5-4,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.50	Vert(LL)	0.10	9-12	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.46	Vert(CT)	-0.19	9-12	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.84	Horz(CT)	0.10	6	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MS						
								Weight: 129 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2 *Except*
 T1: 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5. Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

(lb/size) 6=736/Mechanical, 1=755/0-3-8 (min. 0-1-8)
 Max Horz 1=255(LC 9)
 Max Uplift6=-97(LC 13), 1=-40(LC 12)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-621/69, 2-3=-694/142, 3-4=-794/220
 BOT CHORD 2-13=-136/547, 9-13=-136/547, 8-9=-243/909, 7-8=-243/909, 6-7=-240/913
 WEBS 3-9=-74/534, 4-9=-553/191, 4-6=-1009/229

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T1D	Common	5	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:28 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNri-BOa?1t0JNEURQKJauQDdYU3rl2NeRIV7Akim7ybTof



Scale = 1:55.6




Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.88	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.64	Vert(LL) -0.18 6-12 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.14	Vert(CT) -0.37 6-12 >593 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.39 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 138 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

(lb/size) 5=761/0-3-8 (min. 0-1-8), 1=758/0-3-8 (min. 0-1-8)
 Max Horz 1=-243(LC 8)
 Max Uplift 5=-58(LC 13), 1=-42(LC 12)
 Max Grav 5=775(LC 20), 1=772(LC 19)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-659/207, 2-3=-876/142, 3-4=-819/138, 4-5=-530/142
 BOT CHORD 2-13=0/735, 6-13=0/735, 6-14=0/735, 4-14=0/735
 WEBS 3-6=0/367

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bearing at joint(s) 5, 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 1. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T1DE	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:30 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjrj-7miSZ2ZF_UCgkUhiJShizZOL6jr6LEoaUDpq?ybTod



Scale = 1:55.6



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.88	Vert(LL)	-0.18	6-20	>999	L/d	240	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.64	Vert(CT)	-0.37	6-20	>593		180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.14	Horz(CT)	0.39	5	n/a		n/a		
BCDL	10.0	Code IRC2015/TPI2014		Matrix-MS									
												Weight: 160 lb FT = 20%	

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=761/0-3-8 (min. 0-1-8), 1=758/0-3-8 (min. 0-1-8)
 Max Horz 1=-243(LC 8)
 Max Uplift5=-58(LC 13), 1=-42(LC 12)
 Max Grav5=775(LC 20), 1=772(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-659/207, 2-3=-876/142, 3-4=-819/138, 4-5=-530/142
 BOT CHORD 2-21=0/735, 6-21=0/735, 6-22=0/735, 4-22=0/735
 WEBS 3-6=0/367

NOTES-



- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bearing at joint(s) 5, 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 1. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T1E	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:32 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjrj-39pWtF4pnbkvw1e4pkU9nOeqmvNFaFg52oiwvuybTob



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.50	Vert(LL)	0.26	6-17	>955	L/d	240	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.71	Vert(CT)	-0.50	6-17	>501		180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.14	Horz(CT)	0.72	5	n/a		n/a		
BCDL	10.0	Code IRC2015/TPI2014		Matrix-MS									
												Weight: 173 lb FT = 20%	

LUMBER-
 TOP CHORD 2x10 SP DSS
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-9 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=867/0-3-8 (min. 0-1-8), 5=858/0-3-8 (min. 0-1-8)
 Max Horz 1=262(LC 9)
 Max Uplift 1=-42(LC 12), 5=-53(LC 12)
 Max Grav 1=867(LC 1), 5=863(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-721/219, 2-3=-926/149, 3-4=-1056/184, 4-5=-592/150
 BOT CHORD 2-21=0/951, 6-21=0/951, 6-22=0/951, 4-22=0/951
 WEBS 3-6=0/373

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T1F	Common	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

ID:qVyPb7bITNTQeBoz4CnhCwycNnj-XLNu5b4SXvsnXBDGnr00KcBz0JpsJj0EGSRTRKybToa

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:33 2020 Page 1



8x8 =

Scale = 1:46.5




Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.60	Vert(LL)	-0.08	12	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.36	Vert(CT)	-0.16	6-12	>928	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.07	Horz(CT)	0.21	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP							
								Weight: 93 lb	FT = 20%	

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=533/0-3-8 (min. 0-1-8), 5=536/0-3-8 (min. 0-1-8)
 Max Horz 1=-176(LC 8)
 Max Uplift 1=-21(LC 12), 5=-45(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-413/166, 2-3=-543/79, 3-4=-435/69, 4-5=-356/137
 BOT CHORD 2-6=0/449, 4-6=0/449

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T2	Common	5	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:35 2020 Page 1

ID:qVyPb7bITNTQeBoz4CnhCwycNnj-UkVeVH6i3W6VmVnFUs2sP1GHD7TpdnPXkmwaWDybToY



Scale = 1:48.5




Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.74	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.46	Vert(LL) 0.13 9 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.08	Vert(CT) -0.25 6-9 >677 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) 0.37 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 100 lb FT = 20%	

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=598/0-3-8 (min. 0-1-8), 5=589/0-3-8 (min. 0-1-8)
 Max Horz 1=186(LC 9)
 Max Uplift 1=-21(LC 12), 5=-41(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-448/150, 2-3=-534/96, 3-4=-632/123, 4-5=-400/124
 BOT CHORD 2-6=-3/565, 4-6=-3/565

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T2E	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:37 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNri-Q6dPwy7yb7MCOpX1cH4KUSLdjw8HFVWuqB4Pha5ybToW





Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.74	Vert(LL)	0.13	13	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.46	Vert(CT)	-0.25	6-13	>677		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.08	Horz(CT)	0.37	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP						
								Weight: 105 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=598/0-3-8 (min. 0-1-8), 5=589/0-3-8 (min. 0-1-8)
 Max Horz 1=186(LC 9)
 Max Uplift 1=-21(LC 12), 5=-41(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-448/150, 2-3=-534/96, 3-4=-632/123, 4-5=-400/124
 BOT CHORD 2-6=-3/565, 4-6=-3/565

NOTES-


- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- 4) Gable studs spaced at 2-0-0 oc.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 7) Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T3	Common	10	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:39 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNnj-MVl9Le9C7lcwF6gQjj6oZtR0BkssjQZ7fOuof_ybToU



8x8 =

Scale = 1:46.5





Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.55	Vert(LL)	-0.07	12	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.32	Vert(CT)	-0.14	12	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.07	Horz(CT)	0.16	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP					Weight: 89 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=502/0-3-8 (min. 0-1-8), 5=508/0-3-8 (min. 0-1-8)
 Max Horz 1=-181(LC 13)
 Max Uplift1=-17(LC 12), 5=-53(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-392/160, 2-3=-507/79, 3-4=-375/68, 4-5=-337/137
 BOT CHORD 2-6=0/392, 4-6=0/392

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T3A	Common	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:40 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNri-ghIXZ_Aru2IntGFcHPe164zBW8DOStqGt2eLBQybToT



Scale = 1:45.9



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES GRIP		
TCLL	20.0	Plate Grip DOL	1.15	TC	0.52	Vert(LL)	-0.06	12	>999	240	MT20	197/144
TCDL	10.0	Lumber DOL	1.15	BC	0.31	Vert(CT)	-0.13	12	>999	180		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.07	Horz(CT)	0.14	5	n/a	n/a		
BCDL	10.0	Code IRC2015/TPI2014		Matrix-MP							Weight: 88 lb	FT = 20%

LUMBER-
 TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=493/0-3-8 (min. 0-1-8), 5=499/Mechanical
 Max Horz 1=-173(LC 13)
 Max Uplift 1=-18(LC 12), 5=-50(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-385/155, 2-3=-492/80, 3-4=-372/69, 4-5=-331/131
 BOT CHORD 2-6=0/380, 4-6=0/380


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Bearing at joint(s) 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5.
 - One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T3E	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:46 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNri-frgpp1EbUuVxbBjmdgkRLDCQZVsb19Gz5fP4ybToN



8x8 =

Scale = 1:46.5





Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.55	Vert(LL)	-0.07	16	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.32	Vert(CT)	-0.14	16	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.07	Horz(CT)	0.16	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP					Weight: 94 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=502/0-3-8 (min. 0-1-8), 5=508/0-3-8 (min. 0-1-8)
 Max Horz 1=-181(LC 13)
 Max Uplift1=-17(LC 12), 5=-53(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-392/160, 2-3=-507/79, 3-4=-375/68, 4-5=-337/137
 BOT CHORD 2-6=0/392, 4-6=0/392

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T4	Common	2	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:47 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNnj-72DB1NFEECdoDLHyBNGguZmM7yaPb2PIUdqDxWybToM



8x8 =

Scale = 1:43.9




Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.62	Vert(LL)	-0.09	6-9	>999	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.41	Vert(CT)	-0.20	6-9	>841		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.08	Horz(CT)	0.35	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP					Weight: 97 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=578/0-3-8 (min. 0-1-8), 1=582/0-3-8 (min. 0-1-8)
 Max Horz 1=-170(LC 8)
 Max Uplift 5=-25(LC 12), 1=-23(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-440/165, 2-3=-564/85, 3-4=-584/97, 4-5=-388/132
 BOT CHORD 2-6=0/565, 4-6=0/565

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 5, 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 1. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T4E	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:49 2020 Page 1
 ID:qVvPb7bITNTQeBoz4CnhCwycNri-3QLxR3HUmpTVSfRLJoI8z_rdmFt3yvbyxJK?PybToK



Scale = 1:43.9




Plate Offsets (X,Y)-- [3:0-4-0,0-2-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.62	Vert(LL)	-0.09 6-13	>999	240	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.41	Vert(CT)	-0.20 6-13	>841	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.08	Horz(CT)	0.35 5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MP						
								Weight: 101 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 5=578/0-3-8 (min. 0-1-8), 1=582/0-3-8 (min. 0-1-8)
 Max Horz 1=-170(LC 8)
 Max Uplift5=-25(LC 12), 1=-23(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-440/165, 2-3=-564/85, 3-4=-584/97, 4-5=-388/132
 BOT CHORD 2-6=0/565, 4-6=0/565

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 5, 1 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5 and 1. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T4GR	COMMON	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:51 2020 Page 1

ID:qVyPb7b1TNTQeBoz4CnhCwycNjr-OpThslkIR7DhybkQDKc2Px?iaq2XmmuPFoQ4HybToI



8x8 =

Scale = 1:43.9





Plate Offsets (X,Y)-- [3:0-4-0,0-2-12], [6:0-4-4,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.77	Vert(LL)	-0.19	6-12	>867	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.88	Vert(CT)	-0.37	6-9	>441		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.50	Horz(CT)	0.68	5	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-MP						
	Code IRC2015/TPI2014							
							Weight: 206 lb	FT = 20%

LUMBER-

TOP CHORD 2x10 SP DSS
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 6

REACTIONS. (lb/size) 1=3501/0-3-8 (min. 0-2-12), 5=3495/0-3-8 (min. 0-2-12)
 Max Horz 1=-170(LC 8)
 Max Uplift1=-356(LC 13), 5=-360(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-13=-1936/334, 2-13=-1244/300, 2-3=-3072/420, 3-4=-3076/433, 4-14=-1239/277, 5-14=-1931/297
 BOT CHORD 2-15=-323/2946, 6-15=-323/2946, 6-16=-323/2946, 4-16=-323/2946
 WEBS 3-6=-298/2431

NOTES-

- 2-ply truss to be connected together with 10d (0.120"x3") nails as follows:
 Top chords connected as follows: 2x10 - 2 rows staggered at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 1, 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 752 lb down and 82 lb up at -3-3-4, 785 lb down and 151 lb up at -1-4-4, and 785 lb down and 151 lb up at 8-6-4, and 752 lb down and 82 lb up at 10-5-4 on top chord, and 720 lb down and 93 lb up at 0-7-12, 716 lb down and 117 lb up at 2-7-12, and 716 lb down and 117 lb up at 4-6-4, and 720 lb down and 93 lb up at 6-6-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	T4GR	COMMON	1	2	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:51 2020 Page 2
 ID:qVyPb7bITNTQeBoz4CnhCwycNnj-0pThslklR7DhybkQDKc2Px?iaq2XmmuPFoQ4HybTol

LOAD CASE(S) Standard

Uniform Loads (plf)

Vert: 1-8=-88, 3-8=-60, 3-4=-60, 4-5=-88, 7-10=-20


Concentrated Loads (lb)

Vert: 1=-734 5=-734 9=-720(B) 12=-720(B) 13=-745(B) 14=-745(B) 15=-716(B) 16=-716(B)

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V1	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:53 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNri-yBbSHRK_q2NxxGI6YeN48q0TjNiN?nIBtZHX8AybToG



0-1-0	4-11-0	8-11-0	12-11-0	15-5-8
0-1-0	4-10-0	4-0-0	4-0-0	2-6-8
LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES
TCLL 20.0	2-0-0	TC 0.29	in (loc) l/defl L/d	MT20
TCDL 10.0	Plate Grip DOL 1.15	BC 0.12	Vert(LL) n/a - n/a 999	GRIP 197/144
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Vert(CT) n/a - n/a 999	
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) -0.00 6 n/a n/a	
	Code IRC2015/TPI2014			Weight: 61 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.2 or 2x4 SPF No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing, Except: 10-0-0 oc bracing: 6-7.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 15-4-8.
 (lb) - Max Horz 1=208(LC 9)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 6, 7, 8, 9
 Max Grav All reactions 250 lb or less at joint(s) 1, 6 except 7=263(LC 1), 8=333(LC 1), 9=339(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-266/191
 WEBS 3-8=-256/150

NOTES-



- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) One MTS12 Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1. This connection is for uplift only and does not consider lateral forces.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6, 7, 8, and 9. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V2	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:55 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNnj-uaiCi6LFMfdfAavVf3PYDE5o2BLYTgoTKtmeD2ybToE



Scale = 1:26.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.37	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.20	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.05	Vert(CT) n/a - n/a 999		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Horz(CT) -0.00 5 n/a n/a		
				Weight: 44 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 11-4-8.
 (lb) - Max Horz 1=167(LC 9)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 6, 7
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 6=257(LC 1), 7=362(LC 1)

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-7=-272/175

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) One MTS12 Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1. This connection is for uplift only and does not consider lateral forces.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 5, 6, and 7. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V3	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:56 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjrj-MmGavSmt7zmWojThDmwnlSeynbiJC7AdZXWBIVybToD



Scale = 1:22.0



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.43	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.17	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 28 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 7-5-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=131/7-4-8 (min. 0-1-8), 4=88/7-4-8 (min. 0-1-8), 5=267/7-4-8 (min. 0-1-8)
 Max Horz 1=126(LC 9)
 Max Uplift 1=-35(LC 8), 4=-54(LC 9), 5=-42(LC 12)
 Max Grav 1=131(LC 1), 4=112(LC 19), 5=267(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) One MTS12 Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1. This connection is for uplift only and does not consider lateral forces.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4 and 5. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V4	Valley	1	1	Job Reference (optional)


84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:34:58 2020 Page 1

ID:qVyPb7bITNTQeBoz4CnhCwycNri-J9OLK807fa0E11d4KByFrtjM2OPug1Mw0r?lqNybToB



Scale = 1:15.7



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.19	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.10	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 12 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-9-4 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=91/2-9-0 (min. 0-1-8), 3=91/2-9-0 (min. 0-1-8)
 Max Horz 1=86(LC 9)
 Max Uplift 3=41(LC 9)
 Max Grav 1=102(LC 20), 3=111(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 3. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V5	GABLE	1	1	Job Reference (optional)


84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:00 2020 Page 1

ID:qVvYpB7blTNTQeBoz4CnhCwycNri-jFYW5lqPNBCGyGLnSSc?jwlocJC618x7DU9UPuGybTo9

5-10-8
5-10-8

Scale = 1:33.9



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.53	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 35 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
BOT CHORD 2x4 SP No.3
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-10-8 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 5-10-8.
(lb) - Max Horz 1=203(LC 9)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 6=-114(LC 12), 7=-103(LC 12)
Max Grav All reactions 250 lb or less at joint(s) 1, 5, 6, 7

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-386/346, 2-3=-276/257

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 5, 6, and 7. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V6	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:01 2020 Page 1

ID:qVyPb7bITNTQeBoz4CnhCwycNri-jk4TzAQ0xVOpuVMf0JWYsvLkscMvtO6MipDyQiybTo8



Scale = 1:25.5

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.73	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.39	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2015/TPI2014			Weight: 23 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-10-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=175/4-10-4 (min. 0-1-8), 3=175/4-10-4 (min. 0-1-8)
 Max Horz 1=165(LC 9)
 Max Uplift 3=-78(LC 9)
 Max Grav 1=197(LC 20), 3=214(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-252/216

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 3. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V7	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:03 2020 Page 1

ID:qVyPb7blTNTQeBoz4CnhCwycNnj-f7BEOrSGT7eW7oW17kYQYwQ86P40LlbfA7i3VbybTo6



Scale = 1:20.9

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.43	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.23	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 18 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-10-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=135/3-10-4 (min. 0-1-8), 3=135/3-10-4 (min. 0-1-8)
 Max Horz 1=127(LC 9)
 Max Uplift 3=60(LC 9)
 Max Grav 1=152(LC 20), 3=165(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 3. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V8	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8,400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:04 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNnj-7JlcbBSuEQmNly5DhS3f48zMGpS74IroPnSc11ybTo5



Scale = 1:16.2

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.21	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.11	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 13 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 2-10-8 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=95/2-10-4 (min. 0-1-8), 3=95/2-10-4 (min. 0-1-8)
 Max Horz 1=90(LC 9)
 Max Uplift 3=42(LC 9)
 Max Grav 1=107(LC 20), 3=116(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 3. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V9	GABLE	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:06 2020 Page 1
 ID:qVyPb7bITNTQeBoz4CnhCwycNjrj-4htfM0tU8m205_GEcot579Z2Zad8yYd15s5xj6wybTo3



Scale = 1:46.1

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.80	Vert(LL)	n/a	-	n/a	MT20	197/144
TCDL 10.0	Lumber DOL	1.15	BC 0.08	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.15	Horz(CT)	-0.00	6	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						
								Weight: 63 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2 or 2x4 SPF No.2
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.2 or 2x4 SPF No.2
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 5-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS.

All bearings 8-10-8.
 (lb) - Max Horz 1=316(LC 9)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 6, 8 except 7=-113(LC 12), 9=-141(LC 12)
 Max Grav All reactions 250 lb or less at joint(s) 1, 6, 7, 8, 9

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-560/510, 2-3=-412/380, 3-4=-310/302

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) All plates are 1.5x4 MT20 unless otherwise indicated.
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 6) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 6, 7, 8, and 9. This connection is for uplift only and does not consider lateral forces.
- 7) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V10	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:08 2020 Page 1

ID:qVvYpB7bITNTQeBoz4CnhCwycNri-04?7RZVPiFgPpEaO?wH8bF_8ssQmq0YIOJQqAoybToI



Scale = 1:45.3

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 1.00	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.31	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.10	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) -0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 43 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 2 Rows at 1/3 pts 3-4

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=102/7-10-4 (min. 0-1-8), 4=119/7-10-4 (min. 0-1-8), 5=369/7-10-4 (min. 0-1-8)

Max Horz 1=278(LC 9)
 Max Uplift 1=-58(LC 8), 4=-88(LC 9), 5=-245(LC 12)
 Max Grav 1=203(LC 11), 4=211(LC 19), 5=483(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-482/451
 WEBS 2-5=-391/320

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 4, and 5. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V11	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:10 2020 Page 1

ID:qVyPb7bITNTQeBoz4CnhCwycNri-yT6tsFXfqGWXTtYN1iA3KPDGJESpUSzhnixFhybTo?



Scale = 1:39.6

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.75	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.28	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.09	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 37 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=56/6-10-4 (min. 0-1-8), 4=125/6-10-4 (min. 0-1-8), 5=330/6-10-4 (min. 0-1-8)
 Max Horz 1=241(LC 9)
 Max Uplift1=-71(LC 10), 4=-81(LC 9), 5=-219(LC 12)
 Max Grav 1=176(LC 9), 4=209(LC 19), 5=415(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-446/413
 WEBS 2-5=-353/292

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 4, and 5. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V12	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:12 2020 Page 1

ID:qVyPb7bITNTQeBoz4CnhCwycNjr-urEeGwZvMunFiBim97CXPqlc118sxKV_E001IzYbTnz



Scale = 1:49.4

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.73	in (loc) l/defl L/d	MT20	197/144
TCDL 10.0	Plate Grip DOL 1.15	BC 0.31	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.15	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) -0.00 4 n/a n/a		
	Code IRC2015/TPI2014			Weight: 48 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.2 or 2x4 SPF No.2
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 3-4

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=131/8-7-0 (min. 0-1-8), 4=111/8-7-0 (min. 0-1-8), 5=406/8-7-0 (min. 0-1-8)

Max Horz 1=306(LC 9)
 Max Uplift 1=-57(LC 8), 4=-92(LC 9), 5=-270(LC 12)
 Max Grav 1=230(LC 20), 4=206(LC 19), 5=532(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-511/482
 WEBS 2-5=-428/347

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 4, and 5. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	WELLONS - BREEDEN
2000470-2000470A	V14	Valley	1	1	Job Reference (optional)

84 Components, Dunn, NC 28334

8.400 s Apr 7 2020 MiTek Industries, Inc. Mon Sep 21 08:35:15 2020 Page 1

ID:qVyPb7bITNTQeBoz4CnhCwycNrlj-JQwmvvyboep9paeQLqGmE1Sw84F9G8IEQw_civuybTnw



Scale = 1:38.1

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.68	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.26	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.09	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						
								Weight: 35 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.3
 BOT CHORD 2x4 SP No.3
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=40/6-7-0 (min. 0-1-8), 4=125/6-7-0 (min. 0-1-8), 5=323/6-7-0 (min. 0-1-8)
 Max Horz 1=230(LC 9)
 Max Uplift1=-79(LC 10), 4=-79(LC 9), 5=-214(LC 12)
 Max Grav 1=172(LC 9), 4=206(LC 19), 5=401(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-438/404
 WEBS 2-5=-346/288

NOTES-

- 1) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=30ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 5) One H2.5A Simpson Strong-Tie connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 4, and 5. This connection is for uplift only and does not consider lateral forces.
- 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard