


Job J0920-4322	Truss A1	Truss Type ROOF SPECIAL	Qty 9	Ply 1	Robert Barefoot / Dakota /
Comtech, Inc., Fayetteville, NC 28309, Lenny Norris					Job Reference (optional)

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:29 2020 Page 1
 ID:?SZU4M1j1TjD5OdyTUJJEz4ycis5-rLl_LaK0gwT8In4rN5bRkW48CmP3tOMFialPOLyci4e



4x6 =

Scale: 3/16"=1'




Plate Offsets (X,Y)-- [7:0-3-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.77	Vert(LL)	-0.34	13-15	>898	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.62	Vert(CT)	-0.51	13-15	>602		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.39	Horz(CT)	0.03	11	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.27	11-13	>999		
	Code IRC2015/TPI2014						Weight: 212 lb	FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.1 *Except*
 T1: 2x4 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2 *Except*
 W2: 2x6 SP No.1

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-5-15 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
 6-0-0 oc bracing: 2-16.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 11=0-3-8 (min. 0-1-9), 16=0-3-8 (min. 0-2-0)
 Max Horz 16=220(LC 11)
 Max Uplift 11=-67(LC 13), 16=-116(LC 12)
 Max Grav 11=1303(LC 20), 16=1673(LC 2)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-17=-578/998, 3-17=-568/1048, 3-16=-2554/733, 3-4=-1722/195, 4-5=-1579/223,
 5-18=-1212/287, 6-18=-1148/299, 6-7=-74/533, 7-8=-58/534, 8-19=-1146/315,
 9-19=-1210/303, 9-10=-1539/234, 10-20=-1577/228, 11-20=-1762/205
 BOT CHORD 2-16=-975/617, 16-21=-28/1318, 15-21=-28/1318, 14-15=-28/1318, 13-14=-28/1318,
 13-22=-28/1318, 11-22=-28/1318
 WEBS 5-15=0/689, 9-13=0/663, 6-8=-1863/448

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-10-8 to 3-6-5, Interior(1) 3-6-5 to 18-0-0, Exterior(2) 18-0-0 to 22-4-13, Interior(1) 22-4-13 to 31-8-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 11 except (jt=lb) 16=116.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job J0920-4322	Truss A2	Truss Type COMMON	Qty 6	Ply 1	Robert Barefoot / Dakota /
Comtech, Inc., Fayetteville, NC 28309, Lenny Norris					Job Reference (optional)

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:30 2020 Page 1
 ID: ?SZU4M1j1TjD5OdYTUjEz4ycis5-JysMZwLeRDb?wxfl1xo7gHjdHwAlhrcrtOXE2ywnyci4d



Scale = 1:55.7

Plate Offsets (X,Y)-- [1:0-3-10,0-1-8], [4:0-3-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.90	Vert(LL)	-0.35	10-12	>872	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.60	Vert(CT)	-0.52	10-12	>590		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.43	Horz(CT)	0.03	8	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.22	1-12	>999		
	Code IRC2015/TPI2014						Weight: 188 lb	FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2 *Except*
 W2: 2x6 SP No.1

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 1=Mechanical, 8=0-3-8 (min. 0-1-9)
 Max Horz 1=-219(LC 8)
 Max Uplift 1=-54(LC 12), 8=-68(LC 13)
 Max Grav 1=1287(LC 19), 8=1346(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-13=-1853/232, 2-13=-1678/253, 2-14=-1284/327, 3-14=-1220/339, 3-4=-101/642,
 4-5=-109/643, 5-15=-1219/333, 6-15=-1283/321, 6-7=-1642/260, 7-16=-1682/255,
 8-16=-1865/230
 BOT CHORD 1-17=-58/1405, 12-17=-58/1405, 11-12=-58/1405, 10-11=-58/1405, 10-18=-58/1405,
 8-18=-58/1405
 WEBS 6-10=0/698, 2-12=0/681, 3-5=-2078/516


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-1-4 to 4-6-1, Interior(1) 4-6-1 to 13-0-0, Exterior(2) 13-0-0 to 17-4-13, Interior(1) 17-4-13 to 26-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) All plates are 2x4 MT20 unless otherwise indicated.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 8.
 - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss A2GE	Truss Type GABLE	Qty 2	Ply 1	Robert Barefoot / Dakota /
-------------------	---------------	---------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:31 2020 Page 1
ID:?SZU4M1j1TJD5OdYTUJEz4ycis5-nkQkmGMGCXjsY5EDUWevqx9gAaExLMpYlunVSDyci4c



Scale = 1:56.9

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.04	Vert(LL) -0.00 16 n/r 120	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.02	Vert(CT) -0.00 16 n/r 120		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.13	Horz(CT) 0.01 16 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S			
				Weight: 218 lb	FT = 20%

LUMBER-
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
OTHERS 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 8-25

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 26-0-0.
(lb) - Max Horz 1=-272(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 16, 26, 27, 28, 29, 30, 24, 22, 21, 20, 19 except 1=-133(LC 10), 31=-130(LC 12), 18=-109(LC 13)
Max Grav All reactions 250 lb or less at joint(s) 1, 16, 25, 26, 27, 28, 29, 30, 31, 24, 22, 21, 20, 19, 18

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-320/227


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) 0-0-0 to 4-4-13, Exterior(2) 4-4-13 to 13-0-0, Corner(3) 13-0-0 to 17-4-13, Exterior(2) 17-4-13 to 26-8-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16, 26, 27, 28, 29, 30, 24, 22, 21, 20, 19 except (jt=lb) 1=133, 31=130, 18=109.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss B1	Truss Type Common	Qty 2	Ply 1	Robert Barefoot / Dakota /
-------------------	-------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:32 2020 Page 1
ID:?SZU4M1j1TjD5OdYTUjEz4ycis5-Fw_6zcNvyqrj9FpQ2D98M8i4_WM4qph_YX3?gyci4b



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.41	Vert(LL)	-0.04	5-6	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.26	Vert(CT)	-0.07	5-6	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.09	Horz(CT)	0.01	5	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-R	Wind(LL)	-0.03	6-7	>999	Weight: 58 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x6 SP No.1 *Except*
 W2: 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 7=0-3-8 (min. 0-1-8), 5=0-3-8 (min. 0-1-8)
 Max Horz 7=-140(LC 8)
 Max Uplift 7=-18(LC 12), 5=-34(LC 13)
 Max Grav 7=569(LC 19), 5=635(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-8=-616/128, 8-9=-507/136, 2-9=-476/162, 2-10=-505/162, 10-11=-518/136,
 3-11=-623/128, 1-7=-492/186, 3-5=-565/250
 BOT CHORD 7-12=0/421, 6-12=0/421, 6-13=0/421, 5-13=0/421
 WEBS 2-6=0/385


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-12 to 4-7-9, Interior(1) 4-7-9 to 6-6-0, Exterior(2) 6-6-0 to 10-10-13, Interior(1) 10-10-13 to 13-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BC DL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 5.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss B1GE	Truss Type GABLE	Qty 1	Ply 1	Robert Barefoot / Dakota /
-------------------	---------------	---------------------	----------	----------	----------------------------


Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:33 2020 Page 1
 ID:?SZU4M1j1TjD5OdYTUjEz4ycis5-j6YUByNXj8zanPOccxgNvMFxgOsGpH1qDCGcX6yci4a



4x4 =

Scale = 1:38.4



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.36	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.28	Vert(LL) -0.04 7-8 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.09	Vert(CT) -0.06 7-8 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-R	Horz(CT) 0.01 6 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) -0.04 7-8 >999 240	Weight: 79 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x6 SP No.1 *Except*
 W2: 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 8=0-3-8 (min. 0-1-8), 6=0-3-8 (min. 0-1-8)
 Max Horz 8=-184(LC 10)
 Max Uplift 8=-114(LC 12), 6=-114(LC 13)
 Max Grav 8=632(LC 19), 6=632(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-627/172, 3-4=-627/172, 2-8=-566/262, 4-6=-566/262
 BOT CHORD 8-17=-14/433, 7-17=-14/433, 7-18=-14/433, 6-18=-14/433
 WEBS 3-7=0/393


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 3-6-5, Exterior(2) 3-6-5 to 6-6-0, Corner(3) 6-6-0 to 10-10-13, Exterior(2) 10-10-13 to 13-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 8=114, 6=114.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss B1GR	Truss Type COMMON	Qty 1	Ply 2	Robert Barefoot / Dakota /
-------------------	---------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:34 2020 Page 1
ID: ?SZU4M1j1TjD5OdYTUJEz4ycis5-BJ6tOH09US5RPYzoAeBcRZn3An64Yer_Sr093Yyci4Z



Scale = 1:37.5

Plate Offsets (X,Y)-- [1:0-0-7,0-0-8], [1:0-0-13,0-3-13], [1:Edge,0-1-0], [3:0-0-7,0-0-8], [3:0-0-13,0-3-13], [3:Edge,0-1-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.57	Vert(LL)	-0.05	1-4	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.70	Vert(CT)	-0.09	1-4	>999		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.50	Horz(CT)	0.01	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.03	1-4	>999		
								Weight: 150 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x8 SP No.1
 WEBS 2x4 SP No.2
 WEDGE
 Left: 2x4 SP No.2 , Right: 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 1=0-3-8 (min. 0-2-3), 3=0-3-8 (min. 0-1-15)
 Max Horz 1=140(LC 7)
 Max Uplift 1=-229(LC 8), 3=-203(LC 9)
 Max Grav 1=3745(LC 1), 3=3328(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-3409/260, 2-3=-3410/260
 BOT CHORD 1-5=-126/2443, 5-6=-126/2443, 6-7=-126/2443, 7-8=-126/2443, 4-8=-126/2443,
 4-9=-126/2443, 9-10=-126/2443, 10-11=-126/2443, 11-12=-126/2443, 3-12=-126/2443
 WEBS 2-4=-194/4075

NOTES-

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-9-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=229, 3=203.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1010 lb down and 73 lb up at 1-0-12, 1009 lb down and 74 lb up at 3-0-12, 1009 lb down and 74 lb up at 5-0-12, 1009 lb down and 74 lb up at 7-0-12, and 1009 lb down and 74 lb up at 9-0-12, and 1009 lb down and 74 lb up at 11-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

Job J0920-4322	Truss B1GR	Truss Type COMMON	Qty 1	Ply 2	Robert Barefoot / Dakota / Job Reference (optional)
-------------------	---------------	----------------------	----------	----------	--

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:34 2020 Page 2
ID:?SZU4M1j1TjD5OdYTUJEz4ycis5-BJ6tOHO9US5RPYzoAeBcRZn3An64Yer_Sr093Yyci4Z

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-20, 1-2=-60, 2-3=-60


Concentrated Loads (lb)

Vert: 5=-1010(B) 6=-1009(B) 8=-1009(B) 9=-1009(B) 11=-1009(B) 12=-1009(B)

Job J0920-4322	Truss C1	Truss Type Common	Qty 2	Ply 1	Robert Barefoot / Dakota /
-------------------	-------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:35 2020 Page 1
ID:?SZU4M1j1TjD5OdYTUjEz4ycis5-fvgFcdPnFIDI0iX_jMir_nKlqBZKHC57gVljb?yci4Y



Scale = 1:35.2

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.32	Vert(LL)	-0.02	6-7	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.18	Vert(CT)	-0.04	6-7	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-R	Wind(LL)	0.02	6-7	>999	240		
									Weight: 53 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x6 SP No.1 *Except*
 W2: 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 7=0-3-8 (min. 0-1-8), 5=0-3-8 (min. 0-1-8)
 Max Horz 7=127(LC 9)
 Max Uplift 7=-31(LC 12), 5=-16(LC 13)
 Max Grav 7=518(LC 1), 5=445(LC 1)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-8=-447/117, 8-9=-386/128, 3-9=-362/150, 3-10=-343/150, 10-11=-364/128,
 4-11=-440/117, 2-7=-463/238, 4-5=-394/173
 BOT CHORD 6-7=0/266, 5-6=0/266

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-10-8 to 3-6-5, Interior(1) 3-6-5 to 5-10-0, Exterior(2) 5-10-0 to 10-2-13, Interior(1) 10-2-13 to 11-5-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 5.
 - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss C1GE	Truss Type GABLE	Qty 1	Ply 1	Robert Barefoot / Dakota /
Comtech, Inc., Fayetteville, NC 28309, Lenny Norris					Job Reference (optional)

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:36 2020 Page 1
 ID:?SZU4M1j1TjD5OdYTUJEz4ycis5-7hEdpzQP03M9es6BH3D4X_1TsbvQ0fKHv9VG8Ryci4X



Scale = 1:35.2

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.30	Vert(LL)	-0.03	7-8	>999	240	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.19	Vert(CT)	-0.04	6-7	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-R							
									Weight: 71 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x6 SP No.1 *Except*
 W2: 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 8=0-3-8 (min. 0-1-8), 6=0-3-8 (min. 0-1-8)
 Max Horz 8=168(LC 11)
 Max Uplift 8=-105(LC 12), 6=-105(LC 13)
 Max Grav 8=515(LC 1), 6=515(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-445/157, 3-4=-445/157, 2-8=-463/246, 4-6=-463/246
 BOT CHORD 7-8=-11/287, 6-7=-11/287

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 3-6-5, Exterior(2) 3-6-5 to 5-10-0, Corner(3) 5-10-0 to 10-2-13, Exterior(2) 10-2-13 to 12-6-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 8=105, 6=105.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss C1GR	Truss Type COMMON GIRDER	Qty 1	Ply 2	Robert Barefoot / Dakota / Job Reference (optional)
-------------------	---------------	-----------------------------	----------	-----------------	--

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MITek Industries, Inc. Thu Sep 17 15:30:37 2020 Page 2
ID: ?SZU4M1j1TjD5OdYTUjEz4ycis5-cun?1JR1nNU0G0hNmJ3CPax?7gl?VQ8pEqgtyci4W

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-3=-60, 1-3=-20


Concentrated Loads (lb)

Vert: 4=-1009(B) 5=-1009(B) 6=-1009(B) 7=-1009(B) 8=-1009(B) 9=-1010(B)

Job J0920-4322	Truss VB1	Truss Type VALLEY	Qty 1	Ply 1	Robert Barefoot / Dakota /
-------------------	--------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:38 2020 Page 1
ID: ?SZU4M1j1TjD5OdYTUjEz4ycis5-44LNEFRfYgcttAGZPUGYcPyqIPbGUYkaMT_NCJyci4V



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.24	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.17	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.06	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 39 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 1=10-3-9 (min. 0-1-8), 3=10-3-9 (min. 0-1-8), 4=10-3-9 (min. 0-1-8)
 Max Horz 1=-95(LC 8)
 Max Uplift 1=-22(LC 13), 3=-31(LC 13)
 Max Grav 1=203(LC 1), 3=203(LC 1), 4=354(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 5-1-12, Exterior(2) 5-1-12 to 9-6-9, Interior(1) 9-6-9 to 9-10-12 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - Non Standard bearing condition. Review required.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss VB2	Truss Type VALLEY	Qty 1	Ply 1	Robert Barefoot / Dakota /
-------------------	--------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:39 2020 Page 1
ID:?SZU4M1j1TjD5OdyTuJEz4ycis5-YGvms?SIJ_kjVKrmyBnn8dV0WoyyD?ajb7jwlmcy4U



Scale = 1:19.7

LOADING (psf)	SPACING-	CS.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.14	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P						
	Code IRC2015/TPI2014						Weight: 26 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 1=7-1-2 (min. 0-1-8), 3=7-1-2 (min. 0-1-8), 4=7-1-2 (min. 0-1-8)
Max Horz 1=-63(LC 8)
Max Uplift1=-22(LC 13), 3=-28(LC 13)
Max Grav 1=145(LC 1), 3=145(LC 1), 4=212(LC 1)


FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss VB3	Truss Type VALLEY	Qty 1	Ply 1	Robert Barefoot / Dakota /
Comtech, Inc., Fayetteville, NC 28309, Lenny Norris					Job Reference (optional)

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:39 2020 Page 1
 ID:?SZU4M1j1TjD5OdYTUjEz4ycis5-YGvmS?SIJ_kjVKrmyBnn8dV2FoyD?ujb7jwlmcyi4U



Scale = 1:10.7

Plate Offsets (X,Y)-- [2:0-2-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.03	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.08	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P						
	Code IRC2015/TPI2014						Weight: 12 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 3-10-12 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 1=3-10-12 (min. 0-1-8), 3=3-10-12 (min. 0-1-8)
 Max Horz 1=31(LC 9)
 Max Uplift 1=-5(LC 12), 3=-5(LC 13)
 Max Grav 1=124(LC 1), 3=124(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - Non Standard bearing condition. Review required.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss VC1	Truss Type VALLEY	Qty 1	Ply 1	Robert Barefoot / Dakota /
-------------------	--------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:40 2020 Page 1
ID: ?SZU4M1j1TjD5OdYTUjEz4ycis5-0TT8fLTw4lSa7TQyWwI0hq1AeCIPySZsqnTUHCyci4T



Scale: 1/2"=1'

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.25	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.12	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 34 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 1=8-11-9 (min. 0-1-8), 3=8-11-9 (min. 0-1-8), 4=8-11-9 (min. 0-1-8)
 Max Horz 1=-81(LC 8)
 Max Uplift 1=-28(LC 13), 3=-36(LC 13)
 Max Grav 1=189(LC 1), 3=189(LC 1), 4=275(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - Non Standard bearing condition. Review required.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss VC2	Truss Type VALLEY	Qty 1	Ply 1	Robert Barefoot / Dakota /
-------------------	--------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:41 2020 Page 1
ID: ?SZU4M1j1TjD5OdYTUJEz4ycis5-Uf1WshUYrb_Rkd?84cpFE2aNvcerhvB03RD1peyci4S



Scale = 1:16.7

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.01	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 21 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-9-2 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 1=5-9-2 (min. 0-1-8), 3=5-9-2 (min. 0-1-8), 4=5-9-2 (min. 0-1-8)
Max Horz 1=-49(LC 8)
Max Uplift 1=-17(LC 13), 3=-22(LC 13)
Max Grav 1=115(LC 1), 3=115(LC 1), 4=167(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job J0920-4322	Truss VC3	Truss Type VALLEY	Qty 1	Ply 1	Robert Barefoot / Dakota /
-------------------	--------------	----------------------	----------	----------	----------------------------

Comtech, Inc., Fayetteville, NC 28309, Lenny Norris

Run: 8.300 s Mar 22 2019 Print: 8.300 s Mar 22 2019 MiTek Industries, Inc. Thu Sep 17 15:30:41 2020 Page 1
ID:?SZU4M1j1TjD5OdYTUjEz4ycis5-Uf1WshUYrb_Rkd?84cpFE2aO4ceAhvO03RD1peyci4S




Plate Offsets (X,Y)-- [2:0-2-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.01	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.03	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 7 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-
TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-6-12 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (size) 1=2-6-12 (min. 0-1-8), 3=2-6-12 (min. 0-1-8)
Max Horz 1=18(LC 9)
Max Uplift 1=-3(LC 12), 3=-3(LC 13)
Max Grav 1=70(LC 1), 3=70(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - Non Standard bearing condition. Review required.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard