## Harnett County Department of Public Health

Improvement Permit

•	building permit cannot be issued with only an improvement Permit				
SSUED TO: Adams Homes PROPERTY LOCATION: 484 Spring Flowers Dr SUBDIVISION Carolina Seasons LOT # 29					
ISSUED TO:	SUED TO: Adams Homes  SUED TO: Adams Homes  SUBDIVISION Carolina Seasons  LOT # 29  Site Improvements required prior to Construction Authorization Issuance:  PROPERTY LOCATION: 484 Spring Flowers DI  SUBDIVISION Carolina Seasons  LOT # 29  Site Improvements required prior to Construction Authorization Issuance:				
NEW REPAIR EXPANSION Site Improvements required prior to Construction Authorization Issuance:					
Proposed Wastewater System Type: 25% Reduc	tion				
Projected Daily Flow: 360 GPD	Administration of the control of the				
Number of bedrooms: 3 Number of Occi	pants: 6 max				
Basement Yes 🔀 No	g alayanda t				
Pump Required: Yes 🗵 No 🔲 May be req	ired based on final location and elevations of facilities				
Type of Water Supply Community E Public	■ Well Distance from well feet Permit valid for: ▼ Five years				
Permit conditions:	No expiration				
	the state of the s				
Authorized State Agent::	- REIHS Date: 11-12-2020 SEE ATTACHED SITE SKETCH				
The iccornice of this permit by the feelth Benariment in no way pilat	ntees the usuance of other permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. Th				
	changes. The Improvement Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions				
the Laws and Rules for Sewage Treatment and Disposal and to conditi	ns of this permit				
Account contract on any analysis of a special contract of the special contract	and the second s				
	Construction Authorization				
	(Required for Building Permit)				
The construction and installation requirements of Rules 1950 1957	934, 1935, 1956, 1957, 1958 and 1959 are incorporated by references into this permit and shall be met Systems shall be installed in accordance				
with the attached system fayout					
KEHED TO Adown's Homes	PROPERTY LOCATION: 484 Spring Flowers Dr				
	Carolina Sociana III # 29				
Facility Type: SFR (41'x 48')	New    □ Expansion    □ Repair				
	Kee Cxpansion nepan				
Basement? Yes 🗵 No Basement Fi	tures? 🔲 Yes 🕱 No				
	tures? 🔲 Yes 🕱 No				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )	tures? Yes No  (Initial) Wastewater Flow: 360 GPD				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )	tures? Yes No  (Initial) Wastewater Flow: 360 GPD				
Basement?  Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable ) 25% Reduct	tion (Initial) Wastewater Flow: 360 GPD				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  Installation Requirements/Conditions	tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  1. Linstallation Requirements/Conditions Septic Tank Size 1000 gallons	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  Installation Requirements/Conditions	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center Trenches shall be installed on contour at a Soil Cover: 6 inches				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  1. Linstallation Requirements/Conditions Septic Tank Size 1000 gallons	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150feet				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  1. Linstallation Requirements/Conditions Septic Tank Size 1000 gallons	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center Trenches shall be installed on contour at a Soil Cover: 6 inches				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  1. Linstallation Requirements/Conditions Septic Tank Size 1000 gallons	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150feet				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 inches  Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed  (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM 6 inches below pig				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center Trenches shall be installed on contour at a Soil Cover: 6 inches  Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons  Pump Tank Size ft. TDH vs.	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 inches  Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches above piges.				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable )  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons  Pump Tank Size ft. TDH vs.	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 inches  Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed  (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM 6 inches below pig				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons  Pump Requirements: ft. TDH vs.  Conditions:	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center Trenches shall be installed on contour at a Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches above pigging the property of the proper				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons  Pump Requirements: ft. TDH vs.  Conditions:	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 inches  Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches above piges.				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons  Pump Requirements: ft. TDH vs.  Conditions:	tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 feet on Center Trenches shall be installed on contour at a Soil Cover: 6 inches (Maximum Trench Depth of: 24–30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches above pigents and the second shall be level to +/-1/4" 12 inches above pigents and the second shall be level to +/-1/4" 15 inches above pigents and the second shall be level to +/-1/4" 16 inches above pigents and the second shall be level to +/-1/4" 17 inches above pigents and the second shall be level to +/-1/4" 18 inches above pigents and the second shall be level to +/-1/4" 18 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pinches and the second shall be level to +/-1/4" 19 inches above pi				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons  Pump Tank Size ft. TDH vs.  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST NO UTILITIES ALLOWED IN INITIAL OR REPAIR	tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center Trenches shall be installed on contour at a Soil Cover: 6 inches Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches above piggregate Depth: 2 inches above piggregate Depth: 12 inches tot				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons  Pump Tank Size ft. TDH vs.  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST NO UTILITIES ALLOWED IN INITIAL OR REPAIR	tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 feet on Center Trenches shall be installed on contour at a Soil Cover: 6 inches (Maximum Trench Depth of: 24–30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches above pigents and the second shall be level to +/-1/4" 12 inches above pigents and the second shall be level to +/-1/4" 15 inches above pigents and the second shall be level to +/-1/4" 16 inches above pigents and the second shall be level to +/-1/4" 17 inches above pigents and the second shall be level to +/-1/4" 18 inches above pigents and the second shall be level to +/-1/4" 18 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pigents and the second shall be level to +/-1/4" 19 inches above pinches and the second shall be level to +/-1/4" 19 inches above pi				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  1000 gallons  Pump Tank Size 1000 gallons  Pump Tank Size ft. TDH vs.  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST NO UTILITIES ALLOWED IN INITIAL OR REPAIR	tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 feet Trench Spacing: 9 Feet on Center Trenches shall be installed on contour at a Soil Cover: 6 inches Maximum Trench Depth of: 24-30 inches (Maximum soil cover shall not exceed (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches above piggregate Depth: 2 inches above piggregate Depth: 12 inches tot				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1. 1	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 [Seet Trench Spacing: 9] Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 [Seet Trench Spacing: 9] Inches  Maximum Trench Depth of: 24–30 [Seet Trench Spacing: 9] Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 [Seet Trench Spacing: 9] Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 [Seet Trench Spacing: 9] Inches  Maximum Trench Depth of: 24–30 [Seet Trench Spacing: 9] Inches Soil Cover: 6 [Seet Trench Spacing: 9				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct  (See note below, if applicable 1)  25% Reduct  Installation Requirements/Conditions Septic Tank Size 1000 gallons  Pump Tank Size gallons  Pump Requirements: ft. TDH vs.  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST  NO UTILITIES ALLOWED IN INITIAL OR REPAIR  **If applicable: 1 understand the system type specific  Owner/Legal Representative Signature:  This Construction Authorization is subject to revocation of the site plan.	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 leet Trench Spacing: 9 Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 inches  Maximum Trench Depth of: 24–30 inches (Maximum soil cover shall not exceed  (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches below pig  Aggregate Depth: 2 inches tot  DRAIN FIELD AREA.  If is different from the type specified on the application. I accept the specifications of this permit.  Date:				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct  (See note below, if applicable 1)  25% Reduct  Installation Requirements/Conditions Septic Tank Size 1000 gallons  Pump Tank Size gallons  Pump Requirements: ft. TDH vs.  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST  NO UTILITIES ALLOWED IN INITIAL OR REPAIR  **If applicable: 1 understand the system type specific  Owner/Legal Representative Signature:  This Construction Authorization is subject to revocation of the site plan.	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 [Seet Trench Spacing: 9] Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 [Seet Trench Spacing: 9] Inches  Maximum Trench Depth of: 24–30 [Seet Trench Spacing: 9] Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 [Seet Trench Spacing: 9] Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 [Seet Trench Spacing: 9] Inches  Maximum Trench Depth of: 24–30 [Seet Trench Spacing: 9] Inches Soil Cover: 6 [Seet Trench Spacing: 9				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct (See note below, if applicable 1)  25% Reduct  Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size 1000 gallons  Pump Requirements: ft. TDH vs.  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST NO UTILITIES ALLOWED IN INITIAL OR REPAIR  ""If applicable: I understand the system type specific  Owner/Legal Representative Signature:  This Construction Authorization is subject to revocation if the site plan Construction Authorization is subject to compliance with the provisions	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150				
Basement? Yes No Basement Fi Type of Wastewater System** 25% Reduct  (See note below, if applicable 1)  25% Reduct  Installation Requirements/Conditions Septic Tank Size 1000 gallons  Pump Tank Size gallons  Pump Requirements: ft. TDH vs.  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST  NO UTILITIES ALLOWED IN INITIAL OR REPAIR  **If applicable: 1 understand the system type specific  Owner/Legal Representative Signature:  This Construction Authorization is subject to revocation of the site plan.	tures? Yes No  tion (Initial) Wastewater Flow: 360 GPD  Ction (Repair)  Number of trenches 1  Exact length of each trench 150 leet Trench Spacing: 9 Feet on Center  Trenches shall be installed on contour at a Soil Cover: 6 inches  Maximum Trench Depth of: 24–30 inches (Maximum soil cover shall not exceed  (Trench bottoms shall be level to +/-1/4" 36" above the trench bottom)  in all directions)  GPM  Aggregate Depth: 2 inches below pig  Aggregate Depth: 2 inches tot  DRAIN FIELD AREA.  If is different from the type specified on the application. I accept the specifications of this permit.  Date:				

Application # SFD2010-0035 R

## Harnett County Department of Public Health Site Sketch

Property Location: 484 Spring Flowers Dr  Issued To: Adams Homes Subdivision Carolina Seasons Lot # 29					
Issued To: Adam	s Homes	Subdivision Carolina Seasons	Lot # 29		
Authorized State Agent:	spel Al	NEHS	Date: 11-12-2020		

