



NOTES:

- TRUSSES 16" DEEP
- 24" O.C. UNLESS NOTED
- BEAMS:

B2= (2) 1-3/4" X 9-1/4" LVL
 B3= (2) 1-3/4" X 16" LVL

Note: All dimensions shown 00-00-00 are in Feet-Inches-Sixteenths

THIS LAYOUT IS INTENDED FOR THE PURPOSE OF TRUSS LOCATION AND PLACEMENT ONLY.
 REFER TO THE BUILDING PLANS FOR THE ACTUAL BUILDING CONSTRUCTION.

GENERAL NOTES:
 - DO NOT CUT, DRILL, NOTCH OR MODIFY TRUSSES WITHOUT APPROVAL FROM A CARTER LUMBER TRUSS ASSOCIATE
 - TRUSSES ARE SPACED AT 24" O.C. UNLESS NOTED OTHERWISE
 - REFER TO INDIVIDUAL TRUSS DESIGN DRAWINGS FOR THE LOCATION OF LATERAL BRACING AND MULTI-PLY CONNECTION REQUIREMENTS
 - PER AND TPI 1, 2002 THE TRUSS ENGINEER IS RESPONSIBLE FOR TRUSS TO TRUSS CONNECTIONS AND TRUSS PLY TO PLY CONNECTIONS
 - THIS TRUSS PLACEMENT PLAN RECOMMENDS TRUSS TO BEARING CONNECTIONS AND TRUSS TO BEAM CONNECTIONS WHICH SHALL BE REVIEWED BY THE BUILDING DESIGNER
 - IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER TO RESOLVE ALL ROOF FORCES ADEQUATELY TO THE FOUNDATION

HARDWARE LIST		
QTY	MARK	TYPE
.	.	.
.	.	.
.	.	.
.	.	.
.	.	.
.	.	.



747 OLD HARGRAVE RD LEXINGTON, NC 27295			
Project	2131 - A		
Customer	Adams Homes		
Job Name	L7 CAROLINA SEASONS		
Options	GARAGE LEFT		
Revision			
Ship Date			
Scale	Drawn Date	Drawn By	Order No.
NTS	3/22/22	SB	22020369