

GENERAL NOTES:

- DO NOT CUT, BBILL, NOTCH OR MODIFY TRUSSES WITHOUT APPROVAL FROM A CARTER LUMBER TRUSS ASSOCIATE

- TRUSSES ARE SPACED AT 24" O/C UNLESS NOTED COMMENTS

- PER ANSI TPI 1-2002 THE TRUSS ENGINEER IS RESPONSIBLE FOR TRUSS TO TRUSS CONNECTIONS AND TRUSS RIV TO PLY CONNECTION REQUIREMENTS

- PER ANSI TPI 1-2002 THE TRUSS ENGINEER IS RESPONSIBLE FOR TRUSS TO TRUSS CONNECTIONS AND TRUSS RIV TO PLY CONNECTIONS

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER TO RESOLVE ALL ROOF FORCES ADEQUATELY TO THE FOUNDATION

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER TO RESOLVE ALL ROOF FORCES ADEQUATELY TO THE FOUNDATION

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER TO RESOLVE ALL ROOF FORCES ADEQUATELY TO THE FOUNDATION

- IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER

- TRUSTS ARE TRUSS TO THE BUILDING DESIGNER

- TRUSTS ARE TRUSS TO THE BUILDING DESIGNER

- TRUSTS ARE TRUSS TO THE BUILDING DESIGNER

- THE STATE BUILDING D

ROOF AREA SQ FT