Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit PROPERTY LOCATION: 123 Heath Dr

	PROPERTY LOCATION: 120 1 1000 1	
ISSUED TO: Cumberland Homes Inc	SUBDIVISION Swift Creek	LOT # 5 <u>0</u>
NEW 🔀 REPAIR 🗌 EXPANSI	ON Site Improvements re	quired prior to Construction Authorization Issuance:
Type of Structure: SFD (59'x60')		
Proposed Wastewater System Type: 25% Reduction S	ystem	And the second s
Projected Daily Flow: 480 GPD		
Number of bedrooms: 4 Number of Occu	pants: 8 max	
Basement Yes No	pants.	
Control of the Contro	nired based on final location and elevations of facilities	6 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Type of Water Supply: Community 🔀 Public	Well Distance from well feet	Permit valid for: 🔀 Five years
Permit conditions:		No expiration
	1	
Authorized State Agent::	Q(=++) Date: 11/23/20	SEE ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guara	intees the issoubce of other permits. The permit holder is responsible for ch	cking with appropriate governing bodies in meeting their requirements. This
	changes. The Improvement Permit shall not be affected by a change in own	ership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditio	ns of this permit	
	Construction Authorization	
	(Required for Building Permit)	
The construction and installation requirements of Rules .1950, .1952,	954, .1955, .1956, .1957, .1958. and .1959 are incorporated by references	into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.		
stute to Cumberland Hames Inc	ADDRESS 100 TO 100 100 100 100 100 100 100 100 100 10	-th Du
SSUED TO: Cumberland Homes Inc	PROPERTY LOCATION: 123 He	
	SUBDIVISION Swift Creek	LOT # <u>50</u>
Facility Type: SFD (59'x60')	New 🗌 Expansion 🔲 Repair	
Basement? Yes 🗵 No Basement Fix	tures? Yes No	
Type of Wastewater System** 25% Reduction S	_	(Initial) Wastewater Flows 480 CDD
	youth	(Initial) Wastewater Flow: 480 GPD
See note below, if applicable 🔲	_	
25% Reduction	System (Repair)	
nstallation Requirements/Conditions	Number of trenches 1	
eptic Tank Size 1000 gallons	Exact length of each trench 300 feet	Trench Spacing: 9 Feet on Center
Pump Tank Sizegallons	Trenches shall be installed on contour at a	Soil Cover: 6-18 inches
unip failk sizeganons		
	Maximum Trench Depth of: 18-30 inches	(Maximum soil cover shall not exceed
	(Trench bottoms shall be level to $\pm/-1/4$ "	36" above the trench bottom)
	in all directions)	· ·
Pump Requirements:ft. TDH vs	GPM	inches below pip
	3111	
		Aggregate Depth: inches above pip
Conditions:		inches tota
VATER LINES (INCLUDING IRRIGATION) MILET	BE 10FT. FROM ANY PART OF SEPTIC SYSTEM OR	DEDAID ADEA
		AEFAIR AREA.
IO UTILITIES ALLOWED IN INITIAL OR REPAIR (JKAIN FIELD AKEA.	
*16 applicable: Lundarstand the system type specific	d is different from the two specified on the application	I against the anniforation of this
п аррисате. Д иностявно ине зулет суре престес	d is different from the type specified on the application	i accept the specifications of this permit.
Owner/Legal Representative Signature:		Date:
his Construction Authorization is subject to revocation if the site plan.	plat, or the intended use changes. The Construction Authorization shall not	
	the laws and Rules for Sewage Treatment and Disposal and to the condit	
The province of the province o	Sie new for seriege freatment and orsposal and to the condi-	AND ALL MINCHED SHE SKEICH
outhorized State Agent:	Date:	11/23/20
ů ————	Construction Authorization Expiration I	ate: 11/23/25
	Constitution Authorization Expiration E	utc

Harnett County Department of Public Health Site Sketch

