

Trenco  
818 Soundside Rd  
Edenton, NC 27932

Re: CG1009-F  
McKee-PorticoBungalow;Lot 1009 CarriageGlen

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Builders FirstSource-Apex,NC.

Pages or sheets covered by this seal: I43400172 thru I43400180

My license renewal date for the state of North Carolina is December 31, 2020.

North Carolina COA: C-0844



October 29,2020


Liu, Xuegang

**IMPORTANT NOTE:** The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job CG1009-F	Truss F01GR	Truss Type FLOOR	Qty 1	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen Job Reference (optional)	I43400172
-----------------	----------------	---------------------	----------	----------	---	-----------

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8,240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:50:59 2020 Page 1  
ID:SPpPQnXRhh0KJETLEIz6Peyo\_e3-a44siyaAXPF4h5F8iL4rWixWswYj1OjvPcOzFlyOrrQ



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.53	Vert(LL)	0.00	5	****	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.19	Vert(CT)	-0.01	4-5	>999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.15	Horz(CT)	0.00	4	n/a		
BCDL 5.0	Code IRC2015/TPI2014		Matrix-P					Weight: 16 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.2(flat)  
BOT CHORD 2x4 SP No.2(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 2-7-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 5=0-3-8, 4=Mechanical  
Max Grav 5=663(LC 1), 4=698(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-5=-256/0, 3-4=-256/0  
BOT CHORD 4-5=0/482  
WEBS 2-5=-611/0, 2-4=-646/0

**NOTES-**  
1) Refer to girder(s) for truss to truss connections.  
2) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.  
3) CAUTION, Do not erect truss backwards.  
4) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 4-5=-10, 1-3=-573(F=-473)



October 29, 2020



**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**  
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY  
**TRENCO**  
A MiTek Affiliate  
818 Soundside Road  
Edenton, NC 27932

Job CG1009-F	Truss F03	Truss Type FLOOR	Qty 2	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen I43400173
-----------------	--------------	---------------------	----------	----------	--

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8,240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:50:59 2020 Page 1  
ID:SPpPQnXRhh0KJETLEIz6Peyo\_e3-a44siyaAXPF4h5F8iL4rWixSwN\_1EbvPcOzFlyOrrQ



LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.79	Vert(LL)	-0.40	16-17	>522	480	MT20	244/190	
TCDL	10.0	Lumber DOL	1.00	BC	0.88	Vert(CT)	-0.56	16-17	>379	360	MT20HS	187/143	
BCLL	0.0	Rep Stress Incr	NO	WB	0.80	Horz(CT)	0.10	12	n/a	n/a			
BCDL	5.0	Code IRC2015/TPI2014		Matrix-S									Weight: 92 lb FT = 20%F, 11%E

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1 (flat) *Except* 1-8: 2x4 SP SS(flat)	TOP CHORD	Structural wood sheathing directly applied or 4-9-6 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1 (flat) *Except* 12-19: 2x4 SP SS(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3 (flat)		

**REACTIONS.** (size) 21=0-3-8, 12=0-3-8  
Max Grav 21=1290(LC 1), 12=1340(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**TOP CHORD** 2-3=-2864/0, 3-4=-4947/0, 4-5=-6364/0, 5-6=-6991/0, 6-7=-6662/0, 7-9=-5113/0, 9-10=-2912/0  
**BOT CHORD** 20-21=0/1635, 18-20=0/4059, 17-18=0/5807, 16-17=0/6887, 15-16=0/6991, 14-15=0/6029, 13-14=0/4169, 12-13=0/1622  
**WEBS** 2-21=-2049/0, 2-20=0/1600, 3-20=-1555/0, 3-18=0/1156, 4-18=-1120/0, 4-17=0/724, 5-17=-682/0, 10-12=-2071/0, 10-13=0/1679, 9-13=-1636/0, 9-14=0/1229, 7-14=-1192/0, 7-15=0/823, 6-15=-598/0

- NOTES-**
- All plates are MT20 plates unless otherwise indicated.
  - All plates are 4x6 MT20 unless otherwise indicated.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 700 lb down at 9-5-12 on top chord. The design/selection of such connection device(s) is the responsibility of others.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
 Uniform Loads (plf)  
 Vert: 12-21=-10, 1-11=-100  
 Concentrated Loads (lb)  
 Vert: 6=-700(F)





October 29, 2020

Job CG1009-F	Truss F03A	Truss Type FLOOR	Qty 1	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen Job Reference (optional)	I43400174
-----------------	---------------	---------------------	----------	----------	---	-----------

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8,240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:51:00 2020 Page 1  
ID:SPpPQnXRhh0KJETLElz6Peyo\_e3-2HeEvIboljNxJEqKG3b43wUduKjqmhz2eG7WokyOrrP



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.77	Vert(LL) -0.38	15-16	>547	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.84	Vert(CT) -0.52	15-16	>398	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr NO	WB 0.79	Horz(CT) 0.09	12	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S						
							Weight: 90 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1 (flat) *Except* 1-8: 2x4 SP SS (flat)	TOP CHORD Structural wood sheathing directly applied or 4-10-3 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1 (flat) *Except* 12-18: 2x4 SP SS (flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3 (flat)	

**REACTIONS.** (size) 20=0-3-8, 12=Mechanical  
Max Grav 20=1265(LC 1), 12=1329(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-2800/0, 3-4=-4822/0, 4-5=-6177/0, 5-6=-6757/0, 6-7=-6741/0, 7-9=-5061/0, 9-10=-2884/0  
BOT CHORD 19-20=0/1602, 17-19=0/3965, 16-17=0/5651, 15-16=0/6677, 14-15=0/5958, 13-14=0/4129, 12-13=0/1608  
WEBS 6-15=-666/0, 2-20=-2007/0, 2-19=0/1560, 3-19=-1516/0, 3-17=0/1116, 4-17=-1079/0, 4-16=0/685, 5-16=-650/0, 10-12=-2053/0, 10-13=0/1661, 9-13=-1621/0, 9-14=0/1213, 7-14=-1168/0, 7-15=0/937

- NOTES-**
- All plates are MT20 plates unless otherwise indicated.
  - All plates are 4x6 MT20 unless otherwise indicated.
  - Refer to girder(s) for truss to truss connections.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - CAUTION, Do not erect truss backwards.
  - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 700 lb down at 9-5-12 on top chord. The design/selection of such connection device(s) is the responsibility of others.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 12-20=-10, 1-11=-100  
Concentrated Loads (lb)  
Vert: 6=-700(F)




October 29, 2020

Job CG1009-F	Truss F04G	Truss Type GABLE	Qty 1	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen Job Reference (optional)	I43400175
-----------------	---------------	---------------------	----------	----------	---	-----------

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:51:00 2020 Page 1  
ID:SPpPQnXRhh0KJETLElz6Peyo\_e3-2HeEvlboljNxEqKG3b43wUofKwemtr2eG7WokyOrrP

Scale = 1:15.5



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.08	Vert(LL) n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.02	Vert(CT) n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00	9	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-R					Weight: 36 lb	FT = 20%F, 11%E

**LUMBER-**  
 TOP CHORD 2x4 SP No.2(flat)  
 BOT CHORD 2x4 SP No.2(flat)  
 WEBS 2x4 SP No.3(flat)  
 OTHERS 2x4 SP No.3(flat)

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 8-4-8.  
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 16, 15, 14, 13, 12, 11, 10

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
  - 2) Gable requires continuous bottom chord bearing.
  - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - 4) Gable studs spaced at 1-4-0 oc.
  - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



October 29, 2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932

Job CG1009-F	Truss F05	Truss Type FLOOR	Qty 1	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen I43400176
-----------------	--------------	---------------------	----------	----------	--

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8,240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:51:01 2020 Page 1  
ID:SPpPQnXRhh0KJETLEIz6Peyo\_e3-XTCd7ecQ31VoxOPXqm6Jb70uNj8BVHxBtwt4KAyORo



Scale = 1:15.5




Plate Offsets (X,Y)--	[4:0-1-8,Edge], [10:0-1-8,Edge]				
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.40	Vert(LL) -0.06 8-9 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.57	Vert(CT) -0.07 8-9 >999 360		
BCLL 0.0	Rep Stress Incr YES	WB 0.23	Horz(CT) 0.01 7 n/a n/a		
BCDL 5.0	Code IRC2015/TP12014	Matrix-S		Weight: 42 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (size) 7=0-3-8, 11=Mechanical  
Max Grav 7=454(LC 1), 11=454(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-863/0, 3-4=-863/0, 4-5=-733/0  
BOT CHORD 10-11=0/495, 9-10=0/863, 8-9=0/863, 7-8=0/530  
WEBS 5-7=-677/0, 2-11=-632/0, 5-8=0/264, 2-10=0/490

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) Refer to girder(s) for truss to truss connections.
  - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



October 29, 2020

Job CG1009-F	Truss F07	Truss Type FLOOR	Qty 3	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen I43400177
-----------------	--------------	---------------------	----------	----------	--

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8,240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:51:01 2020 Page 1  
ID:SPpQnXRhh0KJETLEIz6Peyo\_e3-XTcd7ecQ31VoxOPXqm6Jb70xJjDTVJ1Btw4KAYOrO




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [7:0-1-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.22	Vert(LL) -0.02	6-7	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.24	Vert(CT) -0.03	6-7	>999	360		
BCLL 0.0	Rep Stress Incr YES	WB 0.10	Horz(CT) 0.00	6	n/a	n/a		
BCDL 5.0	Code IRC2015/TP12014	Matrix-S					Weight: 30 lb	FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.2(flat)  
BOT CHORD 2x4 SP No.2(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 5-5-8 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 9=0-3-8, 6=Mechanical  
Max Grav 9=284(LC 1), 6=290(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-344/0, 3-4=-344/0  
BOT CHORD 8-9=0/344, 7-8=0/344, 6-7=0/284  
WEBS 4-6=-362/0, 2-9=-422/0

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
  - 2) Refer to girder(s) for truss to truss connections.
  - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - 4) CAUTION, Do not erect truss backwards.



October 29,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
Edenton, NC 27932

Job CG1009-F	Truss F08	Truss Type FLOOR	Qty 11	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen I43400178
-----------------	--------------	---------------------	-----------	----------	--

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:51:02 2020 Page 1  
ID:SPpPQnXRhh0KJETLElz6Peyo\_e3-?fm?K\_d2qKdfYY\_jOTdY8LZ4?7VvEKjL6acdsdyOrrN



Scale = 1:14.6




Plate Offsets (X,Y)-- [4:0-1-8,Edge], [10:0-1-8,Edge]		7-11-0 7-11-0					
<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>
TCLL 40.0	2-0-0	TC 0.35	Vert(LL) -0.04	8-9	>999	480	<b>GRIP</b>
TCDL 10.0	Plate Grip DOL 1.00	BC 0.48	Vert(CT) -0.05	8-9	>999	360	244/190
BCLL 0.0	Lumber DOL 1.00	WB 0.20	Horz(CT) 0.01	7	n/a	n/a	
BCDL 5.0	Rep Stress Incr YES	Matrix-S					Weight: 41 lb
	Code IRC2015/TP12014						FT = 20%F, 11%E

**LUMBER-**  
TOP CHORD 2x4 SP No.2(flat)  
BOT CHORD 2x4 SP No.2(flat)  
WEBS 2x4 SP No.3(flat)

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 7=Mechanical, 11=Mechanical  
Max Grav 7=429(LC 1), 11=429(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-779/0, 3-4=-779/0, 4-5=-671/0  
BOT CHORD 10-11=0/464, 9-10=0/779, 8-9=0/779, 7-8=0/497  
WEBS 5-7=-635/0, 2-11=-592/0, 2-10=0/418

**NOTES-**  
1) Unbalanced floor live loads have been considered for this design.  
2) Refer to girder(s) for truss to truss connections.  
3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails.  
Strongbacks to be attached to walls at their outer ends or restrained by other means.



October 29,2020

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**  
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TP1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY  
**TRENCO**  
A MiTek Affiliate  
818 Soundside Road  
Edenton, NC 27932



Job CG1009-F	Truss F09GR	Truss Type FLOOR	Qty 1	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen I43400179
Builders FirstSource (Apex, NC), Apex, NC - 27523,					Job Reference (optional)

8,240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:51:02 2020 Page 1  
ID:SPpPqnXRhh0KJETLElz6Peyo\_e3-?fm?K\_d2qKdfYY\_jOTdY8LZ\_E7RTEgML6acdsdyOrrN



Scale = 1:14.9




Plate Offsets (X,Y)--	[4:0-1-8,Edge], [5:0-3-12,Edge], [9:0-3-0,0-0-0], [10:0-1-8,Edge]
-----------------------	---

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.72	Vert(LL) -0.06	8-9	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.76	Vert(CT) -0.08	8-9	>999	360		
BCLL 0.0	Rep Stress Incr NO	WB 0.48	Horz(CT) 0.02	7	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S					Weight: 72 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (size) 11=Mechanical, 7=Mechanical  
Max Grav 11=1989(LC 1), 7=1989(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-11=-295/0, 2-3=-4050/0, 3-4=-4050/0, 4-5=-3454/0  
BOT CHORD 10-11=0/2459, 9-10=0/4050, 8-9=0/4050, 7-8=0/2627  
WEBS 5-7=-3204/0, 2-11=-2999/0, 5-8=0/1026, 2-10=0/2009, 4-8=-947/0, 3-10=-805/0, 4-9=-563/14

- NOTES-**
- Unbalanced floor live loads have been considered for this design.
  - Refer to girder(s) for truss to truss connections.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 7-11=-10, 1-6=-501(F=-400)



October 29,2020

Job CG1009-F	Truss F10	Truss Type FLOOR	Qty 1	Ply 1	McKee-PorticoBungalow;Lot 1009 CarriageGlen I43400180
Builders FirstSource (Apex, NC), Apex, NC - 27523,					Job Reference (optional)

8,240 s Mar 9 2020 MiTek Industries, Inc. Wed Oct 28 14:51:03 2020 Page 1  
ID:SPpPQnXRhh0KJETLEIz6Peyo\_e3-TrKNYKdhdbeIWAiZvx8B8nhY6DUXkTz53UKEMAO3yOrrM



Scale = 1:14.6




Plate Offsets (X,Y)--	[10:0-1-8,Edge]				
<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 40.0	Plate Grip DOL 1.00	TC 0.49	Vert(LL) -0.05 9 >999 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.91	Vert(CT) -0.07 8-9 >999 360		
BCLL 0.0	Rep Stress Incr NO	WB 0.58	Horz(CT) 0.02 7 n/a n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S		Weight: 51 lb	FT = 20%F, 11%E

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

**REACTIONS.** (size) 7=Mechanical, 11=Mechanical  
Max Grav 7=1140(LC 1), 11=1140(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-2200/0, 3-4=-2200/0, 4-5=-1836/0  
BOT CHORD 10-11=0/1271, 9-10=0/2200, 8-9=0/2200, 7-8=0/1413  
WEBS 5-7=-1763/0, 2-11=-1585/0, 5-8=0/543, 2-10=0/1214, 4-8=-515/0, 3-10=-624/0

- NOTES-**
- Unbalanced floor live loads have been considered for this design.
  - Refer to girder(s) for truss to truss connections.
  - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
  - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).


**LOAD CASE(S)** Standard  
1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00  
Uniform Loads (plf)  
Vert: 7-11=-10, 1-6=-282(F=-182)



October 29,2020

# Symbols

## PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.

\* Plate location details available in **MITek 20/20 software or upon request.**

## PLATE SIZE

4 X 4

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

## BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

## Industry Standards:

ANSI/TPI 1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-89: Design Standard for Bracing, Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System

6-4-8  
dimensions shown in ft-in-sixteenths  
(Drawings not to scale)



**JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.**

**CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.**

## PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988  
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TPI 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITteK® All Rights Reserved



MITek Engineering Reference Sheet: Mill-7473 rev. 5/19/2020



# General Safety Notes

## Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative T or I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TPI 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TPI 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TPI 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.