Harnett County Department of Public Health

Improvement Permit

A b	uilding permit cannot be issued with only an Improvement	Permit
ISSUED TO: Teddy & Rebecca Stricklan		eaf Dr. (Fairground Rd SR 170:
NEW REPAIR EXPANSION		uired prior to Construction Authorization Issuance:
Type of Structure: 75x57 sfd, 3 bedrooms	2 baths	
Proposed Wastewater System Type: 25% Reduction	on Sys.	
Projected Daily Flow: 360 GPD		
Number of bedrooms: 3 Number of Occupat	nts: <u>b</u> max	
Basement	d based on final location and elevations of facilities	
Pump Required: Yes \(\bigcup \) No \(\times \) May be require Type of Water Supply: \(\bigcup \) Community \(\times \) Public \(\bigcup \) Permit conditions:		Permit valid for: 🔀 Five years 🔲 No expiration
welfallet.	Date: 12 17 2	OZO SEE ATTACHED SITE SKETCH
Authorized State Agent:: The issuance of this permit by the Health Department in way guarante site is subject to revocation if the site plan, plat, or the intended use chathe Laws and Rules for Sewage Treatment and Disposal and to conditions	es the issuance of other permits. The permit holder is responsible for che nges. The Improvement Permit shall not be affected by a change in owne	cking with appropriate governing bodies in meeting their requirements. This reship of the site. This permit is subject to compliance with the provisions of
	Construction Authorization	
	(Required for Building Permit)	
The construction and installation requirements of Rules .1950, .1952, .195		into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.		
Facility Type: 75x57 sfd, 3 bedrooms 2 Basement? Yes No Basement Fixtu	SUBDIVISION Repair res? Yes No	rookleaf Dr. (Fairground Rd SR 1
Type of Wastewater System** 3570	VEDSITION STOTEM	(Initial) Wastewater Flow:360 GPD
(See note below, if applicable 🔲)		
25% 100x		
Installation Requirements/Conditions	Number of trenches 3	Just Carrier
Septic Tank Size 100 gallons	Exact length of each trench feet	Trench Spacing: Feet on Center Soil Cover: inches
Pump Tank Sizegallons	Trenches shall be installed on contour at a Maximum Trench Depth of:inches	(Maximum soil cover shall not exceed
	(Trench bottoms shall be level to +/-1/4"	36" above the trench bottom)
	in all directions)	30 above the trenen bottomy
Pump Requirements:ft. TDH vs	,	inches below pipe
rump kedurements.	_UT 1	Aggregate Depth: inches above pipe
Conditions: 624017 TO 5-BOX EC	LAE DISTAIBUTION	inches total
WATER LINES (INCLUDING IRRIGATION) MUST BE NO UTILITIES ALLOWED IN INITIAL OR REPAIR DE		REPAIR AREA.
**If applicable: 1 understand the system type specified	is different from the type specified on the application.	. I accept the specifications of this permit.
Owner/Legal Representative Signature:		Date:
This Construction Authorization is subject to revocation if the site plan, plat, or the intended use changes. The Construction Authorization shall not be transferred when there is a change in ownership of the site. This		
Construction Authorization is subject to compliance with the provisions of	Laws and Rules for Sewage Treatment and Disposal and to the conditi	ions of this permit. SEE ATTACHED SITE SKETCH
	and the	
Authorized State Agent:	Date:	12114/2020
ANDREW CORNIN	Construction Authorization Expiration D	Date: 12 14/2025

Harnett County Department of Public Health Site Sketch

Property Location: 69 Brooklean Dr. (Fairground Rd 3R 1703)	TD#10
Issued To: Teddy & Rebecca Strickland Subdivision	Lot # TR#10
Authorized State Agent: Date:	12/17/2020
(CANDITY TO D. GOX EGUAL DISTAIGUTION)	4
PLUMBING ON SLAB SHALL BE STUBBED SHALLOW TO MILLOW	
ABEQUATE FALL TO SEPTIC ATEX	
- CONTRACTOR SHALL REVIEW PRE-INSTACL	
WONKSHOO MAY BE DEPENDENT ON FINAC GEPTIC	
- rebubblit to be minded at instack to venich placeme	2007
20' menusher 24' 25' menusher 24'	P.L.
JOAN SED 10001 MIN	
45-1	20 x
>10 8	
Brookter Drive	

This drawing is for illustrative purposes only. System installation must meet all pertinent laws, rules, and regulations.