

NOTICE TO CONTRACTOR  
 All construction must comply with current NC Building Codes and is subject to field inspection and verification.


**APPROVED**  
 Limited building only review  
 Permit holder responsible for full compliance with the code

01/29/2021






**Front Elevation**  
 Scale: 1/4" = 1'0"



**Left Elevation**  
 Scale: 1/8" = 1'0"



**Rear Elevation**  
 Scale: 1/8" = 1'0"



**Right Elevation**  
 Scale: 1/8" = 1'0"

DATE: 8/25/2020

REVISED

DRAWING#


EIV. A

SCALE: 1/4"

DRAWN BY

APPROVED


**The Westbrook**



# First Floor Plan

Scale: 1/4" = 1'-0"

## Kitchen Cabinets



FIRST FLOOR OPENING SCHEDULE			
PRODUCT CODE	SIZE	HINGE	COUNT
36X80 COLONIAL A 1	3'-0"	L	1
192X96 - 8 PANEL - 4 WINDOW	16'-0"	U	1
72X80 SLIDING FRENCH 2	6'-0"	NL	1
2-0 Door Unit	2'-0"	L	1
2-0 Door Unit	2'-0"	R	1
2-4 Door Unit	2'-4"	L	1
2-4 Door Unit	2'-4"	R	1
2-8 Door Unit	2'-8"	R	1
24X24 CASEMENT 1	2'-0" x 2'-0"	N	2
24X32 Single	2'-4" x 3'-2"	N	1
24x310 single	2'-4" x 3'-10"	N	1
28x52 twin	5'-4" x 5'-2"	NN	1

## Areas

First Floor	892
Second Floor	1316
=====	
Total Heated	2208
Garage	512
Front Porch	85

DATE: 8/25/2020

REVISED


DRAWING#

SCALE: 1/4"

DRAWN BY

APPROVED


The Westbrook



Second Floor Plan

Scale: 1/4" = 1'-0"

SECOND FLOOR OPENING SCHEDULE			
PRODUCT CODE	SIZE	HINGE	COUNT
2-0 Door Unit	2'-0"	L	3
2-4 Door Unit	2'-4"	R	1
2-4 Door Unit	2'-4"	L	1
2-6 Door Unit	2'-6"	L	2
2-6 Door Unit	2'-6"	R	2
3-0 Doublehung Door Unit	3'-0"	LR	1
4-0 Doublehung Door Unit	4'-0"	LR	3
20x20 twin	4'-0" x 3'-2"	NA	1
24x310 single	2'-4" x 3'-10"	N	1
28x52 single	2'-8" x 5'-2"	N	2
28x52 twin	5'-4" x 5'-2"	NN	2
12X12 GLASS BLOCK	4'-0" x 1'-0"	N	1



Roof Plan

DATE: 8/25/2020

REVISED


DRAWING#

SCALE: 1/4"

DRAWN BY


APPROVED

The Westbrook




Foundation Plan

Foundation Detail



Footing & Pier Detail




FOUNDATION VENTILATION

892 Sq.Ft. Foundation Area  
 Requires 5.94 Sq.Ft. Ventilation.  
 With 6 Mil. Poly, Plans Indicate  
 Vents For Adequate Cross  
 Ventilation.


DATE: 8/25/2020  
 REVISED  
 DRAWING#

SCALE: 1/4"  
 DRAWN BY  
 APPROVED


The Westbrook



Foundation Plan



TURN-DOWN FOOTING DETAIL



INTEGRAL SLAB FOOTING DETAIL AT BEARING WALL

DATE: 8/25/2020

REVISED


DRAWING#

SCALE: 1/4"

DRAWN BY


APPROVED

The Westbrook




Foundation Plan

Foundation Detail Siding



Lug Footing Detail



DATE: 8/25/2020  
REVISED  
DRAWING#

SCALE: 1/4"  
DRAWN BY  
APPROVED

The Westbrook



**ROOF & FLOOR TRUSSES & BEAMS**

Reilly Road Industrial Park  
Fayetteville, N.C. 28309  
Phone: (910) 864-8787  
Fax: (910) 864-4444

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables ( derived from the prescriptive Code requirements ) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature David Landry  
David Landry

**LOAD CHART FOR JACK STUDS**

(BASED ON TABLES ROE11C & 1D)


NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADERS/BEAMS

END REACTION (IP-TON)	REQ'D STUDS FOR EACH END OF HEADERS/BEAMS	END REACTION (IP-TON)	REQ'D STUDS FOR EACH END OF HEADERS/BEAMS	END REACTION (IP-TON)	REQ'D STUDS FOR EACH END OF HEADERS/BEAMS
1700	1	2550	1	3400	1
3400	2	5100	2	6800	2
5100	3	7650	3	10200	3
6800	4	10200	4	13600	4
8500	5	12750	5	17000	5
10200	6	15300	6		
11900	7				
13600	8				
15300	9				

CITY / CO.	Spring Lake / Cumberland
ADDRESS	29 South Dakota Ct.
MODEL	Roof
DATE REV.	/ /
DRAWN BY	David Landry
SALES REP.	Marshall Naylor

BUILDER	Ben Stout Real Estate
JOB NAME	Lot 2 Sierra Villas
PLAN	Westbrook
SEAL DATE	Seal Date
QUOTE #	Quote #
JOB #	J0121-0105

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com.



**Dimension Notes**

- All exterior wall to wall dimensions are to face of sheathing unless noted otherwise
- All interior wall dimensions are to face of frame wall unless noted otherwise
- All exterior wall to truss dimensions are to face of frame wall unless noted otherwise

**All Walls Shown Are Considered Load Bearing**

**Plumbing Drop Notes**

- Plumbing drop locations shown are NOT exact.
- Contractor to verify ALL plumbing drop locations prior to setting Floor Trusses.
- Adjust spacing as needed not to exceed 24"oc.

Sym	Connector Information				Nail Information	
	Product	Manuf	Qty	Supported Member	Header	Truss
●	HUS410	USP	20	NA	16d/3-1/2"	16d/3-1/2"

Products					
PlotID	Length	Product	Plies	Net Qty	
BM1	25' 0"	1-3/4"x 23-7/8" LVL Kerto-S	3	3	
BM2	7' 0"	1-3/4"x 16" LVL Kerto-S	2	2	
GDH	25' 0"	1-3/4"x 11-7/8" LVL Kerto-S	2	2	

1 Truss Placement Plan  
Scale: 1/4"=1'

▲ = Indicates Left End of Truss  
(Reference Engineered Truss Drawing)  
Do NOT Erect Truss Backwards



**ROOF & FLOOR TRUSSES & BEAMS**

Reilly Road Industrial Park  
 Fayetteville, N.C. 28309  
 Phone: (910) 864-8787  
 Fax: (910) 864-4444

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables ( derived from the prescriptive Code requirements ) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.


Signature David Landry  
 David Landry

**LOAD CHART FOR JACK STUDS**

(BASED ON TABLES ROEHLIC 6 (b))

NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADERS/STROPS

END REACTION (IP / T)	REQ'D STUDS FOR 10' HEADERS	END REACTION (IP / T)	REQ'D STUDS FOR 10' STROPS	END REACTION (IP / T)	REQ'D STUDS FOR 10' HEADERS
1700	1	2550	1	3400	1
3400	2	5100	2	6800	2
5100	3	7650	3	10200	3
6800	4	10200	4	13600	4
8500	5	12750	5	17000	5
10200	6	15300	6		
11900	7				
13600	8				
15300	9				



**Dimension Notes**

- All exterior wall to wall dimensions are to face of sheathing unless noted otherwise
- All interior wall dimensions are to face of frame wall unless noted otherwise
- All exterior wall to truss dimensions are to face of frame wall unless noted otherwise

**All Walls Shown Are Considered Load Bearing**

Roof Area = 2311.33 sq.ft.  
 Ridge Line = 65.83 ft.  
 Hip Line = 40.81 ft.  
 Horiz. OH = 178.13 ft.  
 Raked OH = 124.36 ft.  
 Decking = 79 sheets

**Hatch Legend**

[Blue Box]	Box Storage
[Light Blue Box]	Tray Ceiling
[Red Box]	2nd Floor Walls
[Yellow Box]	Drop Beam

**Connector Information**

Sym	Product	Manuf	Qty	Supported Member	Header	Truss
[Blue Box]	HUS26	USP	14	NA	16d/3-1/2"	16d/3-1/2"

**Products**

PlotID	Length	Product	Plies	Net Qty
BM1	25' 0"	1-3/4"x 23-7/8" LVL Kerto-S	3	3
BM2	7' 0"	1-3/4"x 16" LVL Kerto-S	2	2
GDH	25' 0"	1-3/4"x 11-7/8" LVL Kerto-S	2	2

**1 Truss Placement Plan**  
 Scale: 1/4" = 1'

CITY / CO.	Spring Lake / Cumberland
ADDRESS	29 South Dakota Ct.
MODEL	Roof
DATE REV.	/ /
DRAWN BY	David Landry
SALES REP.	Marshall Naylor
BUILDER	Ben Stout Real Estate
JOB NAME	Lot 2 Sierra Villas
PLAN	Westbrook
SEAL DATE	Seal Date
QUOTE #	Quote #
JOB #	J0121-0105

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com.

▲ = Indicates Left End of Truss  
 (Reference Engineered Truss Drawing)  
 Do NOT Erect Truss Backwards