

Trenco
818 Soundside Rd
Edenton, NC 27932

Re: J1120-5330
Lot 46 South Creek

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Comtech, Inc - Fayetteville.

Pages or sheets covered by this seal: E15095623 thru E15095670

My license renewal date for the state of North Carolina is December 31, 2020.

North Carolina COA: C-0844



November 13, 2020

Gilbert, Eric

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095623
J1120-5330	A01	Piggyback Base	6	1		

Comtech, Inc., Fayetteville, NC - 28314, 8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:08 2020 Page 1
 ID:YFDfFaMnBckfZxe?!GwdkVz?opC-2fcn_xtymsn5xJgY9hWTPavSCx9UI7PAesOg8fyJfOL



Scale = 1:87.8





Plate Offsets (X,Y)-- [4:0-4-0,0-0-8], [5:0-3-0,0-2-12], [7:0-3-0,0-2-12], [13:0-5-4,0-3-8], [14:0-2-0,0-3-12], [15:0-3-0,0-3-8]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.72	Vert(LL) -0.41	11-13	>917	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.74	Vert(CT) -0.57	11-13	>665	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.77	Horz(CT) 0.06	11	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.04	14	>999	240	Weight: 348 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-10-1 oc purlins, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (6-0-0 max.): 5-7.
WEBS 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
	WEBS 1 Row at midpt 5-13, 6-13, 7-11

REACTIONS. (size) 15=0-3-0, 11=0-3-8
 Max Horz 15=167(LC 11)
 Max Uplift 15=120(LC 8)
 Max Grav 15=2300(LC 1), 11=1697(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-609/1291, 2-4=-1441/0, 4-5=-1381/36, 5-6=-769/60, 6-7=-769/60, 7-9=-72/385, 9-10=-216/408
 BOT CHORD 1-15=-1102/615, 14-15=-1263/680, 13-14=-48/935, 11-13=0/571
 WEBS 2-15=-1661/252, 2-14=-64/2308, 4-14=-568/62, 5-14=-45/680, 6-13=-367/103, 7-13=-6/524, 7-11=-1148/68, 9-11=-510/235


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-0-0 to 4-4-13, Interior(1) 4-4-13 to 24-2-4, Exterior(2) 24-2-4 to 28-7-1, Interior(1) 28-7-1 to 35-2-12, Exterior(2) 35-2-12 to 39-7-9, Interior(1) 39-7-9 to 49-5-0 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 15=120.
 - 7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095624
J1120-5330	A02	Piggyback Base	2	1		

Comtech, Inc., Fayetteville, NC - 28314, 8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:09 2020 Page 1
 ID:YFDIFaMnBckfZxe?IGwdkVz?opC-WrAABHuaXAvyZTFkJP1yoSdzLzJjUdgJtW8Dg5yJfOK



Scale = 1:86.7




Plate Offsets (X,Y)-- [4:0-4-0,0-0-8], [5:0-3-0,0-2-12], [7:0-3-0,0-2-12], [13:0-5-4,0-3-8], [14:0-2-4,0-3-8], [15:0-3-0,0-3-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.72	Vert(LL) -0.20	11-13	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.49	Vert(CT) -0.28	11-13	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.58	Horz(CT) 0.05	11	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.03	14	>999	240	Weight: 352 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.2	WEBS 1 Row at midpt 5-13, 6-13, 7-11
SLIDER Right 2x6 SP No.1 -x 4-1-6	

REACTIONS. (size) 15=0-3-0, 11=0-3-8
 Max Horz 15=167(LC 9)
 Max Uplift 15=-131(LC 8)
 Max Grav 15=2225(LC 23), 11=1769(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-609/1292, 2-4=-1197/28, 4-5=-1128/64, 5-6=-580/47, 6-7=-580/47, 7-8=-10/384, 8-10=-200/475
 BOT CHORD 1-15=-1103/615, 14-15=-1261/681, 13-14=-68/762, 11-13=-6/353, 10-11=-263/221
 WEBS 2-15=-1588/246, 2-14=-49/2128, 4-14=-519/68, 5-14=-55/583, 6-13=-375/113, 7-13=0/570, 7-11=-1054/33, 8-11=-511/252

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-0-0 to 4-4-13, Interior(1) 4-4-13 to 24-2-4, Exterior(2) 24-2-4 to 28-7-1, Interior(1) 28-7-1 to 35-2-12, Exterior(2) 35-2-12 to 39-7-9, Interior(1) 39-7-9 to 48-2-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 15=131.
 - 7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095625
J1120-5330	A03GR	PIGGYBACK BASE GIRDE	1	2		

Comtech, Inc., Fayetteville, NC - 28314, 8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:10 2020 Page 1
 ID:YFDiFaMnBckfZxe?IGwdkVz?opC-_1kYPcvDIT1pAdqwH6ZxU??tyku6D2UT5AtnCXYJf0J




Plate Offsets (X,Y)-- [1:0-3-0,0-1-8], [2:0-5-0,0-3-0], [12:0-5-0,0-8-0], [13:0-5-0,0-6-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.38	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.54	Vert(LL) -0.16 9-12 >999 360	M18SHS	244/190
BCLL 0.0 *	Lumber DOL 1.15	WB 0.74	Vert(CT) -0.29 9-12 >999 240		
BCDL 10.0	Rep Stress Incr NO	Matrix-S	Horz(CT) 0.03 8 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.01 12 >999 240	Weight: 652 lb	FT = 20%


LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-7-3 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-5.
BOT CHORD 2x10 SP 2400F 2.0E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except* 1-14,6-8: 2x6 SP No.1, 1-13: 2x4 SP No.1	WEBS 1 Row at midpt 4-9

REACTIONS. (size) 14=0-9-8, 8=0-3-8
 Max Horz 14=100(LC 5)
 Max Grav 14=8872(LC 2), 8=5039(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-7408/0, 2-3=-9023/0, 3-4=-7535/0, 4-5=-4174/0, 5-6=-5081/0, 1-14=-8313/0, 6-8=-5226/0
 BOT CHORD 12-13=0/8252, 9-12=0/5904
 WEBS 2-13=-2229/0, 2-12=-1397/0, 3-12=0/4667, 4-12=0/3307, 4-9=-3529/0, 5-9=0/2467, 1-13=0/8901, 6-9=0/4684

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
 Bottom chords connected as follows: 2x10 - 2 rows staggered at 0-7-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1145 lb down at 1-11-4, 1145 lb down at 3-11-4, 1145 lb down at 5-11-4, 1113 lb down at 7-11-4, 1105 lb down at 9-11-4, 1145 lb down at 11-11-4, 1145 lb down at 13-11-4, 1124 lb down at 15-11-4, and 1100 lb down at 17-11-4, and 1100 lb down at 19-7-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095625
J1120-5330	A03GR	PIGGYBACK BASE GIRDE	1	2	Job Reference (optional)	

Comtech, Inc. Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:10 2020 Page 2
 ID:YFDIFaMnBCkfZxe?IGwdkVz?opC-_1kYPcvDIT1pAdqwH6ZxU??tyku6D2UT5AtnCXyJf0J

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-3=-60, 3-5=-60, 5-6=-60, 7-15=-20

Concentrated Loads (lb)

Vert: 11=-992(B) 16=-992(B) 17=-992(B) 18=-992(B) 20=-992(B) 21=-992(B) 23=-992(B) 24=-992(B) 25=-992(B) 26=-992(B)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095626
J1120-5330	B01GR	Half Hip Girder	1	2	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:13 2020 Page 2

ID:YFDfFaMnBCKfZxe?lGwdkVz?opC-OcPg1ex5aOPO14ZVyF6e6edOPyzzQNLvn86RpsyJf0G

NOTES-

10) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 45 lb down and 39 lb up at 4-8-8, 48 lb down and 36 lb up at 6-9-4, 48 lb down and 36 lb up at 8-9-4, 48 lb down and 36 lb up at 10-9-4, 48 lb down and 36 lb up at 12-9-4, 48 lb down and 36 lb up at 14-9-4, 48 lb down and 36 lb up at 16-9-4, 48 lb down and 36 lb up at 18-9-4, 48 lb down and 36 lb up at 20-9-4, 48 lb down and 36 lb up at 22-9-4, 48 lb down and 36 lb up at 24-9-4, 48 lb down and 36 lb up at 26-9-4, 48 lb down and 36 lb up at 28-9-4, 48 lb down and 36 lb up at 30-9-4, 48 lb down and 36 lb up at 32-9-4, and 48 lb down and 36 lb up at 34-9-4, and 48 lb down and 36 lb up at 36-9-4 on top chord, and 6 lb down and 44 lb up at 2-9-4, 18 lb down and 27 lb up at 4-9-4, 18 lb down and 27 lb up at 6-9-4, 18 lb down and 27 lb up at 8-9-4, 18 lb down and 27 lb up at 10-9-4, 18 lb down and 27 lb up at 12-9-4, 18 lb down and 27 lb up at 14-9-4, 18 lb down and 27 lb up at 16-9-4, 18 lb down and 27 lb up at 18-9-4, 18 lb down and 27 lb up at 20-9-4, 18 lb down and 27 lb up at 22-9-4, 18 lb down and 27 lb up at 24-9-4, 18 lb down and 27 lb up at 26-9-4, 18 lb down and 27 lb up at 28-9-4, 18 lb down and 27 lb up at 30-9-4, 18 lb down and 27 lb up at 32-9-4, and 18 lb down and 27 lb up at 34-9-4, and 18 lb down and 27 lb up at 36-9-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-8=-60, 8-9=-60, 1-10=20

Concentrated Loads (lb)

Vert: 17=5(F) 33=12(F) 34=5(F) 35=5(F) 36=5(F) 37=5(F) 38=5(F) 39=5(F) 40=5(F) 41=5(F) 42=5(F) 43=5(F) 44=5(F) 45=5(F) 46=5(F) 47=5(F) 48=5(F) 49=5(F)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095627
J1120-5330	B02	HALF HIP	1	1		

Job Reference (optional)

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:14 2020 Page 1

ID:YFDfFaMnBckfZxe?lGwdkVz?opC-soz3E_yjLiXFfE8hWydtr9UkMDz9ug20or_LJyJf0F



Scale = 1:65.7




Plate Offsets (X,Y)-- [1:0-4-4,1-1-11], [1:0-0-8,Edge], [2:0-4-0,0-2-5], [4:0-2-4,0-2-0], [11:0-3-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.72	Vert(LL) -0.14	13-14	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.74	Vert(CT) -0.29	13-14	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.60	Horz(CT) 0.07	10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.08	13-14	>999	240	Weight: 267 lb	FT = 20%

LUMBER-
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2
WEDGE
Left: 2x8 SP No.1

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-10-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-5-4 max.): 2-8.
Rigid ceiling directly applied or 10-0-0 oc bracing.
BOT CHORD
WEBS T-Brace: 2x4 SPF No.2 - 3-16, 5-14
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
Brace must cover 90% of web length.

REACTIONS. (size) 10=Mechanical, 1=0-3-8
Max Horz 1=109(LC 12)
Max Grav 10=1514(LC 1), 1=1503(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-2325/174, 2-3=-1845/190, 3-5=-2917/247, 5-6=-2944/216, 6-7=-2002/138, 7-10=-1437/148
BOT CHORD 1-16=-190/1818, 14-16=-247/2917, 13-14=-216/2944, 11-13=-138/2002
WEBS 2-16=0/864, 3-16=-1329/68, 3-14=0/316, 5-13=-427/137, 6-13=-92/1107, 6-11=-1080/188, 7-11=-161/2332

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 7-2-8, Exterior(2) 7-2-8 to 13-5-3, Interior(1) 13-5-3 to 38-2-8 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 8) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.




November 13, 2020

Job J1120-5330	Truss B03	Truss Type HALF HIP	Qty 1	Ply 1	Lot 46 South Creek	E15095628
-------------------	--------------	------------------------	----------	----------	--------------------	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:15 2020 Page 1

ID:YFDfFaMnBCKfZxe?lGwdkVz?opC-K?XRSkzL60f6HOiu4f86B3ie2lXxuKmCFsbYulyJfOE



Scale = 1:66.1




Plate Offsets (X,Y)-- [1:0-4-4,1-1-11], [1:0-0-8,Edge], [2:0-3-0,0-3-5], [10:0-3-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.81	Vert(LL) -0.12	10-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.82	Vert(CT) -0.23	10-12	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.67	Horz(CT) 0.05	9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.06	10-12	>999	240	Weight: 270 lb	FT = 20%


LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2
 WEDGE
 Left: 2x8 SP No.1

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-4-0 oc purlins, except end verticals, and 2-0-0 oc purlins (4-9-4 max.): 2-7.
 Rigid ceiling directly applied or 10-0-0 oc bracing.
 BOT CHORD
 WEBS 1 Row at midpt 6-9
 T-Brace: 2x4 SPF No.2 - 3-14
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
 Brace must cover 90% of web length.

REACTIONS. (size) 9=Mechanical, 1=0-3-8
 Max Horz 1=147(LC 12)
 Max Grav 9=1703(LC 2), 1=1600(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-2382/154, 2-3=-1903/185, 3-5=-2502/200, 5-6=-1903/131, 6-9=-1498/164
 BOT CHORD 1-14=-186/1882, 12-14=-200/2502, 10-12=-131/1903
 WEBS 2-14=0/864, 3-14=-813/73, 5-12=-84/725, 5-10=-983/215, 6-10=-157/2282

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 9-8-8, Exterior(2) 9-8-8 to 15-11-3, Interior(1) 15-11-3 to 38-2-8 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 8) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095629
J1120-5330	B04	HALF HIP	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:16 2020 Page 1

ID:YFDfFaMnBCKfZxe?IGwdkVz?opC-pB5pfgzztJnyuYH4dNfLkGFn69w7douLU6K5QByJf0D



Scale = 1:66.2




Plate Offsets (X,Y)-- [1:0-4-4,1-1-11], [1:0-0-8,Edge], [3:0-2-0,0-2-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.85	Vert(LL) -0.14	1-15	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.63	Vert(CT) -0.31	1-15	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.61	Horz(CT) 0.04	10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.04	13	>999	240		
							Weight: 293 lb	FT = 20%

LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2
 WEDGE
 Left: 2x8 SP No.1

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-4-3 max.): 3-8. Rigid ceiling directly applied or 10-0-0 oc bracing.
 BOT CHORD
 WEBS 1 Row at midpt 7-10
 T-Brace: 2x4 SPF No.2 - 6-11
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance. Brace must cover 90% of web length.

REACTIONS. (size) 10=Mechanical, 1=0-3-8
 Max Horz 1=185(LC 12)
 Max Grav 10=1726(LC 2), 1=1506(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-2277/173, 2-3=-2049/160, 3-4=-1914/175, 4-6=-1912/174, 6-7=-1415/106, 7-10=-1522/169
 BOT CHORD 1-15=-295/1813, 13-15=-163/1652, 11-13=-106/1415
 WEBS 2-15=-300/159, 3-15=0/552, 3-13=-89/441, 4-13=-558/164, 6-13=-95/693, 6-11=-1029/218, 7-11=-145/1938

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 12-2-8, Exterior(2) 12-2-8 to 18-5-3, Interior(1) 18-5-3 to 38-2-8 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 8) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095630
J1120-5330	B05	Hip	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:17 2020 Page 1

ID:YFDfFaMnBCKfZxe?GwdkVz?opC-HNfBt0_cedvpWhsGB4BaHUnyTZDvMLhVim4eydyJf0C



Scale = 1:67.7




Plate Offsets (X,Y)-- [1:0-0-8,Edge], [1:0-4-4,1-1-11]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.88	Vert(LL)	-0.12 10-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.79	Vert(CT)	-0.19 10-12	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.20	Horz(CT)	0.06 9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.03 14	>999	240	Weight: 283 lb	FT = 20%

LUMBER-

TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2
 WEDGE
 Left: 2x8 SP No.1
 SLIDER Right 2x6 SP No.1 -x 4-0-4

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-5-1 oc purlins, except 2-0-0 oc purlins (5-0-15 max.): 4-5.
 Rigid ceiling directly applied or 10-0-0 oc bracing.
 BOT CHORD
 WEBS T-Brace: 2x4 SPF No.2 - 4-12
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
 Brace must cover 90% of web length.

REACTIONS.

(size) 9=Mechanical, 1=0-3-8
 Max Horz 1=165(LC 8)
 Max Grav 9=1683(LC 20), 1=1676(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-2519/193, 2-4=-2351/253, 4-5=-1698/217, 5-7=-2157/245, 7-9=-2370/189
 BOT CHORD 1-14=-78/2102, 12-14=0/1629, 10-12=0/1570, 9-10=-61/1781
 WEBS 2-14=-342/180, 4-14=-33/777, 4-12=-52/294, 5-12=-10/366, 5-10=-20/549

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 14-8-8, Exterior(2) 14-8-8 to 20-11-3, Interior(1) 20-11-3 to 24-8-8, Exterior(2) 24-8-8 to 30-11-3, Interior(1) 30-11-3 to 38-2-8 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095631
J1120-5330	B06	Piggyback Base	1	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:18 2020 Page 1

ID:YFDIFaMnBCKfZxe?IGwdkVz?opC-laDZ4M?EPx1g8rRtloipphK6nzZ35omexQpCU4yJf0B



Scale = 1:66.5



1-3-0	10-6-6	19-8-8	28-10-10	38-2-8
1-3-0	9-3-6	9-2-2	9-2-2	9-3-14


LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.91	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.79	Vert(LL) -0.12 10-12 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.21	Vert(CT) -0.19 10-12 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.06 9 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.03 12 >999 240	Weight: 294 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 4-5-1 oc purlins, except 2-0-0 oc purlins (5-10-1 max.): 4-6.
BOT CHORD 2x6 SP No.1	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	T-Brace: 2x4 SPF No.2 - 5-12
WEDGE	Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
Left: 2x8 SP No.1	Brace must cover 90% of web length.
SLIDER Right 2x6 SP No.1 -x 3-11-10	


REACTIONS. (size) 9=Mechanical, 1=0-3-8
 Max Horz 1=160(LC 10)
 Max Grav 9=1666(LC 2), 1=1658(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-2506/197, 2-4=-2337/252, 4-5=-1771/238, 5-6=-1771/238, 6-7=-2149/244, 7-9=-2352/192
 BOT CHORD 1-14=-83/2080, 12-14=0/1617, 10-12=0/1558, 9-10=-64/1768
 WEBS 2-14=-356/185, 4-14=-35/781, 4-12=-62/435, 5-12=-338/106, 6-12=-49/511, 6-10=-22/553

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 14-2-4, Exterior(2) 14-2-4 to 20-4-15, Interior(1) 20-4-15 to 25-2-12, Exterior(2) 25-2-12 to 31-5-7, Interior(1) 31-5-7 to 38-2-8 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.



November 13, 2020

<p>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	 <p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095632
J1120-5330	B07	PIGGYBACK BASE	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:19 2020 Page 1

ID:YFDfFaMnBckfZxe?IGwdkVz?opC-DmnyHh0sAE9XI?0fJVD2MvthKNyBq5qnA4Zl1WyJf0A



Scale = 1:68.6




Plate Offsets (X,Y)-- [5:0-2-4,0-2-12], [7:0-3-0,0-2-12], [13:0-5-4,0-3-8], [15:0-4-4,0-4-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.92	Vert(LL)	-0.21 11-13	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.58	Vert(CT)	-0.41 13-14	>866	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.86	Horz(CT)	0.21 11	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL)	0.09 13-14	>999	240	Weight: 289 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 10-11.
WEBS 2x4 SP No.2	WEBS T-Brace: 2x4 SPF No.2 - 5-13, 6-13, 7-11
SLIDER Right 2x6 SP No.1 -x 4-5-0	Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance. Brace must cover 90% of web length.

REACTIONS. (size) 15=0-3-8, 11=0-3-8
 Max Horz 15=160(LC 11)
 Max Grav 15=1248(LC 23), 11=1926(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1634/13, 2-3=-2171/149, 3-5=-1901/178, 5-6=-751/192, 6-7=-751/192, 7-8=0/387, 8-10=-54/477
 BOT CHORD 1-15=-42/1804, 14-15=-94/1705, 13-14=-51/1108, 11-13=-29/444, 10-11=-278/107
 WEBS 2-15=-1342/220, 5-14=0/1186, 5-13=-527/29, 6-13=-362/119, 7-13=-31/741, 7-11=-1266/24, 8-11=-512/229

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-0-0 to 4-4-13, Interior(1) 4-4-13 to 14-2-4, Exterior(2) 14-2-4 to 20-6-4, Interior(1) 20-6-4 to 25-2-12, Exterior(2) 25-2-12 to 31-5-7, Interior(1) 31-5-7 to 38-2-8 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 7) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601


ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job J1120-5330	Truss C01	Truss Type ATTIC	Qty 9	Ply 1	Lot 46 South Creek E15095633
-------------------	--------------	---------------------	----------	----------	---------------------------------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:20 2020 Page 1

ID:YDFdFaMnBCKfZxe?lGwdkVz?opC-hyLKV11UxYHON9brsDkHu6PWVmGXZgxbOkJJZyyJf09



Scale = 1:63.2

Plate Offsets (X,Y)-- [4:0-3-0,0-1-1], [5:0-3-0,0-1-1], [8:0-1-0,0-2-0], [11:0-5-0,0-7-0], [13:0-4-0,0-4-12]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.70	Vert(LL)	-0.20 11-13	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.73	Vert(CT)	-0.33 11-13	>889	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.38	Horz(CT)	0.01 10	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.05 13	>999	240		
	Code IRC2015/TPI2014						Weight: 262 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1 *Except* 15-16,17-18: 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 5-1-10 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 4-5.
BOT CHORD 2x10 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x6 SP No.1 *Except* 1-13,8-11: 2x4 SP No.2	WEBS 1 Row at midpt 3-6

REACTIONS. (size) 14=0-3-8, 10=0-3-8
 Max Horz 14=-204(LC 8)
 Max Grav 14=1548(LC 2), 10=1625(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1724/0, 2-3=-1180/12, 3-4=-128/316, 5-6=-131/318, 6-7=-1177/12, 7-8=-1738/0,
 4-5=0/454, 1-14=-1633/0, 8-10=-1700/0
 BOT CHORD 13-14=-169/282, 11-13=0/1226
 WEBS 3-6=-1513/0, 2-13=-15/621, 7-11=0/644, 1-13=0/1177, 8-11=0/1141

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDD=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-12 to 4-7-9, Interior(1) 4-7-9 to 10-1-14, Exterior(2) 10-1-14 to 20-11-12, Interior(1) 20-11-12 to 26-0-9 zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Ceiling dead load (10.0 psf) on member(s). 2-3, 6-7, 3-6; Wall dead load (5.0psf) on member(s).2-13, 7-11
 - 7) Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 11-13
 - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - 9) Attic room checked for L/360 deflection.




November 13,2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095634
J1120-5330	C01GE	GABLE	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:21 2020 Page 1

ID:YFDfFaMnBckfZxe?lGwdkVz?opC-99uuiN16isQF?JA1QwFWRKypfAih1944dO2s5PyJf08



Scale = 1:62.5




Plate Offsets (X,Y)-- [7:0-4-0,0-0-4], [8:0-1-12,0-0-0], [10:0-1-12,0-0-0], [11:0-4-0,0-0-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.16	Vert(LL) 0.00	17	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.29	Vert(CT) 0.00	17	n/r	120		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.23	Horz(CT) 0.00	18	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S						
							Weight: 291 lb	FT = 20%

LUMBER-

TOP CHORD 2x6 SP No.1 *Except*
30-31,32-33: 2x4 SP No.2
BOT CHORD 2x10 SP No.1
WEBS 2x6 SP No.1 *Except*
2-21,16-19: 2x4 SP No.2
OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 7-11.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
JOINTS 1 Brace at Jt(s): 23, 24, 26, 27, 29

REACTIONS.


All bearings 24-11-0.
(lb) - Max Horz 22=-263(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 21, 19
Max Grav All reactions 250 lb or less at joint(s) except 22=641(LC 1), 21=1057(LC 20), 19=1051(LC 21), 18=641(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-529/27, 3-4=-444/37, 4-5=-352/51, 5-6=-566/67, 6-7=-535/50, 11-12=-535/50, 12-13=-566/67, 13-14=-352/43, 14-15=-444/30, 15-16=-529/19, 7-8=-423/55, 8-9=-423/55, 9-10=-423/55, 10-11=-423/55, 2-22=-610/0, 16-18=-610/0
BOT CHORD 21-22=-230/263, 19-21=-39/348
WEBS 5-21=-524/85, 13-19=-524/84, 2-26=-38/369, 25-26=-40/367, 21-25=-41/387, 19-28=-40/386, 28-29=-39/367, 16-29=-37/369

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Ceiling dead load (10.0 psf) on member(s). 5-6, 12-13, 6-24, 23-24, 23-27, 12-27; Wall dead load (5.0psf) on member(s).5-21, 13-19
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 21, 19.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Attic room checked for L/360 deflection.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Job J1120-5330	Truss C02	Truss Type ATTIC	Qty 1	Ply 1	Lot 46 South Creek Job Reference (optional)	E15095635
-------------------	--------------	---------------------	----------	----------	--	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:22 2020 Page 1

ID:YFDIFaMnBCKfZxe?IGwdkVz?opC-dLS4wj2kT9Y6cTIE_emizXVrwaxz1a3Es2oPdryJf07



Scale = 1:63.2

Plate Offsets (X,Y)-- [4:0-3-0,0-1-1], [5:0-3-0,0-1-1], [10:0-5-0,0-7-0], [12:0-5-0,0-7-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.70	Vert(LL) -0.20	10-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.73	Vert(CT) -0.33	10-12	>882	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.38	Horz(CT) 0.01	9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.05	12	>999	240	Weight: 259 lb	FT = 20%

LUMBER-

TOP CHORD 2x6 SP No.1 *Except*
14-15,16-17: 2x4 SP No.2
BOT CHORD 2x10 SP No.1
WEBS 2x6 SP No.1 *Except*
1-12,8-10: 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-1-8 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 4-5.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 3-6

REACTIONS.


(size) 13=0-3-8, 9=0-3-8
Max Horz 13=-139(LC 8)
Max Grav 13=1551(LC 20), 9=1551(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-1728/0, 2-3=-1182/8, 3-4=-124/323, 5-6=-124/323, 6-7=-1182/8, 7-8=-1728/0,
4-5=0/462, 1-13=-1635/0, 8-9=-1635/0
BOT CHORD 10-12=0/1212
WEBS 3-6=-1526/0, 2-12=-12/624, 7-10=-12/624, 1-12=0/1176, 8-10=0/1177

NOTES-

- Unbalanced roof live loads HAVING been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-12 to 4-7-9, Interior(1) 4-7-9 to 10-1-14, Exterior(2) 10-1-14 to 20-11-12, Interior(1) 20-11-12 to 24-8-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Ceiling dead load (10.0 psf) on member(s). 2-3, 6-7, 3-6; Wall dead load (5.0psf) on member(s).2-12, 7-10
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 10-12
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Attic room checked for L/360 deflection.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095636
J1120-5330	C02G	ATTIC	1	2		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:23 2020 Page 1

ID:YFDfFaMnBCkfZxe?lGwdkVz?opC-5X0S733METgzEckQYLH_W11_X_IsmumN5iXzAHyJf06



Scale = 1:64.8

Plate Offsets (X,Y)-- [1:Edge,0-2-4], [2:0-5-0,0-3-0], [2:0-3-9,0-0-0], [4:0-0-2,Edge], [5:0-0-2,Edge], [7:0-5-0,0-2-0], [8:Edge,0-2-4], [10:0-5-0,0-7-12], [12:0-5-0,0-7-4], [14:0-1-7,0-1-12]


LOADING (psf)	SPACING-	8-6-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.84	Vert(LL)	-0.28	10-12	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.69	Vert(CT)	-0.45	10-12	>654		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.93	Horz(CT)	0.01	9	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.07	12	>999		
								Weight: 598 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x10 SP No.1 *Except* 4-5: 2x6 SP No.1, 3-14,6-7: 2x4 SP No.2	TOP CHORD 2-0-0 oc purlins (6-0-0 max.), except end verticals (Switched from sheeted: Spacing > 2-8-0).
BOT CHORD 2x10 SP 2400F 2.0E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x6 SP No.1 *Except* 1-12,8-10: 2x4 SP No.2	

REACTIONS. (size) 13=0-3-8, 9=0-3-8
Max Horz 13=608(LC 8)
Max Grav 13=6601(LC 20), 9=6601(LC 21)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-7512/0, 2-3=-5082/46, 3-4=-325/1496, 5-6=-325/1496, 6-7=-5082/46, 7-8=-7511/0, 4-5=0/2105, 1-13=-6965/0, 8-9=-6966/0
BOT CHORD 12-13=-592/1030, 10-12=0/5236, 9-10=-43/581
WEBS 3-6=-6741/0, 2-12=0/3109, 7-10=0/3109, 1-12=0/5034, 8-10=0/5041

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x10 - 2 rows staggered at 0-9-0 oc, 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x10 - 2 rows staggered at 0-9-0 oc.
Webs connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-2-9 to 4-7-5, Interior(1) 4-7-5 to 10-4-13, Exterior(2) 10-4-13 to 20-8-14, Interior(1) 20-8-14 to 24-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (10.0 psf) on member(s). 2-3, 6-7, 3-6; Wall dead load (5.0psf) on member(s). 2-12, 7-10
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (10.0 psf) applied only to room. 10-12
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Attic room checked for L/360 deflection.



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095637
J1120-5330	C03	Piggyback Base	5	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:24 2020 Page 1

ID:YFDfFaMnBckfZxe?IGwdkVz?opC-akarLP4??noqsmuc52pD3yaF5OfsVWqXJMHWkyJf05




Plate Offsets (X,Y)-- [5:0-3-0,0-1-1], [7:0-3-0,0-1-1], [10:0-1-8,0-2-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.47	Vert(LL)	-0.27 13-15	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.64	Vert(CT)	-0.35 13-15	>871	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.23	Horz(CT)	0.02 12	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.16 13	>999	240	Weight: 219 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-7-3 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 12-13.
WEBS 2x4 SP No.2 *Except* 10-12: 2x6 SP No.1	JOINTS 1 Brace at Jt(s): 17

REACTIONS. (size) 12=0-3-8, 16=0-3-8
 Max Horz 16=160(LC 9)
 Max Grav 12=1176(LC 20), 16=1377(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1022/0, 2-3=-1473/135, 3-4=-902/196, 4-5=-345/78, 7-8=-356/69, 8-9=-934/201, 9-10=-1408/137, 10-12=-1168/123
 BOT CHORD 1-16=0/1012, 15-16=0/1014, 13-15=0/1014, 12-13=-77/301
 WEBS 2-16=-874/269, 3-15=0/627, 9-13=0/469, 4-17=-864/191, 8-17=-864/191, 10-13=-86/1021

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-0-0 to 4-4-13, Interior(1) 4-4-13 to 11-4-14, Exterior(2) 11-4-14 to 23-4-4, Interior(1) 23-4-4 to 26-11-4 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095638
J1120-5330	C03GE	GABLE	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:26 2020 Page 1

ID:YFDfFaMnBckfZxe?IGwdkVz?opC-W6ibI55FWO2Y542?DTrh8NfghBULzRDpnfmdmcyJf03



Scale = 1:58.7

Plate Offsets (X,Y)-- [7:0-1-12,0-1-7], [8:0-3-0,0-1-1], [9:0-3-0,0-1-1]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.14	Vert(LL) -0.00	30	>999	240	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.06	Vert(CT) 0.00	30	>999	180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.11	Horz(CT) -0.00	16	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S					Weight: 259 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals, and 2'-0" oc purlins (6'-0" max.): 8-9.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10'-0" oc bracing.
WEBS 2x6 SP No.1	WEBS 1 Row at midpt 10-21, 7-25
OTHERS 2x4 SP No.2	

REACTIONS. All bearings 26-0-8.
 (lb) - Max Horz 30=198(LC 9)
 Max Uplift All uplift 100 lb or less at joint(s) 18, 19, 20, 21, 25, 26, 27, 28 except 16=-101(LC 9), 17=-154(LC 13), 29=-182(LC 12), 30=-124(LC 8)
 Max Grav All reactions 250 lb or less at joint(s) 16, 17, 18, 19, 20, 23, 24, 26, 27, 28, 29 except 21=325(LC 21), 25=338(LC 22), 30=322(LC 20), 30=268(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 10-21=-257/25, 7-25=-254/60

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2'-0" oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3'-6" tall by 2'-0" wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18, 19, 20, 21, 25, 26, 27, 28 except (jt=lb) 16=101, 17=154, 29=182, 30=124.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095639
J1120-5330	C04	Piggyback Base	10	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:27 2020 Page 1

ID:YFDfFaMnBckfZxe?IGwdkVz?opC_IgzzR6tHiAPjEdBnBMwgbCmPbfNisf?JVAJ2yJf02



Scale = 1:57.8

Plate Offsets (X,Y)-- [5:0-3-0,0-1-1], [7:0-3-0,0-1-1]


LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.46	Vert(LL)	-0.27 12-14	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.65	Vert(CT)	-0.35 12-14	>860	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.23	Horz(CT)	0.02 11	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S	Wind(LL)	0.15 12	>999	240	Weight: 217 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-7-12 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-7.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 11-12.
WEBS 2x4 SP No.2 *Except* 10-11: 2x6 SP No.1	JOINTS 1 Brace at Jt(s): 16

REACTIONS. (size) 11=Mechanical, 15=0-3-8
 Max Horz 15=160(LC 9)
 Max Grav 11=1165(LC 2), 15=1369(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1009/0, 2-3=-1456/133, 3-4=-891/195, 4-5=-346/80, 7-8=-360/70, 8-9=-926/200,
 9-10=-1386/136, 10-11=-1171/120
 BOT CHORD 1-15=0/999, 14-15=0/1001, 12-14=0/1001
 WEBS 2-15=-870/268, 3-14=0/623, 9-12=0/457, 4-16=-851/188, 8-16=-851/188,
 10-12=-46/1008

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCdL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-0-0 to 4-4-13, Interior(1) 4-4-13 to 11-4-14, Exterior(2) 11-4-14 to 23-4-4, Interior(1) 23-4-4 to 26-9-4 zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 13, 2020

Job J1120-5330	Truss D01GR	Truss Type COMMON GIRDER	Qty 1	Ply 2	Lot 46 South Creek E15095640
-------------------	----------------	-----------------------------	----------	----------	---------------------------------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:28 2020 Page 1

ID:YFDfFaMnBCKfZxe?IGwdkVz?opC-SVqLAm7V2?IFKOCOKut9Dokw_?3XRAG6EzFkrVyJf01



Scale = 1:59.4




Plate Offsets (X,Y)-- [1:0-7-13,0-0-4], [1:0-4-8,0-11-14], [10:0-7-12,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.54	Vert(LL) -0.07	8-10	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.40	Vert(CT) -0.13	8-10	>999	240		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.78	Horz(CT) 0.01	7	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.03	1-10	>999	240		
							Weight: 386 lb	FT = 20%

LUMBER-

TOP CHORD 2x6 SP No.1
 BOT CHORD 2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.2 *Except*
 5-7: 2x6 SP No.1

WEDGE
 Left: 2x8 SP No.1

REACTIONS. (size) 1=0-3-8, 8=0-3-8, 7=0-3-0
 Max Horz 1=155(LC 5)
 Max Uplift 7=REL
 Max Grav 1=4349(LC 19), 8=6602(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


TOP CHORD 1-2=-5332/0, 2-3=-5161/0, 3-4=-582/106, 4-5=-640/0, 5-7=-486/0
 BOT CHORD 1-10=0/3929, 8-10=0/1471, 7-8=0/441
 WEBS 3-10=0/6362, 3-8=-2914/0, 4-8=-278/161

NOTES-

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
 Bottom chords connected as follows: 2x10 - 2 rows staggered at 0-5-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; porch right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- "A" indicates Released bearing: allow for upward movement at joint(s) 7.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1506 lb down and 424 lb up at 3-10-6, 1494 lb down at 5-9-10, 1683 lb down at 7-9-10, 1668 lb down at 9-9-10, and 1614 lb down at 11-9-10, and 1634 lb down at 13-9-10 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-3=-60, 3-5=-60, 1-6=-20



November 13, 2020

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095640
J1120-5330	D01GR	COMMON GIRDER	1	2	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:28 2020 Page 2
 ID:YFDfFaMnBckfZxe?IGwdkVz?opC-SVqLAm7V2?IFKOCOKut9Dokw_?3XRAG6EzFkrVyJf01

LOAD CASE(S) Standard

Concentrated Loads (lb)

Vert: 9=-1494(B) 12=-1506(B) 13=-1494(B) 14=-1494(B) 16=-1494(B) 18=-1494(B)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095641
J1120-5330	D01SG	KINGPOST	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:29 2020 Page 1

ID:YFDfFaMnBckfZxe?IGwdkVz?opC-whNkO677pJQ6yYnaucOOm0H81PQZAKLGTd_HNxyJf00




LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.33	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.35	Vert(LL) -0.11 15-17 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.34	Vert(CT) -0.21 15-17 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(LL) 0.01 12 n/a n/a		
	Code IRC2015/TPI2014		Wind(CT) 0.15 15-17 >999 240	Weight: 188 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except*	JOINTS 1 Brace at Jt(s): 19, 20, 22
3-15: 2x6 SP No.1	

REACTIONS. (size) 18=0-3-8, 12=0-3-8
 Max Horz 18=-198(LC 8)
 Max Uplift 18=-34(LC 12), 12=-35(LC 13)
 Max Grav 18=987(LC 19), 12=916(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-591/127, 2-3=-941/444, 3-4=-421/284, 4-5=-506/423, 5-6=-512/437, 6-7=-512/356,
 7-8=-481/253, 8-9=-772/419, 9-10=-662/268, 10-11=-494/140
 BOT CHORD 1-18=-171/592, 17-18=-171/705, 15-17=-171/705, 14-15=-105/449, 13-14=-105/449,
 12-13=-105/449, 11-12=-105/450
 WEBS 3-21=-336/165, 19-21=-454/221, 20-22=-285/142, 15-22=-373/138, 5-19=-393/408,
 3-17=-261/526, 8-14=-280/377, 2-18=-718/416, 10-12=-373/182

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; porch right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) All plates are 2x4 MT20 unless otherwise indicated.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 18, 12.



November 13, 2020

Job J1120-5330	Truss E01GE	Truss Type COMMON SUPPORTED GAB	Qty 1	Ply 1	Lot 46 South Creek Job Reference (optional)	E15095642
-------------------	----------------	------------------------------------	----------	----------	--	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:30 2020 Page 1
ID:YFDIFaMnBCkfZxe?IGwdkVz?opC-Otx6bS8ladYzahMmSjwdDqO7orLvEOPiHkqvNyJf0?




Plate Offsets (X,Y)-- [12:0-1-8,0-2-0]

LOADING (psf)	SPACING-	CS.I.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	Vert(LL)	-0.00	11	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.06	Vert(CT)	0.00	11	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.16	Horz(CT)	0.00	10	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 126 lb	FT = 20%
	Code IRC2015/TPI2014							


LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS. All bearings 13-11-0 except (jt=length) 18=0-3-8.
 (lb) - Max Horz 17=-145(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 15, 16, 13, 10 except 17=-187(LC 9), 11=-127(LC 13), 18=-176(LC 8)
 Max Grav All reactions 250 lb or less at joint(s) 15, 16, 17, 13, 11, 18 except 14=251(LC 22), 10=269(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 15, 16, 13, 10 except (jt=lb) 17=187, 11=127, 18=176.




November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095643
J1120-5330	G1	Common	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:30 2020 Page 1
 ID:YFDfFaMnBckfZxe?IGwdkVz?opC-Otx6bS8ladYzahMmSJwdlDqHdolxvEVPiHkqvNjJf0?



Scale = 1:53.7

Plate Offsets (X,Y)-- [1:0-1-8,0-0-13], [1:0-4-4,1-1-11], [5:0-1-8,0-3-13], [5:0-4-4,0-5-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.47	Vert(LL)	-0.08	6-8	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.40	Vert(CT)	-0.11	5-6	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.16	Horz(CT)	0.02	5	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.02	8	>999		
	Code IRC2015/TPI2014						Weight: 183 lb	FT = 20%


LUMBER-
 TOP CHORD 2x6 SP No.1
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.2
 WEDGE
 Left: 2x8 SP No.1 , Right: 2x8 SP No.1

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=0-3-8, 5=0-3-8
 Max Horz 1=149(LC 8)
 Max Grav 1=1034(LC 19), 5=1034(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1473/118, 2-3=-1347/181, 3-4=-1347/181, 4-5=-1474/118
 BOT CHORD 1-8=-13/1250, 6-8=0/832, 5-6=-13/1147
 WEBS 3-6=-46/650, 4-6=-347/165, 3-8=-46/650, 2-8=-347/165

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 13-2-8, Exterior(2) 13-2-8 to 17-7-5, Interior(1) 17-7-5 to 26-0-11 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.





November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095644
J1120-5330	G2	HIP	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:31 2020 Page 1

ID:YFDfFaMnBCkfZxe?IGwdkVz?opC-s4VUpo9OLwgqBrxy01RsrRMSFC52ehoYwxTOSayJf0_



Scale = 1:49.6

Plate Offsets (X,Y)-- [1:0-4-4,1-1-11], [1:0-1-8,0-0-13], [5:0-0-0,0-0-0], [6:0-1-8,0-3-13], [6:0-4-4,0-5-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.47	Vert(LL)	-0.08	7-9	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.41	Vert(CT)	-0.11	7-9	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.15	Horz(CT)	0.02	6	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.02	1-9	>999		
	Code IRC2015/TPI2014						Weight: 179 lb	FT = 20%


LUMBER-
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2
WEDGE
Left: 2x8 SP No.1 , Right: 2x8 SP No.1

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 3-4.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=0-3-8, 6=0-3-8
Max Horz 1=137(LC 8)
Max Grav 1=1040(LC 19), 6=1040(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-1480/134, 2-3=-1349/188, 3-4=-848/169, 4-5=-1349/188, 5-6=-1480/134
BOT CHORD 1-9=-37/1245, 7-9=0/888, 6-7=-31/1145
WEBS 2-9=-339/169, 3-9=-47/622, 4-7=-47/623, 5-7=-339/170

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 12-2-7, Exterior(2) 12-2-7 to 20-5-3, Interior(1) 20-5-3 to 26-0-11 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095645
J1120-5330	G3	Hip	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:32 2020 Page 1

ID:YFDfFaMnBCkZxe?lGwdkVz?opC-LG3s08A06Eohp?W9Zky5Nevb3cQ4N9fi9bDxzGyJf?z




Plate Offsets (X,Y)-- [1:0-6-8,0-0-13], [1:0-4-4,1-1-11], [4:0-0-8,0-0-13], [4:0-4-4,0-5-4]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.53	Vert(LL)	-0.07	4-5	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.49	Vert(CT)	-0.15	4-5	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.11	Horz(CT)	0.03	4	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.03	1-7	>999		
	Code IRC2015/TPI2014						Weight: 170 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-5-5 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 2-3.
BOT CHORD 2x6 SP No.1	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	T-Brace: 2x4 SPF No.2 - 2-5
WEDGE	Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
Left: 2x8 SP No.1, Right: 2x8 SP No.1	Brace must cover 90% of web length.

REACTIONS.	(size)
Max Horz	1=109(LC 11)
Max Grav	1=1141(LC 19), 4=1119(LC 20)

FORCES.	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	1-2=-1561/137, 2-3=-1162/185, 3-4=-1521/136
BOT CHORD	1-7=-1/1222, 5-7=-3/1212, 4-5=0/1171
WEBS	2-7=0/509, 3-5=0/439

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 9-8-8, Exterior(2) 9-8-8 to 15-11-2, Interior(1) 15-11-2 to 16-8-8, Exterior(2) 16-8-8 to 22-11-3, Interior(1) 22-11-3 to 26-0-11 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.



November 13, 2020

Job J1120-5330	Truss G4	Truss Type Hip	Qty 1	Ply 1	Lot 46 South Creek	E15095646
-------------------	-------------	-------------------	----------	----------	--------------------	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:33 2020 Page 1

ID:YFDfFaMnBCkfZxe?IGwdkVz?opC-pSdEDUBetYwYR94L7RTKwsSnn0nZ6XArOFyVvYjF?y



Scale = 1:45.2




Plate Offsets (X,Y)-- [1:0-6-8,0-0-13], [1:0-4-4,1-1-11], [5:0-0-8,0-0-13], [5:0-4-4,0-5-4]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.46	Vert(LL)	-0.12	6-8	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.41	Vert(CT)	-0.25	6-8	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.42	Horz(CT)	0.03	5	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.01	8	>999		
	Code IRC2015/TPI2014						Weight: 171 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-11-15 oc purlins, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (6-0-0 max.): 2-4.
WEBS 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEDGE	
Left: 2x8 SP No.1, Right: 2x8 SP No.1	

REACTIONS. (size) 1=0-3-8, 5=0-3-8
 Max Horz 1=81(LC 11)
 Max Grav 1=1028(LC 1), 5=1028(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1523/118, 2-3=-1145/148, 3-4=-1145/148, 4-5=-1523/118
 BOT CHORD 1-8=-6/1156, 6-8=-80/1397, 5-6=-6/1156
 WEBS 2-8=0/515, 3-8=-403/107, 3-6=-403/107, 4-6=0/515

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-5 to 4-9-1, Interior(1) 4-9-1 to 7-2-7, Exterior(2) 7-2-7 to 13-2-8, Interior(1) 13-2-8 to 19-2-9, Exterior(2) 19-2-9 to 25-5-3, Interior(1) 25-5-3 to 26-0-11 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job J1120-5330	Truss G5	Truss Type Hip Girder	Qty 1	Ply 2	Lot 46 South Creek Job Reference (optional)	E15095647
-------------------	-------------	--------------------------	----------	----------	--	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:35 2020 Page 1

ID:YFDfFaMnBCKfZxe?IGwdkVz?opC-lr?eACuP9AGgTEkFsVo?HXBvpVoaVx8rZRbabyJf?w



Scale = 1:44.2




Plate Offsets (X,Y)-- [1:0-4-4,1-1-11], [1:0-1-8,0-0-13], [6:0-5-4,0-2-12], [7:0-1-8,0-3-13], [7:0-4-4,0-5-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.24	Vert(LL) -0.03	9-11	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.23	Vert(CT) -0.06	9-11	>999	240		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.14	Horz(CT) 0.02	7	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.04	9-11	>999	240	Weight: 353 lb	FT = 20%

LUMBER-
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1
WEBS 2x4 SP No.2
WEDGE
Left: 2x8 SP No.1 , Right: 2x8 SP No.1

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 2-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=0-3-8, 7=0-3-8
Max Horz 1=-54(LC 30)
Max Uplift 1=-217(LC 5), 7=-217(LC 4)
Max Grav 1=999(LC 23), 7=999(LC 23)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-1529/387, 2-3=-1202/334, 3-5=-1980/558, 5-6=-1981/558, 6-7=-1531/388
BOT CHORD 1-12=-330/1200, 11-12=-561/2013, 9-11=-561/2013, 8-9=-292/1189, 7-8=-292/1183
WEBS 2-12=-154/593, 3-12=-940/292, 5-9=-344/124, 6-9=-296/954

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed ; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



November 13, 2020

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY
TRENCO
A MiTek Affiliate

818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095647
J1120-5330	G5	Hip Girder	1	2	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:35 2020 Page 2
 ID:YFDfFaMnBckfZxe?GwdkVz?opC-lr?eACuP9AGgTEkFsVo?HXBvpVoaVx8rZRbabyJf?w

NOTES-

10) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 30 lb down and 27 lb up at 2-9-3, 45 lb down and 39 lb up at 4-8-8, 48 lb down and 36 lb up at 6-9-3, 48 lb down and 36 lb up at 8-9-3, 48 lb down and 36 lb up at 10-9-3, 48 lb down and 36 lb up at 12-9-3, 48 lb down and 36 lb up at 13-7-12, 48 lb down and 36 lb up at 15-7-12, 48 lb down and 36 lb up at 17-7-12, 48 lb down and 36 lb up at 19-7-12, and 45 lb down and 39 lb up at 21-8-9, and 30 lb down and 27 lb up at 23-7-12 on top chord, and 6 lb down and 44 lb up at 2-9-3, 18 lb down and 27 lb up at 4-9-3, 18 lb down and 27 lb up at 6-9-3, 18 lb down and 27 lb up at 8-9-3, 18 lb down and 27 lb up at 10-9-3, 18 lb down and 27 lb up at 12-9-3, 18 lb down and 27 lb up at 13-7-12, 18 lb down and 27 lb up at 15-7-12, 18 lb down and 27 lb up at 17-7-12, 18 lb down and 27 lb up at 19-7-12, and 18 lb down and 27 lb up at 21-7-12, and 6 lb down and 44 lb up at 23-7-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-2=-60, 2-6=-60, 6-7=-60, 1-7=-20

Concentrated Loads (lb)

Vert: 12=5(F) 8=5(F) 23=12(F) 24=5(F) 25=5(F) 26=5(F) 27=5(F) 28=5(F) 29=5(F) 30=5(F) 31=5(F) 32=12(F)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095648
J1120-5330	M01GE	GABLE	1	1		

Comtech, Inc., Fayetteville, NC - 28314, 8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:36 2020 Page 1
 ID:YFDIFaMnBckfZxe?IGwdkVz?opC-D1INsVDWATI7lcpwoa01YU4JIDqCJ_nI4DB961yJf?v




Plate Offsets (X,Y)-- [1:0-4-3,0-0-5]


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.43	Vert(LL)	-0.00	1-21	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.29	Vert(CT)	-0.00	1-21	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Horz(CT)	-0.02	16	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.00	1	>999		
	Code IRC2015/TPI2014						Weight: 121 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals. Except:
BOT CHORD 2x6 SP No.1	10-0-0 oc bracing: 16-17
WEBS 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
OTHERS 2x4 SP No.2	

REACTIONS. All bearings 10-3-8.
 (lb) - Max Horz 1=216(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 21, 20, 19 except 17=171(LC 1), 1=107(LC 1), 1=107(LC 1), 16=240(LC 8)
 Max Grav All reactions 250 lb or less at joint(s) 17, 1, 20, 19, 18 except 21=322(LC 1), 16=1166(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-611/744, 2-3=-553/706, 3-4=-530/717, 4-5=-498/707, 5-6=-510/791, 6-7=-540/791, 7-9=-508/776, 9-10=-486/802, 10-11=-478/856, 6-16=-337/118
 BOT CHORD 1-21=-661/312, 20-21=-661/312, 19-20=-661/312, 18-19=-661/312, 17-18=-661/312, 15-16=-1093/529, 14-15=-990/491, 13-14=-948/479, 11-13=-955/494


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left exposed ; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) All plates are 2x4 MT20 unless otherwise indicated.
 - 4) Gable studs spaced at 2-0-0 oc.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 7) Bearing at joint(s) 16 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 21, 20, 19 except (jt=lb) 17=171, 1=107, 16=240.



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095649
J1120-5330	PB01	Piggyback	10	1		

Comtech, Inc., Fayetteville, NC - 28314, 8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:37 2020 Page 1
 ID:YFDfFaMnBckfZxe?lGwdkVz?opC-hEsl3rE8xmR_vmO6MHYG4icXgdCJ2RzRjtwieTyJf?u
 11-0-8 5-6-4




LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.22	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.17	Vert(LL) 0.01 5 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Vert(CT) 0.01 5 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 4 n/a n/a	Weight: 38 lb	FT = 20%
	Code IRC2015/TPI2014				

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.2	

REACTIONS. (size) 2=9-6-4, 4=9-6-4, 6=9-6-4
 Max Horz 2=-59(LC 10)
 Max Uplift 2=-4(LC 12), 4=-10(LC 13)
 Max Grav 2=220(LC 1), 4=220(LC 1), 6=382(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-3-2 to 4-7-15, Interior(1) 4-7-15 to 5-6-4, Exterior(2) 5-6-4 to 9-11-1, Interior(1) 9-11-1 to 10-9-6 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
 - 7) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095650
J1120-5330	PB02	GABLE	1	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:38 2020 Page 1

ID:YFDfFaMnBCkZxe?IGwdkVz?opC-9QQ7HBEi4ZrXwzJw?3Vdv9iz1ZENUaXXgGBwyJf?t

11-0-8
11-0-8

Scale = 1:19.2




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.25	Vert(LL)	0.00	5	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.12	Vert(CT)	-0.00	5	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 36 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 3-4.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

REACTIONS. All bearings 9-6-4.
 (lb) - Max Horz 2=30(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 5
 Max Grav All reactions 250 lb or less at joint(s) 2, 5 except 8=328(LC 23), 7=328(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) Provide adequate drainage to prevent water ponding.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Gable studs spaced at 6-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 5.
 - 10) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
 - 11) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.




Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095651
J1120-5330	PB03	Piggyback	16	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:38 2020 Page 1

ID:YFDfFaMnBckfZxe?lGwdkVz?opC-9QQ7HBEi4ZrXwzJw?3Vdv9kt1aWnukaXXgGBWjJf?l



4x4 =

Scale = 1:16.2




Plate Offsets (X,Y)-- [2:0-2-1,0-1-0], [4:0-2-1,0-1-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.07	Vert(LL)	0.00	5	n/r	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.04	Vert(CT)	0.00	5	n/r		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.01	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Code	IRC2015/TPI2014	Matrix-P					Weight: 21 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-10-11 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 2=4-7-4, 4=4-7-4, 6=4-7-4
 Max Horz 2=38(LC 10)
 Max Uplift 2=6(LC 12), 4=10(LC 13)
 Max Grav 2=134(LC 1), 4=134(LC 1), 6=151(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095652
J1120-5330	PB04	Piggyback	12	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:39 2020 Page 1

ID:YFDfFaMnBckfZxe?IGwdkVz?opC-dc_VUXFPTOh94YVUiakA7iw6Rw0WL2kmBPjMyJf?s



Scale: 1"=1'

Plate Offsets (X,Y)-- [2:0-2-1,0-1-0], [4:0-2-1,0-1-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.03	Vert(LL)	0.00	4	n/r	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	0.00	4	n/r		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.01	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Code	IRC2015/TPI2014	Matrix-P					Weight: 16 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-9-3 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 2=3-5-12, 4=3-5-12, 6=3-5-12
 Max Horz 2=30(LC 10)
 Max Uplift 2=6(LC 12), 4=8(LC 13)
 Max Grav 2=108(LC 1), 4=108(LC 1), 6=113(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095653
J1120-5330	VA01	Valley	1	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:40 2020 Page 1
 ID:YFDfFaMnBCkfZxe?lGwdkVz?opC-6pYuhtG1DhpZnE7h1Q5ziKE1YqCXFk_t?r9MFoyJ?r



4x4 =

Scale = 1:66.2



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.31	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.20	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.28	Horz(CT)	-0.01	8	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 114 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 7-10

REACTIONS.


All bearings 23-4-13.
 (lb) - Max Horz 1=234(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 8, 11, 14, 15 except 9=114(LC 18)
 Max Grav All reactions 250 lb or less at joint(s) 1, 8 except 10=392(LC 19), 11=530(LC 19), 13=486(LC 19), 14=267(LC 1), 15=477(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 1-2=-273/228
 WEBS 6-11=-265/138, 2-15=-346/126

NOTES-

- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-10-13 to 5-3-9, Interior(1) 5-3-9 to 22-8-5, Exterior(2) 22-8-5 to 23-4-13 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) All plates are 2x4 MT20 unless otherwise indicated.
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 11, 14, 15 except (jt=lb) 9=114.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095654
J1120-5330	VA02	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:40 2020 Page 1
 ID:YFDfFaMnBckfZxe?IGwdkVz?opC-6pYuhtG1DhpZnE7h1Q5zikE2_qDoFmftr9MFoyJf?r
 17-8-5 18-4-13
 9-10-0 0-8-8



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.22	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.18	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.18	Horz(CT)	-0.01	7	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 86 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	WEBS 1 Row at midpt 6-9
OTHERS 2x4 SP No.2	

REACTIONS. All bearings 18-4-13.
 (lb) - Max Horz 1=196(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 7, 11, 13 except 8=107(LC 18)
 Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 9=380(LC 19), 11=550(LC 19), 12=347(LC 19), 13=413(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 5-11=-270/140, 2-13=-302/87

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-10-13 to 5-3-9, Interior(1) 5-3-9 to 17-8-5, Exterior(2) 17-8-5 to 18-4-13 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 11, 13 except (jt=lb) 8=107.



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095655
J1120-5330	VA03	Valley	1	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:41 2020 Page 1

ID:YFDfFaMnBckfZxe?lGwdkVz?opC-a?6GvDHf_?xPOOitb7cCFYnEXEZM_EF1DVuvnEyJf?q



4x4 = Scale = 1:46.6




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.17	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.16	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.09	Horz(CT)	-0.00	6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 61 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	
OTHERS 2x4 SP No.2	

REACTIONS. All bearings 13-4-13.
 (lb) - Max Horz 1=158(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 6, 9 except 7=138(LC 18)
 Max Grav All reactions 250 lb or less at joint(s) 1, 6 except 8=423(LC 19), 9=433(LC 19), 10=351(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 4-9=263/145, 3-10=255/77

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-10-13 to 2-10-5, Interior(1) 2-10-5 to 12-8-5, Exterior(2) 12-8-5 to 13-4-13 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 9 except (jt=lb) 7=138.




November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095656
J1120-5330	VA04	Valley	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:42 2020 Page 1
 ID:YFDfFaMnBckfZxe?IGwdkVz?opC-2Bge6ZIHJ3G0XG49q7RnIKPwew5j9AS9eTKhyJf?p



Scale = 1:38.1

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.19	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.13	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 42 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.


All bearings 9-5-10.
 (lb) - Max Horz 1=120(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 4, 7 except 5=106(LC 18)
 Max Grav All reactions 250 lb or less at joint(s) 1, 4 except 6=360(LC 19), 7=435(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-7=-298/160

NOTES-

- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-12 to 4-9-2, Interior(1) 4-9-2 to 8-9-2, Exterior(2) 8-9-2 to 9-5-10 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 7 except (jt=lb) 5=106.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095657
J1120-5330	VA05	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:42 2020 Page 1
 ID:YFDIFaMnBckfZxe?IGwdkVz?opC-2Bge6ZIHJ3G0XG49q7RnIKPXewwjiUAS9eTKhyJf?p




LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.15	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.03	Horz(CT)	0.00	4	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 29 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	
OTHERS 2x4 SP No.2	

REACTIONS. All bearings 6-11-10.
 (lb) - Max Horz 1=81(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 4, 5, 7
 Max Grav All reactions 250 lb or less at joint(s) 1, 4, 6 except 7=320(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-7=-251/156

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-12 to 4-10-9, Interior(1) 4-10-9 to 6-3-2, Exterior(2) 6-3-2 to 6-11-10 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) Gable requires continuous bottom chord bearing.
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 4, 5, 7.




November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095658
J1120-5330	VA06	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:43 2020 Page 1

ID:YFDIFaMnBckfZxe?IGwdkVz?opC-WNE0KvIvWcB7ehrGjYegKzsbF2GGS9AJhpN0s7yJf?o



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-R						Weight: 17 lb	FT = 20%
	Code IRC2015/TPI2014								

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-5-10 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 1=4-5-10, 3=4-5-10, 5=4-5-10, 4=4-5-10
 Max Horz 1=43(LC 12)
 Max Uplift 3=-32(LC 19), 5=-10(LC 12), 4=-28(LC 3)
 Max Grav 1=115(LC 1), 3=12(LC 12), 5=248(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-12 to 4-5-10 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) Gable requires continuous bottom chord bearing.
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 5, 4.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095659
J1120-5330	VD01	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:44 2020 Page 1

ID:YFDIFaMnBckfZxe?IGwdkVz?opC-_anOXFJXHwJ_FrQSGFAvAPkGSbOBZLTwT7aOzyJf?n



Scale = 1:44.3

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.20	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.14	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.13	Horz(CT)	-0.00	5	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 58 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS.


All bearings 10-1-14.
 (lb) - Max Horz 1=146(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 5, 7
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 6=357(LC 19), 7=512(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-7=-327/198

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-12, Interior(1) 4-9-12 to 8-9-12, Exterior(2) 8-9-12 to 10-0-2 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 5, 7.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095660
J1120-5330	VD02	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:44 2020 Page 1

ID:YFDfFaMnBckfZxe?IGwdkVz?opC-_anOXFJXHwJ_FrQSGFAvtAPlzScsBaGTwT7aOZyJf?n



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.15	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.11	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.07	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 n/a n/a	Weight: 47 lb	FT = 20%
	Code IRC2015/TPI2014				

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

All bearings 8-6-11.
 (lb) - Max Horz 1=116(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 7
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 6=313(LC 19), 7=380(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 2-7=-290/191

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 7-2-9, Exterior(2) 7-2-9 to 8-4-15 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 7.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095661
J1120-5330	VD03	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:46 2020 Page 1
 ID:YFDfFaMnBckfZxe?lGwdkVz?opC-wyv9ywLopXZIV9arOgCNybU5TFlyfVEmNnchTSyJf?l



Scale = 1:31.1


LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.15	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 n/a n/a	Weight: 35 lb	FT = 20%
	Code IRC2015/TPI2014				

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	
OTHERS 2x4 SP No.2	

REACTIONS. All bearings 6-11-8.
 (lb) - Max Horz 1=85(LC 12)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 7
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 6 except 7=341(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-7=-288/202

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-4-13 to 4-9-10, Interior(1) 4-9-10 to 5-7-6, Exterior(2) 5-7-6 to 6-9-12 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 7.



November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095662
J1120-5330	VD04	Valley	1	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:46 2020 Page 1

ID:YFDfFaMnBCkfZxe?IGwdkVz?opC-wyv9ywLopXZiV9arOgCNybU5?FlqfVWmNnchTSyJf?!



Scale = 1:22.8



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0 Plate Grip DOL 1.15	TC 0.18	Vert(LL) n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.07	Vert(CT) n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00		n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P					Weight: 25 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 5-4-4 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 1=5-4-4, 4=5-4-4, 5=5-4-4
 Max Horz 1=55(LC 12)
 Max Uplift 4=22(LC 13)
 Max Grav 1=137(LC 1), 4=28(LC 20), 5=223(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095663
J1120-5330	VD05	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:47 2020 Page 1
 ID:YFDfFaMnBckfZxe?IGwdkVz?opC-O9TXAGLQarhZ6J91yOjcUp1lpfetOy_vcRLE?uyJf?k



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.01	Horz(CT)	0.00		n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 15 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 3-9-1 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 1=3-9-1, 4=3-9-1, 5=3-9-1
 Max Horz 1=28(LC 9)
 Max Uplift 1=2(LC 13), 4=13(LC 13)
 Max Grav 1=77(LC 1), 4=43(LC 20), 5=139(LC 19)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 4.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095664
J1120-5330	VG01	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:48 2020 Page 1

ID:YFDfFaMnBCkfZxe?lGwdkVz?opC-tL1vNcM2L9pQkSkEV5Er10ZQy3yX7NB3q55nXKyJf?



Scale = 1:45.7

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.15	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.19	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.14	Horz(CT)	0.00	7	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 96 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

All bearings 21-9-2.
 (lb) - Max Horz 1=117(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 12, 13, 10, 8
 Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 11=441(LC 19), 12=438(LC 19), 13=281(LC 1), 10=438(LC 20), 8=281(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 3-12=-268/131, 5-10=-268/131

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-12 to 4-10-9, Interior(1) 4-10-9 to 10-10-9, Exterior(2) 10-10-9 to 15-3-6, Interior(1) 15-3-6 to 21-3-5 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 12, 13, 10, 8.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095665
J1120-5330	VG02	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:49 2020 Page 1
 ID:YFDfFaMnBCkfZxe?IGwdkVz?opC-LXbHayNg6SxHMcJQ3ol4aE6bTTIbsrPC3lqL3nyJf?



Scale = 1:36.8

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.17	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.13	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.08	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a	Weight: 68 lb	FT = 20%
	Code IRC2015/TPI2014				

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1
 OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

All bearings 16-9-2.
 (lb) - Max Horz 1=89(LC 9)
 Max Uplift All uplift 100 lb or less at joint(s) 9, 6
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 8=387(LC 19), 9=398(LC 19), 6=398(LC 20)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-9=-282/136, 4-6=-282/136

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-12 to 4-10-9, Interior(1) 4-10-9 to 8-4-9, Exterior(2) 8-4-9 to 12-9-6, Interior(1) 12-9-6 to 16-3-5 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 6.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.


Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095666
J1120-5330	VG03	Valley	1	1		

Comtech, Inc., Fayetteville, NC - 28314, 8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:49 2020 Page 1
 ID: YFDfFaMnBCkfZxe?GwdkVz?opC-LXbHayNg6SxHMcJQ3ol4aE6b6TJlss?C3lqL3nyJf?11-9-2




LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.13	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.09	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Horz(CT)	0.00	5	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 44 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.2	

REACTIONS. All bearings 11-9-2.
 (lb) - Max Horz 1=61(LC 9)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 8, 6
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=263(LC 1), 8=297(LC 23), 6=297(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-5-12 to 4-10-9, Interior(1) 4-10-9 to 5-10-9, Exterior(2) 5-10-9 to 10-3-6, Interior(1) 10-3-6 to 11-3-5 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 8, 6.




November 13, 2020

Job J1120-5330	Truss VG04	Truss Type Valley	Qty 1	Ply 1	Lot 46 South Creek Job Reference (optional)	E15095667
-------------------	---------------	----------------------	----------	----------	--	-----------

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:50 2020 Page 1
ID:YFDfFaMnBckfZxe?IGwkdVz?opC-pk9goIOitm38zmudWGJ6Rfn6sgybJeLLOaucDyJf?h



Scale = 1:15.6

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.11	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.06	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a	Weight: 23 lb	FT = 20%
	Code IRC2015/TPI2014				

LUMBER-

TOP CHORD 2x4 SP No.1
BOT CHORD 2x4 SP No.1
OTHERS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS.

(size) 1=6-9-2, 3=6-9-2, 4=6-9-2
Max Horz 1=-33(LC 8)
Max Uplift 1=-4(LC 12), 3=-7(LC 13)
Max Grav 1=126(LC 1), 3=126(LC 1), 4=212(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.



November 13, 2020

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095668
J1120-5330	X1	JACK-OPEN	27	1		

Comtech, Inc. Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:50 2020 Page 1
 ID:YFDfFaMnBckfZxe?IGwkdVz?opC-pk9golOltm38zmudWGJ6RfoxsgBbJbLLOaucDyJf?h




LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.06	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.05	Vert(LL) -0.00 5 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) 0.00 5 >999 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) -0.01 3 n/a n/a	Weight: 18 lb	FT = 20%
	Code IRC2015/TPI2014				

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 3-8-14 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

REACTIONS. (size) 3=Mechanical, 4=Mechanical, 5=0-3-8
 Max Horz 5=74(LC 12)
 Max Uplift 3=-31(LC 12), 4=-20(LC 12)
 Max Grav 3=59(LC 19), 4=29(LC 10), 5=237(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TC DL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.




November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095669
J1120-5330	X2	Jack-Open Girder	3	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:51 2020 Page 1

ID:YFDIFaMnBCKfZxe?IGwdkVz?opC-Hwi2?ePwe4B?bwToBDoYffByTG0WKmuVX2JS8fyJf?g



Scale = 1:14.6

LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	-0.00	6	>999	240	MT20	244/190	
TCDL	10.0	Lumber DOL	1.15	BC	0.04	Vert(CT)	0.00	5-6	>999	180			
BCLL	0.0 *	Rep Stress Incr	NO	WB	0.02	Horz(CT)	-0.01	4	n/a	n/a	Weight: 17 lb FT = 20%		
BCDL	10.0	Code	IRC2015/TPI2014	Matrix-P									

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.1	TOP CHORD	Structural wood sheathing directly applied or 3-8-14 oc purlins, except
BOT CHORD	2x6 SP No.1	BOT CHORD	2-0-0 oc purlins: 3-4.
WEBS	2x4 SP No.2		Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS. (size) 4=Mechanical, 5=Mechanical, 6=0-3-8
 Max Horz 6=45(LC 8)
 Max Uplift 4=8(LC 4), 5=24(LC 8), 6=2(LC 8)
 Max Grav 4=45(LC 1), 5=18(LC 32), 6=207(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 5, 6.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 22 lb down and 42 lb up at 2-2-5 on top chord, and 40 lb up at 2-2-7 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (plf)
 Vert: 1-3=-60, 3-4=-60, 1-5=-20
 Concentrated Loads (lb)
 Vert: 3=21(F) 7=25(F)




November 13, 2020

Job	Truss	Truss Type	Qty	Ply	Lot 46 South Creek	E15095670
J1120-5330	Y1	JACK-OPEN	3	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.330 s Oct 7 2020 MiTek Industries, Inc. Fri Nov 13 08:32:52 2020 Page 1

ID:YDFdFaMnBckfZxe?IGwdkVz?opC-I6GQD_PZPNJsD41?kxJnBsk8kgMn3DBeli3?g6yJf?f



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.04	Vert(LL) 0.00	5	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.04	Vert(CT) 0.00	5	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.01	Horz(CT) -0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P	Wind(LL) -0.00	5	>999	240	Weight: 13 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 2-8-8 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

REACTIONS. (size) 3=Mechanical, 4=Mechanical, 5=0-3-8
 Max Horz 5=44(LC 12)
 Max Uplift 3=-15(LC 12), 4=-32(LC 21)
 Max Grav 3=23(LC 19), 4=4(LC 10), 5=224(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=120mph (3-second gust) Vasd=95mph; TCCL=6.0psf; TCCL=6.0psf; h=15ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone; cantilever left exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - 4) Refer to girder(s) for truss to truss connections.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4.




November 13, 2020

Symbols

PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.


* Plate location details available in **MITek 20/20 software or upon request.**

PLATE SIZE

4 X 4


The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TP1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-89: Design Standard for Bracing, Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate
BCSI: Connected Wood Trusses.

Numbering System

6-4-8
dimensions shown in ft-in-sixteenths
(Drawings not to scale)



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TP1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITteK® All Rights Reserved



MITek Engineering Reference Sheet: Mill-7473 rev. 5/19/2020



General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative T or I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TP1 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TP1 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TP1 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.