


GDH Kerto-S LVL 1.750" X 16.000" 3-Ply - PASSED

Level: Level



Member Information

| | | | |
|---------------------|---------------|----------------|-------------|
| Type: | Girder | Application: | Floor |
| Plies: | 3 | Design Method: | ASD |
| Moisture Condition: | Dry | Building Code: | IBC 2012 |
| Deflection LL: | 480 | Load Sharing: | Yes |
| Deflection TL: | 360 | Deck: | Not Checked |
| Importance: | Normal | | |
| Temperature: | Temp <= 100°F | | |

Reactions UNPATTERNED lb (Uplift)

| Brg | Live | Dead | Snow | Wind | Const |
|-----|------|------|------|------|-------|
| 1 | 0 | 1127 | 951 | 0 | 0 |
| 2 | 0 | 1127 | 951 | 0 | 0 |

Bearings

| Bearing | Length | Cap. React | D/L lb | Total | Ld. Case | Ld. Comb. |
|---------|--------|------------|------------|-------|----------|-----------|
| 1 - SPF | 3.500" | 27% | 1127 / 951 | 2078 | L | D+S |
| 2 - SPF | 3.500" | 27% | 1127 / 951 | 2078 | L | D+S |

Analysis Results

| Analysis | Actual | Location | Allowed | Capacity | Comb. | Case |
|--------------|----------------|-----------|---------------|-------------|-------|------|
| Moment | 9334 ft-lb | 9'5" | 62010 ft-lb | 0.151 (15%) | D+S | L |
| Unbraced | 9334 ft-lb | 9'5" | 10984 ft-lb | 0.850 (85%) | D+S | L |
| Shear | 1735 lb | 17'3 3/8" | 20608 lb | 0.084 (8%) | D+S | L |
| LL Defl inch | 0.078 (L/2813) | 9'5 1/16" | 0.460 (L/480) | 0.170 (17%) | S | L |
| TL Defl inch | 0.171 (L/1288) | 9'5 1/16" | 0.613 (L/360) | 0.280 (28%) | D+S | L |

Design Notes

- 1 Fasten all plies using 3 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 2 Refer to last page of calculations for fasteners required for specified loads.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on single ply width.

| ID | Load Type | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1 | Uniform | | | Top | 101 PLF | 0 PLF | 101 PLF | 0 PLF | 0 PLF | A4A |
| | Self Weight | | | | 19 PLF | | | | | |

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

Manufacturer Info


Metsä Wood
 301 Merritt 7 Building, 2nd Floor
 Norwalk, CT 06851
 (800) 622-5850
www.metsawood.com/us
 ICC-ES: ESR-3633

Comtech, Inc.
 1001 S. Reilly Road, Suite #639
 Fayetteville, NC
 USA
 28314
 910-864-TRUS



GDH Kerto-S LVL 1.750" X 16.000" 3-Ply - PASSED

Level: Level



Multi-Ply Analysis

Fasten all plies using 3 rows of 10d Box nails (.128x3") at 12" o.c.. Nail from both sides. Maximum end distance not to exceed 6"

| | |
|--------------------------|-----------|
| Capacity | 0.0 % |
| Load | 0.0 PLF |
| Yield Limit per Foot | 245.6 PLF |
| Yield Limit per Fastener | 81.9 lb. |
| Yield Mode | IV |
| Edge Distance | 1 1/2" |
| Min. End Distance | 3" |
| Load Combination | |
| Duration Factor | 1.00 |

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

Manufacturer Info


Metsä Wood
 301 Merritt 7 Building, 2nd Floor
 Norwalk, CT 06851
 (800) 622-5850
 www.metsawood.com/us
 ICC-ES: ESR-3633

Comtech, Inc.
 1001 S. Reilly Road, Suite #639
 Fayetteville, NC
 USA
 28314
 910-864-TRUS



GDH-1 Kerto-S LVL 1.750" X 11.875" 2-Ply - PASSED

Level: Level



Member Information

| | | | |
|---------------------|---------------|----------------|-------------|
| Type: | Girder | Application: | Floor |
| Plies: | 2 | Design Method: | ASD |
| Moisture Condition: | Dry | Building Code: | IBC 2012 |
| Deflection LL: | 480 | Load Sharing: | No |
| Deflection TL: | 360 | Deck: | Not Checked |
| Importance: | Normal | | |
| Temperature: | Temp <= 100°F | | |

Reactions UNPATTERNED lb (Uplift)

| Brg | Live | Dead | Snow | Wind | Const |
|-----|------|------|------|------|-------|
| 1 | 0 | 1696 | 1631 | 0 | 0 |
| 2 | 0 | 1696 | 1631 | 0 | 0 |

Bearings

| Bearing | Length | Cap. | React D/L | Ib | Total | Ld. Case | Ld. Comb. |
|---------|--------|------|-------------|------|-------|----------|-----------|
| 1 - SPF | 3.500" | 64% | 1696 / 1631 | 3327 | L | D+S | |
| 2 - SPF | 3.500" | 64% | 1696 / 1631 | 3327 | L | D+S | |

Analysis Results

| Analysis | Actual | Location | Allowed | Capacity | Comb. | Case |
|--------------|---------------|----------|---------------|--------------|-------|------|
| Moment | 10893 ft-lb | 7' | 22897 ft-lb | 0.476 (48%) | D+S | L |
| Unbraced | 10893 ft-lb | 7' | 10911 ft-lb | 0.998 (100%) | D+S | L |
| Shear | 2747 lb | 1'2 5/8" | 10197 lb | 0.269 (27%) | D+S | L |
| LL Defl inch | 0.195 (L/832) | 7' 1/16" | 0.339 (L/480) | 0.580 (58%) | S | L |
| TL Defl inch | 0.398 (L/408) | 7' 1/16" | 0.451 (L/360) | 0.880 (88%) | D+S | L |

Design Notes

- 1 Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 2 Refer to last page of calculations for fasteners required for specified loads.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top loads must be supported equally by all plies.
- 5 Top must be laterally braced at a maximum of 8'2 5/8" o.c.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on single ply width.

| ID | Load Type | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1 | Uniform | | | Top | 233 PLF | 0 PLF | 233 PLF | 0 PLF | 0 PLF | G1 |
| | Self Weight | | | | 9 PLF | | | | | |

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

Manufacturer Info


Metsä Wood
 301 Merritt 7 Building, 2nd Floor
 Norwalk, CT 06851
 (800) 622-5850
www.metsawood.com/us
 ICC-ES: ESR-3633

Comtech, Inc.
 1001 S. Reilly Road, Suite #639
 Fayetteville, NC
 USA
 28314
 910-864-TRUS



GDH-1 Kerto-S LVL 1.750" X 11.875" 2-Ply - PASSED

Level: Level



Multi-Ply Analysis

Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6"

| | |
|--------------------------|-----------|
| Capacity | 0.0 % |
| Load | 0.0 PLF |
| Yield Limit per Foot | 163.7 PLF |
| Yield Limit per Fastener | 81.9 lb. |
| Yield Mode | IV |
| Edge Distance | 1 1/2" |
| Min. End Distance | 3" |
| Load Combination | |
| Duration Factor | 1.00 |

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

Manufacturer Info



Metsä Wood
 301 Merritt 7 Building, 2nd Floor
 Norwalk, CT 06851
 (800) 622-5850
 www.metsawood.com/us
 ICC-ES: ESR-3633

Comtech, Inc.
 1001 S. Reilly Road, Suite #639
 Fayetteville, NC
 USA
 28314
 910-864-TRUS



BM1 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED

Level: Level



Member Information

| | |
|---------------------|---------------|
| Type: | Girder |
| Plies: | 2 |
| Moisture Condition: | Dry |
| Deflection LL: | 480 |
| Deflection TL: | 360 |
| Importance: | Normal |
| Temperature: | Temp <= 100°F |

| | |
|----------------|-------------|
| Application: | Floor |
| Design Method: | ASD |
| Building Code: | IBC 2012 |
| Load Sharing: | No |
| Deck: | Not Checked |

Reactions UNPATTERNED lb (Uplift)

| Brg | Live | Dead | Snow | Wind | Const |
|-----|------|------|------|------|-------|
| 1 | 0 | 1564 | 1541 | 0 | 0 |
| 2 | 0 | 1564 | 1541 | 0 | 0 |

Bearings

| Bearing | Length | Cap. React | D/L lb | Total | Ld. Case | Ld. Comb. |
|---------|--------|------------|-------------|-------|----------|-----------|
| 1 - SPF | 3.500" | 60% | 1564 / 1541 | 3105 | L | D+S |
| 2 - SPF | 3.500" | 60% | 1564 / 1541 | 3105 | L | D+S |

Analysis Results

| Analysis | Actual | Location | Allowed | Capacity | Comb. | Case |
|--------------|----------------|----------|---------------|-------------|-------|------|
| Moment | 4423 ft-lb | 3'3 1/2" | 14423 ft-lb | 0.307 (31%) | D+S | L |
| Unbraced | 4423 ft-lb | 3'3 1/2" | 10451 ft-lb | 0.423 (42%) | D+S | L |
| Shear | 2161 lb | 1' | 7943 lb | 0.272 (27%) | D+S | L |
| LL Defl inch | 0.040 (L/1842) | 3'3 1/2" | 0.153 (L/480) | 0.260 (26%) | S | L |
| TL Defl inch | 0.080 (L/914) | 3'3 1/2" | 0.204 (L/360) | 0.390 (39%) | D+S | L |

Design Notes

- 1 Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 2 Refer to last page of calculations for fasteners required for specified loads.
- 3 Girders are designed to be supported on the bottom edge only.
- 4 Top loads must be supported equally by all plies.
- 5 Top braced at bearings.
- 6 Bottom braced at bearings.
- 7 Lateral slenderness ratio based on single ply width.

| ID | Load Type | Location | Trib Width | Side | Dead 0.9 | Live 1 | Snow 1.15 | Wind 1.6 | Const. 1.25 | Comments |
|----|-------------|----------|------------|------|----------|--------|-----------|----------|-------------|----------|
| 1 | Uniform | | | Top | 468 PLF | 0 PLF | 468 PLF | 0 PLF | 0 PLF | A1 |
| | Self Weight | | | | 7 PLF | | | | | |

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

Manufacturer Info


Metsä Wood
 301 Merritt 7 Building, 2nd Floor
 Norwalk, CT 06851
 (800) 622-5850
www.metsawood.com/us
 ICC-ES: ESR-3633

Comtech, Inc.
 1001 S. Reilly Road, Suite #639
 Fayetteville, NC
 USA
 28314
 910-864-TRUS



BM1 Kerto-S LVL 1.750" X 9.250" 2-Ply - PASSED

Level: Level



Multi-Ply Analysis

Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c.. Maximum end distance not to exceed 6"

| | |
|--------------------------|-----------|
| Capacity | 0.0 % |
| Load | 0.0 PLF |
| Yield Limit per Foot | 163.7 PLF |
| Yield Limit per Fastener | 81.9 lb. |
| Yield Mode | IV |
| Edge Distance | 1 1/2" |
| Min. End Distance | 3" |
| Load Combination | |
| Duration Factor | 1.00 |

Notes

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

Lumber

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

Handling & Installation

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 2/26/2023

Manufacturer Info

Metsä Wood
 301 Merritt 7 Building, 2nd Floor
 Norwalk, CT 06851
 (800) 622-5850
www.metsawood.com/us
 ICC-ES: ESR-3633

Comtech, Inc.
 1001 S. Reilly Road, Suite #639
 Fayetteville, NC
 USA
 28314
 910-864-TRUS

