

- I. GENERAL
1) DESIGN BUILDING CODE: 2018 NORTH CAROLINA RESIDENTIAL CODE.
2) THE CONTRACTOR SHALL COORDINATE ALL DIMENSIONS AND ELEVATIONS SHOWN ON THESE DRAWINGS WITH THE ARCHITECTURAL AND OTHER TRADES DRAWINGS.
3) THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING TEMPORARY BRACING AND SHORING, AS REQUIRED, TO INSURE VERTICAL AND LATERAL STABILITY OF THE ENTIRE STRUCTURE OR PORTION THEREOF DURING CONSTRUCTION.

- II. SITE VERIFICATION WORK
1) BOTTOM OF ALL EXTERIOR FOOTINGS SHALL BE A MINIMUM OF 1'-0" BELOW EXTERIOR GRADE, UNLESS NOTED OTHERWISE (UNO).
2) VERIFY EXISTING UTILITIES PRIOR TO START OF ANY EXCAVATION WORKS. COORDINATE WITH CIVIL DRAWINGS FOR WORKS RELATED TO UTILITIES.
3) ALL FOOTINGS SHALL PROJECT AT LEAST 1 FT INTO UNDISTURBED NATURAL SOIL OR COMPACTED STRUCTURAL FILL.

- III. CAST-IN-PLACE CONCRETE (AS APPLICABLE)
1) ALL CONCRETE WORK SHALL BE IN ACCORDANCE WITH ACI-301, ACI-318 AND ACI-302.
2) REINFORCING STEEL
i. DEFORMED BILLET STEEL: ASTM A615 - GRADE 60
ii. WELDED WIRE FABRIC (WWF): ASTM A185
3) ALL REINFORCING SHALL BE DETAILED, FABRICATED AND PLACED IN ACCORDANCE WITH THE MANUAL OF STANDARD PRACTICE FOR DETAILING CONCRETE STRUCTURES (ACI-315).
4) REINFORCEMENT SPLICES SHALL BE LAP SPLICES WITH A MINIMUM LAP OF 48 BAR DIAMETERS UNLESS NOTED OTHERWISE.

- IV. WOOD
1) ALL LUMBER SHALL CONFORM TO NATIONAL DESIGN SPECIFICATION (NDS) FOR WOOD CONSTRUCTION WITH 2015 SUPPLEMENT.
2) LUMBER SHALL BE SOUND, SEASONED, AND FREE FROM WARP.
3) ALL STUDS SHALL BE INSTALLED IN ACCORDANCE WITH AF & PA (AMERICAN FOREST & PAPER ASSOCIATION) REQUIREMENTS.
4) STUD BEARING WALLS AND EXTERIOR STUD WALLS SHALL BE CONTINUOUSLY BRIDGED WITH WOOD BLOCKING AT MID-SPAN VERTICAL SPACING BETWEEN FLOOR (AND ROOF) LEVELS.

- V. REINFORCED MASONRY (CMU)
1. ALL MASONRY SHALL BE REINFORCED CONCRETE MASONRY UNIT IN ACCORDANCE WITH THE LATEST EDITION OF ACI 530/ASCE 5/TMS 402.
2. MINIMUM MASONRY BLOCK (ASTM C90) STRENGTH SHALL (FM) BE 2000 PSI.
3. TYP. E 'S' MORTAR (ASTM C270) SHALL BE USED USING 3/8" FULL BEDDING REINFORCED W/ 9 GAGE GALVANIZED LADDER WIRE EVERY 2ND ROW.
4. FILLED CELLS SHALL BE REINFORCED WITH #4 REBARS @ 48" O.C. (UNLESS OTHERWISE IS SPECIFIED ON THE PLANS).
5. GROUT SHALL BE PEA ROCK PUMP MIX (ASTM C476) WITH A MINIMUM COMPRESSIVE STRENGTH OF 3000 PSI (28 DAY) (ASTM C1019). TARGETED SLUMP SHALL BE 8"-11".

- VI. STRUCTURAL STEEL
1) STRUCTURAL STEEL SHALL CONFORM TO AISC 'S' SPECIFICATION FOR THE DESIGN, FABRICATION AND ERECTION OF STRUCTURAL STEEL FOR BUILDINGS', LATEST EDITION, EXCEPT CHAPTER 4.2.1, CODE OF STANDARD PRACTICE.
2) ALL STRUCTURAL STEEL SHALL BE
i. W SHAPES: ASTM 992 (WHERE AVAILABLE) OR ASTM A572 (GRADE 50)
ii. PLATES, CHANNELS AND ANGLES: ASTM A572 (GRADE 50) OR A36
iii. STRUCTURAL TUBES (HSS): ASTM A500 (GRADE B)
iv. PIPE SECTIONS: ASTM A53 (STANDARD PIPE, UNO)
v. BOLTS: ASTM A325 OR A490 BOLTS.
vi. ANCHOR BOLTS: ASTM F1554 GRADE 55

WARNING: THE STRUCTURAL INTEGRITY OF THE BUILDING SHOWN IN THESE PLANS DEPENDS ON COMPLETION ACCORDING TO THE PLANS AND SPECIFICATIONS. STRUCTURAL MEMBERS ARE NOT SELF-BRACING UNTIL PERMANENTLY AFFIXED TO THE STRUCTURE. THE DESIGNER ASSUME NO LIABILITY FOR THE STRUCTURE DURING CONSTRUCTION.

- DEFLECTION CRITERIA:
DESCRIPTION TOTAL LOAD LIVE LOAD
ROOF TRUSSES/RAFTERS/CEILING JOISTS L/240 L/960 OR 1/2" MAX
FLOOR JOISTS/FLOOR TRUSSES L/240 L/960 OR 1/4" MAX
MEMBERS SUPPORTING BRICK/HORIZONTAL MASONRY MEMBERS L/600 OR 0.3" MAX
JOISTS/TRUSSES SUPPORTING CERAMIC TILE L/720

DESIGN LOADS:
DESCRIPTION DEAD LOAD LIVE LOAD SNOW LOAD (psf)
ROOF 17 PSF 20 PSF 10 PSF
FLOOR 15 PSF 40 PSF -
ATTIC W/O STORAGE 10 PSF 10 PSF -
ATTIC W/ LIMIT STORAGE 10 PSF 20 PSF -
HABITABLE ATTICS & ATTICS W/ FIXED STAIR 10 PSF 30 PSF -
SLEEPING ROOMS 15 PSF 30 PSF -
BALCONIES & DECKS 10 PSF 40 PSF -
STAIRS 10 PSF 40 PSF -
GUARD RAILS & HAND RAILS - 200 LBS (G) -

- DESIGN LOADS:
DESCRIPTION DEAD LOAD LIVE LOAD SNOW LOAD (psf)
ROOF 17 PSF 20 PSF 10 PSF
FLOOR 15 PSF 40 PSF -
ATTIC W/O STORAGE 10 PSF 10 PSF -
ATTIC W/ LIMIT STORAGE 10 PSF 20 PSF -
HABITABLE ATTICS & ATTICS W/ FIXED STAIR 10 PSF 30 PSF -
SLEEPING ROOMS 15 PSF 30 PSF -
BALCONIES & DECKS 10 PSF 40 PSF -
STAIRS 10 PSF 40 PSF -
GUARD RAILS & HAND RAILS - 200 LBS (G) -

FASTENERS:
NO. DESCRIPTION OF BUILDING ELEMENT NUMBER AND TYPE OF FASTENER SPACING AND LOCATION
1 BLOCKING BETWEEN JOISTS OR RAFTERS TO TOP PLATE (3) 8d COMMON (2 1/2"x0.131") TOE NAIL
2 CEILING JOISTS TO PLATE (3) 8d COMMON (2 1/2"x0.131") PER JOIST, TOE NAIL
3 CEILING JOISTS NOT ATTACHED TO PARALLEL RAFTER, LAPS OVER PARTITIONS 4-10d BOX (3"x0.128") FACE NAIL
4 CEILING JOISTS ATTACHED TO PARALLEL RAFTER (HEEL JOINT) [SEE SECTIONS R802.3.1 AND R802.3.2 AND TABLE R802.5.1(9)] TABLE R802.5.1(9) FACE NAIL

DEFLECTION CRITERIA:
DESCRIPTION TOTAL LOAD LIVE LOAD
ROOF TRUSSES/RAFTERS/CEILING JOISTS L/240 L/960 OR 1/2" MAX
FLOOR JOISTS/FLOOR TRUSSES L/240 L/960 OR 1/4" MAX
MEMBERS SUPPORTING BRICK/HORIZONTAL MASONRY MEMBERS L/600 OR 0.3" MAX
JOISTS/TRUSSES SUPPORTING CERAMIC TILE L/720

DESIGN LOADS:
DESCRIPTION DEAD LOAD LIVE LOAD SNOW LOAD (psf)
ROOF 17 PSF 20 PSF 10 PSF
FLOOR 15 PSF 40 PSF -
ATTIC W/O STORAGE 10 PSF 10 PSF -
ATTIC W/ LIMIT STORAGE 10 PSF 20 PSF -
HABITABLE ATTICS & ATTICS W/ FIXED STAIR 10 PSF 30 PSF -
SLEEPING ROOMS 15 PSF 30 PSF -
BALCONIES & DECKS 10 PSF 40 PSF -
STAIRS 10 PSF 40 PSF -
GUARD RAILS & HAND RAILS - 200 LBS (G) -

FASTENERS:
NO. BUILDING MATERIALS NUMBERS AND TYPE OF FASTENER SPACING OF FASTENERS EDGES INTERMEDIATE SUPPORTS
WOOD STRUCTURAL PANELS, SUB-FLOOR, ROOF AND INTERIOR WALL SHEATHING TO FRAMING & PARTICLE BOARD WALL SHEATHING TO FRAMING
30 3/8" - 1/2" 8d (2"x0.113") COMMON NAIL (SUBFLOOR, WALL) (J) 6" 12" (g)
31 5/16" - 1/2" 8d (2"x0.113") COMMON NAIL (SUBFLOOR, WALL) 8d (2 1/2"x0.131") COMMON NAIL (ROOF)(F) 6" 12" (g)
32 1/2" x 6" 8d (2 1/2"x0.131") COMMON NAIL 6" 12" (g)
33 1 1/8" - 1 1/4" 10d (3"x0.148") COMMON NAIL OR 8d (2 1/2"x0.131") DEFORMED NAIL 6" 12"

FASTENER SCHEDULE PER INTERNATIONAL RESIDENTIAL CODE

WOOD SPECIES:
SPECIES Fb Ft (a) Fv (a) Fc II (a) Fc.I (a) E Emin
HEM FIR #2 850 psi 525 psi 150 psi 405 psi 1300 psi 1300000 psi 470000 psi
SPF #2 875 psi 450 psi 425 psi 1150 psi 1400000 psi 510000 psi
THICKNESS WIDTH SOUTHERN PINE #2
2" TO 4" 2" TO 4" 1050 psi 850 psi 175 psi 565 psi 1100 psi 1400000 psi 510000 psi
5" TO 6" 1250 psi 725 psi 175 psi 565 psi 1600 psi 1600000 psi 580000 psi
8" 1200 psi 650 psi 175 psi 565 psi 1600 psi 1600000 psi 580000 psi
10" 1050 psi 575 psi 175 psi 565 psi 1500 psi 1600000 psi 580000 psi
12" 975 psi 550 psi 175 psi 565 psi 1450 psi 1600000 psi 580000 psi
MICROLAM LVL (ML) 2600 psi 1555 psi 285 psi 2510 psi 750 psi 1900000 psi 965710 psi
PARALLAM PSL 1.8E 2400 psi 1755 psi 190 psi 2500 psi 425 psi 1900000 psi 914880 psi
PARALLAM 2.0E 2900 psi 2025 psi 280 psi 2900 psi 750 psi 2000000 psi 1016535 psi
TIMERSTRAND LSL 1.3E 1900 psi 1075 psi 400 psi 1400 psi 680 psi 1300000 psi 660750 psi
TIMERSTRAND LSL 1.5E 2325 psi 1070 psi 310 psi 2050 psi 800 psi 1550000 psi 787815 psi

CONCRETE CLEAR COVERS:
DESCRIPTION MIN. COVER (IN.)
CONCRETE CAST AGAINST AND PERMANENTLY EXPOSED TO EARTH 3"
CONCRETE EXPOSED TO EARTH OR WEATHER #6 THROUGH #16 BARS 2"
#5 BAR, W31 OR D31 WIRE AND SMALLER 1 1/2"
CONCRETE NOT EXPOSED TO EARTH OR WEATHER SLAB, WALLS, JOISTS 3/4"
BEAMS, COLUMNS (PRIMARY REINF., TIES, STIRRUPS, SPIRALS) 1 1/2"
SHELLS, FOLDED PLATES #6 BARS AND LARGER 3/4"
#5 BAR W31 OR D31 WIRE AND SMALLER 1/2"

BUILDING INFORMATION:
DESCRIPTION LEVELS CRAWL SPACE, FIRST FLOOR & ATTIC
FIRST FLOOR AREA 1,131 SQ FT
DECK AREA 521 SQ FT
BUILDING HEIGHT 19'-1" REAR (ABOVE GRADE) 17'-9" FRONT (ABOVE GRADE)

REVISIONS
NO. DATE DESCRIPTIONS
0 06/14/21 PERMIT

192 MELS MEADOWS DRIVE
FUQUAY VARINA, NC 27526




06/14/2021


EQUAGEN engineering by ingenuity
FIRM # P-1869
121 EDINBURGH SOUTH DRIVE, SUITE 103
CARY, NC 27511
PHONE: 919.267.3004
EMAIL: INFO@EQUAGEN.COM

DRAWN BY: DG
CHECKED BY: MKC
DATE: 05/25/21
SCALE: AS SHOWN
T1.0 20-2053

SET PRINT SIZE TO SCALE: 11x17 LANDSCAPE



1. FLOOR PLAN
1/8"=1'-0"




2. REAR ELEVATION
1/8"=1'-0"


WINDOWS NOTES:
1) PROVIDE AT LEAST 1 EGRESS WINDOW PER BED ROOM.
2) PROVIDE SAFETY GLAZING FOR REAR FULL WALL WINDOWS. REFER TO NCRC 2018 REQUIREMENTS FOR GLASS.

- PROVIDE FOLLOWING MINIMUM INSULATION:
- R-19 ON FLOOR/SYSTEM
 - R-15 ON EXTERIOR WALLS
 - R-15 ON BASEMENT WALLS
 - R-38 AT ATTIC CEILING


*EGRESS WINDOW NOTE:
1) AT LEAST ONE WINDOW TO BE OF EGRESS IN EACH BEDROOM (MIN 5.7 SQ. FT CLEAR SPACE WHEN OPEN).
2) DEPENDING UPON WINDOW TYPE, i.e. DOUBLE HUNG, CASEMENT AND MANUFACTURER, SHOWN WINDOW DIMENSIONS MAY VARY.



3. LEFT ELEVATION
1/8"=1'-0"



4. RIGHT ELEVATION
1/8"=1'-0"



5. FRONT ELEVATION
1/8"=1'-0"


REVISIONS	
NO.	DATE
0	06/14/21
	PERMIT
	DESCRIPTIONS

FLOOR PLAN, ELEVATIONS
192 MELS MEADOWS DRIVE
FUQUAY VARINA, NC 27526



06/14/2021
EQUAGEN engineering by ingenuity
FIRM # P-1869
121 EDINBURGH SOUTH DRIVE, SUITE 103
CARY, NC 27511
PHONE: 919.267.3004
EMAIL: INFO@EQUAGEN.COM

DRAWN BY:	DG
CHECKED BY:	MKC
DATE:	05/25/21
SCALE:	AS SHOWN
A1.0	20-2053



1. BUILDING SECTION
1/4"=1'-0"

- NOTES:
- 1) CONTRACTOR TO ENSURE CRAWL SPACE GRADE IS SLOPED AWAY FROM THE HOUSE
 - 2) FINISHED DECK FLOOR CAN BE 2 1/2" +/- LOWER THAN BUILDING FINISHED FLOOR LEVEL FOR ADEQUATE ATTACHMENT OF DECK JOISTS WITH HOUSE RIM BOARD (BAND JOIST). CONTRACTOR TO VERIFY.

REVISIONS	
NO.	DATE
0	06/14/21
	PERMIT DESCRIPTIONS

BUILDING SECTION

192 MELS MEADOWS DRIVE
FUQUAY VARINA, NC 27526




06/14/2021

EQUAGEN
engineering by ingenuity

FIRM # P-1869
121 EDINBURGH SOUTH DRIVE, SUITE 103
CARY, NC 27511
PHONE: 919.267.3004
EMAIL: INFO@EQUAGEN.COM

DRAWN BY:	DG
CHECKED BY:	MKC
DATE:	05/25/21
SCALE:	AS SHOWN


A2.0 20-2053



GENERAL FLOOR FRAMING PLAN NOTES:

1. LOCATE FLOOR JOISTS CLEAR OF PLUMBING AND MECHANICAL.
2. KING STUDS SHALL BE NAILED TO EACH END OF HEADER WITH MIN OF (2) 16d NAILS. IF THE HEADER IS FLUSH, PROVIDE ONLY ONE KING STUD INSTEAD, AT EACH HEADER END. MATCH SIZE OF KING AND JACK STUDS WITH WALL, TYP
3. ALL FACE MOUNT FLOOR JOISTS AND BEAM/HEADERS SHALL BE CONNECTED USING SIMPSON HANGER.
4. STRUCTURAL FLOOR MEMBERS SHALL NOT BE DRILLED OR NOTCHED IN EXCESS OF THE LIMITATIONS SPECIFIED IN R502.8
5. WOOD STRUCTURAL PANELS USED FOR SUBFLOOR SHALL MEET THE REQUIREMENTS OF TABLE R503.2.1(1).
6. STUDS AND DOUBLE TOP PLATE SHALL NOT BE DRILLED OR NOTCHED IN EXCESS OF THE LIMITATIONS SPECIFIED IN R602.6
7. STRUCTURAL SHEATHING SHALL BE ATTACHED TO WALL STUDS PER TABLE R602.10.1

PIER LEGENDS

 8x16 CMU PIER (GROUT SOLID)

FOOTING SCHEDULE			
TYPE	DIMENSION	DEPTH	REINF. (BOT) EW
F1	2'-0"X2'-0"	1'-0"	(2)#5 EW; BOT. OF FOOTING 12" BELOW GRADE
F2	2'-0"X2'-0"	1'-0"	(3)#5, 6" BUMPOUT OF CF FOR END PIER
F3	2'-6"X2'-0"	1'-0"	(3)#5 TRANS, 6" BUMPOUT OF CF EACH SIDE
F4	1'-4"X1'-4"	1'-0"	BOT. OF FOOTING MIN 12" BELOW GRADE
F5	2'-6"X2'-6"	1'-0"	BOT. OF FOOTING MIN. 12" BELOW GRADE
CF	1'-6" CONT	0'-10"	(2)#5, CONT., BOT OF FOOTING 2' BELOW GRADE

1. FOUNDATION PLAN AND FRAMING PLAN
3/16"=1'-0"

REVISIONS			
NO.	DATE	DESCRIPTIONS	
0	06/14/21	PERMIT	


FOUNDATION PLAN, SCHEDULE
192 MELS MEADOWS DRIVE
FUQUAY VARINA, NC 27526




EQUAGEN engineering by ingenuity
FIRM # P-1869
121 EDINBURGH SOUTH DRIVE, SUITE 103
CARY, NC 27511
PHONE: 919.267.3004
EMAIL: INFO@EQUAGEN.COM

DRAWN BY:	DG
CHECKED BY:	MKC
DATE:	05/25/21
SCALE:	AS SHOWN

S1.0 20-2053



1. ROOF PLAN
1/8"=1'-0"



2. SHEAR WALL PLAN
1/8"=1'-0"

WALL BRACING PLAN NOTES:

- ON PLAN DENOTES THE LOCATION OF BRACED WALL PANELS. STUD WALL AT BRACED WALL PANEL LOCATIONS SHALL BE A MIN. OF 2x4 SPF #1/#2 AT 16" OC MAXIMUM, UNO. REFER TO SHEETS S4.0 FOR MORE INFO.
- BRACED WALL PANELS SHALL BE CONNECTED TO FLOOR FRAMING PER SECTION R602.10.4.4 AND BRACED WALL PANELS SHALL BE CONNECTED TO ROOF FRAMING PER R602.10.4.5.

REVISIONS	
NO.	DATE
0	06/14/21
	PERMIT
	DESCRIPTIONS

ROOF PLAN, SHEAR WALL PLAN

192 MELS MEADOWS DRIVE
FUQUAY VARINA, NC 27526




06/14/2021

EQUAGEN
engineering by ingenuity


FIRM # P-1869
121 EDINBURGH SOUTH DRIVE, SUITE 103
CARY, NC 27511
PHONE: 919.267.3004
EMAIL: INFO@EQUAGEN.COM

DRAWN BY:	DG
CHECKED BY:	MKC
DATE:	05/25/21
SCALE:	AS SHOWN
S2.0	20-2053




1. DECK STAIRS DETAIL

3/4"=1'-0"




3. TYP. METAL POST SECTION/DETAIL
NOT TO SCALE




2. DECK DETAILS

3/4"=1'-0"



4 SECTION
NOT TO SCALE

5. SECTION
NOT TO SCALE




6. BEAM SPLICE DETAILS

NTS

REVISIONS	
NO.	DATE
0	06/14/21
	PERMIT
	DESCRIPTIONS

DECK STAIRS, DECK DETAILS

192 MELS MEADOWS DRIVE
FUQUAY VARINA, NC 27526



06/14/2021



FIRM # P-1869
121 EDINBURGH SOUTH DRIVE, SUITE 103
CARY, NC 27511
PHONE: 919.267.3004
EMAIL: INFO@EQUAGEN.COM

DRAWN BY:	DG
CHECKED BY:	MKC
DATE:	05/25/21
SCALE:	AS SHOWN

S3.0 20-2053

WALL BRACING PER IRC 2015
PRESCRIPTIVE METHOD

WIND SPEED ≤ 115 MPH
SEISMIC DESIGN CATEGORY: B

BRACED WALL PANEL LEGEND:

WSP (XX)
LENGTH OF WALL PANEL IN INCHES

AT EXTERIOR FACE OF WALL:
WOOD STRUCTURAL PANEL: 7/16" OSB WALL SHEATHING w/ 8d COMMON NAILS (2 1/2"x0.131") AT 4" OC AT EDGES & 12" OC AT INTERMEDIATE SUPPORTS
AN ALTERNATIVE:
16 GAUGE x 1 3/4" STAPLES AT 3" OC AT EDGES & 6" OC AT INTERMEDIATE SUPPORTS

AT INTERIOR FACE OF WALL:
1/2" GYPSUM BOARD/SHEATHING WITH 5d COOLER NAILS AT 4" OC AT EDGES AND INTERMEDIATE SUPPORTS.

GB (XX)
LENGTH OF WALL PANEL IN INCHES


1/2" GYPSUM SHEATHING W/ 13 GAUGE, 1 3/8" LONG, 19/64" HEAD NAIL OR 0.098" DIA, 1 1/4" LONG, ANNULAR-RINGED NAIL OR 5d COOLER NAIL, 0.086" DIA, 1 5/8" LONG, 15/64" HEAD, OR GYPSUM BOARD NAIL W/ 0.086" DIA, 1 5/8" LONG, 9/32" HEAD @ 4" OC AT EDGES AND INTERMEDIATE SUPPORTS, OR 1 1/4" SCREWS TYPE W OR S, 12" OC W/ 4" AT EDGES AND INTERMEDIATE SUPPORTS W/ MIN 5/8" PENETRATION TO WOOD FRAMING.

NOTE:
WSP = WOOD STRUCTURAL PANEL | CS = CONTINUOUSLY SHEATHED
PF = PORTAL FRAME | GB = GYPSUM BOARD

FOR CONTINUOUS SHEATHING BRACED WALL METHOD, PROVIDE:


- AT EXTERIOR FACE OF WALL:
7/16" OSB WITH 8d NAILS AT 4" OC ON EDGES AND 12" OC ON FIELD.
- AT INTERIOR FACE OF WALL:
1/2" GYPSUM BOARD/SHEATHING WITH 5d COOLER NAILS AT 4" OC AT EDGES AND INTERMEDIATE SUPPORTS.

SHEATHING SHALL BE EXTENDED CONTINUOUS 12" ABOVE AND BELOW THE FLOOR SYSTEM.




NOTE 1:
1/2" DIA ANCHOR BOLTS (7" MIN EMBED) w/ 2"x2"x3/16" WASHER PLATES @ 4'-0" OC MAX AT 12" MAX FROM EA END OF WALL.


AN ALTERNATIVE: USE SIMPSON STRAPS LMA4/LMA5 @ 4'-0" OC, TYP.




1 HOLD-DOWN DETAIL
SCALE : NTS
AT CONCRETE FOUNDATION




2 HOLD-DOWN DETAIL
SCALE : NTS
AT RAISED WOOD FLOOR




END CONDITION - 1 END CONDITION - 2




END CONDITION - 3 END CONDITION - 4




3 END CONDITIONS FOR BRACED WALL LINES WITH CONTINUOUS SHEATHING METHOD
SCALE : NTS



OVER CONCRETE OR MASONRY BLOCK FOUNDATION



OVER RAISED WOOD FLOOR - FRAMING ANCHOR OPTION
(WHEN PORTAL SHEATHING DOES NOT LAP OVER BAND OR RIM BOARD)



OVER RAISED WOOD FLOOR - OVERLAP OPTION
(WHEN PORTAL SHEATHING LAPS OVER BAND OR RIM BOARD)

FRONT ELEVATION

SECTION

4 CONTINUOUS SHEATHING PORTAL FRAME (CS-PF)
SCALE : NTS


REFERENCE: IRC 2015 FIG. R602.10.6.4

PORTAL FRAME REQUIREMENTS									
MIN. SIZE & GRADE OF WALL STUDS	MAX. PONY WALL HEIGHT (FEET)	MAX. TOTAL WALL HEIGHT (FEET)	MAX. OPENING WIDTH (FEET)	REQUIRED TENSION CAPACITY OF STRAP (LBS)	MIN. SIZE & GRADE OF WALL STUDS	MAX. PONY WALL HEIGHT (FEET)	MAX. TOTAL WALL HEIGHT (FEET)	MAX. OPENING WIDTH (FEET)	REQUIRED TENSION CAPACITY OF STRAP (LBS)
2x4 SPF #1/#2 GRADE	0	10	18	1000	2x4 # 2 GRADE	2	12	18	3850
			9	1000				9	2350
			16	1000				16	DESIGN REQUIRED
	1	10	18	1200	2x6 STUD GRADE	2	12	9	1000
			9	1000				16	2050
			16	2025				18	2450
	2	10	18	2400	2x6 STUD GRADE	4	12	9	1500
			9	1200				16	3150
			16	3200				18	3675

REVISIONS			
NO.	DATE	DESCRIPTIONS	
0	06/14/21	PERMIT	

WALL BRACING DETAILS

192 MELS MEADOWS DRIVE
FUQUAY VARINA, NC 27526




06/14/2021

EQUAGEN
engineering by ingenuity

FIRM # P-1869
121 EDINBURGH SOUTH DRIVE, SUITE 103
CARY, NC 27511
PHONE: 919.267.3004
EMAIL: INFO@EQUAGEN.COM

DRAWN BY:	DG
CHECKED BY:	MKC
DATE:	05/25/21
SCALE:	AS SHOWN


S4.0 20-2053




1 BRACED WALL PANEL CONNECTION WHEN PARALLEL TO FLOOR/CEILING FRAMING
SCALE : NTS

ROOF FRAMING BLOCKING		
DISTANCE, D	REQUIREMENT	REF. DETAIL
0 - 9 1/4"	NO BLOCKING REQUIRED	NONE
9 1/4" - 11 1/4"	SOLID 2x ₄ BLOCKING BETWEEN RAFTERS OR TRUSSES	DETAIL 3
11 1/4" - 48"	SOFFIT BLOCKING OR VERTICAL BLOCKING PANEL	DETAIL 4 OR DETAIL 5
OVER 48"	ENGINEERED DESIGN REQUIRED	NONE


NOTE:
D: DISTANCE FROM TOP OF BRACING UNIT TO TOP OF ROOF SHEATHING




3 BLOCKING BETWEEN ROOF FRAMING MEMBERS
SCALE : NTS




4 SOFFIT BLOCKING PANELS
SCALE : NTS



2 BRACED WALL PANEL CONNECTION WHEN PERPENDICULAR TO FLOOR/CEILING FRAMING
SCALE : NTS




A SECTION
SCALE : NTS




B SECTION
SCALE : NTS

5 VERTICAL BLOCKING PANEL
SCALE : NTS



6 FRAMING DETAIL AT WALL INTERSECTIONS
SCALE : NTS



7 FRAMING DETAIL AT WALL CORNERS
SCALE : NTS

NOTE: USE WOOD TO METAL SCREWS @ 2\"/>

REVISIONS			
NO.	DATE	DESCRIPTIONS	
0	06/14/21	PERMIT	

WALL, ROOF BRACING DETAILS
192 MELS MEADOWS DRIVE
FUQUAY VARINA, NC 27526



EQUAGEN
engineering by ingenuity
FIRM # P-1869
121 EDINBURGH SOUTH DRIVE, SUITE 103
CARY, NC 27511
PHONE: 919.267.3004
EMAIL: INFO@EQUAGEN.COM

DRAWN BY:	DG
CHECKED BY:	MKC
DATE:	05/25/21
SCALE:	AS SHOWN
S5.0	20-2053