Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit
PROPERTY LOCATION: 134 Kingswood Ct (SR1116)

| Walter to LIGH Constructors | CURRINGIAN Ockmont | | LOT # 322 |
|--|--|--|--|
| ISSUED TO: H&H Constructors | SUBDIVISION Oakmont | mind min to Construction Authorise | |
| NEW REPAIR EXPANSION | site improvements re | quired prior to Construction Authoriza | tion issuance. |
| Type of Structure: 50' x 45' SFD | | | |
| Proposed Wastewater System Type: 25% reduction | | | |
| Projected Daily Flow: 600 GPD | | | |
| Number of bedrooms: 5 Number of Occupants: 10 | max | | |
| Basement Yes 🗵 No | | | |
| | final location and elevations of facilities | | _ |
| Type of Water Supply: Community Public Well | Distance from wellfeet | Permit valid for: | ★ Five years |
| Permit conditions: | | | No expiration |
| | | | |
| | | | |
| Authorized State Agent:: Make MRE147 | Date: 06-03-21 | SEE ATTAC | HED SITE SKETCH |
| The issuance of this permit by the Health Department in no way guarantees the issua | | | |
| site is subject to revocation if the site plan, plat, or the intended use changes. The In | | nership of the site. This permit is subject to con | mpliance with the provisions of |
| the Laws and Rules for Sewage Treatment and Disposal and to conditions of this perm | L. | | |
| | | | |
| | onstruction Authorization | | |
| | (Required for Building Permit) | | |
| The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1 | | s into this permit and shall be met. Systems sh | nall be installed in accordance |
| with the attached system layout. | | | |
| | | | 10) |
| ISSUED TO: H&H Constructors | | Kingswood Ct (SR11 | |
| | SUBDIVISION Oakmont | | LOT # 322 |
| Facility Type: 50' x 45' SFD | New Expansion Repair | | |
| Basement? Yes No Basement Fixtures? | · | | |
| pasement: | 163 | | |
| Tues of Wassesser Sustant ** 25% reduction | _ | (Initial) Wastawater Flows 6 | on GPD |
| Type of Wastewater System** 25% reduction | | (Initial) Wastewater Flow: _6 | GOO GPD |
| (See note below, if applicable) | | (Initial) Wastewater Flow: _6 | GPD GPD |
| (See note below, if applicable () 25% reduction | (Repair) | (Initial) Wastewater Flow: _6 | GPD GPD |
| (See note below, if applicable () 25% reduction | of trenches 4 | (Initial) Wastewater Flow: <u>6</u> | GPD GPD |
| (See note below, if applicable) | of trenches 4 | (Initial) Wastewater Flow: _6 Trench Spacing: 9 F | |
| (See note below, if applicable) | of trenches $\frac{4}{75}$ feet | Trench Spacing: 9F | |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Size gallons Trenches | of trenches 4 gth of each trench 75 feet shall be installed on contour at a | Trench Spacing: 9 Fool Cover: 6 inc | Feet on Center ches |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Sizegallons Trenches Maximum | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches | Trench Spacing: 9 Foil Cover: 6 incomparison | Feet on Center ches ot exceed |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Size gallons Trenches Maximum (Trench | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" | Trench Spacing: 9 Fool Cover: 6 inc | Feet on Center ches ot exceed |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Size gallons Trenches Maximum (Trench in all di | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" | Trench Spacing: 9 Foil Cover: 6 incomparison | Feet on Center ches ot exceed |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Size gallons Trenches Maximum (Trench | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" | Trench Spacing: 9 Foil Cover: 6 inc | Feet on Center ches ot exceed |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Size gallons Trenches Maximum (Trench in all di | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" | Trench Spacing: 9 Foil Cover: 6 inc. (Maximum soil cover shall no 36" above the trench bottom | Feet on Center ches It exceed m) |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Size gallons Trenches Maximum (Trench in all di Pump Requirements:ft. TDH vsGPM | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) | Trench Spacing: 9 Foil Cover: 6 inc | Feet on Center ches of exceed m) inches below pipe inches above pipe |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Size gallons Trenches Maximum (Trench in all di | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) | Trench Spacing: 9 Foil Cover: 6 inc. (Maximum soil cover shall no 36" above the trench bottom | Feet on Center ches ot exceed m) inches below pipe |
| (See note below, if applicable ☐) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Sizegallons Trenches Maximum (Trench in all di Pump Requirements:ft. TDH vsGPM Conditions: | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) | Trench Spacing: 9 Foil Cover: 6 incomparison | Feet on Center ches of exceed m) inches below pipe inches above pipe |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Size gallons Trenches Maximum (Trench in all di Pump Requirements:ft. TDH vsGPM | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) | Trench Spacing: 9 Foil Cover: 6 incomparison | Feet on Center ches of exceed m) inches below pipe inches above pipe |
| (See note below, if applicable ☐) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Sizegallons Trenches Maximum (Trench in all di Pump Requirements:ft. TDH vsGPM Conditions: | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR | Trench Spacing: 9 Foil Cover: 6 incomparison | Feet on Center ches of exceed m) inches below pipe inches above pipe |
| See note below, if applicable 25% reduction | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. | Trench Spacing: 9 Foil Cover: 6 inc. (Maximum soil cover shall no 36" above the trench botton Aggregate Depth: | Feet on Center ches ot exceed m) inches below pipe inches above pipe inches total |
| (See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1250 gallons Pump Tank Sizegallons Trenches Maximum (Trenches in all di Pump Requirements:ft. TDH vsGPM Conditions: | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. | Trench Spacing: 9 Foil Cover: 6 inc. (Maximum soil cover shall no 36" above the trench botton Aggregate Depth: | Feet on Center ches ot exceed m) inches below pipe inches above pipe inches total |
| See note below, if applicable 25% reduction | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. | Trench Spacing: 9 Soil Cover: 6inc (Maximum soil cover shall no 36" above the trench botton Aggregate Depth: REPAIR AREA. | Feet on Center ches ot exceed m) inches below pipe inches above pipe inches total |
| See note below, if applicable 25% reduction | of trenches 4 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches bottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. It from the type specified on the application | Trench Spacing: 9 Soil Cover: 6inc (Maximum soil cover shall no 36" above the trench botton Aggregate Depth: REPAIR AREA. Date: | Feet on Center ches it exceed in) inches below pipe inches above pipe inches total |
| See note below, if applicable 25% reduction | of trenches 4 gth of each trench 75 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. It from the type specified on the application ended use changes. The Construction Authorization shall not | Trench Spacing: 9 Soil Cover: 6 inc (Maximum soil cover shall no 36" above the trench botton Aggregate Depth: | Feet on Center ches It exceed It exceed It inches below pipe Inches above pipe Inches total It is permit. |
| See note below, if applicable 25% reduction | of trenches 4 gth of each trench 75 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. It from the type specified on the application ended use changes. The Construction Authorization shall not | Trench Spacing: 9 Soil Cover: 6 inc (Maximum soil cover shall no 36" above the trench botton Aggregate Depth: | Feet on Center ches it exceed in) inches below pipe inches above pipe inches total |
| See note below, if applicable 25% reduction | of trenches 4 gth of each trench 75 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches oottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. It from the type specified on the application ended use changes. The Construction Authorization shall not | Trench Spacing: 9 Soil Cover: 6 inc (Maximum soil cover shall no 36" above the trench botton Aggregate Depth: | Feet on Center ches It exceed It exceed It inches below pipe Inches above pipe Inches total It is permit. |
| See note below, if applicable 25% reduction | of trenches 4 gth of each trench 75 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches bottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. It from the type specified on the application Rules for Sewage Treatment and Disposal and to the cond | Trench Spacing: 9 Soil Cover: 6 | Feet on Center ches It exceed It exceed It inches below pipe Inches above pipe Inches total It is permit. |
| See note below, if applicable 25% reduction | of trenches 4 gth of each trench 75 gth of each trench 75 shall be installed on contour at a Trench Depth of: 18" - 22" inches bottoms shall be level to +/-1/4" ections) ROM ANY PART OF SEPTIC SYSTEM OR D AREA. It from the type specified on the application Rules for Sewage Treatment and Disposal and to the cond | Trench Spacing: 9 Soil Cover: 6 | Feet on Center ches It exceed It exceed It inches below pipe Inches above pipe Inches total It is permit. |

Harnett County Department of Public Health Site Sketch

Property Location: 134 Kingswood Ct (SR1116)

Issued To: H&H Constructors

Subdivision Oakmont

Lot # 322

Authorized State Agent: Date: 06-03-21

