


Job 21030025-A	Truss A1	Truss Type Piggyback Base	Qty 4	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:25

Page: 1

ID: HxQ6YJNKN98LVg1CHcl7hWz8hzU-bG9YI19qMA_Z2IXQi1NmWTglbHsj9WTmB1qC1yz8KtS



Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.84	Vert(LL)	-0.18	11-13	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.79	Vert(CT)	-0.26	11-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.64	Horz(CT)	0.04	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 345 lb	FT = 20%	

LUMBER	TOP CHORD	2x6 SP No.2	BOT CHORD	2x6 SP No.2	WEBS	2x4 SP No.2 *Except* W1,W2,W3:2x4 SP No.3, W10:2x6 SP No.2	OTHERS	2x6 SP No.2
REACTIONS (lb/size)	10=1557/0' 5 1/2", (min. 0' 2 1/8"), 18=1614/0' 3 1/2", (min. 0' 1 1/2")	Max Horiz	18=332 (LC 13)	Max Uplift	10=-163 (LC 15), 18=-191 (LC 14)	Max Grav	10=1791 (LC 6), 18=1821 (LC 5)	

BRACING	TOP CHORD	Structural wood sheathing directly applied or 5-0-13 oc purlins, except end verticals, and 2-0-0 oc purlins (5-2-9 max.): 4-7.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.	
WEBS	1 Row at midpt	5-13, 5-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-19=-926/134, 3-19=-872/140, 3-20=-1605/184, 20-21=-1598/201, 4-21=-1550/237, 4-22=-1425/243, 22-23=-1425/243, 23-24=-1425/243, 5-24=-1425/243, 5-25=-1319/244, 6-25=-1319/244, 6-26=-1319/244, 26-27=-1319/244, 7-27=-1319/244, 7-28=-1444/236, 28-29=-1493/200, 8-29=-1505/182, 8-10=-1568/220
BOT CHORD	14-15=-225/312, 14-31=-213/863, 13-31=-213/863, 13-32=-245/1557, 12-32=-245/1557, 11-12=-245/1557
WEBS	8-11=-135/1294, 4-13=-4/487, 5-13=-397/225, 3-13=-117/630, 5-11=-601/230, 7-11=-12/448, 2-14=-71/1392, 3-14=-935/212, 2-18=-1834/191

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-11-2, Interior (1) 1-11-2 to 5-3-7, Exterior(2R) 5-3-7 to 15-11-9, Interior (1) 15-11-9 to 24-1-4, Exterior(2R) 24-1-4 to 34-9-14, Exterior(2E) 34-9-14 to 38-7-3 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 18 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 10 and 18. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 21030025-A	Truss A2	Truss Type Piggyback Base	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:26

Page: 1

ID:u97ysgDk1M?CoVNYT?Ei3z8hvp-3TjwzdAS7T6Qf6cGlu?2hCUVhC7uzjvPhZiZPz8KtR




Plate Offsets (X, Y): [2:0' 1 1/2", 0' 1/4"], [4:0' 4", 0' 2 13/16"], [7:0' 4", 0' 2 13/16"], [12:0' 5", 0' 4 1/2"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.83	Vert(LL)	-0.18	10-12	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.78	Vert(CT)	-0.26	10-12	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.64	Horz(CT)	0.04	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 342 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.2 *Except* W1,W3,W2:2x4 SP No.3, W10:2x6 SP No.2
OTHERS 2x6 SP No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-3-12 oc purlins, except end verticals, and 2-0-0 oc purlins (5-2-11 max.): 4-7.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 5-12, 5-10

REACTIONS (lb/size) 9=1487/0' 4", (min. 0' 2 1/16"), 17=1610/0' 3 1/2", (min. 0' 1 1/2")
Max Horiz 17=327 (LC 13)
Max Uplift 9=-144 (LC 15), 17=-189 (LC 14)
Max Grav 9=1732 (LC 6), 17=1816 (LC 5)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-18=-924/122, 3-18=-870/127, 3-19=-1599/180, 19-20=-1592/197, 4-20=-1544/232, 4-21=-1418/236, 21-22=-1418/236, 22-23=-1418/236, 5-23=-1418/236, 5-24=-1308/228, 6-24=-1308/228, 6-25=-1308/228, 25-26=-1308/228, 7-26=-1308/228, 7-27=-1430/220, 27-28=-1481/192, 8-28=-1491/166, 8-9=-1512/201
BOT CHORD 13-14=-232/305, 13-29=-220/854, 12-29=-220/854, 12-30=-250/1548, 11-30=-250/1548, 10-11=-250/1548
WEBS 4-12=-2/483, 5-12=-391/223, 3-12=-117/627, 7-10=-8/445, 3-13=-932/213, 8-10=-135/1298, 5-10=-606/231, 2-13=-69/1388, 2-17=-1829/189

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-11-0, Interior (1) 1-11-0 to 5-3-10, Exterior(2R) 5-3-10 to 15-11-6, Interior (1) 15-11-6 to 24-1-8, Exterior(2R) 24-1-8 to 33-7-10, Exterior(2E) 33-7-10 to 37-4-12 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 17 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9 and 17. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss A3	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:26

Page: 1

ID:Oc4tZzqLeW19Cw9ealioxoz8hfX-3TjwzdAS7T6Qfv6cGlu?2hCTAhE_uvvvPhZiZPz8KtR



Scale = 1:71.3

Plate Offsets (X, Y): [4:0' 4",0' 2 13/16"], [7:0' 4",0' 2 3/4"], [8:0' 4 15/16",0' 2 1/2"], [13:0' 4",0' 3 1/2"], [14:0' 3",0' 3 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.17	11-13	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.66	Vert(CT)	-0.28	11-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.82	Horz(CT)	0.15	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 338 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W5,W6,W8,W7:2x4 SP No.2, W1,W10:2x6 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-6-9 oc purlins, except end verticals, and 2-0-0 oc purlins (4-4-1 max.): 4-7.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 5-13, 7-11, 5-11
 WEBS 2 Rows at 1/3 pts 3-15

REACTIONS

(lb/size) 10=1554/0' 5 1/2", (min. 0' 2 1/16"), 15=1619/0' 5 1/2", (min. 0' 1 13/16")
 Max Horiz 15=362 (LC 13)
 Max Uplift 10=-168 (LC 15), 15=-194 (LC 14)
 Max Grav 10=1736 (LC 3), 15=1757 (LC 5)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-4=-2479/384, 4-19=-1933/333, 19-20=-1933/333, 20-21=-1933/333, 5-21=-1933/333, 5-22=-1034/260, 22-23=-1034/260, 6-23=-1034/260, 6-24=-1034/260, 24-25=-1034/260, 7-25=-1034/260, 7-26=-1189/232, 26-27=-1295/196, 8-27=-1307/178, 2-15=-383/214, 8-10=-1624/199
 BOT CHORD 14-15=-499/1648, 13-14=-311/1816, 12-13=-259/1564, 11-12=-259/1564
 WEBS 3-14=-18/911, 4-14=-93/1012, 5-14=-211/735, 5-13=-542/240, 7-11=-60/316, 3-15=-2288/229, 8-11=-112/1268, 5-11=-797/212

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-11-2, Interior (1) 1-11-2 to 5-2-14, Exterior(2R) 5-2-14 to 15-11-9, Interior (1) 15-11-9 to 24-1-4, Exterior(2R) 24-1-4 to 34-9-14, Exterior(2E) 34-9-14 to 38-7-3 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
- Bearing at joint(s) 15 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15 and 10. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss A4	Truss Type Piggyback Base	Qty 3	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:27

Page: 1

ID:h26DlckO_ZTWISQ2UYAYAUdz8heM-XfHIAzB4unEHH3hoqSPEbulew5aDdN93eLJJ5rz8KlQ



Scale = 1:68.1

Plate Offsets (X, Y): [3:0' 4",0' 2 13/16"], [6:0' 4",0' 2 3/4"], [7:0' 4 15/16",0' 2 1/2"], [12:0' 4",0' 3 1/2"], [13:0' 3",0' 3 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.17	10-12	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.66	Vert(CT)	-0.28	10-12	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.82	Horz(CT)	0.15	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 333 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W1,W10:2x6 SP No.2, W6,W5,W8,W7:2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-6-8 oc purlins, except end verticals, and 2-0-0 oc purlins (4-3-14 max.): 3-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-12, 6-10, 4-10
 WEBS 2 Rows at 1/3 pts 2-14

REACTIONS

(lb/size) 9=1557/0' 5 1/2", (min. 0' 2 1/16"), 14=1491/0' 5 1/2", (min. 0' 11/16")
 Max Horiz 14=340 (LC 13)
 Max Uplift 9=-166 (LC 15), 14=-157 (LC 14)
 Max Grav 9=1739 (LC 3), 14=1650 (LC 5)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2490/374, 3-18=-1940/325, 18-19=-1940/325, 19-20=-1940/325, 4-20=-1940/325, 4-21=-1035/258, 21-22=-1035/258, 5-22=-1035/258, 5-23=-1035/258, 23-24=-1035/258, 6-24=-1035/258, 6-25=-1191/231, 25-26=-1297/195, 7-26=-1308/177, 7-9=-1625/197
 BOT CHORD 13-14=-487/1660, 12-13=-308/1819, 11-12=-256/1567, 10-11=-256/1567
 WEBS 3-13=-88/1026, 2-13=-21/905, 4-12=-543/239, 4-13=-205/741, 6-10=-56/317, 2-14=-2324/253, 4-10=-800/209, 7-10=-110/1270

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-2-12 to 4-0-1, Interior (1) 4-0-1 to 5-2-14, Exterior(2R) 5-2-14 to 15-11-9, Interior (1) 15-11-9 to 24-1-4, Exterior(2R) 24-1-4 to 34-9-14, Exterior(2E) 34-9-14 to 38-7-3 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bearing at joint(s) 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9 and 14. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss A5	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:28

Page: 1

ID:6uKnVS_xHi?g6XwufvsHrz8he2-?rrhNJBif5M7VCG?NAWT86ipiUwRMqNCI?2sdHz8KIP



Scale = 1:66.7

Plate Offsets (X, Y): [3:0' 4",0' 2 13/16"], [6:0' 4",0' 2 3/4"], [11:0' 4",0' 3 1/2"], [12:0' 3",0' 3 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.17	9-11	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.66	Vert(CT)	-0.28	9-11	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.82	Horz(CT)	0.15	8	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 331 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3 *Except* W1,W10:2x6 SP No.2, W6,W5,W8,W7:2x4 SP No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-6-8 oc purlins, except end verticals, and 2-0-0 oc purlins (4-4-1 max.): 3-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 4-11, 6-9, 4-9
WEBS 2 Rows at 1/3 pts 2-13

REACTIONS (lb/size) 8=1492/0' 5 1/2", (min. 0' 2"), 13=1492/0' 5 1/2", (min. 0' 1 11/16")
Max Horiz 13=336 (LC 11)
Max Uplift 8=-149 (LC 15), 13=-155 (LC 14)
Max Grav 8=1706 (LC 6), 13=1650 (LC 5)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2491/378, 3-17=-1940/328, 17-18=-1940/328, 18-19=-1940/328, 4-19=-1940/328, 4-20=-1037/244, 20-21=-1037/244, 5-21=-1037/244, 5-22=-1037/244, 22-23=-1037/244, 6-23=-1037/244, 6-24=-1190/210, 24-25=-1294/181, 7-25=-1308/156, 7-8=-1571/179
BOT CHORD 12-13=-497/1648, 11-12=-313/1820, 10-11=-261/1567, 9-10=-261/1567
WEBS 3-12=-91/1026, 2-12=-23/905, 4-11=-543/241, 4-12=-211/734, 6-9=-71/317, 2-13=-2325/260, 4-9=-798/211, 7-9=-109/1275

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-2-12 to 4-0-1, Interior (1) 4-0-1 to 5-2-14, Exterior(2R) 5-2-14 to 15-11-9, Interior (1) 15-11-9 to 24-1-4, Exterior(2R) 24-1-4 to 33-8-15, Exterior(2E) 33-8-15 to 37-6-4 zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Bearing at joint(s) 13 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8 and 13. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss A6	Truss Type Piggyback Base	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:28

Page: 1

ID:auTRPEcY1gYILWuuhgr3Ooz8hdE-?rrhNJBif5M7vCG?NAwT86lpgUwSMqECf?2sdHz8KfP



Scale = 1:66.6

Plate Offsets (X, Y): [3:0' 4",0' 2 13/16"], [6:0' 4",0' 2 3/4"], [11:0' 4",0' 3 1/2"], [12:0' 3",0' 3 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.85	Vert(LL)	-0.17	9-11	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.66	Vert(CT)	-0.28	9-11	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.83	Horz(CT)	0.15	8	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 330 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W1,W10:2x6 SP No.2, W6,W5,W8,W7:2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-6-9 oc purlins, except end verticals, and 2-0-0 oc purlins (4-4-1 max.): 3-6.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-11, 6-9, 4-9
 WEBS 2 Rows at 1/3 pts 2-13

REACTIONS (lb/size) 8=1487/0' 4", (min. 0' 2"), 13=1487/0' 5 1/2", (min. 0' 1 11/16")
 Max Horiz 13=337 (LC 11)
 Max Uplift 8=-148 (LC 15), 13=-155 (LC 14)
 Max Grav 8=1701 (LC 6), 13=1645 (LC 5)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2481/379, 3-17=-1932/329, 17-18=-1932/329, 18-19=-1932/329, 4-19=-1932/329, 4-20=-1022/242, 20-21=-1022/242, 5-21=-1022/242, 5-22=-1022/242, 22-23=-1022/242, 6-23=-1022/242, 6-24=-1173/209, 24-25=-1276/181, 7-25=-1289/156, 7-8=-1570/178
 BOT CHORD 12-13=-498/1643, 11-12=-314/1810, 10-11=-262/1558, 9-10=-262/1558
 WEBS 3-12=-91/1021, 2-12=-23/901, 4-11=-539/242, 4-12=-212/735, 6-9=-74/310, 2-13=-2316/260, 4-9=-806/211, 7-9=-109/1272

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-2-12 to 3-11-14, Interior (1) 3-11-14 to 5-2-14, Exterior(2R) 5-2-14 to 15-11-6, Interior (1) 15-11-6 to 24-1-8, Exterior(2R) 24-1-8 to 33-7-10, Exterior(2E) 33-7-10 to 37-4-12 zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Bearing at joint(s) 13 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 8 and 13. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 21030025-A	Truss A7	Truss Type Piggyback Base	Qty 3	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:29

Page: 1

ID:eKwzi_CHUKjLj28J3TDYt8z8hcT-U2P3bfCKQOU_WMrBxtRigJq0zulu5FSL6foQAJz8Kt0




Plate Offsets (X, Y): [3:0' 4",0' 2 13/16"], [7:0' 4",0' 2 3/4"], [8:Edge,0' 1/4"], [10:0' 3 3/4",Edge], [12:0' 7",0' 4"], [13:0' 3",0' 3 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.75	Vert(LL)	-0.17	11	>999	240	MT20 244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.52	Vert(CT)	-0.32	12-13	>999	180	
TCDL	10.0	Rep Stress Incr	YES	WB	0.96	Horz(CT)	0.26	8	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0										Weight: 317 lb FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2 *Except* B4:2x4 SP No.2
WEBS 2x4 SP No.3 *Except* W1:2x6 SP No.2, W6:2x4 SP 2400F 2.0E, W5,W7:2x4 SP No.2
WEDGE Right: 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-5-11 oc purlins, except end verticals, and 2-0-0 oc purlins (3-7-9 max.): 3-7.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 4-12, 2-14

REACTIONS (lb/size) 8=1471/ Mechanical, (min. 0' 1 1/2"), 14=1471/0' 5 1/2", (min. 0' 1 9/16")
Max Horiz 14=-259 (LC 12)
Max Uplift 8=-140 (LC 15), 14=-145 (LC 14)
Max Grav 8=1500 (LC 21), 14=1505 (LC 20)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2277/362, 3-21=-1794/346, 21-22=-1794/346, 22-23=-1794/346, 4-23=-1794/346, 4-24=-2705/284, 24-25=-2705/284, 5-25=-2705/284, 5-26=-2705/284, 6-26=-2705/284, 6-27=-2721/287, 7-27=-2721/287, 7-28=-2199/223, 8-28=-2316/198
BOT CHORD 13-14=-360/1398, 12-13=-218/1609, 6-10=-337/111, 9-10=-107/1856, 8-9=-104/1860
WEBS 3-13=-35/779, 2-13=-51/829, 4-12=-2714/444, 4-13=-161/623, 7-9=0/289, 2-14=-2163/337, 4-10=-207/2202, 10-12=-320/2589, 7-10=-256/1147

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-2-12 to 3-11-2, Interior (1) 3-11-2 to 5-2-14, Exterior(2R) 5-2-14 to 15-10-5, Interior (1) 15-10-5 to 24-2-9, Exterior(2R) 24-2-9 to 33-3-10, Exterior(2E) 33-3-10 to 37-0-0 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Bearing at joint(s) 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 140 lb uplift at jt(s) 14.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss A8	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:29

Page: 1

ID:48xD8mj7kKoz2sT5hRR5mnmz8hZE-U2P3bfCKQOU_WMrBxtRigJq02Jd5FIl6foQAjz8Kt0



Scale = 1:69.2

Plate Offsets (X, Y): [4:0' 4",0' 2 13/16"], [8:0' 4",0' 2 3/4"], [11:0' 3 3/4",Edge], [13:0' 7",0' 4"], [14:0' 3",0' 3 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	Vert(LL)	-0.17	12	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	Vert(CT)	-0.32	13-14	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	Horz(CT)	0.26	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0									Weight: 322 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2 *Except* B4:2x4 SP No.2
 WEBS 2x4 SP No.3 *Except* W1:2x6 SP No.2, W5,W8:2x4 SP No.2, W6:2x4 SP 2400F 2.0E
 WEDGE Right: 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-5-15 oc purlins, except end verticals, and 2-0-0 oc purlins (3-7-13 max.): 4-8.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 5-13, 3-15

REACTIONS (lb/size) 9=1467/ Mechanical, (min. 0' 1 1/2"), 15=1599/0' 5 1/2", (min. 0' 1 11/16")
 Max Horiz 15=-270 (LC 12)
 Max Uplift 9=-142 (LC 15), 15=-182 (LC 14)
 Max Grav 9=1498 (LC 22), 15=1633 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 3-4=-2265/378, 4-22=-1787/360, 22-23=-1787/360, 23-24=-1787/360, 5-24=-1787/360, 5-25=-2700/289, 25-26=-2700/289, 6-26=-2700/289, 6-27=-2700/289, 7-27=-2700/289, 7-28=-2716/292, 8-28=-2716/292, 8-29=-2198/229, 9-29=-2307/204, 2-15=-361/218
 BOT CHORD 14-15=-380/1369, 13-14=-221/1605, 7-11=-336/112, 10-11=-110/1855, 9-10=-107/1859
 WEBS 4-14=-40/763, 3-14=-48/836, 5-14=-172/615, 5-13=-2708/450, 8-10=0/289, 3-15=-2124/301, 5-11=-210/2198, 11-13=-326/2583, 8-11=-259/1141

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-10-4, Interior (1) 1-10-4 to 5-2-14, Exterior(2R) 5-2-14 to 15-10-5, Interior (1) 15-10-5 to 24-2-9, Exterior(2R) 24-2-9 to 33-3-10, Exterior(2E) 33-3-10 to 37-0-0 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Bearing at joint(s) 15 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 142 lb uplift at joint 9.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job 21030025-A	Truss A8	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:29

Page: 2

ID:48xD8mj7kKoz2sT5hRR5mnz8hZE-U2P3bfCKQOU_WMrBxtRigJq02uJd5FIL6foQAjz8KtO

LOAD CASE(S) Standard


Job 21030025-A	Truss A9	Truss Type Piggyback Base Structural Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-----------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:30

Page: 1

ID:or?_G4EDoxiVDhAhm8u6Sz8hQp-yEzRo?DyBicr8WQNVbyxDXNAQlbwqkBVkJXziAz8KtN



Scale = 1:71.3

Plate Offsets (X, Y): [4:0' 4", 0' 2 13/16"], [11:0' 4", 0' 2 3/4"], [21:0' 4", 0' 3 1/2"], [22:0' 3", 0' 3 3/4"], [29:0' 3", 0' 2 1/2"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.77	Vert(LL)	-0.17 19-21	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.66	Vert(CT)	-0.28 19-21	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.80	Horz(CT)	0.15 18	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0										
										Weight: 391 lb	FT = 20%

LUMBER	BRACING
TOP CHORD	TOP CHORD
BOT CHORD	BOT CHORD
WEBS	WEBS
OTHERS	WEBS
	JOINTS

REACTIONS (lb/size) 18=1554/0' 5 1/2", (min. 0' 2"), 23=1619/0' 5 1/2", (min. 0' 1 13/16")
 Max Horiz 23=362 (LC 13)
 Max Uplift 18=-168 (LC 15), 23=-194 (LC 14)
 Max Grav 18=1718 (LC 6), 23=1755 (LC 5)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD
 3-4=-2477/385, 4-37=-1939/336, 37-38=-1939/336, 38-39=-1939/336, 5-39=-1939/336, 5-40=-1123/266, 40-41=-1123/266, 6-41=-1123/266, 6-42=-1123/266, 7-42=-1123/266, 7-43=-885/220, 8-43=-885/220, 8-9=-885/220, 9-10=-885/220, 10-11=-885/220, 11-12=-1020/201, 12-13=-1081/190, 13-14=-1124/171, 14-15=-1096/96, 15-16=-1104/91, 2-23=-384/215, 18-33=-1608/196, 16-33=-1366/94
 BOT CHORD
 22-23=-498/1645, 21-22=-304/1794, 20-21=-253/1544, 19-20=-253/1544
 WEBS
 4-22=-82/977, 3-22=-21/917, 5-21=-528/237, 5-22=-222/734, 19-32=-45/299, 11-32=-99/284, 3-23=-2281/227, 5-19=-650/153, 19-29=-124/1138, 29-31=-70/1220, 16-31=-72/1186, 14-29=-367/118, 7-24=-368/99, 24-25=-383/104, 25-26=-403/109, 26-32=-361/102, 27-32=-387/112, 27-28=-364/102, 28-29=-383/104, 29-30=-411/155, 30-33=-460/157

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-11-2, Interior (1) 1-11-2 to 5-2-14, Exterior(2R) 5-2-14 to 15-11-9, Interior (1) 15-11-9 to 24-1-4, Exterior(2R) 24-1-4 to 34-10-8, Interior (1) 34-10-8 to 38-7-3 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.

Job 21030025-A	Truss A9	Truss Type Piggyback Base Structural Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-----------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:30

Page: 2

ID:or?_G4EDoxiVDhAhm8bU6Sz8hQp-yEzRo?DyBicr8WQNVbyxDXNAQlbwqkBVKJXziAz8KtN

- 12) Bearing at joint(s) 23 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 13) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 18 and 23. This connection is for uplift only and does not consider lateral forces.
- 14) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 15) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 21030025-A	Truss A10	Truss Type Piggyback Base Girder	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:31 Page: 1
ID:HxQ6YJNKN98LVg1CHcl7hWz8hzU-QQWp0LEayOkimg?Z3IUAlkwVCi4RZiLeZzHWEcz8KtM




Plate Offsets (X, Y): [2:0' 7 1/2", 4' 1 1/8"], [9:0' 4", 0' 2 13/16"], [13:0' 5", 0' 2 1/2"], [19:0' 4", 0' 2 13/16"], [34:0' 5", 0' 1 1/8"], [39:0' 5", 0' 6"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	0.00 39-40	>999	240	MT20 244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.07	Vert(CT)	0.00 39-40	>999	180	
TCDL	10.0	Rep Stress Incr	NO	WB	0.36	Horz(CT)	0.00 26	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH						
BCDL	10.0									Weight: 651 lb FT = 20%

REACTIONS	ALL BEARINGS 18' 1 7/16", except 26=1' 11 1/4", 27=1' 11 1/4", 32=5' 6 3/4", 33=5' 6 3/4", 31=5' 6 3/4", 35=1' 9 1/4", 30=1' 10 1/2", 29=1' 10 1/2", 28=1' 10 1/2"
(lb) - Max Horiz	48=361 (LC 11)
Max Uplift	All uplift 100 (lb) or less at joint(s) 26, 27, 28, 29, 31, 32, 33, 46, 47, 48 except 37=-237 (LC 9), 44=-115 (LC 12), 45=-111 (LC 57)
Max Grav	All reactions 250 (lb) or less at joint(s) 26, 27, 28, 29, 30, 32, 33, 45, 47, 48 except 31=294 (LC 36), 35=496 (LC 36), 37=2692 (LC 36), 38=1777 (LC 36), 39=1208 (LC 36), 40=1788 (LC 36), 41=1291 (LC 39), 42=1467 (LC 39), 43=1425 (LC 39), 44=1312 (LC 33), 46=1200 (LC 23)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
BOT CHORD	47-48=-361/335, 46-47=-343/278, 45-46=-343/278, 44-45=-284/236, 43-44=-284/236, 42-43=-284/236, 41-42=-284/236, 40-41=-284/236, 40-76=-284/236, 39-76=-284/236
WEBS	16-51=-256/70, 11-60=-315/86, 38-60=-309/86, 10-62=-284/74, 62-63=-274/75, 40-63=-273/78

- NOTES**
- Attached 11-2-12 scab 32 to 39, back face(s) 2x8 SP 2400F 2.0E with 2 row(s) of 10d (0.131"x3") nails spaced 9" o.c. except : starting at 0-9-2 from end at joint 39, nail 2 row (s) at 4" o.c. for 10-6-6.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 3x6 MT20 unless otherwise indicated.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

Job 21030025-A	Truss A10	Truss Type Piggyback Base Girder	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:31

Page: 2

ID:HxQ6YJNKN98LVg1CHcl7hWz8hzU-QQWp0LEay0king?Z3IUAlkwVCi4RZILeZzHWEcz8KtM

- 10) Gable studs spaced at 2-0-0 oc.
- 11) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 12) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 13) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 26, 47, 48, 32, 45, 33, 31, 29, 28, 27, 37, 44, and 46. This connection is for uplift only and does not consider lateral forces.
- 14) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 15) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 16) Use MiTek THD28 (With 28-16d nails into Girder & 16-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-9-0 from the left end to 15-9-0 to connect truss(es) F4 (1 ply 2x6 SP), F3 (1 ply 2x6 SP), F1 (1 ply 2x6 SP) to front face of bottom chord.
- 17) Use MiTek THDH26-2 (With 22-16d nails into Girder & 8-16d nails into Truss) or equivalent at 17-8-8 from the left end to connect truss(es) F2 (2 ply 2x6 SP) to front face of bottom chord.
- 18) Use MiTek JUS26 (With 4-10d nails into Girder & 4-10d nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 19-9-0 from the left end to 21-9-0 to connect truss(es) J04A (1 ply 2x6 SP) to front face of bottom chord.
- 19) Fill all nail holes where hanger is in contact with lumber.
- 20) WARNING: The following hangers are manually applied but fail due to geometric considerations: THD28 on front face at 3-9-0 from the left end, THD28 on front face at 5-9-0 from the left end, THD28 on front face at 7-9-0 from the left end, THD28 on front face at 9-9-0 from the left end, THD28 on front face at 11-9-0 from the left end, THD28 on front face at 13-9-0 from the left end, THD28 on front face at 15-9-0 from the left end.
- 21) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.
- 22) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-60, 2-9=-60, 9-19=-60, 19-24=-60, 24-25=-60, 26-48=-20
Concentrated Loads (lb)
Vert: 36=-224 (F), 35=-224 (F), 38=-1212 (F), 40=-1212 (F), 41=-1212 (F), 42=-1212 (F), 43=-1187 (F), 44=-1095 (F), 46=-1095 (F), 76=-1212 (F), 77=-2581 (F)


Job 21030025-A	Truss B1	Truss Type Piggyback Base	Qty 6	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:34

Page: 1

ID:kya_mR0YsZdhMB37_7X_0Pz8gat-q?CyeNGTEw7Hd7j8kQ1tNNYpdvwemao5FxVArxz8KtJ



Scale = 1:69.5

Plate Offsets (X, Y): [3:0' 5", 0' 4 1/2"], [4:0' 4", 0' 2 13/16"], [5:0' 4", 0' 2 13/16"], [10:0' 5", 0' 4 1/2"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.95	Vert(LL)	0.09	15-22	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.87	Vert(CT)	-0.36	11-12	>916	180	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.70	Horz(CT)	0.06	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 285 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2 *Except* T3:2x6 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W4:2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-9-9 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 6-9

REACTIONS (lb/size) 2=1329/0' 3", (min. 0' 1 3/4"), 9=1463/ Mechanical, (min. 0' 1 1/2"), 15=487/0' 5 1/2", (min. 0' 1 1/2")
 Max Horiz 2=250 (LC 11)
 Max Uplift 2=-145 (LC 15), 9=-94 (LC 15), 15=-327 (LC 11)
 Max Grav 2=1502 (LC 45), 9=1715 (LC 49), 15=897 (LC 41)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-23=-2105/272, 23-24=-2041/295, 24-25=-1927/315, 3-25=-1895/319, 3-26=-1899/171, 4-26=-1757/209, 4-27=-1389/199, 27-28=-1389/199, 28-29=-1389/199, 5-29=-1389/199, 5-30=-1754/161, 6-30=-1890/122, 32-33=-258/90, 7-33=-362/82, 7-9=-324/106
 BOT CHORD 2-34=-78/1637, 34-35=-78/1637, 35-36=-78/1637, 15-36=-78/1637, 14-15=-131/1659, 13-14=-131/1659, 12-13=0/1378, 11-12=0/1378, 10-11=0/1378, 10-37=-43/1516, 37-38=-43/1516, 9-38=-43/1516
 WEBS 6-9=-1800/48, 3-13=-305/358, 5-17=0/703, 10-17=0/684, 13-16=-30/720, 4-16=-16/736, 3-15=-826/231

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-10-9, Interior (1) 1-10-9 to 9-7-14, Exterior(2R) 9-7-14 to 29-9-2, Interior (1) 29-9-2 to 33-3-8, Exterior(2E) 33-3-8 to 37-0-4 zone; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 200.0lb AC unit load placed on the bottom chord, 19-8-8 from left end, supported at two points, 5-0-0 apart.
- Provide adequate drainage to prevent water ponding.
- All plates are MT20 plates unless otherwise indicated.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 2.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 94 lb uplift at joint 9.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15 and 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job 21030025-A	Truss B1	Truss Type Piggyback Base	Qty 6	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:34

Page: 2

ID:kya_mR0YsZdhMB37_7X_0Pz8gat-q?CyeNGTEw7Hd7j8kQ1tNNYpdwemao5FxFarxz8KtJ

16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss B2	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:34

Page: 1

ID: ?T0Mcu?UhSkfU8SbyVTwXVz8gX0-q?CyeNGTEw7Hd7j8kQ1tNNYufuy8mWa5FxVArxz8KtJ



Scale = 1:69.5

Plate Offsets (X, Y): [3:0' 5\", 0' 4 1/2\"], [4:0' 4\", 0' 2 3/4\"], [13:0' 4\", 0' 4 1/4\"]

Loading	(psf)	Spacing	2'	CSI	0.63	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.63	Vert(LL)	-0.39 11-13	>848	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.71	Vert(CT)	-0.61 11-13	>541	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.90	Horz(CT)	0.02 11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0										
										Weight: 294 lb	FT = 20%

<p>LUMBER</p> <p>TOP CHORD 2x6 SP No.2</p> <p>BOT CHORD 2x6 SP No.2 *Except* B2:2x6 SP 2400F 2.0E</p> <p>WEBS 2x4 SP No.2 *Except* W7,W1,W4:2x4 SP No.3</p> <p>OTHERS 2x4 SPF No.2(flat)</p> <p>REACTIONS (lb/size) 2=526/0' 3", (min. 0' 1 1/2\"), 11=1129/ Mechanical, (min. 0' 1 1/2\"), 15=1438/0' 5 1/2\", (min. 0' 2 1/16\")</p> <p>Max Horiz 2=300 (LC 18)</p> <p>Max Uplift 2=-29 (LC 11), 11=-190 (LC 11), 15=-190 (LC 11)</p> <p>Max Grav 2=526 (LC 2), 11=1532 (LC 37), 15=1727 (LC 3)</p>	<p>BRACING</p> <p>TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-11-11 max.): 4-9.</p> <p>BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.</p> <p>WEBS I-Brace: 2x4 SPF No.2 - 7-11</p> <p>T-Brace: 2x4 SPF No.2 - 8-11, 4-15, 5-13</p> <p>Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.</p> <p>Brace must cover 90% of web length.</p>
---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD	2-19=-341/83, 19-20=-289/17, 3-22=-285/27, 4-23=-1155/135, 23-24=-1155/135, 5-24=-1155/135, 5-6=-1095/111, 6-7=-1095/111, 8-11=-319/79
BOT CHORD	14-15=-123/606, 14-29=-123/606, 13-29=-123/606, 12-13=-127/774, 12-30=-127/774, 11-30=-127/774
WEBS	7-11=-1281/218, 4-15=-1010/102, 3-15=-604/307, 5-13=-584/196, 7-13=0/645, 4-13=-64/846

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-10-9, Interior (1) 1-10-9 to 9-7-14, Exterior(2R) 9-7-14 to 20-2-7, Interior (1) 20-2-7 to 33-6-12, Exterior(2E) 33-6-12 to 37-3-8 zone; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 190 lb uplift at joint 11.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15 and 2. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job 21030025-A	Truss B2	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:34

Page: 2

ID:?T0Mcu?UhSkfU8SbyVTwXVz8gX0-q?CyeNGTEw7Hd7j8kQ1tNNYufvy8mWa5FxVArxz8KtJ

- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 14) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard


Job 21030025-A	Truss B3	Truss Type Half Hip	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:35

Page: 1

ID:FvK1A5AmXSIFtd?xbAuHFz8gUD-ICmKriH5?EF8EHIL18Y6wa45HJJGV_IUEuBFkNNz8KI



Scale = 1:70.7

Plate Offsets (X, Y): [13:0' 4", 0' 4 1/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.51	Vert(LL)	-0.30	12-13	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.65	Vert(CT)	-0.48	12-13	>687	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.87	Horz(CT)	0.02	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 292 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2 *Except* B3:2x6 SP 2400F 2.0E
 WEBS 2x4 SP No.2 *Except* W7,W1,W4:2x4 SP No.3
 OTHERS 2x4 SPF No.2(flat)

REACTIONS (lb/size) 2=528/0' 3", (min. 0' 1 1/2"), 12=1124/ Mechanical, (min. 0' 1 1/2"), 16=1442/0' 5 1/2", (min. 0' 2 1/16")
 Max Horiz 2=400 (LC 14)
 Max Uplift 2=-33 (LC 11), 12=-189 (LC 11), 16=-188 (LC 11)
 Max Grav 2=537 (LC 36), 12=1516 (LC 37), 16=1726 (LC 3)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-10.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS I-Brace: 2x4 SPF No.2 - 7-12
 T-Brace: 2x4 SPF No.2 - 9-12, 5-16, 6-13
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
 Brace must cover 90% of web length.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-20=-365/52, 3-20=-293/18, 3-21=-281/9, 5-22=-1147/137, 22-23=-1148/137, 6-23=-1149/137, 6-7=-1091/114, 9-12=-319/79
 BOT CHORD 2-25=-173/260, 25-26=-173/260, 26-27=-173/260, 16-27=-173/260, 15-16=-121/590, 15-28=-121/590, 28-29=-121/590, 14-29=-121/590, 13-14=-121/590, 13-30=-130/771, 30-31=-130/771, 12-31=-130/771
 WEBS 3-16=-554/285, 5-16=-1061/124, 6-13=-587/199, 7-13=0/627, 5-13=-72/857, 7-12=-1266/219

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-10-9, Interior (1) 1-10-9 to 9-7-14, Exterior(2R) 9-7-14 to 20-2-7, Interior (1) 20-2-7 to 33-6-12, Exterior(2E) 33-6-12 to 37-3-8 zone; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 189 lb uplift at joint 12.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 16 and 2. This connection is for uplift only and does not consider lateral forces.

Job 21030025-A	Truss B3	Truss Type Half Hip	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:35

Page: 2

ID:FvK1A5AmXSIFTfd?xbAuHFz8gUD-ICmKriH5?EF8EHIL18Y6wa45HJJGV_1EUBFKNNz8Ktl

- 12) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 14) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard


Job 21030025-A	Truss B4	Truss Type Half Hip	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:36

Page: 1

ID:5UR8YT5V4JKh25HzmUXAEz8gRk-mOKI32lJmYN?sRtXr3LSodDujhOERbNJf_Hvpz8KH



Scale = 1:70.7

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	0.09	17-20	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.46	Vert(CT)	-0.18	15-17	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.87	Horz(CT)	0.02	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 287 lb	FT = 20%	

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W3,W5,W6:2x4 SP No.2
 OTHERS 2x4 SPF No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (5-3-0 max.): 5-10.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-17.
 WEBS I-Brace: 2x4 SPF No.2 - 8-12
 WEBS T-Brace: 2x4 SPF No.2 - 9-12, 5-17
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance. Brace must cover 90% of web length.

REACTIONS (lb/size) 2=427/0' 3", (min. 0' 1 1/2"), 12=1088/ Mechanical, (min. 0' 1 1/2"), 17=1579/0' 5 1/2", (min. 0' 2 3/16")
 Max Horiz 2=326 (LC 14)
 Max Uplift 2=-28 (LC 14), 12=-180 (LC 11), 17=-250 (LC 11)
 Max Grav 2=496 (LC 21), 12=1441 (LC 37), 17=1838 (LC 37)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-21=-321/57, 21-22=-277/15, 5-24=-1144/158, 24-25=-1145/158, 25-26=-1145/158, 6-26=-1146/158, 6-7=-1144/157, 7-8=-1144/157, 9-12=-360/90
 BOT CHORD 17-31=-76/283, 16-31=-76/283, 15-16=-76/283, 14-15=-145/1082, 14-32=-145/1082, 13-32=-145/1082, 13-33=-145/1082, 12-33=-145/1082
 WEBS 3-17=-489/214, 5-17=-1314/213, 5-15=-133/1205, 6-15=-637/221, 8-13=0/489, 8-12=-1465/197

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-3 to 1-10-9, Interior (1) 1-10-9 to 6-7-14, Exterior(2R) 6-7-14 to 17-2-7, Interior (1) 17-2-7 to 33-6-12, Exterior(2E) 33-6-12 to 37-3-8 zone; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 180 lb uplift at joint 12.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at j(s) 17 and 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job 21030025-A	Truss B4	Truss Type Half Hip	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:36

Page: 2

ID:5UR8YT5V4JKh25HZmUXAEmz8gRk-mOKi32ljmYN?sRtXrr3LSodDujhOERbNJF_Hvpz8KtH

- 13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 14) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard


Job 21030025-A	Truss B5	Truss Type Half Hip Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:39

Page: 1

ID:OpdM7hFEmB3hNS41V7CzcDz8MF7-mOKi32JjmYN?sRtXrr3LSodDdjhvEPINJF_Hvpz8KH



Scale = 1:70.6

Plate Offsets (X, Y): [3:0' 3", 0' 3"]

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SPF No.2(flat)

REACTIONS (lb/size) 2=107/0' 3", (min. 0' 1 1/2"), 11=2531/ Mechanical, (min. 0' 1 1/2"), 16=4186/0' 5 1/2", (min. 0' 2 11/16")
 Max Horiz 2=253 (LC 12)
 Max Uplift 2=-228 (LC 53), 11=-884 (LC 9), 16=-1511 (LC 9)
 Max Grav 2=290 (LC 19), 11=2808 (LC 43), 16=4600 (LC 43)

BRACING

TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-9.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-16.
 WEBS T-Brace: 2x4 SPF No.2 - 4-16
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
 Brace must cover 90% of web length.


Job 21030025-A	Truss C1	Truss Type Attic	Qty 4	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	---------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:41

Page: 1

ID:NYvMWYUlvkpfFHGZj?3471z8gNL-7L7b6mLsb4?HyCIUeOFw9rK0kRlrvnw7sXi2b1z8KiC



Scale = 1:55.9

Plate Offsets (X, Y): [2:0' 3",0' 1 1/4"], [6:0' 5 1/2",0' 3"], [7:0' 5 1/2",0' 3"], [10:0' 3",0' 1 1/4"], [12:0' 3 1/2",0' 7"], [14:0' 3 1/2",0' 7"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.92	Vert(LL)	-0.24	12-14	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.35	Vert(CT)	-0.36	12-14	>816	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.44	Horz(CT)	0.01	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH		Attic	-0.16	12-14	>999	360		
BCDL	10.0											
											Weight: 256 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x10 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except* W5:2x4 SP No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-7.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
JOINTS 1 Brace at Jt(s): 16

REACTIONS (lb/size) 11=1190/0' 5 1/2", (min. 0' 1 1/2"), 15=1318/0' 3 1/2", (min. 0' 1 1/2")
Max Horiz 15=254 (LC 13)
Max Grav 11=1607 (LC 46), 15=1713 (LC 46)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-17=-1812/0, 17-18=-1691/0, 18-19=-1652/0, 3-19=-1614/0, 3-4=-1138/93, 4-5=-1039/112, 5-6=-499/135, 6-20=-323/160, 20-21=-323/160, 21-22=-323/160, 7-22=-323/160, 7-8=-496/133, 8-9=-1140/113, 9-23=-1601/0, 23-24=-1639/0, 24-25=-1678/0, 10-25=-1799/0, 2-15=-1820/0, 10-11=-1718/0
BOT CHORD 14-15=-260/308, 13-14=0/1170, 12-13=0/1170
WEBS 3-14=-20/822, 9-12=-41/807, 5-16=-1314/71, 8-16=-1313/70, 2-14=0/1146, 10-12=0/1134

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-4-1, Exterior(2R) 5-4-1 to 19-5-7, Interior (1) 19-5-7 to 21-9-4, Exterior(2E) 21-9-4 to 24-9-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 3-5, 8-9, 5-16, 8-16; Wall dead load (5.0psf) on member(s).3-14, 9-12
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 12-14
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Attic room checked for L/360 deflection.

LOAD CASE(S) Standard


Job 21030025-A	Truss C2	Truss Type Attic Girder	Qty 1	Ply 3	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	----------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:41

Page: 1

ID:zmVCishpe95_s4doF7A0yaz8drf7j7b6mLsb4?HyClUeOFW9rK?6kSXvoP7sXi2b1z8KtC



Scale = 1:61.1

Plate Offsets (X, Y): [2:0' 3",0' 1 3/4"], [6:0' 5 1/2",0' 3"], [7:0' 5 1/2",0' 3"], [11:0' 8 1/4",0' 1 1/2"], [12:0' 3 1/2",0' 8"], [14:0' 3 1/2",0' 4 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	1.00	Vert(LL)	-0.19	12-14	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.27	Vert(CT)	-0.31	12-14	>925	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.45	Horz(CT)	0.01	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH		Attic	-0.12	12-14	>999	360		
BCDL	10.0											
											Weight: 761 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2 *Except* T2:2x6 SP 2400F 2.0E
 BOT CHORD 2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.3 *Except* W5:2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 6-7.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 16

REACTIONS (lb/size) 11=3890/0' 3 1/2", (min. 0' 1 1/2"), 15=3553/0' 3 1/2", (min. 0' 1 1/16")
 Max Horiz 15=253 (LC 9)
 Max Grav 11=4746 (LC 2), 15=6102 (LC 2)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-17=-4593/0, 17-18=-4448/0, 3-18=-4424/0, 3-4=-2482/0, 4-5=-2405/0, 5-6=-116/557, 6-19=0/898, 19-20=0/898, 20-21=0/898, 7-21=0/898, 7-8=-126/568, 8-9=-2428/0, 9-22=-4480/0, 22-23=-4505/0, 10-23=-4617/0, 2-15=-4447/0
 BOT CHORD 15-24=-174/501, 14-24=-174/501, 13-14=0/3032, 12-13=0/3032
 WEBS 3-14=0/2837, 9-12=0/3004, 5-16=-4004/0, 8-16=-3919/0, 2-14=0/2890, 10-12=0/3305, 10-11=-4861/0, 6-16=-71/259

NOTES

- 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x6 - 2 rows staggered at 0' 9" oc, 2x4 - 1 row at 0' 9" oc.
 Bottom chords connected as follows: 2x10 - 5 rows staggered at 0' 8" oc.
 Web connected as follows: 2x4 - 1 row at 0' 9" oc, Except member 9-12 2x4 - 1 row at 0' 4" oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 3-5, 8-9, 5-16, 8-16; Wall dead load (5.0psf) on member(s).3-14, 9-12
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 12-14
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job 21030025-A	Truss C2	Truss Type Attic Girder	Qty 1	Ply 3	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	----------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:41

Page: 2

ID:zmVCishpe95_s4doF7A0uaz8dri-7L7b6mLsb4?HyClUeOfW9rK?6kSXvoP7sXi2b1z8KtC

- 16) Use MiTek THDH28-2 (With 36-16d nails into Girder & 4-16d nails into Truss) or equivalent at 19-5-0 from the left end to connect truss(es) GR2 (2 ply 2x6 SP) to back face of bottom chord.
- 17) Fill all nail holes where hanger is in contact with lumber.
- 18) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 2350 lb down at 1-2-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 19) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 - Uniform Loads (lb/ft)
 - Vert: 1-2=-60, 2-3=-60, 3-5=-70, 5-6=-60, 6-7=-60, 7-8=-60, 8-9=-70, 9-10=-60, 15-24=-20, 14-24=-73 (B=-53), 12-14=-83 (B=-53), 11-12=-20, 5-16=-10, 8-16=-10
 - Drag: 3-14=-10, 9-12=-10
 - Concentrated Loads (lb)
 - Vert: 12=-2828 (B), 24=-1175 (B)
- 2) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 - Uniform Loads (lb/ft)
 - Vert: 1-2=-60, 2-3=-60, 3-5=-70, 5-6=-60, 6-7=-60, 7-8=-60, 8-9=-70, 9-10=-60, 15-24=-20, 14-24=-214 (B=-194), 12-14=-224 (B=-194), 11-12=-20, 5-16=-10, 8-16=-10
 - Drag: 3-14=-10, 9-12=-10
 - Concentrated Loads (lb)
 - Vert: 12=-2482 (B), 24=-2350 (B)


Job 21030025-A	Truss C2A	Truss Type Attic Girder	Qty 1	Ply 3	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:42

Page: 1

ID: glll919GIXaddnKiM7HYMOz8dLx-byhzK6MUM078aMKhC6AlI3tEu8nyeGqG5BRc7Tz8KtB



Scale = 1:61.1

Plate Offsets (X, Y): [2:0' 3", 0' 1 3/4"], [6:0' 5 1/2", 0' 3"], [7:0' 5 1/2", 0' 3"], [11:0' 8 1/4", 0' 1 1/2"], [12:0' 3 1/2", 0' 8"], [14:0' 3 1/2", 0' 4 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	-0.18	12-14	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.26	Vert(CT)	-0.29	12-14	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.44	Horz(CT)	0.01	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH		Attic	-0.11	12-14	>999	360		
BCDL	10.0											
											Weight: 761 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E *Except* T3, T1: 2x6 SP No.2
 BOT CHORD 2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.3 *Except* W5: 2x4 SP No.2

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 6-7.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 16

REACTIONS (lb/size) 11=3726/0' 3 1/2", (min. 0' 1 1/2"), 15=3513/0' 3 1/2", (min. 0' 1 1/16")
 Max Horiz 15=286 (LC 9)
 Max Grav 11=4545 (LC 2), 15=6057 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-17=-4501/0, 17-18=-4356/0, 3-18=-4332/0, 3-4=-2437/0, 4-5=-2360/0, 5-6=-151/526, 6-19=0/839, 19-20=0/839, 20-21=0/839, 7-21=0/839, 7-8=-186/508, 8-9=-2370/0, 9-22=-4417/0, 22-23=-4443/0, 10-23=-4554/0, 2-15=-4340/0
 BOT CHORD 15-24=-192/510, 14-24=-192/510, 13-14=0/2979, 12-13=0/2979
 WEBS 3-14=0/2751, 9-12=0/2979, 5-16=-3915/0, 8-16=-3779/0, 10-11=-4802/0, 2-14=0/2842, 10-12=0/3247, 6-16=-80/291

NOTES

- 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x6 - 2 rows staggered at 0' 9" oc, 2x4 - 1 row at 0' 9" oc.
 Bottom chords connected as follows: 2x10 - 5 rows staggered at 0' 8" oc.
 Web connected as follows: 2x4 - 1 row at 0' 9" oc, Except member 9-12 2x4 - 2 rows staggered at 0' 9" oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 3-5, 8-9, 5-16, 8-16; Wall dead load (5.0psf) on member(s). 3-14, 9-12
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 12-14
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Load case(s) 1, 2 has/have been modified. Building designer must review loads to verify that they are correct for the intended use of this truss.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job 21030025-A	Truss C2A	Truss Type Attic Girder	Qty 1	Ply 3	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:42

Page: 2

ID:glll919GIXaddnKiM7HYMOz8dlx-bYhzK6MUM078aMKhC6Ali3tEu8nyeGqG5BRc7Tz8KtB

- 16) Use MiTek THDH28-2 (With 36-16d nails into Girder & 4-16d nails into Truss) or equivalent at 19-5-0 from the left end to connect truss(es) GR2 (2 ply 2x6 SP) to front face of bottom chord.
- 17) Fill all nail holes where hanger is in contact with lumber.
- 18) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 2350 lb down at 1-1-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 19) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 - Uniform Loads (lb/ft)
 - Vert: 1-2=-60, 2-3=-60, 3-5=-70, 5-6=-60, 6-7=-60, 7-8=-60, 8-9=-70, 9-10=-60, 15-24=-20, 14-24=-73 (F=-53), 12-14=-83 (F=-53), 11-12=-20, 5-16=-10, 8-16=-10
 - Drag: 3-14=-10, 9-12=-10
 - Concentrated Loads (lb)
 - Vert: 12=-2624 (F), 24=-1175 (F)
- 2) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15
 - Uniform Loads (lb/ft)
 - Vert: 1-2=-60, 2-3=-60, 3-5=-70, 5-6=-60, 6-7=-60, 7-8=-60, 8-9=-70, 9-10=-60, 15-24=-20, 14-24=-214 (F=-194), 12-14=-224 (F=-194), 11-12=-20, 5-16=-10, 8-16=-10
 - Drag: 3-14=-10, 9-12=-10
 - Concentrated Loads (lb)
 - Vert: 12=-2233 (F), 24=-2350 (F)


Job 21030025-A	Truss C3	Truss Type Attic	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	---------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:43

Page: 1

ID:MC1LTaCPsSn5JGR5U_o6R2z8dgi-3kFLXRN67hF?CWvtmph_FGNPF6sNh4PKrB9fwz8KtA



Scale = 1:59.9

Plate Offsets (X, Y): [2:0' 3",0' 1 1/4"], [6:0' 5 1/2",0' 3"], [7:0' 5 1/2",0' 3"], [12:0' 3 1/2",0' 7"], [14:0' 3 1/2",0' 4 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.89	Vert(LL)	-0.23	12-14	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.35	Vert(CT)	-0.35	12-14	>831	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.49	Horz(CT)	0.01	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH		Attic	-0.16	12-14	>999	360		
BCDL	10.0											
											Weight: 254 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.3 *Except* W5:2x4 SP No.2

BRACING
 TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-7.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 16

REACTIONS (lb/size) 11=1612/0' 3 1/2", (min. 0' 1 11/16"), 15=1295/0' 3 1/2", (min. 0' 1 1/2")
 Max Horiz 15=286 (LC 11)
 Max Grav 11=2005 (LC 46), 15=1683 (LC 46)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-17=-1746/0, 17-18=-1625/0, 18-19=-1586/0, 3-19=-1547/0, 3-4=-1103/95, 4-5=-1005/115, 5-6=-509/131, 6-20=-335/145, 20-21=-335/145, 21-22=-335/145, 7-22=-335/145, 7-8=-507/133, 8-9=-1110/116, 9-23=-1545/0, 23-24=-1570/0, 10-24=-1695/0, 2-15=-1758/0
 BOT CHORD 14-15=-274/325, 13-14=0/1125, 12-13=0/1125
 WEBS 3-14=-45/788, 9-12=-89/754, 5-16=-1241/72, 8-16=-1257/69, 2-14=0/1101, 10-11=-2230/9, 10-12=0/1228

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-4-1, Exterior(2R) 5-4-1 to 19-5-7, Interior (1) 19-5-7 to 21-3-12, Exterior(2E) 21-3-12 to 24-3-12 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 3-5, 8-9, 5-16, 8-16; Wall dead load (5.0psf) on member(s). 3-14, 9-12
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 12-14
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 460 lb down and 80 lb up at 24-3-12 on top chord. The design/selection of such connection device(s) is the responsibility of others.
 - Attic room checked for L/360 deflection.

LOAD CASE(S) Standard
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (lb/ft)

Job 21030025-A	Truss C3	Truss Type Attic	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	---------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:43

Page: 2

ID:MC1LTaCPsSn5JGR5U_o6R2z8dgi-3kFLXRN67hF?CWvtmph_FGPNFX6sNh4PKrB9fwz8KtA

Vert: 1-2=-60, 2-3=-60, 3-5=-70, 5-6=-60, 6-7=-60, 7-8=-60, 8-9=-70, 9-10=-60, 14-15=-20, 12-14=-30, 11-12=-20, 5-16=-10, 8-16=-10

Drag: 3-14=-10, 9-12=-10

Concentrated Loads (lb)

Vert: 10=-437


Job 21030025-A	Truss C4	Truss Type Attic Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	----------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:43

Page: 1

ID:FBFfupiDvIFaDI6BgJlvguz8NF5-3kFLXRN67hF?CWvtmpH_FGPOnX6pNgpPKrB9fwz8KtA



Scale = 1:62

Plate Offsets (X, Y): [2:0' 3\", 0' 1 1/4\"], [5:0' 5\", Edge], [6:0' 5 1/2\", 0' 3\"], [7:0' 5 1/2\", 0' 3\"], [11:0' 7 3/4\", 0' 1 1/2\"], [12:0' 3 1/2\", 0' 8\"], [14:0' 3 1/2\", 0' 5 3/4\"]

LUMBER
 TOP CHORD 2x6 SP No.2 *Except* T4, T1:2x6 SP 2400F 2.0E
 BOT CHORD 2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.3 *Except* W5:2x4 SP No.2

REACTIONS (lb/size) 11=3136/0' 3 1/2\", (min. 0' 1 1/2\"), 15=2921/0' 3 1/2\", (min. 0' 1 1/2\")
 Max Horiz 15=253 (LC 9)
 Max Uplift 11=-411 (LC 13), 15=-342 (LC 12)
 Max Grav 11=3440 (LC 48), 15=3302 (LC 46)

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (10-0-0 max.): 6-7.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 16


Job 21030025-A	Truss C5	Truss Type Attic Structural Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	--------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:44

Page: 1

ID: ?xDUAoH_RV5?w7M7oii7fRz8MCW-XwpkknOku?NspgU3JXCdNlyZexSK65EZYVwiCMz8Kt9



Scale = 1:58.5

Plate Offsets (X, Y): [9:0' 5 1/2", 0' 3"], [12:0' 8 1/4", 0' 3 3/4"], [20:0' 3 1/2", 0' 7"], [22:0' 3 1/2", 0' 4 3/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.79	Vert(LL)	-0.22	20-22	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.33	Vert(CT)	-0.33	20-22	>892	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.70	Horz(CT)	0.01	18	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH		Attic	-0.15	20-22	>999	360		
BCDL	10.0											
											Weight: 285 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.3 *Except* W5,W2:2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-8-2 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 9-12.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 25, 26, 31, 32, 34

REACTIONS

(lb/size) 18=1190/0' 5 1/2", (min. 0' 1 1/2"), 24=1318/0' 3 1/2", (min. 0' 1 1/2")
 Max Horiz 24=254 (LC 13)
 Max Grav 18=1608 (LC 46), 24=1720 (LC 46)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1526/0, 3-4=-1870/0, 4-36=-1744/0, 5-36=-1647/0, 5-6=-1141/94, 6-7=-1043/113, 7-8=-515/115, 8-9=-384/123, 9-37=-443/140, 10-37=-443/140, 10-38=-443/140, 11-38=-443/140, 11-39=-443/140, 12-39=-443/140, 12-13=-511/116, 13-14=-1138/113, 14-40=-1655/0, 15-40=-1741/0, 15-41=-1811/0, 16-41=-1874/0, 16-17=-1538/0, 2-24=-1332/28, 17-18=-1255/0
 BOT CHORD 23-24=-261/284, 22-23=-261/284, 21-22=0/1171, 20-21=0/1171
 WEBS 5-22=0/905, 14-20=0/922, 7-31=-1273/68, 30-31=-1271/68, 25-30=-1271/68, 25-27=-1256/67, 26-27=-1256/67, 13-26=-1256/67, 9-29=-87/259, 12-28=-88/254, 2-33=0/1176, 32-33=0/1197, 22-32=0/1223, 20-34=0/1195, 34-35=0/1165, 17-35=0/1145, 3-33=-544/27, 23-33=-673/45, 16-35=-576/80, 19-35=-710/100

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-3-13, Interior (1) 1-3-13 to 5-4-1, Exterior(2R) 5-4-1 to 19-5-7, Interior (1) 19-5-7 to 21-9-4, Exterior(2E) 21-9-4 to 24-9-4 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 5-7, 13-14, 7-31, 30-31, 25-30, 25-27, 26-27, 13-26; Wall dead load (5.0psf) on member(s).5-22, 14-20
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 20-22

Job 21030025-A	Truss C5	Truss Type Attic Structural Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	--------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:44

Page: 2

ID: ?xDUAoH_RV5?w7M7oi7fRz8MCW-XwpkknOku?NspgU3JXCdnUyZexSK65EZYVwiCMz8Kt9

- 14) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 15) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 16) Attic room checked for L/360 deflection.

LOAD CASE(S) Standard


Job 21030025-A	Truss CJ04	Truss Type Diagonal Hip Girder	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-----------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:45

Page: 1

ID:vrFglwb8uhnkJusWhUqH75z8fwP-07N6y7PMfJVJRq3GIEkSKhVpWLS1riPin8gGkoz8Kt8



Scale = 1:35.7

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.46	Vert(LL)	0.01	4-5	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.11	Vert(CT)	-0.01	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.00	Horz(CT)	-0.01	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0										Weight: 33 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-6-12 oc purlins, except end verticals.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=40/ Mechanical, (min. 0' 1 1/2"), 4=24/ Mechanical, (min. 0' 1 1/2"), 5=448/0' 5 7/16", (min. 0' 1 1/2")
Max Horiz 5=150 (LC 12)
Max Uplift 3=-73 (LC 12), 4=-25 (LC 9), 5=-131 (LC 12)
Max Grav 3=115 (LC 19), 4=76 (LC 7), 5=558 (LC 19)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-5=502/141

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 73 lb uplift at joint 3.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at j(s) 5 and 4. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 11) "NAILED" indicates 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
- 12) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-60, 2-3=-60, 4-5=-20
Concentrated Loads (lb)
Vert: 7=46 (B), 8=3 (F=1, B=2)


Job 21030025-A	Truss CJ08	Truss Type Diagonal Hip Girder	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-----------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:45

Page: 1

ID:daRkZnKPWQT48G1EmoQa5yz8fvs-07N6y7PMFJVJRq3GtEkSKhVpBLmqrh3in8gGkoz8Kt8



Scale = 1:47.7

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.48	Vert(LL)	0.15	6-7	>680	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.51	Vert(CT)	-0.19	6-7	>552	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.09	Horz(CT)	0.00	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 80 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SPF No.2(flat)

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS T-Brace: 2x4 SPF No.2 - 2-6
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
 Brace must cover 90% of web length.

REACTIONS (lb/size) 6=504/ Mechanical, (min. 0' 1 1/2"), 7=603/0' 4 9/16", (min. 0' 1 1/2")
 Max Horiz 7=287 (LC 12)
 Max Uplift 6=-447 (LC 12), 7=-198 (LC 8)
 Max Grav 6=565 (LC 19), 7=612 (LC 19)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-7=-517/127, 2-8=-272/113, 3-6=-448/330
 BOT CHORD 7-11=-287/96, 11-12=-287/96, 6-12=-287/96
 WEBS 2-6=-98/292

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; porch left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - 7) Refer to girder(s) for truss to truss connections.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 447 lb uplift at joint 6.
 - 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7. This connection is for uplift only and does not consider lateral forces.
 - 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 11) "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - 12) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.
 - 13) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (lb/ft)
 Vert: 1-2=-60, 2-3=-60, 3-4=-60, 5-7=-20

Job 21030025-A	Truss CJ08	Truss Type Diagonal Hip Girder	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-----------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:45

Page: 2

ID:daRkZnKPWQT48G1EmoQa5yz8fvs-07N6y7PMFJVJRq3GtEkSKhVpBLmqrh3in8gGkoz8Kt8

Concentrated Loads (lb)

Vert: 10=-200 (F=-100, B=-100), 11=1 (F=1, B=1), 12=-37 (F=-19, B=-19)


Job 21030025-A	Truss D1	Truss Type Piggyback Base	Qty 3	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:46

Page: 1

ID:IMFwRB1mXYMQeaXhyYjPGz8MBL-UJwU9TP?Qcda3zeSRyFhsv1v9l6wa6fs0oPpGEz8Kl7



Scale = 1:53.6

Plate Offsets (X, Y): [4:0' 7 1/2", 0' 5 1/4"], [5:0' 7 1/2", 0' 3"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.78	Vert(LL)	0.08	8-13	>999	240	MT20 244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.45	Vert(CT)	-0.11	8-13	>999	180	
TCDL	10.0	Rep Stress Incr	YES	WB	0.19	Horz(CT)	0.04	7	n/a	n/a	
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0										Weight: 192 lb FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W2:2x4 SP No.2
 SLIDER Left 2x4 SP No.3 -- 1' 6", Right 2x4 SP No.3 -- 1' 6"

BRACING

TOP CHORD Structural wood sheathing directly applied or 3-11-15 oc purlins, except
 2-0-0 oc purlins (6-0-0 max.): 4-5.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-8

REACTIONS (lb/size) 2=1103/0' 5 1/2", (min. 0' 1 5/8"), 7=993/0' 5 1/2", (min. 0' 1 1/2")
 Max Horiz 2=247 (LC 13)
 Max Uplift 2=-111 (LC 14), 7=-76 (LC 15)
 Max Grav 2=1378 (LC 45), 7=1280 (LC 45)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-915/405, 3-19=-1353/102, 19-20=-1222/108, 4-20=-1143/154, 4-21=-778/232, 21-22=-778/232, 22-23=-778/232, 5-23=-778/232, 5-24=-1141/155, 24-25=-1217/109, 6-25=-1348/103, 6-7=-788/105
 BOT CHORD 2-26=-329/861, 10-26=-82/861, 10-27=-85/834, 27-28=-85/834, 9-28=-85/834, 8-9=-85/834, 8-29=0/803, 7-29=0/803
 WEBS 4-10=0/460, 5-8=-8/468

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-8-10 to 1-3-6, Interior (1) 1-3-6 to 5-0-6, Exterior(2R) 5-0-6 to 19-10-10, Interior (1) 19-10-10 to 21-11-0, Exterior(2E) 21-11-0 to 24-11-0 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss D2	Truss Type Piggyback Base Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:46

Page: 1

ID:RXJbYACj_L7RVZ?hcb2Ppzz8MA1-UJwU9TP?Qcda3zeSRyFhsv1wPI60azcs0oPpGEz8K17



Scale = 1:55.6

Plate Offsets (X, Y): [2:Edge,0], [6:0' 10 1/4",0' 3 3/4"], [7:0' 10 1/4",0' 3 3/4"], [10:0' 7 1/4",Edge], [10:1' 2 1/2",0' 2"], [11:0' 6 1/4",0' 2 1/2"], [12:0' 8",0' 6 1/4"], [14:0' 3 1/2",0' 6 1/4"], [15:0' 5 3/4",0' 1 1/2"]

LUMBER		BRACING	
TOP CHORD	2x6 SP No.2	TOP CHORD	Structural wood sheathing directly applied or 3-11-0 oc purlins, except
BOT CHORD	2x8 SP 2400F 2.0E	BOT CHORD	2-0-0 oc purlins (6-0-0 max.): 6-7. Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3 *Except* W3,W4:2x4 SP No.2		
SLIDER	Left 2x6 SP No.2 -- 1' 6", Right 2x6 SP No.2 -- 1' 6"		
REACTIONS (lb/size)	2=8204/0' 5 1/2", (min. 0' 3 9/16"), 10=10090/0' 5 1/2", (min. 0' 4 1/2")		
	Max Horiz 2=248 (LC 9)		
	Max Uplift 2=-1355 (LC 12), 10=-963 (LC 13)		
	Max Grav 2=8657 (LC 45), 10=10816 (LC 47)		


Job 21030025-A	Truss D3	Truss Type Piggyback Base Structural Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-----------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:47

Page: 1

ID: lbfzpiAXCdv7ljwgBPwozez8M3c-yVUsNpQdBwRg7De?fmwP6aDL9U1JZe?FS9Mohz8Kt6



Scale = 1:55.6

Plate Offsets (X, Y): [8:0' 7 1/2", 0' 5 1/4"], [12:0' 7 1/2", 0' 3"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.24	Vert(LL)	-0.05	17-36	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.33	Vert(CT)	-0.09	17-36	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horz(CT)	0.01	16	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 281 lb	FT = 20%	

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3 *Except* O1,O2:2x4 SPF No.2(flat)
SLIDER Left 2x4 SP No.3 -- 1' 6", Right 2x4 SP No.3 -- 1' 6"

REACTIONS All bearings 12' 9 1/2". except 16=0' 5 1/2", 19=0' 3 1/2"
(lb) - Max Horiz 2=248 (LC 13), 38=248 (LC 13)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 16, 19, 21, 24, 38 except
20=-221 (LC 15), 23=-114 (LC 14), 25=-186 (LC 14)
Max Grav All reactions 250 (lb) or less at joint(s) 19, 25 except 2=379 (LC 25), 16=810 (LC 49), 20=395 (LC 49), 21=326 (LC 38), 22=387 (LC 53), 23=301 (LC 47), 24=256 (LC 47), 38=379 (LC 25)

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except
2-0-0 oc purlins (6-0-0 max.): 8-12.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 8-22
WEBS T-Brace: 2x4 SPF No.2 - 21-30
Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
Brace must cover 90% of web length.
1 Brace at Jt(s): 26, 27, 28, 30

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 3-4=-258/142, 6-7=-251/196, 7-8=-253/189, 8-9=-256/117, 9-10=-256/117, 10-11=-256/117, 11-12=-256/117, 12-13=-355/116, 13-14=-466/140, 14-44=-603/118, 44-45=-640/91, 15-45=-733/90, 15-16=-474/0
BOT CHORD 19-20=-25/320, 18-19=-25/320, 17-18=-25/320, 17-46=0/448, 16-46=0/448
WEBS 22-31=-313/0, 8-30=0/339, 28-30=0/329, 27-28=0/308, 17-27=0/259, 26-33=-377/221, 14-33=-414/252, 27-32=-398/245, 26-32=-410/241, 20-29=-412/258, 27-29=-400/247, 9-30=-291/47, 21-30=-296/58

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-0-6, Exterior(2R) 5-0-6 to 19-10-10, Interior (1) 19-10-10 to 21-11-0, Exterior(2E) 21-11-0 to 24-11-0 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Job 21030025-A	Truss D3	Truss Type Piggyback Base Structural Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-----------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:47

Page: 2

ID:1bfzpiAXCdv7ljwgBPwozez8M3c-yVUsNpQdBwIRg7De?fmwP6aDL9U1JZe?FS9Mohz8Kt6

- 11) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 12) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 16, 2, 20, 21, 23, 24, 25, and 19. This connection is for uplift only and does not consider lateral forces.
- 13) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 14) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 15) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard


Job 21030025-A	Truss F1	Truss Type Piggyback Base	Qty 5	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:48

Page: 1

ID: 1eE6Vvh3804HNFIPKQCn13z8hL3-Qi2Ea9RFxEtIIHorYNH9yK7M?YIQ2_D8T6uwl7z8Kt5



Scale = 1:56.7

Plate Offsets (X, Y): [2:Edge,0], [6:0' 3 3/4",0' 3 1/4"], [7:0' 3 3/4",0' 3 1/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.38	Vert(LL)	-0.15	15-16	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.64	Vert(CT)	-0.28	13-15	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.38	Horz(CT)	-0.02	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 218 lb	FT = 20%	

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W2,W3:2x4 SP No.2
 SLIDER Left 2x6 SP No.2 -- 1' 6"

BRACING
 TOP CHORD Structural wood sheathing directly applied or 5-6-4 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-7.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 11-12.

REACTIONS (lb/size) 2=1178/0' 5 1/2", (min. 0' 1 9/16"), 11=1072/ Mechanical, (min. 0' 1 1/2")
 Max Horiz 2=254 (LC 11)
 Max Uplift 2=-13 (LC 14)
 Max Grav 2=1333 (LC 39), 11=1232 (LC 39)


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-700/60, 3-25=-1424/0, 25-26=-1402/0, 26-27=-1252/0, 4-27=-1248/0, 4-28=-1327/69, 5-28=-1206/79, 5-6=-1157/107, 6-29=-678/153, 29-30=-678/153, 30-31=-678/153, 7-31=-678/153, 7-32=-1133/112, 8-32=-1304/75, 8-33=-1197/0, 33-34=-1202/0, 9-34=-1366/0, 9-11=-1224/0
 BOT CHORD 2-16=-86/911, 15-16=0/649, 14-15=0/649, 13-14=0/649, 12-13=0/649
 WEBS 9-12=0/916, 16-17=-25/547, 6-17=-15/569, 7-18=-5/512, 12-18=-15/496, 4-16=-359/321, 8-12=-390/287

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-4-1, Exterior(2R) 5-4-1 to 19-6-15, Interior (1) 19-6-15 to 21-2-4, Exterior(2E) 21-2-4 to 24-2-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 200.0lb AC unit load placed on the bottom chord, 12-5-8 from left end, supported at two points, 5-0-0 apart.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job 21030025-A	Truss F2	Truss Type Piggyback Base Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-------------------------------------	----------	----------	------------------------------------------------------------



Scale = 1:58.4

Plate Offsets (X, Y): [2:Edge,0' 3\"/>

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.59	Vert(LL)	-0.13	14-15	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.71	Vert(CT)	-0.19	14-15	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.53	Horz(CT)	0.02	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 466 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x6 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-6.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	

REACTIONS (lb/size) 10=2436/ Mechanical, (min. 0' 1 1/2\"/>

Max Horiz 16=253 (LC 9)
Max Uplift 10=-286 (LC 13), 16=-261 (LC 12)
Max Grav 10=2601 (LC 37), 16=2467 (LC 37)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-21=-632/166, 21-22=-478/171, 3-22=-469/174, 3-4=-2767/405, 4-5=-2581/429, 5-23=-1401/294, 23-24=-1401/294, 24-25=-1401/294, 6-25=-1401/294, 6-7=-2619/434, 7-26=-2534/320, 26-27=-2582/310, 8-27=-2702/303, 2-16=-656/194, 8-10=-2355/265
BOT CHORD 15-16=-279/1848, 15-28=-167/1425, 14-28=-167/1425, 13-14=0/2125, 12-13=0/2125, 11-12=-91/1311
WEBS 7-11=-327/308, 15-17=-338/1385, 5-17=-250/1708, 6-18=-254/1375, 11-18=-354/1173, 17-20=-786/0, 19-20=-786/0, 18-19=-786/0, 3-15=-216/353, 8-11=-145/1653, 14-17=0/815, 3-16=-2316/219, 12-18=0/944

- NOTES**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x6 - 2 rows staggered at 0' 9" oc, 2x4 - 1 row at 0' 9" oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0' 7" oc.
Web connected as follows: 2x4 - 1 row at 0' 9" oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 200.0lb AC unit load placed on the bottom chord, 12-5-8 from left end, supported at two points, 5-0-0 apart.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 286 lb uplift at joint 10.

Job 21030025-A	Truss F2	Truss Type Piggyback Base Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:49

Page: 2

ID:oAj7Aen4FT48KTvx06LfMkz8hKx-uucdoVStiX?9wRN164oOUXFTUy3YnO5limeTtZz8Kt4

- 14) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 16. This connection is for uplift only and does not consider lateral forces.
- 15) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 16) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 17) Use MiTek THDH26-2 (With 22-16d nails into Girder & 8-16d nails into Truss) or equivalent spaced at 11-3-9 oc max. starting at 8-1-7 from the left end to 19-5-0 to connect truss(es) GR1 (2 ply 2x6 SP), GR3 (2 ply 2x6 SP) to front face of bottom chord.
- 18) Fill all nail holes where hanger is in contact with lumber.

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-60, 2-5=-60, 5-6=-60, 6-8=-60, 9-16=-20
Concentrated Loads (lb)
Vert: 12=-100, 14=-100, 28=-1345 (F), 29=-1154 (F)


Job 21030025-A	Truss F3	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:50

Page: 1

ID: CIPGpgqyYOSjBxeWTEvM_Nz8hKu-M4A?r:SVTr80XbxDgnJd1ChxMRgWuvRxQN1P0z8Kt3



Scale = 1:56

Plate Offsets (X, Y): [4:0' 3 3/4", 0' 3 1/4"], [5:0' 3 3/4", 0' 3 1/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	-0.13	14	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.59	Vert(CT)	-0.27	11-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.37	Horz(CT)	0.01	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 217 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W4, W5:2x4 SP No.2

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 9-10.

REACTIONS (lb/size) 9=1051/ Mechanical, (min. 0' 1 1/2"), 15=1050/ Mechanical, (min. 0' 1 1/2")
 Max Horiz 15=214 (LC 11)
 Max Grav 9=1207 (LC 38), 15=1208 (LC 38)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-21=-1355/0, 21-22=-1179/0, 2-22=-1175/0, 2-23=-1292/80, 3-23=-1171/91, 3-4=-1112/118, 4-24=-653/158, 24-25=-653/158, 25-26=-653/158, 5-26=-653/158, 5-27=-1094/118, 6-27=-1273/80, 6-28=-1161/0, 28-29=-1166/0, 7-29=-1330/0, 1-15=-1180/0, 7-9=-1190/0
 BOT CHORD 14-15=-251/244, 13-14=0/606, 12-13=0/606, 11-12=0/606, 10-11=0/606
 WEBS 6-10=-401/286, 14-17=-18/526, 4-17=-7/539, 5-18=-6/510, 10-18=-15/497, 2-14=-418/290, 7-10=0/887, 1-14=0/878

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) interior zone and C-C Exterior(2E) 0-3-4 to 3-3-4, Interior (1) 3-3-4 to 5-0-9, Exterior(2R) 5-0-9 to 19-3-7, Interior (1) 19-3-7 to 20-10-12, Exterior(2E) 20-10-12 to 23-10-12 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - 200.0lb AC unit load placed on the bottom chord, 12-5-8 from left end, supported at two points, 5-0-0 apart.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss F4	Truss Type Piggyback Base	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:50

Page: 1

ID:5Wenf1Tcdz9gYyI4zI8Dz8HkQ-M4A?rSVTr80XbxDgnJd1CeGMTsVwkRqXN1P0z8K13



Scale = 1:61.6

Plate Offsets (X, Y): [4:0' 5 1/2", 0' 3"], [5:0' 5 1/2", 0' 3"], [7:0' 2 15/16", Edge], [15:0' 4", 0' 4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.52	Vert(LL)	-0.06	11-12	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.45	Vert(CT)	-0.09	15-16	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.31	Horz(CT)	0.05	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 219 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2 *Except* B3:2x4 SP No.3, B4:2x4 SP No.2
 WEBS 2x4 SP No.3 *Except* W10,W6:2x4 SP No.2

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-5.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS 1 Row at midpt 4-15, 5-13, 2-16

REACTIONS (lb/size) 9=954/ Mechanical, (min. 0' 1 1/2"), 16=955/ Mechanical, (min. 0' 1 1/2")
 Max Horiz 16=214 (LC 10)
 Max Uplift 9=70 (LC 15), 16=65 (LC 14)
 Max Grav 9=1163 (LC 44), 16=1132 (LC 44)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-18=-342/73, 2-3=-1063/213, 3-4=-923/231, 4-20=-658/222, 20-21=-658/222, 21-22=-658/222, 5-22=-658/222, 5-6=-1134/224, 6-23=-1150/179, 23-24=-1218/172, 7-24=-1345/144, 1-16=-314/97, 7-9=-1123/97
 BOT CHORD 16-25=-145/848, 25-26=-145/848, 15-26=-145/848, 11-12=-177/17, 8-11=-46/884, 7-8=-25/903
 WEBS 4-13=-58/438, 5-11=-43/585, 12-15=-47/757, 6-11=-356/213, 2-16=-977/99

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-3-4 to 3-3-4, Interior (1) 3-3-4 to 4-9-12, Exterior(2R) 4-9-12 to 19-5-8, Interior (1) 19-5-8 to 21-1-0, Exterior(2E) 21-1-0 to 24-1-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 70 lb uplift at joint 9 and 65 lb uplift at joint 16.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss F5	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:51

Page: 1

ID:stwBkOBAmGij0vUQ0_ThY4z8MgK-qHkNCBT7E9Gt9IWPEVrsZylsmpdFLFb947axSz8Kt2



Scale = 1:64

Plate Offsets (X, Y): [2:0' 6 3/4\", 0' 1/8\"], [6:0' 5 1/2\", 0' 3\"], [7:0' 5 1/2\", 0' 3\"], [9:0' 4\", 0' 1/4\"], [17:0' 4\", 0' 4\"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	-0.06	13-14	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.48	Vert(CT)	-0.10	10-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.36	Horz(CT)	0.07	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 220 lb	FT = 20%	

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2 *Except* B3,B4:2x4 SP No.2
WEBS 2x4 SP No.3 *Except* W8:2x6 SP No.2, W4:2x4 SP No.2
SLIDER Left 2x4 SP No.3 -- 1' 6"

BRACING
TOP CHORD Structural wood sheathing directly applied or 5-11-14 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-7.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 6-17, 7-15

REACTIONS (lb/size) 2=1094/0' 5 1/2", (min. 0' 1 9/16"), 11=980/0' 3 1/2", (min. 0' 1 1/2")
Max Horiz 2=255 (LC 11)
Max Uplift 2=-111 (LC 14), 11=-72 (LC 15)
Max Grav 2=1328 (LC 45), 11=1226 (LC 45)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-732/0, 3-22=-1319/128, 22-23=-1301/132, 23-24=-1216/158, 4-24=-1152/166, 4-5=-1154/206, 5-6=-1019/224, 6-25=-730/219, 25-26=-730/219, 26-27=-730/219, 7-27=-730/219, 7-8=-1249/222, 8-28=-1265/178, 28-29=-1341/163, 9-29=-1430/141, 9-11=-1197/97
BOT CHORD 2-30=-235/963, 30-31=-137/963, 17-31=-137/963, 14-16=-271/0, 14-32=-13/795, 13-32=-13/795, 10-13=-42/979, 9-10=-28/974
WEBS 15-17=-84/265, 6-15=-59/501, 7-13=-44/682, 14-17=-48/821, 8-13=-382/217, 4-17=-316/224

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-2-3, Exterior(2R) 5-2-3 to 19-9-0, Interior (1) 19-9-0 to 21-6-13, Exterior(2E) 21-6-13 to 24-6-13 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 11. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss F6	Truss Type Piggyback Base	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:52

Page: 1

ID:Dvqn2L3yahvMG7ZSopHp?Uz8MfB-ITIIQWUJ?SOJnu5cnCM56AH1PA9s_oVkOks7Uuz8Kt1



Scale = 1:64

Plate Offsets (X, Y): [2:0' 6 3/4", 0' 1/8"], [6:0' 5 1/2", 0' 3"], [7:0' 5 1/2", 0' 3"], [9:0' 4", 0' 1/4"], [17:0' 4", 0' 4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	-0.06	13-14	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.48	Vert(CT)	-0.10	10-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.36	Horz(CT)	0.07	11	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 220 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2 *Except* B3,B4:2x4 SP No.2
 WEBS 2x4 SP No.3 *Except* W8:2x6 SP No.2, W4:2x4 SP No.2
 SLIDER Left 2x4 SP No.3 -- 1' 6"

BRACING
 TOP CHORD Structural wood sheathing directly applied or 5-11-14 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 6-7.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS 1 Row at midpt 6-17, 7-15

REACTIONS (lb/size) 2=1094/0' 5 1/2", (min. 0' 1 9/16"), 11=980/0' 3 1/2", (min. 0' 1 1/2")
 Max Horiz 2=278 (LC 13)
 Max Uplift 2=-111 (LC 14), 11=-73 (LC 15)
 Max Grav 2=1328 (LC 45), 11=1226 (LC 45)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-734/0, 3-22=-1319/129, 22-23=-1301/132, 23-24=-1216/158, 4-24=-1152/166, 4-5=-1154/207, 5-6=-1019/224, 6-25=-730/219, 25-26=-730/219, 26-27=-730/219, 7-27=-730/219, 7-8=-1249/218, 8-28=-1265/174, 28-29=-1341/158, 9-29=-1430/137, 9-11=-1197/94
 BOT CHORD 2-30=-250/970, 30-31=-145/970, 17-31=-145/970, 14-16=-271/0, 14-32=-30/803, 13-32=-30/803, 10-13=-6/979, 9-10=0/974
 WEBS 15-17=-84/265, 6-15=-59/501, 7-13=-48/676, 14-17=-63/828, 8-13=-381/217, 4-17=-316/224

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-2-3, Exterior(2R) 5-2-3 to 19-9-0, Interior (1) 19-9-0 to 21-6-13, Exterior(2E) 21-6-13 to 24-6-13 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 11. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss F7	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:53

Page: 1

ID:2tnK0rIj9C5HctQPcHoApVz8MeI-nfr7dsV0mmWaP2goLwtKfNq94ZStjF_udOch0Kz8Kt0



Scale = 1:64.5

Plate Offsets (X, Y): [2:0' 6 3/4\", 0' 1/8\"], [6:0' 5 1/2\", 0' 3\"], [7:0' 5 1/2\", 0' 3\"], [9:0' 8 1/2\", 0' 3 1/4\"], [10:Edge, 0' 6\"], [17:0' 4\", 0' 4\"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	-0.11	12-13	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.69	Vert(CT)	-0.21	12-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.35	Horz(CT)	0.07	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 222 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2 *Except* B3,B4:2x4 SP No.2
 WEBS 2x4 SP No.3 *Except* W4:2x4 SP No.2
 SLIDER Left 2x4 SP No.3 -- 1' 6", Right 2x6 SP No.2 -- 1' 1 7/16"

REACTIONS (lb/size) 2=1110/0' 5 1/2", (min. 0' 1 9/16"), 10=993/0' 5 1/2", (min. 0' 1 1/2")
 Max Horiz 2=256 (LC 13)
 Max Uplift 2=-112 (LC 14), 10=-74 (LC 15)
 Max Grav 2=1347 (LC 45), 10=1234 (LC 45)

BRACING

TOP CHORD Structural wood sheathing directly applied or 4-8-11 oc purlins, except
 2-0-0 oc purlins (6-0-0 max.): 6-7.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
 6-0-0 oc bracing: 14-16.
 10-0-0 oc bracing: 12-13
 WEBS 1 Row at midpt 6-17, 7-15

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-748/0, 3-26=-1341/130, 26-27=-1323/133, 27-28=-1237/159, 4-28=-1175/167, 4-5=-1176/208, 5-6=-1041/225,
 6-29=-746/220, 29-30=-746/220, 30-31=-746/220, 7-31=-746/220, 7-8=-1326/227, 8-32=-1333/181, 32-33=-1401/167,
 33-34=-1421/162, 9-34=-1506/159, 9-10=-13/577
 BOT CHORD 2-35=-235/980, 35-36=-131/980, 17-36=-131/980, 14-16=-262/0, 14-37=-10/838, 13-37=-10/838, 12-13=-36/1049,
 9-12=-19/976, 11-12=-51/383, 10-11=-63/359
 WEBS 6-15=-60/512, 7-13=-49/792, 14-17=-47/844, 8-13=-422/218, 4-17=-315/224, 9-11=-389/68

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-2-3, Exterior(2R) 5-2-3 to 19-9-0, Interior (1) 19-9-0 to 21-11-0, Exterior(2E) 21-11-0 to 24-11-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 10 and 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job 21030025-A	Truss F7	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:53

Page: 2

ID:2tnK0rlj9C5HctQPeHoApVz8Mel-nfr7dsVOmmWaP2goLwtKfNq94ZStjF_udOch0Kz8Kt0

LOAD CASE(S) Standard


Job 21030025-A	Truss F8	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:53

Page: 1

ID:gimdqwrnx7XlhPNuV_4Tdz8Mp1-nfr7dsV0mmWaP2goLwtKfNq94ZSsJF_udOch0Kz8Kt0



Scale = 1:64.5

Plate Offsets (X, Y): [2:0' 6 3/4", 0' 1/8"], [6:0' 5 1/2", 0' 3"], [7:0' 5 1/2", 0' 3"], [9:0' 8 1/2", 0' 3 1/4"], [10:Edge, 0' 6"], [17:0' 4", 0' 4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	-0.11	12-13	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.69	Vert(CT)	-0.21	12-13	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.35	Horz(CT)	0.07	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 222 lb	FT = 20%	

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2 *Except* B3,B4:2x4 SP No.2
WEBS 2x4 SP No.3 *Except* W4:2x4 SP No.2
SLIDER Left 2x4 SP No.3 -- 1' 6", Right 2x6 SP No.2 -- 1' 1 7/16"

REACTIONS (lb/size) 2=1110/0' 5 1/2", (min. 0' 1 9/16"), 10=993/0' 5 1/2", (min. 0' 1 1/2")
Max Horiz 2=256 (LC 11)
Max Uplift 2=-112 (LC 14), 10=-74 (LC 15)
Max Grav 2=1347 (LC 45), 10=1234 (LC 45)

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-8-11 oc purlins, except
2-0-0 oc purlins (6-0-0 max.): 6-7.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
6-0-0 oc bracing: 14-16.
10-0-0 oc bracing: 12-13
WEBS 1 Row at midpt 6-17, 7-15

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-748/0, 3-26=-1341/130, 26-27=-1323/133, 27-28=-1237/159, 4-28=-1175/167, 4-5=-1176/208, 5-6=-1041/225, 6-29=-746/220, 29-30=-746/220, 30-31=-746/220, 7-31=-746/220, 7-8=-1326/227, 8-32=-1333/181, 32-33=-1401/167, 33-34=-1421/162, 9-34=-1506/159, 9-10=-13/576
BOT CHORD 2-35=-235/980, 35-36=-131/980, 17-36=-131/980, 14-16=-262/0, 14-37=-10/838, 13-37=-10/838, 12-13=-36/1049, 9-12=-19/976, 11-12=-51/383, 10-11=-63/359
WEBS 6-15=-60/512, 7-13=-49/792, 14-17=-47/844, 4-17=-315/224, 8-13=-422/218, 9-11=-389/68

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-2-3, Exterior(2R) 5-2-3 to 19-9-0, Interior (1) 19-9-0 to 21-11-0, Exterior(2E) 21-11-0 to 24-11-0 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 10 and 2. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job 21030025-A	Truss F8	Truss Type Piggyback Base	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:53

Page: 2

ID:gimdqwRnx7XhIPNuV_4Tdz8Mp1-nfr7dsVOmmWaP2goLwtKfNq94ZSsjF_udOch0Kz8Kt0

LOAD CASE(S) Standard


Job 21030025-A	Truss F9	Truss Type Piggyback Base Structural Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-----------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:54

Page: 1

ID:RA029Y6TWJ_zLS6eMzG8Xvz8MZz-FrPWrcW0X4eR0CF_vdOZBbNO4zu7SgG1s2LEyZ8Kt?



Scale = 1:69.2

Plate Offsets (X, Y): [10:0' 5 1/2",0' 3"], [14:0' 5 1/2",0' 3"], [19:0' 8 1/2",0' 2 1/2"], [20:Edge,0' 6"], [26:0' 4",0' 2 1/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	-0.06	23-24	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.30	Vert(CT)	-0.13	23-24	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.47	Horz(CT)	0.01	20	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 302 lb	FT = 20%	

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2 *Except* B3,B4:2x4 SP No.2
 WEBS 2x4 SP No.3 *Except* W4:2x4 SP No.2
 OTHERS 2x4 SP No.3 *Except* O1:2x4 SPF No.2(flat)
 SLIDER Left 2x4 SP No.3 -- 1' 6", Right 2x6 SP No.2 -- 1' 1 7/16"

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except
 2-0-0 oc purlins (10-0-0 max.): 10-14.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS 1 Row at midpt 10-28
 JOINTS 1 Brace at Jt(s): 33, 34, 35, 39, 40, 41

REACTIONS All bearings 9' 10 1/2". except 20=0' 5 1/2", 28=0' 3 1/2"
 (lb) - Max Horiz 2=270 (LC 13), 42=270 (LC 13)
 Max Uplift All uplift 100 (lb) or less at joint(s) 30, 31 except 2=-117 (LC 10), 20=-145 (LC 15), 29=-104 (LC 15), 32=-161 (LC 14), 42=-117 (LC 10)
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 30, 31, 42 except 20=711 (LC 39), 28=1092 (LC 22), 29=253 (LC 39), 32=268 (LC 47)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 4-50=-118/283, 5-6=0/253, 6-7=0/311, 7-8=0/305, 8-9=0/374, 9-10=0/340, 15-16=-276/190, 16-17=-261/183, 17-18=-388/175, 18-54=-405/156, 54-55=-490/142, 55-56=-568/133, 19-56=-597/121, 19-20=-23/313
 BOT CHORD 25-26=-13/354, 23-24=0/388, 19-23=0/361
 WEBS 26-28=-955/0, 10-26=-309/48, 24-33=-9/417, 14-33=-15/410, 26-39=-813/29, 34-39=-566/0, 34-37=-581/0, 14-37=-512/0, 25-28=-273/229, 18-24=-315/175

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 5-2-3, Exterior(2R) 5-2-3 to 19-9-0, Interior (1) 19-9-0 to 23-8-14, Exterior(2E) 23-8-14 to 26-8-14 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

Job 21030025-A	Truss F9	Truss Type Piggyback Base Structural Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-----------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:54

Page: 2

ID:RA029Y6TwJ_zLS6eMzG8Xvz8MZz-FrPWrcW0X4eR0CF_vdOZBbNO4zu7SgG1s2LEYnz8Kt?

- 12) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 20, 29, 30, 31, and 32. This connection is for uplift only and does not consider lateral forces.
- 13) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 14) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 15) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard


Job 21030025-A	Truss G1	Truss Type Piggyback Base	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:55

Page: 1

ID:pl1MImpvjelz7Ok74IClez8MXm-j2zu2YWeiNmleMqBTLvokovRQNBsB9uA4i5o4Dz8Kt_



Scale = 1:51.9

Plate Offsets (X, Y): [2:0' 3 1/2", 0' 1 1/2"], [3:0' 2 1/8", Edge], [5:0' 2 1/8", Edge], [6:0' 3 1/4", 0' 1"], [8:0' 5", 0' 4 1/2"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.81	Vert(LL)	-0.07	8-9	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.40	Vert(CT)	-0.15	8-9	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.38	Horz(CT)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 167 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.2 *Except* W4,W3:2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-11-12 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-5. Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 7=796/0' 5 1/2", (min. 0' 1 1/2"), 9=926/0' 5 1/2", (min. 0' 1 1/2")
 Max Horiz 9=226 (LC 11)
 Max Uplift 7=-86 (LC 11), 9=-89 (LC 11)
 Max Grav 7=986 (LC 39), 9=1106 (LC 39)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-10=-960/295, 10-11=-815/301, 11-12=-710/312, 3-12=-539/346, 3-4=-499/347, 4-5=-499/347, 5-13=-538/345, 13-14=-710/310, 14-15=-813/299, 6-15=-937/293, 2-9=-1015/325, 6-7=-902/299
 BOT CHORD 9-16=-346/411, 16-17=-346/411, 8-17=-346/411
 WEBS 2-8=-203/418, 6-8=-175/415, 4-8=-206/382

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 4-2-1, Exterior(2R) 4-2-1 to 16-7-15, Interior (1) 16-7-15 to 17-2-4, Exterior(2E) 17-2-4 to 20-2-4 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9 and 7. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss G2	Truss Type Hip	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	-------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:56

Page: 1

ID: IrEsoAssS3bm4KyG98rENz8MWQ-BEXGGuXG3hu9GWPN02Q1G0ScnX5wCkMJqLcfz8Ksz



Scale = 1:51.2

Plate Offsets (X, Y): [2:0' 3 1/2", 0' 1 1/2"], [3:0' 3 1/8", 0' 2"], [5:0' 3 1/8", 0' 2"], [6:0' 3 1/4", 0' 1"], [8:0' 5", 0' 4 1/2"]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.81	Vert(LL)	-0.07	8-9	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.40	Vert(CT)	-0.15	8-9	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.38	Horz(CT)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 166 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.2 *Except* W3,W4:2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-11-12 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-5.
 Rigid ceiling directly applied or 10-0-0 oc bracing.
 MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS

(lb/size) 7=796/0' 5 1/2", (min. 0' 1 1/2"), 9=926/0' 5 1/4", (min. 0' 1 1/2")
 Max Horiz 9=222 (LC 11)
 Max Uplift 7=-84 (LC 11), 9=-91 (LC 11)
 Max Grav 7=986 (LC 39), 9=1106 (LC 39)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-10=-963/296, 10-11=-820/302, 11-12=-715/313, 3-12=-545/347, 3-4=-508/348, 4-5=-508/348, 5-13=-544/346,
 13-14=-715/312, 14-15=-817/301, 6-15=-939/295, 2-9=-1015/325, 6-7=-902/299
 BOT CHORD 9-16=-338/405, 16-17=-338/405, 8-17=-338/405
 WEBS 4-8=-203/380, 6-8=-173/424, 2-8=-201/417

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 4-2-1, Exterior(2R) 4-2-1 to 16-7-15, Interior (1) 16-7-15 to 17-2-4, Exterior(2E) 17-2-4 to 20-2-4 zone; porch left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 7 and 9. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss G3	Truss Type Hip Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	--------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:56

Page: 1

ID: BV9McELOVr4JKEsvsTYDjjz8MUV-BEXGGuXG3hu9GWPNO2Q1G0ScDnZdwc6KJMqLcfz8Ksz



Scale = 1:47.5

Plate Offsets (X, Y): [4:0' 5 3/8", 0' 3"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.81	Vert(LL)	0.05	7-9	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.30	Vert(CT)	-0.06	7-9	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.32	Horz(CT)	0.01	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 355 lb	FT = 20%	

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W4:2x4 SP No.2

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-4.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 6=2044/0' 3 1/2", (min. 0' 1 1/2"), 10=2167/0' 5 1/4", (min. 0' 1 1/2")
 Max Horiz 10=231 (LC 9)
 Max Uplift 6=-1090 (LC 13), 10=-1122 (LC 12)
 Max Grav 6=2281 (LC 47), 10=2383 (LC 45)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-11=-2411/1239, 3-11=-2240/1287, 3-12=-1646/1026, 12-13=-1646/1026, 13-14=-1646/1026, 14-15=-1646/1026, 15-16=-1646/1026, 4-16=-1646/1026, 4-17=-2262/1284, 5-17=-2425/1239, 2-10=-2297/1164, 5-6=-2195/1129
 BOT CHORD 9-10=-234/252, 9-18=-904/1666, 18-19=-904/1666, 8-19=-904/1666, 8-20=-904/1666, 7-20=-904/1666
 WEBS 2-9=-943/1686, 5-7=-948/1654, 3-9=-379/647, 4-7=-337/639

- NOTES**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x6 - 2 rows staggered at 0' 9" oc, 2x4 - 1 row at 0' 9" oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0' 9" oc.
 Web connected as follows: 2x4 - 1 row at 0' 9" oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One LUGT2 MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 10 and 6. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

Job 21030025-A	Truss G3	Truss Type Hip Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	--------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:56

Page: 2

ID: BV9McEL0Vr4JKEsvsTYDjjz8MUV-BEXGGuXG3hu9GWPNO2Q1G0ScDnZdwc6KJMqLcfz8Ksz

- 14) Use MiTek HJC26 (With 16-16d nails into Girder & 10d nails into Truss) or equivalent spaced at 7-11-4 oc max. starting at 6-5-6 from the left end to 14-4-10 to connect truss (es) J06A (1 ply 2x6 SP), CJ08 (1 ply 2x6 SP), J06A (1 ply 2x6 SP), CJ08 (1 ply 2x6 SP) to front face of bottom chord.
- 15) Fill all nail holes where hanger is in contact with lumber.
- 16) "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.
- 17) Minimum of a double stud required directly beneath this truss to attach LUGT2 tiedown.
- 18) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 251 lb down and 177 lb up at 6-5-0, 272 lb down and 177 lb up at 8-5-12, 272 lb down and 172 lb up at 10-5-0, and 272 lb down and 177 lb up at 12-4-4, and 251 lb down and 177 lb up at 14-5-0 on top chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (lb/ft)

Vert: 1-2=-60, 2-3=-60, 3-4=-60, 4-5=-60, 6-10=-20

Concentrated Loads (lb)

Vert: 3=-218 (F), 4=-218 (F), 9=-594 (F), 7=-594 (F), 12=-218 (F), 14=-218 (F), 16=-218 (F), 18=-58 (F), 19=-58 (F), 20=-58 (F)


Job 21030025-A	Truss GR1	Truss Type Roof Special Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-----------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:57

Page: 1

ID:7ezKZgxaYYqvFOtIQPEpW?z8NNq-fQ5eTEYuq?00tg_ZamxGpD?nbBqff82TY0au86z8Ksy



Scale = 1:49

Loading	(psf)	Spacing	1' 11 1/4"	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.77	Vert(LL)	-0.07	6-7	>989	240
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.63	Vert(CT)	-0.11	6-7	>669	180
TCDL	10.0	Rep Stress Incr	NO	WB	0.02	Horz(CT)	0.05	6	n/a	n/a
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH						
BCDL	10.0									
										Weight: 149 lb FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2 *Except* B3:2x4 SP No.3
 WEBS 2x4 SP No.3
 OTHERS 2x4 SPF No.2(flat)

BRACING

TOP CHORD 2-0-0 oc purlins (6-0-0 max.): 1-4, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 2-10

REACTIONS (lb/size) 6=1364/ Mechanical, (min. 0' 1 1/2"), 10=1947/ Mechanical, (min. 0' 1 1/2")
 Max Uplift 6=-274 (LC 9), 10=-434 (LC 8)
 Max Grav 6=1395 (LC 21), 10=1988 (LC 22)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 8-10=-1494/238, 2-8=-1075/87, 3-6=-766/82
 BOT CHORD 10-15=-71/257, 9-15=-71/257

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0' 9" oc, 2x6 - 2 rows staggered at 0' 9" oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0' 9" oc, 2x4 - 1 row at 0' 9" oc.
 Web connected as follows: 2x4 - 1 row at 0' 9" oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 434 lb uplift at joint 10 and 274 lb uplift at joint 6.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Use MiTek JUS26 (With 4-10d nails into Girder & 4-10d nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 0-7-12 from the left end to 4-7-12 to connect truss(es) J07A (1 ply 2x6 SP), J07 (1 ply 2x6 SP) to back face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 522 lb down and 18 lb up at 0-7-12, and 517 lb down and 16 lb up at 2-7-12, and 517 lb down and 16 lb up at 4-7-12 on top chord. The design/selection of such connection device(s) is the responsibility of others.
- Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

Job 21030025-A	Truss GR1	Truss Type Roof Special Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-----------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:57

Page: 2

ID:7ezKZgxaYYqvFOlQPEpW?z8NNq-fQ5eTEYuq?00tg_ZamxGpD?nbBqff82TY0au86z8Ksy

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-58, 2-3=-58, 3-4=-58, 9-10=-19, 5-7=-19
Concentrated Loads (lb)
Vert: 12=-500, 13=-489, 14=-489, 15=-432 (B), 17=-449 (B), 19=-449 (B)


Job 21030025-A	Truss GR2	Truss Type Flat Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	---------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:58

Page: 1

ID: YBxy9hFcVcii8FcPaxEAn0z8e5l-7df0gaZWbl8tVpZm8TTVLRX3?a8QOYkdmgJSgYz8Kxs



Scale = 1:44.8

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.34	Vert(LL)	0.13	7-8	>673	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.73	Vert(CT)	-0.16	7-8	>539	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.25	Horz(CT)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
											Weight: 151 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD 2-0-0 oc purlins: 1-5, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 7=2644/ Mechanical, (min. 0' 1 1/2"), 8=2848/ Mechanical, (min. 0' 1 1/2")
 Max Uplift 7=-597 (LC 9), 8=-497 (LC 8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-8=-1346/80, 4-7=-985/71
 BOT CHORD 8-15=-38/471, 15-16=-38/471, 16-17=-38/471, 17-18=-38/471, 7-18=-38/471
 WEBS 3-8=-1020/82, 3-7=-1020/82

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0' 9" oc, 2x6 - 2 rows staggered at 0' 9" oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0' 9" oc.
 Web connected as follows: 2x4 - 1 row at 0' 9" oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 497 lb uplift at joint 8 and 597 lb uplift at joint 7.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Use MiTek JUS26 (With 4-10d nails into Girder & 4-10d nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-2-8 from the left end to 7-2-8 to connect truss(es) J05D (1 ply 2x6 SP) to front face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 769 lb down and 35 lb up at 0-0-0, 754 lb down and 29 lb up at 1-2-8, 754 lb down and 29 lb up at 3-2-8, and 754 lb down and 29 lb up at 5-2-8, and 769 lb down and 36 lb up at 7-7-0 on top chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

Job 21030025-A	Truss GR2	Truss Type Flat Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	---------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:58

Page: 2

ID:YBxy9hFcVcii8FcPaxEAn0z8e5l-7df0gaZWbl8tVpZm8TTVLRX3?a8QOYkdmgJSgYz8Ksx

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (lb/ft)
 Vert: 1-2=-60, 2-4=-60, 4-5=-60, 6-9=-20
 Concentrated Loads (lb)
 Vert: 2=-754, 4=-754, 7=-304 (F), 10=-726, 12=-726, 13=-726, 15=-298 (F), 17=-298 (F), 18=-298 (F)


Job 21030025-A	Truss GR3	Truss Type Roof Special Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-----------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:58

Page: 1

ID:FEMyZNwNTR1PtrZKgwBpl4z8NMZ-7df0gaZWb18tVpZm8TTVLRXzkaEBOBndmgJSgYz8Ksx



Scale = 1:43.5

Loading	(psf)	Spacing	1' 11 1/4"	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.75	Vert(LL)	0.04	6-7	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.36	Vert(CT)	-0.06	6-7	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.02	Horz(CT)	0.02	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 135 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2 *Except* B3:2x4 SP No.3
 WEBS 2x4 SP No.3

BRACING

TOP CHORD 2-0-0 oc purlins (6-0-0 max.): 1-4, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 6=1174/ Mechanical, (min. 0' 1 1/2"), 10=1678/ Mechanical, (min. 0' 1 1/2")
 Max Uplift 6=-275 (LC 9), 10=-434 (LC 8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 8-10=-1346/243, 2-8=-1064/98, 3-6=-758/90

NOTES

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0' 9" oc, 2x6 - 2 rows staggered at 0' 9" oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0' 9" oc, 2x4 - 1 row at 0' 9" oc.
 Web connected as follows: 2x4 - 1 row at 0' 9" oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 434 lb uplift at joint 10 and 275 lb uplift at joint 6.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- Use MiTek JUS26 (With 4-10d nails into Girder & 4-10d nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 0-7-12 from the left end to 4-7-12 to connect truss(es) J04C (1 ply 2x6 SP), J04A (1 ply 2x6 SP) to front face of bottom chord.
- Fill all nail holes where hanger is in contact with lumber.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 515 lb down and 25 lb up at 0-7-12, and 510 lb down and 23 lb up at 2-7-12, and 510 lb down and 23 lb up at 4-7-12 on top chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
 Uniform Loads (lb/ft)
 Vert: 1-2=-58, 2-3=-58, 3-4=-58, 9-10=-19, 5-7=-19

Job 21030025-A	Truss GR3	Truss Type Roof Special Girder	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-----------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:58

Page: 2

ID:FEMyZNwNTR1PtrZKgwBpl4z8NMZ-7df0gaZWbl8tVpZm8TTVLRXzkaEBObNdmgJSgYz8Ksx

Concentrated Loads (lb)

Vert: 12=-493, 13=-483, 14=-483, 15=-304 (F), 17=-293 (F), 18=-293 (F)


Job 21030025-A	Truss H1	Truss Type Common Supported Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	--------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:59

Page: 1

ID: 1keL8XEQ3bPpCcW7C0tZjKz8MTL-bpDPuwZ8McGk7z8yiA_kue4Hq_ff70Bm?K3?C_z8Ksw



Scale = 1:43.2

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.17	Horz(CT)	0.00	12	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 154 lb	FT = 20%	

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 OTHERS 2x4 SP No.3 *Except* O1:2x4 SPF No.2(flat)
 SLIDER Left 2x4 SP No.3 -- 1' 6", Right 2x4 SP No.3 -- 1' 6"

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
 WEBS T-Brace: 2x4 SPF No.2 - 7-17
 Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
 Brace must cover 90% of web length.

REACTIONS All bearings 15' 6".
 (lb) - Max Horiz 2=-225 (LC 12), 21=-225 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 12, 15, 16, 18, 19, 21, 25 except 14=-150 (LC 15), 20=-161 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 14, 15, 17, 19, 20 except 2=270 (LC 25), 12=260 (LC 22), 16=269 (LC 22), 18=269 (LC 21), 21=270 (LC 25), 25=260 (LC 22)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 BOT CHORD 2-20=-93/288, 19-20=-93/289, 18-19=-93/289, 17-18=-93/290, 16-17=-93/290, 15-16=-93/289, 14-15=-92/289, 12-14=-92/288

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Corner(3E) -1-9-14 to 1-2-2, Exterior(2N) 1-2-2 to 4-9-0, Corner(3R) 4-9-0 to 10-9-0, Exterior(2N) 10-9-0 to 14-3-14, Corner(3E) 14-3-14 to 17-3-14 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 12, 18, 19, 20, 16, 15, and 14. This connection is for uplift only and does not consider lateral forces.
 - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 12.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard


Job 21030025-A	Truss J01	Truss Type Jack-Open	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:59

Page: 1

ID:JNxOoF0XmrNngRs8Nybxdz8g3l-bpDPuwZ8McGk7z8yiA_kue4Bt_f772tm?K3?C_z8Ksw



Scale = 1:32.1

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.53	Vert(LL)	0.00	4-5	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	0.00	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0										Weight: 15 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 1-2-6 oc purlins, except end verticals.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=-67/ Mechanical, (min. 0' 1 1/2"), 4=-3/ Mechanical, (min. 0' 1 1/2"), 5=271/0' 3", (min. 0' 1 1/2")
 Max Horiz 5=100 (LC 14)
 Max Uplift 3=-111 (LC 21), 4=-26 (LC 14), 5=-39 (LC 14)
 Max Grav 3=19 (LC 18), 4=16 (LC 7), 5=442 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-5=-409/378

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 111 lb uplift at joint 3.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4 and 5. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J02	Truss Type Jack-Open	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:59

Page: 1

ID:BhEmmFUNpX9OEHIScWGr9cz8g2i-bpDPuwZ8McGk7z8yiA_kue4HO_fX72tm?K3?C_z8Ksw



Scale = 1:25.8

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.18	Vert(LL)	0.00	4-7	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	0.00	4-7	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 20 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 2-9-13 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=258/0' 3", (min. 0' 1 1/2"), 3=54/ Mechanical, (min. 0' 1 1/2"),
4=19/ Mechanical, (min. 0' 1 1/2")

Max Horiz 2=106 (LC 14)
Max Uplift 2=-49 (LC 14), 3=-34 (LC 14), 4=-9 (LC 11)
Max Grav 2=411 (LC 21), 3=87 (LC 21), 4=44 (LC 7)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 34 lb uplift at joint 3.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4 and 2. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J02A	Truss Type Jack-Open	Qty 4	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:06:59

Page: 1

ID:CEHcvtuiozSZJWM_b3tqYmz8g2A-bpDPuwZ8McGk7z8yiA_kue465_dp72tm?K3?C_z8Ksw



Scale = 1:24.2

Plate Offsets (X, Y): [2:0' 3\", 0' 1 3/4\"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.83	Vert(LL)	0.00	4-5	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.17	Vert(CT)	0.00	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.03	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 22 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 2-3-15 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=14/ Mechanical, (min. 0' 1 1/2\"), 4=16/ Mechanical, (min. 0' 1 1/2\"), 5=258/0' 3 1/2\", (min. 0' 1 1/2\")
Max Horiz 5=140 (LC 14)
Max Uplift 3=-73 (LC 14), 4=-38 (LC 14)
Max Grav 3=45 (LC 21), 4=40 (LC 7), 5=385 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-5=-358/161

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 73 lb uplift at joint 3.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J04	Truss Type Jack-Open	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:00

Page: 1

ID: oBfkPTG8VVL9XGDxw4x5Jz8g1h-4?nn5Gan7wObk7i8FuVzRsdRaOzxsV6wE_oZIQz8Ksv



Scale = 1:28.8

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.21	Vert(LL)	0.02	4-7	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.15	Vert(CT)	-0.02	4-7	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 31 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-11-3 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=327/0' 3", (min. 0' 1 1/2"), 3=118/ Mechanical, (min. 0' 1 1/2")
1/2"), 4=56/ Mechanical, (min. 0' 1 1/2")
Max Horiz 2=123 (LC 18)
Max Uplift 2=-21 (LC 11), 3=-73 (LC 14), 4=-18 (LC 11)
Max Grav 2=426 (LC 21), 3=200 (LC 21), 4=88 (LC 7)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 73 lb uplift at joint 3.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4 and 2. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J04A	Truss Type Jack-Closed	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	---------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:00

Page: 1

ID:v8yBmSXvC0R7JFpv3BTk?Jz8hLG-4?nn5Gan7wObk7i8FuVzRsdQc0_nsUrwE_oZlQz8Ksv



Scale = 1:35.2

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.27	Vert(LL)	-0.01	5-6	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.09	Vert(CT)	-0.01	5-6	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horz(CT)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 45 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-4-8 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 5=197/ Mechanical, (min. 0' 1 1/2"), 6=180/ Mechanical, (min. 0' 1 1/2")

Max Horiz 6=169 (LC 14)

Max Uplift 5=-174 (LC 14)

Max Grav 5=312 (LC 20), 6=244 (LC 20)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-5=-263/231

BOT CHORD 5-6=-260/107

WEBS 1-5=-113/274

NOTES

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 174 lb uplift at joint 5.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


Job 21030025-A	Truss J04B	Truss Type Jack-Open	Qty 4	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:00

Page: 1

ID:Wj6pYofHQrrqyW29kV3SZz8g?u-4?nn5Gan7wObk7i8FuVzRsdQdOx7sV6wE_oZlQz8Ksv



Scale = 1:29.6

Plate Offsets (X, Y): [2:0' 2", 0' 2"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.27	Vert(LL)	0.02	4-5	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.26	Vert(CT)	0.02	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.05	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 35 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x6 SP No.2

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 4-3-15 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=93/ Mechanical, (min. 0' 1 1/2"), 4=37/ Mechanical, (min. 0' 1 1/2")
 1/2"), 5=316/0' 3 1/2", (min. 0' 1 1/2")
 Max Horiz 5=212 (LC 14)
 Max Uplift 3=-133 (LC 14), 4=-39 (LC 11)
 Max Grav 3=185 (LC 21), 4=75 (LC 7), 5=417 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-5=-383/99

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 133 lb uplift at joint 3.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J04C	Truss Type Jack-Closed	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	---------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:00

Page: 1

ID:v8yBmSXvC0R7JFpv3BTK?Jz8hLG-4?nn5Gan7wObk7i8FuVzRsdQIO_hsUwwE_oZlQz8Ksv



Scale = 1:44.7

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.27	Vert(LL)	-0.01	4-5	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	-0.01	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0											
											Weight: 50 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W4:2x6 SP No.2

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-2-8 oc purlins, except end verticals.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=170/0' 3 1/2", (min. 0' 1 1/2"), 5=201/ Mechanical, (min. 0' 1 1/2")
 Max Horiz 5=-167 (LC 15)
 Max Uplift 5=-208 (LC 15)
 Max Grav 4=231 (LC 21), 5=317 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-5=-260/147

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 208 lb uplift at joint 5.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J05A	Truss Type Jack-Open	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:01

Page: 1

ID:B1yvhp1DG2X1L3Vjeu01Puz8fyq-YCK9JbbPuDWSMHHKpb0Cz39X3olebxM3TeY6Htz8Ksu



Scale = 1:34.4

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.55	Vert(LL)	0.04	4-5	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.25	Vert(CT)	0.03	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.03	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0										Weight: 37 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-3-5 oc purlins, except end verticals.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=127/ Mechanical, (min. 0' 1 1/2"), 4=53/ Mechanical, (min. 0' 1 1/2"), 5=344/0' 3", (min. 0' 1 1/2")
 Max Horiz 5=248 (LC 14)
 Max Uplift 3=-147 (LC 14), 4=-29 (LC 11)
 Max Grav 3=238 (LC 21), 4=97 (LC 7), 5=414 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-5=-373/111

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; porch left exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 147 lb uplift at jt(s) 3.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J05B	Truss Type Jack-Open Girder	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	--------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:01

Page: 1

ID:9wwwCU3j6lZdObl2aCEWJxwz8fvL-YCK9JbbPuDWSMHkpb0Cz39Zl0l2bxM3TeY6Htz8Ksu



Scale = 1:39.9

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	0.02	5-6	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.22	Vert(CT)	-0.03	5-6	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.00	Horz(CT)	0.07	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 35 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 5-3-5 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-4.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=240/ Mechanical, (min. 0' 1 1/2"), 5=97/ Mechanical, (min. 0' 1 1/2"), 6=453/0' 3", (min. 0' 1 1/2")
Max Horiz 6=150 (LC 12)
Max Uplift 4=-116 (LC 9), 5=-44 (LC 9), 6=-115 (LC 12)
Max Grav 4=287 (LC 33), 5=139 (LC 7), 6=607 (LC 34)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-6=537/133

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone; porch left exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate at joint(s) 6.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 116 lb uplift at joint 4.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6 and 5. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
 - "NAILED" indicates 3-10d (0.148"x3") or 2-12d (0.148"x3.25") toe-nails per NDS guidelines.
 - In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
Uniform Loads (lb/ft)
Vert: 1-2=-60, 2-3=-60, 3-4=-60, 5-6=-20
Concentrated Loads (lb)
Vert: 3=-65 (F), 9=-140 (F), 10=-9 (F), 11=-54 (F)


Job 21030025-A	Truss J05C	Truss Type Jack-Open	Qty 14	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	-----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:01

Page: 1

ID:hYy6_9KTzxwb0tB7kP2zTz8fuZ-YCK9JbbPuDWSMHHKpb0Cz39VUoJYbxM3TeY6Htz8Ksu



Scale = 1:30.6

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.65	Vert(LL)	0.02	4-5	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.19	Vert(CT)	-0.02	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.02	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0											
											Weight: 37 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-3-5 oc purlins, except end verticals.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 3=127/ Mechanical, (min. 0' 1 1/2"), 4=53/ Mechanical, (min. 0' 1 1/2"), 5=344/0' 5 1/2", (min. 0' 1 1/2")
 Max Horiz 5=248 (LC 14)
 Max Uplift 3=-147 (LC 14)
 Max Grav 3=238 (LC 21), 4=97 (LC 7), 5=414 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-5=-373/122

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Refer to girder(s) for truss to truss connections.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 147 lb uplift at jt(s) 3.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J05D	Truss Type Jack-Closed	Qty 4	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	---------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:01

Page: 1

ID:t67CwTaz8qmY7Hlm9QvDb2z8hCA-YCK9JbbPuDWSMHHKpb0Cz39bAoKxbw63TeY6Htz8Ksu



Scale = 1:42.2

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.29	Vert(LL)	-0.01	4-5	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	-0.01	4-5	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horz(CT)	n/a	-	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 49 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-2-8 oc purlins, except end verticals.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=178/0' 3 1/2", (min. 0' 1 1/2"), 5=201/ Mechanical, (min. 0' 1 1/2")

Max Horiz 5=-172 (LC 15)
 Max Uplift 5=-211 (LC 15)
 Max Grav 4=242 (LC 21), 5=318 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-5=-268/151

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 6) Refer to girder(s) for truss to truss connections.
- 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 211 lb uplift at joint 5.
- 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J05E	Truss Type Jack-Open	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:02

Page: 1

ID:HnrF2avaggzUMOYPxpGlvaz8ftp-0OuXWxc1eXeJ_RsXNJXRWHikCCfqKOCChIHfpJz8Kst



Scale = 1:38.5

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.39	Vert(LL)	0.02	5-6	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.12	Vert(CT)	-0.02	5-6	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.05	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0										Weight: 36 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-3-5 oc purlins, except end verticals, and 2-0-0 oc purlins: 3-4.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 4=127/ Mechanical, (min. 0' 1 1/2"), 5=52/ Mechanical, (min. 0' 1 1/2"), 6=344/0' 3", (min. 0' 1 1/2")
 Max Horiz 6=199 (LC 14)
 Max Uplift 4=-85 (LC 14), 5=-26 (LC 11), 6=-6 (LC 11)
 Max Grav 4=143 (LC 35), 5=97 (LC 7), 6=528 (LC 36)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-6=481/78

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 85 lb uplift at joint 4.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard


Job 21030025-A	Truss J06	Truss Type Jack-Closed	Qty 7	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	---------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:02

Page: 1

ID:BJBRRcOihcd9vFJ8Dn7a6z8frd-0OuXWxc1eXeJ_RsXNJXRWHii5CaeKOCChIHfpJz8Kst



Scale = 1:25.9

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.53	Vert(LL)	-0.04	4-7	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.39	Vert(CT)	-0.07	4-7	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 31 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x6 SP No.2

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=382/0' 5 1/2", (min. 0' 1 1/2"), 4=231/0' 1 1/2", (min. 0' 1 1/2")
Max Horiz 2=81 (LC 10)
Max Uplift 2=-114 (LC 10), 4=-41 (LC 14)
Max Grav 2=496 (LC 21), 4=306 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-8 to 1-2-7, Interior (1) 1-2-7 to 2-0-5, Exterior(2R) 2-0-5 to 6-3-4 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J06A	Truss Type Jack-Open	Qty 5	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:02

Page: 1

ID:JleylWAtd8XyI8LL0a79_0z8fqu-0OuXWxc1eXeJ_RsXNJXRWHihCCYaKOcChIHfpJz8Kst



Scale = 1:36

Plate Offsets (X, Y): [2:0' 2", 0' 2"]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.59	Vert(LL)	0.11	4-5	>654	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.52	Vert(CT)	0.10	4-5	>736	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	-0.14	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0										Weight: 46 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x6 SP No.2

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6'-0" oc purlins, except end verticals.

Rigid ceiling directly applied or 10'-0" oc bracing.

REACTIONS (lb/size) 3=157/ Mechanical, (min. 0' 1 1/2"), 4=68/ Mechanical, (min. 0' 1 1/2"), 5=389/0' 3 1/2", (min. 0' 1 1/2")
 Max Horiz 5=285 (LC 14)
 Max Uplift 3=-181 (LC 14), 4=-47 (LC 11)
 Max Grav 3=278 (LC 21), 4=117 (LC 7), 5=447 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-5=-402/48, 2-6=-317/66, 6-7=-306/79, 7-8=-303/85, 8-9=-297/149, 3-9=-273/169

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 2-1-5, Exterior(2R) 2-1-5 to 6-4-4 zone; porch left exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-0" x 6'-0" tall by 2'-0" x 0" wide will fit between the bottom chord and any other members.
 - 7) Refer to girder(s) for truss to truss connections.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 181 lb uplift at joint 3.
 - 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 4. This connection is for uplift only and does not consider lateral forces.
 - 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J07	Truss Type Jack-Closed	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	---------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:02

Page: 1

ID:v8yBmSXvC0R7JFpv3Btk?Jz8hLG-0OuXWxc1eXeJ_RsXNJXRWHiidCZUKOcChHfpJz8Kst



Scale = 1:46

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.56	Vert(LL)	0.10	7-10	>974	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.46	Vert(CT)	-0.15	7-10	>630	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.04	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 68 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 SLIDER Left 2x6 SP No.2 -- 1' 6"

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 4-7

REACTIONS (lb/size) 2=431/0' 5 1/2", (min. 0' 1 1/2"), 7=318/ Mechanical, (min. 0' 1 1/2")
 Max Horiz 2=327 (LC 14)
 Max Uplift 7=-180 (LC 14)
 Max Grav 2=478 (LC 5), 7=500 (LC 5)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-799/334, 3-12=-297/60, 12-13=-293/96, 13-14=-267/103, 14-15=-264/103, 4-15=-252/171, 4-7=-351/332
 BOT CHORD 2-16=-341/173

- NOTES**
- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 3-9-0, Exterior(2R) 3-9-0 to 7-11-15 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - 3) Unbalanced snow loads have been considered for this design.
 - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Refer to girder(s) for truss to truss connections.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 180 lb uplift at joint 7.
 - 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J07A	Truss Type Jack-Closed	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	---------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:03

Page: 1

ID:NgS9y3kLy7RVmG6qPGzGzH7z8NRz-UaSvkHcfPrmAbbRjx02g2UEr6byA3pRMwy1DLz8Kss



Scale = 1:48

Loading	(psf)	Spacing	1' 11 1/4"	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.05	6-7	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.31	Vert(CT)	-0.10	6-7	>924	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.16	Horz(CT)	0.00	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 79 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 3-6

REACTIONS

(lb/size) 6=300/ Mechanical, (min. 0' 1 1/2"), 7=422/0' 3 1/2", (min. 0' 1 1/2")
 Max Horiz 7=316 (LC 14)
 Max Uplift 6=-217 (LC 14)
 Max Grav 6=445 (LC 21), 7=462 (LC 21)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-7=-388/0, 2-8=-305/74, 8-9=-275/109, 9-10=-271/111, 10-11=-269/115, 3-11=-257/181, 3-6=-366/340
 BOT CHORD 6-7=-509/124
 WEBS 2-6=-128/524

NOTES

- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-9-14 to 1-2-2, Interior (1) 1-2-2 to 3-9-0, Exterior(2R) 3-9-0 to 7-11-15 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Refer to girder(s) for truss to truss connections.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 217 lb uplift at joint 6.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss J08	Truss Type Jack-Closed	Qty 18	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	---------------------------	-----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:03

Page: 1

ID:bdIS_1B7R8Mr79j9J40R1z8fli-UaSvkHcfPrmAbbRjx02g2UEqibsK3rsMwy1DLz8Kss



Scale = 1:25

Plate Offsets (X, Y): [2:0' 4 13/16\", 0' 1 1/2\"]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.73	Vert(LL)	-0.10	4-7	>927	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.68	Vert(CT)	-0.17	4-7	>533	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							Weight: 36 lb	FT = 20%
BCDL	10.0											

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x6 SP No.2

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.

Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 2=438/0' 3 1/2", (min. 0' 1 1/2"), 4=295/0' 1 1/2", (min. 0' 1 1/2")
 Max Horiz 2=55 (LC 13)
 Max Uplift 2=-127 (LC 10), 4=-42 (LC 10)
 Max Grav 2=551 (LC 21), 4=371 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 1) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-11-0 to 1-1-0, Interior (1) 1-1-0 to 3-5-12, Exterior(2R) 3-5-12 to 7-8-11 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 3) Unbalanced snow loads have been considered for this design.
- 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 7) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- 8) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
- 9) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
- 10) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss K1	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	----------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:03

Page: 1

ID:VeH5e9ibS2aL47d71?ptntuz8fzS-UaSvkHcfPrmAbbRjx02g2UEyWb0g3ntMwy1DLz8Kss



Scale = 1:62

Plate Offsets (X, Y): [4:0' 2 1/8",Edge], [10:0' 2 1/8",Edge]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.23	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.02	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.32	Horiz(TL)	0.00	14	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 270 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.2 *Except* ST4,ST1:2x4 SP No.3, O2,O1,O3,O4:2x4 SPF No.2(flat)

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 4-10.
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing, Except: 10-0-0 oc bracing: 24-25,14-15.
 WEBS T-Brace: 2x4 SPF No.2 - 3-23, 2-24, 11-17, 12-15

REACTIONS All bearings 16' 6".

(lb) - Max Horiz 25=-104 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) except 14=-186 (LC 11), 15=-241 (LC 15), 18=-103 (LC 10), 22=-104 (LC 11), 24=-244 (LC 14), 25=-193 (LC 10)
 Max Grav All reactions 250 (lb) or less at joint(s) 14, 17, 19, 20, 21, 23, 25 except 15=412 (LC 48), 18=501 (LC 37), 22=501 (LC 37), 24=416 (LC 46)

JOINTS

Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c.,with 3in minimum end distance.
 Brace must cover 90% of web length.
 1 Brace at Jt(s): 26, 27, 28, 29, 30, 34

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 22-28=490/110, 26-28=494/111, 5-26=471/106, 18-29=490/109, 27-29=494/110, 9-27=471/105

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) interior zone and C-C Corner(3E) 5-3-14 to 8-3-14, Corner(3R) 8-3-14 to 12-7-14, Exterior(2N) 12-7-14 to 14-2-6, Corner(3R) 14-2-6 to 18-6-6, Corner(3E) 18-6-6 to 21-6-6 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Vertical gable studs spaced at 2-0-0 oc and horizontal gable studs spaced at 2-11-8 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.

Job 21030025-A	Truss K1	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	----------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:03

Page: 2

ID:VeH5e9ibS2aL47d71?ptuz8fiS-UaSvkHcfPrmAbbRjx02g2UEyWb0g3ntMwy1DLlz8Kss

- 13) One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 25, 14, 22, 18, 24, and 15. This connection is for uplift only and does not consider lateral forces.
- 14) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 15) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 16) Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.

LOAD CASE(S) Standard


Job 21030025-A	Truss L1	Truss Type Common Supported Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	--------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:04

Page: 1

ID:2oLrGtKHgS9Q912HyeKUHcz8fh8-yn0lxddHA8u1Dk0vUkZvbin4T?LyoADV9cmmuCz8Ksr



Scale = 1:40

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.08	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.57	Horz(CT)	0.00	9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MR								
BCDL	10.0										Weight: 122 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS All bearings 12' 7".

- (lb) - Max Horiz 15=238 (LC 11)
- Max Uplift All uplift 100 (lb) or less at joint(s) 11, 13 except 9=-149 (LC 11), 10=-166 (LC 15), 14=-174 (LC 14), 15=-142 (LC 10)
- Max Grav All reactions 250 (lb) or less at joint(s) 9, 14 except 10=304 (LC 25), 11=271 (LC 22), 12=266 (LC 14), 13=285 (LC 21), 15=295 (LC 25)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-15=-230/374, 3-4=-140/351, 4-5=-182/445, 5-6=-182/445, 6-17=-123/358, 7-17=-140/351
 WEBS 5-12=-499/138

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Corner(3E) -1-9-14 to 1-2-2, Exterior(2N) 1-2-2 to 3-3-8, Corner(3R) 3-3-8 to 9-5-4, Corner(3E) 9-5-4 to 12-5-4 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 15, 9, 13, 14, 11, and 10. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

Job 21030025-A	Truss M1	Truss Type Roof Special	Qty 3	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	----------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:04

Page: 1

ID:WpVVAfMvQqi2O00G?ZFgOaz8fgK-yn0LxddHA8u1Dk0vUkZvbin0D?Blo87V9cmmuZc8Ksr




Plate Offsets (X, Y): [2:0' 1 1/2",Edge], [5:0' 2 15/16",0' 1 3/4"], [7:0' 5",0' 4 1/2"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.68	Vert(LL)	-0.15	7-11	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.76	Vert(CT)	-0.28	7-11	>776	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.70	Horz(CT)	0.20	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 115 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2 *Except* T3:2x6 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3 *Except* W3:2x4 SP No.2

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 4-4-9 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 2=856/0' 3 1/2", (min. 0' 1 1/2"), 6=746/0' 3", (min. 0' 1 1/2")
 Max Horiz 2=170 (LC 13)
 Max Uplift 2=-137 (LC 10), 6=-42 (LC 15)
 Max Grav 2=920 (LC 39), 6=786 (LC 22)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-13=-1482/275, 13-14=-1404/289, 3-14=-1360/302, 3-4=-1908/498, 4-15=-869/237, 15-16=-886/212, 5-16=-906/205,
 5-6=-544/188
 BOT CHORD 2-7=-63/1332, 5-7=0/692
 WEBS 3-7=-1245/358, 4-7=-340/1699

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-9 to 1-3-0, Interior (1) 1-3-0 to 9-4-2, Exterior(2R) 9-4-2 to 14-5-8, Interior (1) 14-5-8 to 15-5-0, Exterior(2E) 15-5-0 to 18-5-0 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Bearing at joint(s) 6 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 6 and 2. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss M2	Truss Type Roof Special Structural Gable	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	---------------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:05

Page: 1

ID:7aSVOiLL711PEdH1onkvizs8ff2-Qzag8zevxS0trub62R588vKCvPvXbOfNGWJQez8Ksq



Scale = 1:44.3

Plate Offsets (X, Y): [2:Edge,0' 1/2"], [8:0' 2 15/16",0' 1 3/4"], [10:0' 5",0' 4 1/2"]

Loading	(psf)	Spacing	2'	CSI	0.62	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.62	Vert(LL)	-0.15 12-13	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.87	Vert(CT)	-0.27 10-17	>814	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.70	Horz(CT)	0.19 9	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							
BCDL	10.0									Weight: 121 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2 *Except* T3:2x6 SP 2400F 2.0E
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.3 *Except* W3:2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 5-1-10 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 2=856/0' 3 1/2", (min. 0' 1 1/2"), 9=746/0' 3", (min. 0' 1 1/2")
Max Horiz 2=170 (LC 13)
Max Uplift 2=-137 (LC 10), 9=-42 (LC 15)
Max Grav 2=920 (LC 39), 9=786 (LC 22)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-19=-1459/258, 3-19=-1428/259, 3-4=-1439/281, 4-5=-1402/298, 5-20=-1431/324, 6-20=-1420/330, 6-7=-1900/489,
7-21=-897/252, 21-22=-915/226, 8-22=-934/220, 8-9=-544/188
BOT CHORD 2-13=-71/1347, 12-13=-71/1347, 11-12=-71/1347, 10-11=-71/1347, 8-10=0/708
WEBS 6-10=-1052/266, 7-10=-333/1698

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) -1-10-9 to 1-3-0, Interior (1) 1-3-0 to 9-4-2, Exterior(2R) 9-4-2 to 14-5-8, Interior (1) 14-5-8 to 15-5-0, Exterior(2E) 15-5-0 to 18-5-0 zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 9 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 9 and 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss N1	Truss Type Roof Special	Qty 3	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	----------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:05

Page: 1

ID: NKWZ_oYXzKz_wPO5dv_zYXz8hLF-Qzag8zevxS0trub62R588vKA2PXAXkZfNGWJQez8Ksq



Scale = 1:40.4

Plate Offsets (X, Y): [4:0' 1 15/16", 0' 1 3/4"]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.74	Vert(LL)	-0.10	6-11	>999	240	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.72	Vert(CT)	-0.17	6-11	>824	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.12	Horz(CT)	0.13	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 76 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
 BOT CHORD 2x6 SP No.2
 WEBS 2x4 SP No.3
 WEDGE Right: 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 -- 1' 6"

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=458/0' 3", (min. 0' 1 1/2"), 5=471/0' 3", (min. 0' 1 1/2")
 Max Horiz 1=-162 (LC 15)
 Max Uplift 1=-29 (LC 15), 5=-36 (LC 15)
 Max Grav 1=548 (LC 21), 5=541 (LC 22)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-564/105, 3-13=-472/96, 4-13=-545/66, 4-5=-371/76
 BOT CHORD 1-6=-101/334, 4-6=0/334
 WEBS 3-6=-7/296

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 1-3-7 to 4-3-7, Exterior(2R) 4-3-7 to 8-9-0, Interior (1) 8-9-0 to 9-8-8, Exterior(2E) 9-8-8 to 12-8-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 5 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss P1	Truss Type Common Supported Gable	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	-------------	--------------------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:05

Page: 1

ID:IXb8YpR1uigMTBifScTQ?z8MPD-Qzag8zevxs0trub62R588vKJCPijXlFNGWJQez8Ksq



Scale = 1:38.1

Loading	(psf)	Spacing	1' 11 1/4"	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.15	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.13	Horz(CT)	0.00	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 121 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
OTHERS 2x4 SP No.3
SLIDER Left 2x4 SP No.3 -- 1' 6", Right 2x4 SP No.3 -- 1' 6"

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS All bearings 12' 7".
(lb) - Max Horiz 2=185 (LC 13), 17=185 (LC 13)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 10, 13, 15, 17, 21 except 12=-148 (LC 15), 16=-153 (LC 14)
Max Grav All reactions 250 (lb) or less at joint(s) 2, 10, 12, 14, 16, 17, 21 except 13=275 (LC 22), 15=275 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
BOT CHORD 2-16=-74/262, 15-16=-74/263, 14-15=-74/264, 13-14=-74/264, 12-13=-74/263, 10-12=-73/262

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Corner(3E) -1-9-14 to 1-2-2, Exterior(2N) 1-2-2 to 3-3-8, Corner(3R) 3-3-8 to 9-3-8, Exterior(2N) 9-3-8 to 11-4-14, Corner(3E) 11-4-14 to 14-4-14 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 10, 15, 16, 13, and 12. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard



Job 21030025-A	Truss PB04	Truss Type Piggyback	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:06

Page: 1

ID: _8g4UjI87o?p1CwbmpBoWNz8MXs-u982MJfXim9kS2Alc8cNg7sVip2xGCcocwFty4z8Ksp



Scale = 1:26.3

Plate Offsets (X, Y): [2:0' 2 3/8", 0' 1"], [3:0' 2 1/2", Edge], [4:0' 2 3/8", 0' 1"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.04	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 13 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 2' 10 3/8".
(lb) - Max Horiz 2=-42 (LC 12), 6=-42 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 6, 9
Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 6, 9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 21030025-A	Truss PB05	Truss Type Piggyback	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:06

Page: 1

ID:ZOmXJB3ys4UYsqot77CCN3z8Ma1-u982MJfXim9kS2Alc8cNg7sUsp12GCSocwFty4z8Ksp



Scale = 1:24

Plate Offsets (X, Y): [2:0' 2 3/8\", 0' 1\"], [4:0' 2 3/8\", 0' 1\"]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.10	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 22 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-9-1 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 4' 7 3/8\".

(lb) - Max Horiz 2=-62 (LC 12), 7=-62 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 10
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 6, 7, 10

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard




Job 21030025-A	Truss PB05A	Truss Type Piggyback	Qty 19	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	----------------	-------------------------	-----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:07

Page: 1

ID: NKWZ_oYXzKZ_wPO5dv_zYXz8hLF-MMiQZfgAT3Hb4CIUAs7cDKPfcDNH?fhxra?QVWz8Kso



Scale = 1:24

Plate Offsets (X, Y): [2:0' 2 3/8", 0' 1"], [4:0' 2 3/8", 0' 1"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.10	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.10	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 22 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-9-1 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 4' 7 3/8".

- (lb) - Max Horiz 2=-62 (LC 12), 7=-62 (LC 12)
- Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 10
- Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 6, 7, 10

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard




Job 21030025-A	Truss PB05B	Truss Type Piggyback	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	----------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:07

Page: 1

ID:hc?cuY1io5_8SMeJFJQOXEz8ein-MMIQZfgAT3Hb4CIUAs7cDKPgMDO6?fmra?QVWz8Kso



Scale = 1:24

Plate Offsets (X, Y): [2:0' 2 3/8",0' 1"], [4:0' 2 3/8",0' 1"]

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

REACTIONS All bearings 4' 7 3/8".

(lb) - Max Horiz 2=-62 (LC 12), 7=-62 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 10
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 6, 7, 10

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-9-1 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.



Job 21030025-A	Truss PB05C	Truss Type Piggyback	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	----------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:07

Page: 1

ID:rW4yB8Y9kdhYyYlBcVC4kz8hLE-MMiQZfgAT3Hb4CIUAs7cDKPgMDO6?fmxra?QVWz8Kso



Scale = 1:24

Plate Offsets (X, Y): [2:0' 2 3/8", 0' 1"], [4:0' 2 3/8", 0' 1"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.05	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 44 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-9-1 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 4' 7 3/8".

- (lb) - Max Horiz 2=-62 (LC 12), 7=-62 (LC 12)
- Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 10
- Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 6, 7, 10

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 2-ply truss to be connected together as follows:
 Top chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0' 9" oc.
 Bottom chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0' 9" oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 21030025-A	Truss PB05D	Truss Type Piggyback	Qty 2	Ply 3	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	----------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:08

Page: 1

ID:GquQcRZX?4qPFYstf1_gVTz8drs-rYFon?goENPSiMKhjZerYrMjcdk6254Ek_1zz8Ksn



Scale = 1:24

Plate Offsets (X, Y): [2:0' 2 3/8", 0' 1"], [4:0' 2 3/8", 0' 1"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.03	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 66 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 5-9-1 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 4' 7 3/8".
 (lb) - Max Horiz 2=-62 (LC 12), 7=-62 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 10
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 6, 7, 10

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 3-ply truss to be connected together as follows:
 Top chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0' 9" oc.
 Bottom chords connected with 10d (0.131"x3") nails as follows: 2x4 - 1 row at 0' 9" oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard




Job 21030025-A	Truss PB06	Truss Type Piggyback	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:08

Page: 1

ID: Y4Dq8K9fm8Er4PHPA3hYsfz8MOH-rYFon?goENPSiMKhjZerlYyqVcjfk6S54Ek_1zz8Ksn



Scale = 1:26.8

Plate Offsets (X, Y): [2:0' 2 3/8", 0' 1"], [6:0' 2 3/8", 0' 1"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.03	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	14	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 26 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 5' 2 13/16".
 (lb) - Max Horiz 2=-70 (LC 12), 11=-70 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 6, 11, 14 except 8=-111 (LC 15), 10=-112 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 6, 8, 9, 10, 11, 14

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 6, 10, and 8. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard




Job 21030025-A	Truss PB06A	Truss Type Piggyback	Qty 3	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	----------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:09

Page: 1

ID:Ujs?7pOalz8sKE2oYX?7fz8MO_-JkpA_KhQ?hXJJWutHH94IU_X01CTZ9EItUXZPz8Ksm



Scale = 1:25

Plate Offsets (X, Y): [2:0' 2 3/8", 0' 1"], [4:0' 2 3/8", 0' 1"]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.13	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.14	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horz(CT)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 25 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3

BRACING

TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 5' 2 13/16".
 (lb) - Max Horiz 2=-70 (LC 12), 7=-70 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 10
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 6, 7, 10

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard



Job 21030025-A	Truss PB06B	Truss Type Piggyback	Qty 1	Ply 2	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	----------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:09

Page: 1

ID:FGL1pYUbpRd0pYrbGEgtSLz8MNs-JkpA_KhQ?hXJJWutHH94IIU?Z02JTZGEItUXZPz8Ksm



Scale = 1:25

Plate Offsets (X, Y): [2:0' 2 3/8", 0' 1"], [4:0' 2 3/8", 0' 1"]

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 5' 2 13/16".
 (lb) - Max Horiz 2=-70 (LC 12), 7=-70 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 10
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 6, 7, 10


Job 21030025-A	Truss PB07	Truss Type Piggyback	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:09

Page: 1

ID:ZG9KDTLwRJdqpTlvanJoTz8fiU-JkpA_KhQ?hXJJWutHH94IU?H03TTZIEitUXZPz8Ksm



Scale = 1:26.8

Plate Offsets (X, Y): [2:0' 2 3/8", 0' 1"], [6:0' 2 3/8", 0' 1"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 34 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 6' 4 13/16".
(lb) - Max Horiz 2=-83 (LC 12), 11=-83 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 11 except 8=-107 (LC 15), 10=-109 (LC 14)
Max Grav All reactions 250 (lb) or less at joint(s) 2, 6, 8, 9, 10, 11, 14

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-2-10 to 3-2-10, Exterior(2R) 3-2-10 to 4-3-14, Exterior(2E) 4-3-14 to 7-3-14 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 8, and 10. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard




Job 21030025-A	Truss PB09	Truss Type Piggyback	Qty 6	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:10

Page: 1

ID:JNvr8PzfZeF7VvKLYJ_HPnz8gaw-nwNZCgi2m_fAxT3r_gJrz162QKMC0BOXXD45rz8Ksl



Scale = 1:25

Plate Offsets (X, Y): [2:0' 2 9/16", 0' 1 1/2"], [4:0' 2 9/16", 0' 1 1/2"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.34	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.34	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.03	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							Weight: 33 lb	FT = 20%
BCDL	10.0											

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 8' 7/16".
 (lb) - Max Horiz 2=70 (LC 13), 7=70 (LC 13)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 11
 Max Grav All reactions 250 (lb) or less at joint(s) except 2=321 (LC 21), 4=321 (LC 22), 6=280 (LC 22), 7=321 (LC 21), 11=321 (LC 22)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-3-5 to 3-3-5, Exterior(2R) 3-3-5 to 6-3-5, Exterior(2E) 6-3-5 to 9-3-5 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 4. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 21030025-A	Truss PB18	Truss Type Piggyback	Qty 2	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:10

Page: 1

ID:sStErOCzHKS_n_00lfjZ011z8hQr-nwNZCgi2m_faxT3r_gJrz1A_QPhC?AOXXD45rz8Ksl



Scale = 1:38

Plate Offsets (X, Y): [2:0' 2 9/16", 0' 1 1/2"], [10:0' 2 9/16", 0' 1 1/2"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.09	Horz(CT)	0.00	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0											
										Weight: 94 lb	FT = 20%	

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 17' 3 5/8".
 (lb) - Max Horiz 2=-143 (LC 12), 20=-143 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 12, 14, 15, 17, 18, 19, 20
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 10, 12, 14, 16, 18, 19, 20, 24 except 15=265 (LC 22), 17=265 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-3-5 to 3-4-15, Interior (1) 3-4-15 to 6-4-15, Exterior(2R) 6-4-15 to 12-4-15, Interior (1) 12-4-15 to 15-4-15, Exterior(2E) 15-4-15 to 18-6-8 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 17, 18, 19, 15, 14, and 12. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 21030025-A	Truss PB18A	Truss Type Piggyback	Qty 17	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	----------------	-------------------------	-----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:11

Page: 1

ID:sMK_wLr5EmmeDldbUkQ3tz8hzX-F7xxP0JgXln1Zp2FPiBYNAaHmqidxS9XmBzeelz8Ksk



Scale = 1:38

Plate Offsets (X, Y): [2:0' 2 9/16\", 0' 1 1/2\"], [6:0' 2 9/16\", 0' 1 1/2\"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.34	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.21	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horz(CT)	0.00	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 76 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 17' 3 5/8".
 (lb) - Max Horiz 2=-143 (LC 12), 12=-143 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 6, 12, 16 except 8=-157 (LC 15), 11=-158 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 6, 12, 16 except 8=546 (LC 6), 10=309 (LC 27), 11=542 (LC 5)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-11=-418/193, 5-8=-418/193

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-3-5 to 3-3-5, Interior (1) 3-3-5 to 6-4-15, Exterior(2R) 6-4-15 to 12-4-15, Interior (1) 12-4-15 to 15-6-8, Exterior(2E) 15-6-8 to 18-6-8 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 11, 8, and 6. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard


Job 21030025-A	Truss PB22	Truss Type Piggyback	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:11

Page: 1

ID:XGS_OY_rw9cot?PPnyh?Hz8gX1-F7xxP0JgXln1Zp2FPIBYNAaHyqk4xSZXmBzeelz8Ksk



Scale = 1:45.6

Plate Offsets (X, Y): [2:0' 2 9/16", 0' 1 1/2"], [3:0' 4 13/16", Edge], [7:0' 2 1/2", 0' 2 1/4"]

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.11	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horz(CT)	0.00	10	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 76 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 10-0-0 oc purlins, except
 2-0-0 oc purlins (6-0-0 max.): 3-10.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS All bearings 21' 7 3/16".

(lb) - Max Horiz 2=61 (LC 14), 19=61 (LC 14)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 11, 12, 13, 15, 16, 17, 18, 19 except 10=133 (LC 35)
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 10, 11, 19 except 12=350 (LC 35), 13=430 (LC 35), 15=388 (LC 35), 16=346 (LC 35), 17=495 (LC 35), 18=282 (LC 35)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

WEBS 4-17=-412/108, 5-16=-267/96, 6-15=-306/101, 8-13=-357/92, 9-12=-276/78

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-3-5 to 3-0-0, Exterior(2R) 3-0-0 to 7-0-0, Interior (1) 7-0-0 to 19-4-5, Exterior(2E) 19-4-5 to 22-4-5 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 20.0 psf on overhangs non-concurrent with other live loads.
- Provide adequate drainage to prevent water ponding.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 4-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=133.
- One RT7A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 18, 17, 16, 15, 13, and 12. This connection is for uplift only and does not consider lateral forces.
- One RT16A MiTek connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 11. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job 21030025-A	Truss PB22	Truss Type Piggyback	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	-------------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:11

Page: 2

ID: XGS_OY_rw9cot?tPPnyh?Hz8gX1-F7xxP0JgXln1Zp2FPiBYNAaHyqk4xSZXmBzeelz8Ksk

- 17) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.
- 18) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard



Job 21030025-A	Truss V02	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:12

Page: 1

ID:z4eotf2W13tioNDOJpU7AYz8MLr-jVJcMjllcvuAzdSyPjnwN6X7E5Mgw5h_riBAkz8Ksj



Scale = 1:24.9

Plate Offsets (X, Y): [2:0' 2 1/2\", Edge]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.05	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP							Weight: 8 lb	FT = 20%
BCDL	10.0											

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 2-5-13 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=99/2' 5 13/16\", (min. 0' 1 1/2\"), 3=99/2' 5 13/16\", (min. 0' 1 1/2\")
Max Horiz 1=25 (LC 13)
Max Uplift 1=-7 (LC 14), 3=-7 (LC 15)
Max Grav 1=114 (LC 20), 3=114 (LC 21)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 7 lb uplift at joint 1 and 7 lb uplift at joint 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V03	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:12

Page: 1

ID:voDjVNxnGjsYeGczesQan8z8gaz-jVJcMjllcvuAzdSyPjnwN6SYE_Ygwuh_riBAkz8Ksj



Scale = 1:30.6

Plate Offsets (X, Y): [2:0' 2 1/2", Edge]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.34	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.48	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.01	Horiz(TL)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 14 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 3-6-2 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=91/3' 6 1/8", (min. 0' 1 1/2"), 4=-459/3' 6 1/8", (min. 0' 1 1/2"), 5=632/3' 6 1/8", (min. 0' 1 1/2")
Max Horiz 1=67 (LC 14)
Max Uplift 1=-1 (LC 15), 4=-504 (LC 23), 5=-172 (LC 14)
Max Grav 1=103 (LC 20), 4=135 (LC 14), 5=681 (LC 23)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 504 lb uplift at joint 4, 1 lb uplift at joint 1 and 172 lb uplift at joint 5.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V04	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:12

Page: 1

ID:i7DxasZ2sS2ssvb7Sqm6Eyz8hdl-jJVJcMjllcvuAzdSyPjnwN6X2E4vgwih_riBAkz8Ksj



Scale = 1:21.8

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.07	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 15 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 3-11-8 oc purlins.
 Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=49/3' 11 1/2", (min. 0' 1 1/2"), 3=49/3' 11 1/2", (min. 0' 1 1/2"),
 4=219/3' 11 1/2", (min. 0' 1 1/2")
 Max Horiz 1=42 (LC 11)
 Max Uplift 1=-1 (LC 15), 3=-4 (LC 15), 4=-30 (LC 14)
 Max Grav 1=80 (LC 20), 3=80 (LC 21), 4=224 (LC 20)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 1 lb uplift at joint 1, 4 lb uplift at joint 3 and 30 lb uplift at joint 4.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V04A	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:13

Page: 1

ID:voDjVNxnGjsYeGczesQan8z8gaz-BV3hqikw3v1lo7CeW7E0SbfgcdOePNqDVSliAz8Ksi



Scale = 1:35.7

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.23	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	0.00	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 25 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 4-10-2 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 4' 10 1/8".

- (lb) - Max Horiz 1=116 (LC 14)
- Max Uplift All uplift 100 (lb) or less at joint(s) 4 except 5=-198 (LC 23), 6=-109 (LC 14)
- Max Grav All reactions 250 (lb) or less at joint(s) 1, 4, 5 except 6=347 (LC 23)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Exterior(2R) 3-0-4 to 3-9-10, Exterior(2E) 3-9-10 to 4-7-2 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4 except (jt=lb) 6=108, 5=197.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V05	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:13

Page: 1

ID:IM74eH89gC52dHFLGvdNA4z8hcY-BV3hqjkw3v1o7CeW7E0SbfhudPBPnfqDVSliAz8Ksi



Scale = 1:23.8

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.11	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 20 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 5-1-13 oc purlins.
 Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=52/5' 1 13/16", (min. 0' 1 1/2"), 3=52/5' 1 13/16", (min. 0' 1 1/2")
 1/2"), 4=308/5' 1 13/16", (min. 0' 1 1/2")
 Max Horiz 1=56 (LC 11)
 Max Uplift 4=-50 (LC 14)
 Max Grav 1=96 (LC 20), 3=96 (LC 21), 4=324 (LC 20)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 50 lb uplift at joint 4.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V06	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:13

Page: 1

ID:hJefQy2_nc5F3BJzdl9gCz8he5-BV3hqikw3v1lo7CeW7E0SbfffEdOdPM5qDVSLiAz8Ksi



Scale = 1:26.2

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.22	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.24	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.08	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 26 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-7-8 oc purlins.
Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=47/6' 7 1/2", (min. 0' 1 1/2"), 3=47/6' 7 1/2", (min. 0' 1 1/2"),
4=435/6' 7 1/2", (min. 0' 1 1/2")
Max Horiz 1=-73 (LC 10)
Max Uplift 1=-6 (LC 21), 3=-6 (LC 20), 4=-82 (LC 14)
Max Grav 1=109 (LC 20), 3=109 (LC 21), 4=471 (LC 20)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-4=-325/200

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Exterior(2R) 3-0-4 to 3-7-12, Exterior(2E) 3-7-12 to 6-7-12 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 6 lb uplift at joint 1, 6 lb uplift at joint 3 and 82 lb uplift at joint 4.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V06A	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:13

Page: 1

ID: N_n5jyP11?PGQBACZxpKMz8gay-BV3hqkw3v1o7CeW7E0SbfcCdLWPMCqDVSlIAz8Ksi



Scale = 1:40.1

Plate Offsets (X, Y): [1:0' 5 13/16\", Edge]

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.41	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.43	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.01	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 34 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 6' 2 1/8".
(lb) - Max Horiz 1=164 (LC 14)
Max Uplift All uplift 100 (lb) or less at joint(s) 4 except 5=-388 (LC 23),
6=-173 (LC 14)
Max Grav All reactions 250 (lb) or less at joint(s) 1, 4, 5 except 6=520 (LC 23)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Exterior(2R) 3-0-4 to 5-1-10, Exterior(2E) 5-1-10 to 5-11-2 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCCL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4 except (jt=lb) 6=173, 5=388.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V07	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:14

Page: 1

ID:IM74eH89gC52dHFLGvdNA4z8hcY-fid312IzqD9cQHnq4qIF?oCou1hl8ogzS9BIEdz8Ksh



Scale = 1:28.1

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.35	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.34	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.19	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 32 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 7-9-13 oc purlins.
 Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 7' 9 13/16".
 (lb) - Max Horiz 1=87 (LC 10)
 Max Uplift All uplift 100 (lb) or less at joint(s) 3, 4, 9 except 1=119 (LC 21)
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 3, 9 except 4=775 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-10=-85/313, 2-10=-35/334, 2-11=-35/396, 3-11=-55/313
 WEBS 2-4=-635/177

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Exterior(2R) 3-0-4 to 4-10-1, Exterior(2E) 4-10-1 to 7-10-1 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 4, 3 except (jt=lb) 1=118.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V07A	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:14

Page: 1

ID:N_n5jyP11?PGQBACZxpKmz8gay-fid312LzqD9cQHnq4qIF?oCpw1kN8pfzS9BIEdz8Ksh



Scale = 1:44.6

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.28	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.12	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 46 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 7' 6 1/8".

- (lb) - Max Horiz 1=213 (LC 14)
- Max Uplift All uplift 100 (lb) or less at joint(s) 1, 7 except 6=-176 (LC 22), 8=-193 (LC 14)
- Max Grav All reactions 250 (lb) or less at joint(s) 1, 5, 6 except 7=352 (LC 23), 8=426 (LC 23)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-415/228
 WEBS 2-8=-322/414

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 3-5-10, Exterior(2R) 3-5-10 to 6-5-10, Exterior(2E) 6-5-10 to 7-3-2 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7 except (jt=lb) 8=193, 6=175.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V08	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:14

Page: 1

ID: N_n5jyP11?PGQBACZxpKMz8gay-fid312lZqD9cQHnq4qIF?oCqQ1k58oNzS9BIEdz8Ksh



Scale = 1:49

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.25	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.16	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.14	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MP								
BCDL	10.0										Weight: 57 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 8' 10 1/8".

(lb) - Max Horiz 1=262 (LC 14)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 7 except 6=-178 (LC 22), 8=-227 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 5, 6 except 7=335 (LC 23), 8=515 (LC 23)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-398/231
 WEBS 2-8=-333/385

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 4-9-10, Exterior(2R) 4-9-10 to 7-9-10, Exterior(2E) 7-9-10 to 8-7-2 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7 except (jt=lb) 8=227, 6=178.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V09	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:15

Page: 1

ID:9VC14mygl5kysDmWXKtOCQz8he4-7uBSFomBbXHT1RM1eXGUY0kyMR06IEU7hpxrn3z8Ksg



Scale = 1:30.5

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.43	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.43	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.21	Horiz(TL)	0.01	4	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 38 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 9-3-8 oc purlins.
 Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=40/9' 3 1/2", (min. 0' 1 1/2"), 3=40/9' 3 1/2", (min. 0' 1 1/2"),
 4=663/9' 3 1/2", (min. 0' 1 1/2")
 Max Horiz 1=-105 (LC 10)
 Max Uplift 1=-39 (LC 21), 3=-39 (LC 20), 4=-134 (LC 14)
 Max Grav 1=108 (LC 20), 3=108 (LC 21), 4=738 (LC 21)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-102/342, 2-3=-87/342
 WEBS 2-4=-560/190

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Exterior(2R) 3-0-4 to 6-3-12, Exterior(2E) 6-3-12 to 9-3-12 zone; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 39 lb uplift at joint 1, 39 lb uplift at joint 3 and 134 lb uplift at joint 4.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V10	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:15

Page: 1

ID:AJnJnCagIAjU39J0YHLnAz8hdH-7uBSFOmBbXHT1RM1eXGUY0kzTR4btG77hpxrn3z8Ksg



Scale = 1:35

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.36	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.14	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.11	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 45 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS

All bearings 10' 5 13/16".
 (lb) - Max Horiz 1=-119 (LC 10)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 5 except 6=-173 (LC 15),
 8=-179 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 5, 7 except 6=487 (LC 21), 8=487 (LC 20)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-13=-260/104, 4-14=-260/104
 WEBS 2-8=-530/368, 4-6=-530/368

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Exterior(2R) 3-0-4 to 7-6-1, Exterior(2E) 7-6-1 to 10-6-1 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=179, 6=172.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V10A	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	---------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:15

Page: 1

ID:RALTw3z1oL7GtamMIHS2sZz8gax-7uBSFOmBbXHT1RM1eXGUY0k_FR2gtFN7hpxrn3z8Kkg



Scale = 1:54.6

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.31	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.26	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.16	Horiz(TL)	0.01	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH							Weight: 67 lb	FT = 20%
BCDL	10.0											

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD
 WEBS

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.
 1 Row at midpt 3-7

REACTIONS All bearings 10' 2 1/8".

(lb) - Max Horiz 1=311 (LC 14)
 Max Uplift All uplift 100 (lb) or less at joint(s) 5, 7 except 6=-141 (LC 22),
 8=-263 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 5, 6 except 1=257 (LC 25),
 7=314 (LC 23), 8=614 (LC 23)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-400/247
 WEBS 2-8=-363/374

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 6-1-10, Exterior(2R) 6-1-10 to 9-1-10, Exterior(2E) 9-1-10 to 9-11-2 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- Unbalanced snow loads have been considered for this design.
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7 except (jt=lb) 8=263, 6=140.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V11	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:16

Page: 1

ID:rALTW3z1oL7GtamMIHS2sZz8gax-7uBSFOmBbXHT1RM1eXGUY0k?UR49IEQ7hpxrn3z8Ksg



Scale = 1:59.2

Loading	(psf)	Spacing	2'	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.23	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.22	Horiz(TL)	0.00	6	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 81 lb	FT = 20%

LUMBER

TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD
 BOT CHORD
 WEBS

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.
 1 Row at midpt 4-8, 5-7

REACTIONS All bearings 11' 6 1/8".

(lb) - Max Horiz 1=360 (LC 14)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 8 except 7=182 (LC 22), 9=226 (LC 14), 10=136 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 6, 7 except 1=295 (LC 14), 8=395 (LC 23), 9=516 (LC 23), 10=366 (LC 23)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-511/314, 2-3=-356/214
 WEBS 3-9=-311/322

NOTES

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 7-5-10, Exterior(2R) 7-5-10 to 10-5-10, Exterior(2E) 10-5-10 to 11-3-2 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
- 4) Unbalanced snow loads have been considered for this design.
- 5) Gable requires continuous bottom chord bearing.
- 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 8 except (jt=lb) 9=226, 10=135, 7=182.
- 9) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V12	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:16

Page: 1

ID:If?Txbj7SxDOT8EgM7WiOCz8heO-c4kqSknpLqPKfaxDBFnj4DH8frR5cjaGvTgPJvz8Ksf



Scale = 1:35.5

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.12	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.10	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 54 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 11' 11 1/2".
 (lb) - Max Horiz 1=136 (LC 11)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 5 except 6=172 (LC 15), 8=177 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 5, 7 except 6=448 (LC 21), 8=448 (LC 20)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=251/120, 3-4=251/105
 WEBS 2-8=413/239, 4-6=413/237

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Exterior(2R) 3-0-4 to 8-11-12, Exterior(2E) 8-11-12 to 11-11-12 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=177, 6=171.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V13	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:16

Page: 1

ID:eWlh?YbIV3la5CkVaFoaJNz8hdG-c4kqSknpLqPKfaxDBFj4DH8lrQoci?GvTgPJvz8Ksf



Scale = 1:37.5

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.13	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 61 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 13' 1 13/16".
 (lb) - Max Horiz 1=-150 (LC 10)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1, 5 except 6=-182 (LC 15), 8=-186 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 5 except 6=429 (LC 21), 7=359 (LC 23), 8=429 (LC 20)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-8=-367/246, 4-6=-367/246

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 3-7-3, Exterior(2R) 3-7-3 to 9-7-3, Interior (1) 9-7-3 to 10-2-1, Exterior(2E) 10-2-1 to 13-2-1 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=186, 6=181.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V14	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:17

Page: 1

ID:DrYr5GkmDFL4lpswr1xxPz8heN-4HICg4nR68XAHkWPlydRqJRFmbL8CQ87Qyrxz8Kse



Scale = 1:40

Loading	(psf)	Spacing	2'	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.20	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 69 lb	FT = 20%

LUMBER	
TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
OTHERS	2x4 SP No.3

BRACING	
TOP CHORD	
BOT CHORD	

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 14' 7 1/2".
(lb) - Max Horiz 1=-167 (LC 12)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 5 except 6=-200 (LC 15), 8=-204 (LC 14)
Max Grav All reactions 250 (lb) or less at joint(s) 1, 5 except 6=470 (LC 21), 7=405 (LC 23), 8=470 (LC 20)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-386/242, 4-6=-386/240

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 4-4-0, Exterior(2R) 4-4-0 to 10-4-0, Interior (1) 10-4-0 to 11-7-12, Exterior(2E) 11-7-12 to 14-7-12 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=203, 6=199.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 21030025-A	Truss V15	Truss Type Valley	Qty 1	Ply 1	2810 Norrington-Roof-Creekview Job Reference (optional)
-------------------	--------------	----------------------	----------	----------	------------------------------------------------------------

Carter Components, Sanford, NC, user

Run: 8.5 S 0 Apr 29 2021 Print: 8.500 S Apr 29 2021 MiTek Industries, Inc. Tue Jun 08 14:07:17

Page: 1

ID:UaRpEeBrIRMQKLmosKSX4Rz8hvs-4HICg4nR68XAHkWPlylydRqJOFmfl7?Q87Qyrzx8Kse



Scale = 1:42.1

Loading	(psf)	Spacing	2'	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.33	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf)	20.0	Lumber DOL	1.15	BC	0.17	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.28	Horiz(TL)	0.00	5	n/a	n/a		
BCLL	0.0*	Code	IRC2018/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 76 lb	FT = 20%

LUMBER
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 6-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 15' 9 13/16".
 (lb) - Max Horiz 1=-181 (LC 12)
 Max Uplift All uplift 100 (lb) or less at joint(s) 1 except 6=-217 (LC 15),
 8=-221 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 1, 5 except 6=510 (LC 6), 7=446 (LC 23), 8=511 (LC 23)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-7=-252/0, 2-8=-394/255, 4-6=-394/253

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) exterior zone and C-C Exterior(2E) 0-0-4 to 3-0-4, Interior (1) 3-0-4 to 4-11-3, Exterior(2R) 4-11-3 to 10-11-3, Interior (1) 10-11-3 to 12-10-1, Exterior(2E) 12-10-1 to 15-10-1 zone; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - TCLL: ASCE 7-16; Pr=20.0 psf (roof LL: Lum DOL=1.15 Plate DOL=1.15); Pf=20.0 psf (Lum DOL=1.15 Plate DOL=1.15); Is=1.0; Rough Cat B; Fully Exp.; Ce=0.9; Cs=1.00; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=221, 6=217.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard