Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

	SUBDIVISION Miriam Ring LOT # 3
ISSUED TO: Weaver Homes NEW X REPAIR EXPANSION	Site Improvements required prior to Construction Authorization Issuance:
	site improvements required prior to construction Authorization issuance.
Type of Structure: 35' x 47' SFD	
Proposed Wastewater System Type: 25% reduction	
Projected Daily Flow: 360 GPD	
Number of bedrooms: 3 Number of Occupants: 6	_max
Basement Yes No	
Pump Required: Yes No May be required based on final	nce from well feet Permit valid for: 🔀 Five years
Type of Water Supply: Community Public Well Dista	No expiration
Permit conditions:	— In Cophaton
111	
Authorized State Agent: Mala Me nei	Date: 08-27-21 SEE ATTACHED SITE SKETCH
	er permits. The permit holder is responsible for checking with appropriate governing bodies in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvemen	t Permit shall not be affected by a change in ownership of the site. This permit is subject to compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit	
Consti	ruction Authorization
	quired for Building Permit)
	. 1958, and 1959 are incorporated by references into this permit and shall be met. Systems shall be installed in accordance
with the attached system layout.	, 1730. and 1737 are incorporated by received and that period and man of ince systems man of instance in accordance
1.000000000000000000000000000000000000	
ISSUED TO: Weaver Homes	PROPERTY LOCATION: 5926 Rosser Pittman Rd (SR1215)
	SUBDIVISION Miriam Ring LOT # 3
Facility Type: 35' x 47' SFD New	Expansion Repair
Basement? Yes No Basement Fixtures? Yes	⊠ No
Type of Wastewater System** 25% reduction	(Initial) Wastewater Flow: 360 GPD
(See note below, if applicable)	
25% reduction	(Repair)
	thes 5
	each trench 75 feet Trench Spacing: 9 Feet on Center
Pump Tank Sizegallons Trenches shall be	e installed on contour at a Soil Cover: 6 inches
Pump Tank Sizegallons Trenches shall be Maximum Trench	each trench 75feet
Pump Tank Sizegallons Trenches shall be Maximum Trench	e installed on contour at a Soil Cover: 6 inches
Pump Tank Sizegallons Trenches shall be Maximum Trench	each trench 75 feet Trench Spacing: 9 Feet on Center Soil Cover: 6 installed on contour at a h Depth of: 18" - 24" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom)
Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions	each trench 75 feet Trench Spacing: 9 Feet on Center Soil Cover: 6 installed on contour at a h Depth of: 18" - 24" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom)
Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions	each trench 75feet
Pump Tank Size gallons Trenches shall be Maximum Trenches (Trench bottoms in all directions) Pump Requirements: ft. TDH vsGPM	each trench 75feet
Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions	each trench 75feet
Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions Pump Requirements:ft. TDH vsGPM Conditions:	each trench 75feet
Pump Tank Sizegallons	reach trench 75 feet Trench Spacing: 9 Feet on Center re installed on contour at a Soil Cover: 6 inches re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed
Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions Pump Requirements:ft. TDH vsGPM Conditions:	reach trench 75 feet Trench Spacing: 9 Feet on Center re installed on contour at a Soil Cover: 6 inches re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed
Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions Pump Requirements:ft. TDH vsGPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE	each trench 75feet
Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions Pump Requirements:ft. TDH vsGPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE	reach trench 75 feet Trench Spacing: 9 Feet on Center re installed on contour at a Soil Cover: 6 inches re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed re installed on contour at a soil Cover shall not exceed
Pump Tank Size	each trench 75
Pump Tank Size	each trench 75
Pump Tank Size	reach trench 75 feet Trench Spacing: 9 Feet on Center see installed on contour at a Soil Cover: 6 inches he Depth of: 18" - 24" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches total ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. The type specified on the application. I accept the specifications of this permit. Date: Changes The Construction Authorization shall not be transferred when there is a change in ownership of the site. This
Pump Tank Size	reach trench 75 feet Trench Spacing: 9 Feet on Center see installed on contour at a Soil Cover: 6 inches he Depth of: 18" - 24" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches total ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. The type specified on the application. I accept the specifications of this permit. Date: Changes The Construction Authorization shall not be transferred when there is a change in ownership of the site. This
Pump Tank Size	reach trench 75 feet Trench Spacing: 9 Feet on Center Soil Cover: 6 inches he installed on contour at a Soil Cover: 6 inches he Depth of: 18" - 24" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches total ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. A. The type specified on the application. I accept the specifications of this permit. Date: Changes The Construction Authorization shall not be transferred when there is a change in ownership of the site. This Sewage Treatment and Disposal and to the conditions of this permit. SEE ATTACHED SITE SKETCH
Pump Tank Size	reach trench 75 feet Trench Spacing: 9 Feet on Center see installed on contour at a Soil Cover: 6 inches he Depth of: 18" - 24" inches (Maximum soil cover shall not exceed shall be level to +/-1/4" 36" above the trench bottom) Aggregate Depth: inches above pipe inches total ANY PART OF SEPTIC SYSTEM OR REPAIR AREA. The type specified on the application. I accept the specifications of this permit. Date: Changes The Construction Authorization shall not be transferred when there is a change in ownership of the site. This

Harnett County Department of Public Health Site Sketch

Property Location: 5926 Ro	osser Pittman Rd (SR1215)	
Issued To: Weaver Homes	Subdivision Miriam Ring	Lot # 3
	11/1/1/11	Date: 08-27-21
Authorized State Agent:	IUM 11- REHS	Date: 00-27-21

