Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

Waster to Manuar Haman	PROPERTY LOCATION: 3900 ROS		LOT # 4
ISSUED TO: Weaver Homes NEW REPAIR EXPANSION	SUBDIVISION Miriam Ring	quired prior to Construction Author	
NEW REPAIR EXPANSION Structure: 35' x 38' SFD	site improvements rec	faired prior to construction Author	nzation issuance.
Proposed Wastewater System Type: 25% reduction			
Projected Daily Flow: 360 GPD			
	max		
Basement Yes X No	11144		
Pump Required: ☐Yes ☐ No ☒ May be required based on final lo	cation and elevations of facilities		
Type of Water Supply: Community Public Well Distan		Permit valid for:	▼ Five years
Permit conditions:			☐ No expiration
TOTAL CONSTITUTION			
11 1			
Authorized State Agent:: Meh Me REHS	Date: 08-27-21		TACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other	permits. The permit holder is responsible for che	cking with appropriate governing bodies in	n meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.	Permit shall not be affected by a change in own	ership of the site. This permit is subject to	compliance with the provisions of
the Laws and Rules for sewage freatment and Disposal and to Conditions of this permit.			
C			
Constr	uction Authorization.		
	uired for Building Permit)		
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957,	.1958. and .1959 are incorporated by references	into this permit and shall be met. System	s shall be installed in accordance
with the attached system layout.			
ISSUED TO: Weaver Homes	PROPERTY LOCATION: 5908	Rosser Pittman Ro	(SR1215)
1330ED TO. TY GOVERN THEM ISO	SUBDIVISION Miriam Rin		LOT # 4
Facility Type: 35' x 38' SFD	Expansion Repair	19	
Basement? Yes No Basement Fixtures? Yes	⊠ No		
	△ NO	# * * B W	
			360 CPD
,		(Initial) Wastewater Flow:	360 GPD
(See note below, if applicable)	(D:-)	(Initial) Wastewater Flow:	360 GPD
(See note below, if applicable) 25% reduction	(Repair)	(Initial) Wastewater How:	360 GPD
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Number of trenc	nes <u>1</u>		
(See note below, if applicable)	nes 1 each trench 225 feet	Trench Spacing: 9	Feet on Center
(See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Frenches shall be	nes 1 vach trench 225 installed on contour at a	Trench Spacing: 9 Soil Cover: 6	_ Feet on Center
(See note below, if applicable □) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Frenches shall be	nes 1 each trench 225 feet	Trench Spacing: 9	_ Feet on Center
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Fxact length of exact	nes 1 vach trench 225 installed on contour at a	Trench Spacing: 9 Soil Cover: 6	_ Feet on Center inches not exceed
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Fxact length of exact	nes 1 vach trench 225 installed on contour at a Depth of: 18" - 24" inches	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall	_ Feet on Center inches not exceed
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions)	nes 1 vach trench 225 installed on contour at a Depth of: 18" - 24" inches	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall	_ Feet on Center inches not exceed
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions)	nes 1 vach trench 225 installed on contour at a Depth of: 18" - 24" inches	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot	_ Feet on Center .inches not exceed ttom)
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Sizegallons Frenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM	nes 1 rach trench 225 feet installed on contour at a Depth of: 18" - 24" inches shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall	_ Feet on Center .inches not exceed ttom) inches below pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Trenches shall be Maximum Trench (Trench bottoms in all directions)	nes 1 rach trench 225 feet installed on contour at a Depth of: 18" - 24" inches shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot	_ Feet on Center _inches not exceed ttom)inches below pipeinches above pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Frenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM Conditions:	nes 1 rach trench 225 rinstalled on contour at a Depth of: 18" - 24" rinches shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth:	_ Feet on Center _inches not exceed ttom)inches below pipeinches above pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Frenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM Conditions:	nes 1 rach trench 225 installed on contour at a Depth of: 18" - 24" inches shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth:	_ Feet on Center _inches not exceed ttom)inches below pipeinches above pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Frenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM Conditions:	nes 1 rach trench 225 installed on contour at a Depth of: 18" - 24" inches shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth:	_ Feet on Center _inches not exceed ttom)inches below pipeinches above pipe
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Sizegallons Frenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA	nes 1 rach trench 225 rest installed on contour at a Depth of: 18" - 24" reshall be level to +/-1/4" NY PART OF SEPTIC SYSTEM OR	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth: REPAIR AREA.	_ Feet on Center _inches not exceed ttom) inches below pipe inches above pipe inches total
(See note below, if applicable) 25% reduction Installation Requirements/Conditions Septic Tank Size 1000gallons Pump Tank Sizegallons Frenches shall be Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM Conditions:	nes 1 rach trench 225 rest installed on contour at a Depth of: 18" - 24" reshall be level to +/-1/4" NY PART OF SEPTIC SYSTEM OR	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth: REPAIR AREA.	_ Feet on Center _inches not exceed ttom) inches below pipe inches above pipe inches total
See note below, if applicable 25% reduction 25% reductions 25% reduction 25% reduction 25% reductions 25	thes 1 I pack trench 225 Installed on contour at a Depth of: 18" - 24" Inches shall be level to +/-1/4" NY PART OF SEPTIC SYSTEM OR inches type specified on the application of the type specified on the application in	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth: REPAIR AREA.	_ Feet on Center _inches not exceed ttom) inches below pipe inches above pipe inches total this permit.
See note below, if applicable 25% reduction 25% reductions 25% reduction 25% reduction 25% reductions 25	thes 1 I pack trench 225 Installed on contour at a Depth of: 18" - 24" Inches shall be level to +/-1/4" NY PART OF SEPTIC SYSTEM OR inches type specified on the application of the type specified on the application in	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth: REPAIR AREA.	_ Feet on Center _inches not exceed ttom) inches below pipe inches above pipe inches total this permit.
See note below, if applicable 25% reduction	the second secon	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth: REPAIR AREA. Date: Date: be transferred when there is a change in	_ Feet on Center _inches not exceed ttom) inches below pipe inches above pipe inches total this permit.
See note below, if applicable 25% reduction 25% reductions 25% reduction 25% reduction 25% reductions 25	the second secon	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth: REPAIR AREA. Date: Date: be transferred when there is a change in	_ Feet on Center _inches not exceed ttom) inches below pipe inches above pipe inches total this permit.
See note below, if applicable 25% reduction 1000	rest 1 reach trench 225 feet installed on contour at a Depth of: 18" - 24" inches shall be level to +/-1/4" NY PART OF SEPTIC SYSTEM OR the type specified on the application thanges. The Construction Authorization shall not the condition in the same of the condition o	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth: REPAIR AREA. Date: Date: be transferred when there is a change in ions of this permit. SEE	_ Feet on Center _inches not exceed ttom) inches below pipe inches above pipe inches total this permit.
See note below, if applicable 25% reduction 18	rest 1 reach trench 225 feet installed on contour at a Depth of: 18" - 24" inches shall be level to +/-1/4" NY PART OF SEPTIC SYSTEM OR the type specified on the application thanges. The Construction Authorization shall not the condition in the same of the condition o	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench bot Aggregate Depth: REPAIR AREA. Date: Date: be transferred when there is a change in ions of this permit. SEE	_ Feet on Center _inches not exceed ttom) inches below pipe inches above pipe inches total this permit.

Harnett County Department of Public Health Site Sketch

Property Location: 5908 Rosser Pittman Rd (SR1215) Issued To: Weaver Homes Subdivision Miriam Ring Lot # 4 Date: 08-27-21 Authorized State Agent: N 15-30.43.M S 77°17'26"W (ω) DRIVEWAY EASEMENT SP.TT 211.11.53.E S 11.11.53.E

NCSB # 1215 ROSSER PITTMAN RD. 60' RW