



Hatch Legend

	2nd Floor Bearing Walls @ 8' 1-1/2"
	= Denotes Left End of Truss (Reference Engineered Truss Drawing)
	Do Not Erect Trusses Backwards

All Truss Reactions are Less than 3,000 lbs. Unless Noted Otherwise.

-- Denotes Reaction Greater than 3,000 lbs.

Truss Placement Plan
SCALE: 1/4" = 1'

HANGER LEGEND

	= USP LUGT2 / 2-Ply Tie-Down
	= USP HUS26 / Single 2x Hanger

LOAD CHART FOR JACK STUDS

NO. JACKS	SPACING	LOAD	NO. JACKS	SPACING	LOAD
1700	1	2550	3400	2	1275
3400	2	5100	5100	3	850
5100	3	7650	6800	4	680
6800	4	10200	8500	5	510
8500	5	12750	10200	6	340
10200	6	15300	11900	7	255
11900	7		13600	8	170
13600	8		15300	9	85

BUILDER	Watermark Homes
JOB NAME	Lot 74 South Creek
PLAN	The Palmetto III / 3 Car / GR
SEAL DATE	11/4/20
QUOTE #	Quote #
JOB #	J1120-5315

CITY / CO.	Harnett Co. / Harnett
ADDRESS	Lot 74 South Creek
MODEL	Roof
DATE REV.	11/12/20
DRAWN BY	Curtis Quick
SALES REP.	Anthony Williams

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSH-B1 and BCSH-B3 provided with the truss delivery package or online @ sbcindustry.com

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature: Curtis Quick
Curtis Quick

ROOF & FLOOR TRUSSES & BEAMS

Reilly Road Industrial Park
Fayetteville, N.C. 28309
Phone: (910) 864-8787
Fax: (910) 864-4444