

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	A01	GABLE	2	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:17 2021 Page 1
ID:KceFwG7y3ILnKoF4owlohVyTryG-XQ1ouoELixqWpicbQ6acJziDCqy0GX650f59lyTrau

0-10-8	16-8-0	33-4-0
0-10-8	16-8-0	16-8-0

Scale = 1:55.8




Plate Offsets (X,Y)-- [4:0-2-8,0-2-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.08	Vert(LL)	-0.00	1	n/r	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.05	Vert(CT)	0.00	1	n/r		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.14	Horz(CT)	0.00	20	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2018/TPI2014						Weight: 205 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 11-29

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 33-4-0.
 (lb) - Max Horz 2=147(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 31, 32, 33, 34, 35, 36, 37, 28, 27, 25, 24, 23, 22, 21
 Max Grav All reactions 250 lb or less at joint(s) 2, 29, 31, 32, 33, 34, 35, 36, 37, 28, 27, 25, 24, 23, 22, 21, 20

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; B=45ft; L=33ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -0-10-8 to 2-8-0, Exterior(2N) 2-8-0 to 16-8-0, Corner(3R) 16-8-0 to 20-0-0, Exterior(2N) 20-0-0 to 33-4-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 31, 32, 33, 34, 35, 36, 37, 28, 27, 25, 24, 23, 22, 21.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	A02	Common	10	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:19 2021 Page 1
ID:KceFwG7y3LnKoF4owlohVyTryG-To9YJUfBY4E20m_YXd4OOng0HhU0FPZK8CEAYTras



Scale = 1:59.2





Plate Offsets (X,Y)-- [2:0-2-0,0-1-8]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.00	TC 0.91	Vert(LL)	-0.33 11-13	>982	240	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.93	Vert(CT)	-0.54 11-13	>603	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.83	Horz(CT)	0.05 9	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-MS						
								Weight: 165 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2 *Except*
T3: 2x4 SP No.1
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 1 Row at midpt 5-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=68/Mechanical, 9=1557/0-3-8 (min. 0-2-1), 2=1095/0-3-8 (min. 0-1-8)
Max Horz 2=147(LC 11)
Max Uplift 8=55(LC 23), 9=35(LC 12), 2=63(LC 12)
Max Grav 8=145(LC 24), 9=1740(LC 19), 2=1212(LC 17)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-21=-2043/89, 3-21=-1965/122, 3-4=-1513/141, 4-22=-1410/160, 5-22=-1407/180,
5-23=-846/164, 6-23=-847/145, 6-7=-952/125, 7-24=0/582, 8-24=-12/465
BOT CHORD 2-14=-35/1851, 13-14=-65/1710, 13-25=0/869, 12-25=0/869, 12-26=0/869, 11-26=0/869,
10-11=-13/416, 9-10=-13/416, 8-9=-411/47
WEBS 5-13=-22/943, 7-11=0/630, 7-9=-1698/122, 3-13=-619/157, 3-14=0/272

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=33ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-10-8 to 2-5-8, Interior(1) 2-5-8 to 16-8-0, Exterior(2R) 16-8-0 to 20-0-0, Interior(1) 20-0-0 to 33-4-0 zone; cantilever left and right exposed ; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 9, 2.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	A03	Common	6	1	


Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:20 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-x?jxWqGE2sC5gALA6F8JxcK3hQdGDacYn_tmmyTrar

0-10-8	5-10-11	8-7-0	16-8-0	24-9-0	27-5-5	33-4-0	34-2-8
0-10-8	5-10-11	2-8-5	8-1-0	8-1-0	2-8-5	5-10-11	0-10-8

4x6 =

Scale = 1:59.2



0-0-8	5-10-11	8-7-0	12-0-0	16-8-0	21-4-0	24-9-0	27-5-5	33-3-8	33-4-0
0-0-8	5-10-3	2-8-5	3-5-0	4-8-0	4-8-0	3-5-0	2-8-5	5-10-3	0-0-8

Plate Offsets (X,Y)-- [2:0-2-0,0-1-8], [8:0-2-0,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.77	Vert(LL)	-0.33	12-14	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.91	Vert(CT)	-0.58	12-14	>692		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.37	Horz(CT)	0.09	8	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS						
	Code IRC2018/TPI2014							
							Weight: 167 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1 *Except*
 B3: 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-

TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=1386/0-3-8 (min. 0-1-12), 2=1386/0-3-8 (min. 0-1-13)
 Max Horz 2=148(LC 11)
 Max Uplift 8=69(LC 12), 2=69(LC 12)
 Max Grav 8=1533(LC 18), 2=1533(LC 17)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-22=-2741/114, 3-22=-2662/147, 3-4=-2223/167, 4-23=-2122/186, 5-23=-2117/206,
 5-24=-2117/206, 6-24=-2122/186, 6-7=-2223/167, 7-25=-2662/146, 8-25=-2740/114
 BOT CHORD 2-15=-35/2479, 14-15=-65/2343, 14-26=0/1513, 13-26=0/1513, 12-27=0/1513, 12-27=0/1513,
 11-12=-68/2234, 10-11=-68/2234, 8-10=-38/2368
 WEBS 5-14=-22/934, 5-12=-22/935, 7-12=-611/156, 7-10=0/265, 3-14=-610/156, 3-15=0/266

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; B=45ft; L=33ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-10-8 to 2-5-8, Interior(1) 2-5-8 to 16-8-0, Exterior(2R) 16-8-0 to 20-0-0, Interior(1) 20-0-0 to 34-2-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 2.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	A04	COMMON	4	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:21 2021 Page 1
 ID:KceFwG7y3ILnKof4owlohVyTryG-QBGJkAHspAKylJwNfyFYUpsBBqyWy_Pi0edJl3yTrao



Scale = 1:56.4



0-0-8	5-10-11	8-7-0	12-0-0	21-4-0	24-9-0	27-5-5	29-3-8	33-4-0
0-0-8	5-10-3	2-8-5	3-5-0	9-4-0	3-5-0	2-8-5	1-10-3	4-0-8

Plate Offsets (X,Y)-- [2:0-2-0,0-1-8], [8:0-2-0,0-1-8]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.00	TC 0.91	Vert(LL)	-0.33 12-14	>999	240	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.97	Vert(CT)	-0.54 12-14	>655	180		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.53	Horz(CT)	0.07 10	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-MS						
								Weight: 168 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 7-10
	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=120/0-3-0 (min. 0-1-8), 10=1432/0-3-8 (min. 0-1-14), 2=1219/0-3-8 (min. 0-1-9)
 Max Horz 2=-148(LC 10)
 Max Uplift 8=-102(LC 12), 10=-39(LC 12), 2=-69(LC 12)
 Max Grav 8=173(LC 24), 10=1610(LC 2), 2=1347(LC 17)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-22=-2339/108, 3-22=-2261/140, 3-4=-1811/162, 4-23=-1709/181, 5-23=-1705/201,
 5-24=-1377/194, 6-24=-1383/174, 6-7=-1483/155, 7-25=0/418, 8-25=0/289
 BOT CHORD 2-15=-30/2120, 14-15=-60/1980, 14-26=0/1146, 13-26=0/1146, 13-27=0/1146, 12-27=0/1146,
 11-12=-60/1150, 10-11=-60/1150, 10-28=-273/23, 8-28=-273/23
 WEBS 5-14=-26/933, 5-12=-10/362, 7-12=-102/273, 7-10=-1924/94, 3-14=-616/155, 3-15=0/274

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; B=45ft; L=33ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-10-8 to 2-5-8, Interior(1) 2-5-8 to 16-8-0, Exterior(2R) 16-8-0 to 20-0-0, Interior(1) 20-0-0 to 34-2-8 zone; cantilever left and right exposed ; end vertical left and right exposed; porch right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BC DL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10, 2 except (jt=lb) 8=102.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	A05	Common	6	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:23 2021 Page 1
 ID:KceFwG7y3lLnKof4owlohVyTryG-MaO39rI6LnagXd4InNh0ZEyWidesQt_?Uy6QNxyTrao

0-10-8	5-10-11	8-7-0	11-3-5	16-8-0	22-0-11	24-9-0	27-5-5	33-4-0	34-2-8
0-10-8	5-10-11	2-8-5	2-8-5	5-4-11	5-4-11	2-8-5	2-8-5	5-10-11	0-10-8

Scale: 3/16"=1'



0-0-8	5-10-11	8-7-0	12-0-0	16-8-0	21-4-0	24-9-0	27-5-5	33-3-8	33-4-0
0-0-8	5-10-3	2-8-5	3-5-0	4-8-0	4-8-0	3-5-0	2-8-5	5-10-3	0-0-8

Plate Offsets (X,Y)-- [2:0-2-4,Edge], [8:0-2-4,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.00	TC 0.97	Vert(LL)	-0.42	13	>957	240	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.98	Vert(CT)	-0.73	13	>546	180	MT18HS	244/190
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.59	Horz(CT)	0.10	8	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-MS							Weight: 180 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.2 *Except*
 B1: 2x4 SP No.1, B3: 2x4 SP DSS
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing. Except:
 6-0-0 oc bracing: 14-17

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1472/0-3-8 (min. 0-2-0), 8=1472/0-3-8 (min. 0-2-0)
 Max Horz 2=148(LC 11)
 Max Uplift 2=-18(LC 12), 8=-18(LC 12)
 Max Grav 2=1706(LC 17), 8=1706(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-26=-3113/4, 3-26=-3033/37, 3-4=-2618/49, 4-27=-2518/68, 5-27=-2512/88,
 5-28=-2516/87, 6-28=-2522/67, 6-7=-2623/48, 7-29=-3033/37, 8-29=-3112/4
 BOT CHORD 2-19=0/2811, 18-19=0/2688, 18-30=0/1886, 30-31=0/1886, 16-31=0/1886, 13-16=0/1886,
 13-32=0/1886, 12-32=0/1886, 11-12=0/2581, 10-11=0/2581, 8-10=0/2700
 WEBS 17-18=-3/963, 5-17=0/1136, 5-14=0/1144, 12-14=-1/971, 7-12=-595/162, 3-18=-596/161


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=33ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-10-8 to 2-5-8, Interior(1) 2-5-8 to 16-8-0, Exterior(2R) 16-8-0 to 20-0-0, Interior(1) 20-0-0 to 34-2-8 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	A06	Common	3	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:24 2021 Page 1
 ID:KceFwG7y3lLnKof4owlohVyTryG-qmyRMBJk65iX9nfxL4DF5SuhU1zr9KC8icrvOyTran



Scale: 3/16"=1'





Plate Offsets (X,Y)-- [2:0-2-4,Edge], [8:0-2-4,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.00	TC 0.97	Vert(LL)	-0.42	12	>957	240	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 1.00	Vert(CT)	-0.73	12	>546	180	MT18HS	244/190
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.59	Horz(CT)	0.10	8	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-MS							Weight: 178 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.2 *Except*
 B3: 2x4 SP DSS, B1: 2x4 SP No.1
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing. Except:
 6-0-0 oc bracing: 13-16

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=1419/Mechanical, 2=1472/0-3-8 (min. 0-2-0)
 Max Horz 2=147(LC 11)
 Max Uplift 2=18(LC 12)
 Max Grav 8=1660(LC 18), 2=1707(LC 17)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-25=-3113/4, 3-25=-3034/37, 3-4=-2620/49, 4-26=-2519/69, 5-26=-2513/88,
 5-27=-2519/91, 6-27=-2524/72, 6-7=-2625/52, 7-28=-3040/48, 8-28=-3118/20
 BOT CHORD 2-18=0/2807, 17-18=0/2685, 17-29=0/1882, 29-30=0/1882, 15-30=0/1882, 12-15=0/1882,
 12-31=0/1882, 11-31=0/1882, 10-11=0/2586, 9-10=0/2586, 8-9=0/2708
 WEBS 16-17=-4/963, 5-16=0/1136, 5-13=0/1146, 11-13=-2/973, 7-11=-598/163, 3-17=-596/161


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=33ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-10-8 to 2-5-8, Interior(1) 2-5-8 to 16-8-0, Exterior(2R) 16-8-0 to 20-0-0, Interior(1) 20-0-0 to 33-4-0 zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) All plates are MT20 plates unless otherwise indicated.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - 6) Refer to girder(s) for truss to truss connections.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2.
 - 8) This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	A07	Common	4	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:25 2021 Page 1
 ID:KceFwG7y3lLnKoF4owlohVyTryG-lyWqaXKMtOqOmxD8uokUef1vPRKAurplXGbXRqyTram



Scale = 1:58.6




Plate Offsets (X,Y)-- [2:0-2-0,0-1-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.77	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.93	Vert(LL) -0.33 11-13 >999 240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.37	Vert(CT) -0.58 11-13 >692 180		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.09 8 n/a n/a		
	Code IRC2018/TPI2014			Weight: 165 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.1
 BOT CHORD 2x4 SP No.1 *Except*
 B3: 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
 2-2-0 oc bracing: 8-9.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 8=1333/Mechanical, 2=1387/0-3-8 (min. 0-1-13)
 Max Horz 2=147(LC 11)
 Max Uplift 8=-44(LC 12), 2=-70(LC 12)
 Max Grav 8=1486(LC 18), 2=1533(LC 17)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-21=-2742/114, 3-21=-2663/147, 3-4=-2224/167, 4-22=-2124/186, 5-22=-2118/206,
 5-23=-2119/211, 6-23=-2125/191, 6-7=-2226/172, 7-24=-2669/157, 8-24=-2747/129
 BOT CHORD 2-14=-59/2475, 13-14=-88/2340, 13-25=0/1509, 12-25=0/1509, 12-26=0/1509, 11-26=0/1509,
 10-11=-82/2238, 9-10=-82/2238, 8-9=-57/2376
 WEBS 5-13=-22/935, 5-11=-22/937, 7-11=-614/157, 7-9=0/266, 3-13=-610/156, 3-14=0/266


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=33ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-10-8 to 2-5-8, Interior(1) 2-5-8 to 16-8-0, Exterior(2R) 16-8-0 to 20-0-0, Interior(1) 20-0-0 to 33-4-0 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8, 2.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	B01	GABLE	1	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:26 2021 Page 1
 ID:KceFwG7y3lLnKoF4owlohVyTryG-m94CntL_eiyFO5oKSVFjBtaGLruFdN2RAwK4_GyTral



Scale = 1:36.5



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.04	Vert(LL) -0.00 12 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Vert(CT) 0.00 12 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 12 n/a n/a		
	Code IRC2018/TPI2014			Weight: 105 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 20-8-0.
 (lb) - Max Horz 2=86(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 20, 21, 22, 23, 18, 17, 15, 14, 12
 Max Grav All reactions 250 lb or less at joint(s) 2, 19, 20, 21, 22, 23, 18, 17, 15, 14, 12

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -0-10-8 to 2-4-0, Exterior(2N) 2-4-0 to 10-4-0, Corner(3R) 10-4-0 to 13-4-0, Exterior(2N) 13-4-0 to 21-6-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 20, 21, 22, 23, 18, 17, 15, 14, 12.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job KELLY 22-52-09	Truss B02	Truss Type Common	Qty 6	Ply 1	Job Reference (optional)
-----------------------	--------------	----------------------	----------	----------	--------------------------

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:28 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-iXByCZMFAJCydOyjawHBGHfXGeTN5DCkdDpB29yTraj



Scale = 1:37.7



LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.00	TC 0.34	Vert(LL) -0.06 9-16 >999 240	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.51	Vert(CT) -0.14 9-16 >999 180		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.20	Horz(CT) 0.03 6 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014	Matrix-MS		Weight: 95 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-7-7 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=879/0-3-8 (min. 0-1-8), 6=879/0-3-8 (min. 0-1-8)
Max Horz 2=-86(LC 10)
Max Uplift 2=-52(LC 12), 6=-52(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-17=-1422/177, 3-17=-1383/194, 3-18=-1275/192, 4-18=-1200/208, 4-19=-1200/208,
5-19=-1275/192, 5-20=-1383/194, 6-20=-1422/177
BOT CHORD 2-10=-99/1237, 9-10=-6/820, 8-9=-106/1237, 6-8=-106/1237
WEBS 4-9=-46/488, 5-9=-315/140, 4-10=-46/488, 3-10=-315/140


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 10-4-0, Exterior(2R) 10-4-0 to 13-4-0, Interior(1) 13-4-0 to 21-6-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job KELLY 22-52-09	Truss B03	Truss Type Common Girder	Qty 1	Ply 2	Job Reference (optional)
-----------------------	--------------	-----------------------------	----------	----------	--------------------------

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:30 2021 Page 1
ID:KceFwG7y3ILnKoF4owlohVyTryG-fwJdFOVhxTgti65hLJfLkwiSC5Z7v15XIH71yTrah



Scale = 1:37.2

0-0-8	5-7-0	10-4-0	15-1-0	20-7-8	22-8-0
0-0-8	5-6-8	4-9-0	4-9-0	5-6-8	0-0-8
Plate Offsets (X,Y)-- [1:0-4-0,0-1-15], [5:0-4-0,0-1-15], [7:0-3-9,0-3-0]					

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.00	TC 0.16	Vert(LL)	-0.05	8	>999	240	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.30	Vert(CT)	-0.07	6-8	>999	180		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.25	Horz(CT)	0.02	5	n/a	n/a		
BCDL 10.0	Code IRC2018/TPI2014		Matrix-MS							
									Weight: 254 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x8 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=1390/0-3-8 (min. 0-1-8), 5=1494/0-3-8 (min. 0-1-8)
 Max Horz 1=-77(LC 6)
 Max Uplift1=-271(LC 8), 5=-308(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-2491/519, 2-3=-1735/395, 3-4=-1735/395, 4-5=-2504/524
 BOT CHORD 1-14=-414/2180, 14-15=-414/2180, 9-15=-414/2180, 9-16=-414/2180, 16-17=-414/2180,
 8-17=-414/2180, 8-18=-418/2192, 18-19=-418/2192, 7-19=-418/2192, 6-7=-418/2192,
 6-20=-418/2192, 20-21=-418/2192, 5-21=-418/2192, 5-22=-311/1656
 WEBS 3-8=-278/1225, 4-8=-819/209, 4-6=-87/452, 2-8=-806/204, 2-9=-82/440

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-7-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=271, 5=308.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 125 lb down and 75 lb up at 2-1-4, 125 lb down and 75 lb up at 4-1-4, 125 lb down and 75 lb up at 6-1-4, 125 lb down and 75 lb up at 8-1-4, 125 lb down and 75 lb up at 10-1-4, 125 lb down and 75 lb up at 12-1-4, 125 lb down and 75 lb up at 14-1-4, 125 lb down and 75 lb up at 16-1-4, and 125 lb down and 75 lb up at 18-1-4, and 132 lb down and 68 lb up at 20-1-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	B03	Common Girder	1	2	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:30 2021 Page 2
ID:KceFwG7y3ILnKoF4owlohVyTryG-fwJdFOVhxTgti65hLJfLkwiSC5Z7v15XIH71yTrah

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.00

Uniform Loads (plf)

Vert: 1-3=-60, 3-5=-60, 1-5=-20



Concentrated Loads (lb)

Vert: 8=-125(B) 14=-125(B) 15=-125(B) 16=-125(B) 17=-125(B) 18=-125(B) 19=-125(B) 20=-125(B) 21=-125(B) 22=-132(B)

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	C01	GABLE	1	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:31 2021 Page 1
ID:KceFwG7y3ILnKoF4owlohVyTryG-76t5qbP7SEbXUshIF2rutwH74sbYldbAJB2rfUyTrag



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.03	Vert(LL) -0.00 8 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.03	Vert(CT) -0.00 8 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 8 n/a n/a		
	Code IRC2018/TPI2014			Weight: 53 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 12-0-0.
(lb) - Max Horz 2=-53(LC 10)
Max Uplift All uplift 100 lb or less at joint(s) 2, 8, 13, 14, 11, 10
Max Grav All reactions 250 lb or less at joint(s) 2, 8, 12, 13, 14, 11, 10

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Corner(3E) -0-10-8 to 2-0-0, Exterior(2N) 2-0-0 to 6-0-0, Corner(3R) 6-0-0 to 9-0-0, Exterior(2N) 9-0-0 to 12-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8, 13, 14, 11, 10.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	C02	Common	2	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:32 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-bIRT2wPIDYjO60GUpmM7Q7qBhFri13hKYrnOBWytTraf



Scale = 1:22.7




Plate Offsets (X,Y)-- [2:0-0-8,Edge], [4:0-0-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.45	Vert(LL)	-0.04	6-9	>999	240	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.42	Vert(CT)	-0.08	6-9	>999	180		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.11	Horz(CT)	0.01	4	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-MS							
	Code IRC2018/TPI2014								
								Weight: 45 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=533/0-3-8 (min. 0-1-8), 4=532/0-3-8 (min. 0-1-8)
 Max Horz 2=-53(LC 10)
 Max Uplift 2=-41(LC 12), 4=-41(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-13=-676/166, 13-14=-609/171, 3-14=-607/187, 3-15=-607/187, 15-16=-609/171,
 4-16=-676/166
 BOT CHORD 2-6=-58/543, 4-6=-58/543
 WEBS 3-6=0/281


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 6-0-0, Exterior(2R) 6-0-0 to 9-0-0, Interior(1) 9-0-0 to 12-10-8 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	C03	Common Girder	1	2	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:33 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-3V?rFGQN_srFk9rgMTtMzLMLf25mNLtNvXyjMyTrae



Scale = 1:20.9

Plate Offsets (X,Y)-- [1:0-3-1,0-1-15], [3:0-3-1,0-1-15]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.64	Vert(LL)	-0.07	4-6	>999	240	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.99	Vert(CT)	-0.14	4-6	>999	180		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.66	Horz(CT)	0.02	3	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-MS							
	Code IRC2018/TPI2014								

Weight: 122 lb FT = 20%

LUMBER-

TOP CHORD 2x4 SP No.2
BOT CHORD 2x8 SP No.1
WEBS 2x4 SP No.2

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-2-5 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=5966/0-3-8 (req. 0-3-15), 3=4423/0-3-8 (min. 0-2-13)
Max Horz 1=-44(LC 25)
Max Uplift 3=-23(LC 8)
Max Grav 1=6626(LC 2), 3=4754(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-6389/0, 2-3=-6392/0
BOT CHORD 1-9=0/5697, 9-10=0/5697, 4-10=0/5697, 4-11=0/5697, 11-12=0/5697, 3-12=0/5697
WEBS 2-4=0/5355

NOTES-

- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-5-0 oc.
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- WARNING: Required bearing size at joint(s) 1 greater than input bearing size.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1614 lb down at 0-2-4, 1610 lb down at 0-10-4, 1607 lb down at 2-11-12, 1433 lb down and 64 lb up at 4-11-12, 1433 lb down and 64 lb up at 6-11-12, and 1433 lb down and 64 lb up at 8-11-12, and 1435 lb down and 62 lb up at 10-11-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.00

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	C03	Common Girder	1	2	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:33 2021 Page 2
 ID:KceFwG7y3lLnKoF4owlohVyTryG-3V?rFGQN_srFk9rgMTtMzLMILf25mNLtnVXyjMyTrae

LOAD CASE(S) Standard

Uniform Loads (plf)

Vert: 1-2=-60, 2-3=-60, 1-3=-20


Concentrated Loads (lb)

Vert: 1=-1406(B) 6=-1402(B) 8=-1314(B) 9=-1399(B) 10=-1313(B) 11=-1313(B) 12=-1313(B)

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V01	GABLE	2	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:34 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-XhZDScR0l9z6LJPswBObVYvXQ3ZVVz9c?9GVGpyTrad



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.00	TC 0.43	Vert(LL)	n/a	-	n/a	999	MT20
TCDL 10.0	Lumber DOL	1.15	BC 0.27	Vert(CT)	n/a	-	n/a	999	244/190
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.11	Horz(CT)	0.00	5	n/a	n/a	
BCDL 10.0	Code IRC2018/TPI2014		Matrix-S						
								Weight: 62 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 17-8-0.
(lb) - Max Horz 1=63(LC 11)
Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 9, 6
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 8=430(LC 1), 9=445(LC 23), 6=445(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 3-8=-301/80, 2-9=-354/190, 4-6=-354/190


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-7-9 to 3-7-9, Interior(1) 3-7-9 to 8-10-0, Exterior(2R) 8-10-0 to 11-10-0, Interior(1) 11-10-0 to 17-0-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 9, 6.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V02	GABLE	2	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:35 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-?t7cgySeWT5zzT_3Uuvq2mSftTu1EQfmEp02oFyTrac



Scale = 1:22.5

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.00	TC 0.58	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.38	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.09	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2018/TPI2014	Matrix-S		Weight: 45 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=226/13-8-0 (min. 0-1-8), 3=226/13-8-0 (min. 0-1-8), 4=540/13-8-0 (min. 0-1-8)
Max Horz 1=-47(LC 10)
Max Uplift1=-20(LC 12), 3=-20(LC 12)
Max Grav 1=229(LC 23), 3=229(LC 24), 4=540(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-4=-358/160


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-7-9 to 3-7-9, Interior(1) 3-7-9 to 6-10-0, Exterior(2R) 6-10-0 to 9-10-0, Interior(1) 9-10-0 to 13-0-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V03	Valley	2	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:36 2021 Page 1
ID:KceFwG7y3LlnKoF4owlohVyTryG-T4g_tISGHnDqbdZF2cQ3az_wotHUzuYvTTIcKhyTrab



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.25	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.18	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 31 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=153/9-7-0 (min. 0-1-8), 3=153/9-7-0 (min. 0-1-8), 4=366/9-7-0 (min. 0-1-8)
 Max Horz 1=-32(LC 10)
 Max Uplift 1=-13(LC 12), 3=-13(LC 12)
 Max Grav 1=155(LC 23), 3=155(LC 24), 4=366(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-7-9 to 3-7-9, Interior(1) 3-7-9 to 4-10-0, Exterior(2R) 4-10-0 to 7-10-0, Interior(1) 7-10-0 to 9-0-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V04	Valley	2	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:37 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-yGEM5eTu24LhCn8RbJxl7BX7sGbdiLb3i7V9s7yTraa



Scale = 1:11.3

LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES		GRIP	
TCLL	20.0	Plate Grip DOL	1.00	TC	0.10	Vert(LL)	n/a	-	n/a	999	MT20	244/190	
TCDL	10.0	Lumber DOL	1.15	BC	0.25	Vert(CT)	n/a	-	n/a	999	Weight: 16 lb FT = 20%		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Horz(CT)	0.00	3	n/a	n/a			
BCDL	10.0	Code IRC2018/TPI2014		Matrix-P									

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-8-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=176/5-7-0 (min. 0-1-8), 3=176/5-7-0 (min. 0-1-8)
Max Horz 1=17(LC 11)
Max Uplift 1=-6(LC 12), 3=-6(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V05	GABLE	1	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:38 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-QSokl_UWpOTYqxje91TXgO4GagzjRotCwnEjPayTraZ



Scale = 1:27.9

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.23	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.13	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.06	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
	Code IRC2018/TPI2014			Weight: 61 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 16-11-0.
(lb) - Max Horz 1=60(LC 11)
Max Uplift All uplift 100 lb or less at joint(s) 9, 6
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 8=260(LC 1), 9=373(LC 23), 6=373(LC 24)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-9=-279/156, 4-6=-279/156


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-7-9 to 3-7-9, Interior(1) 3-7-9 to 8-5-8, Exterior(2R) 8-5-8 to 11-5-8, Interior(1) 11-5-8 to 16-3-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 6.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V06	GABLE	1	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:39 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-ufM6WKV8aibPS4lqjk_mCccN?4FgAEpL9R_Gx0yTraY



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.50	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.34	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.08	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 42 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=212/12-11-0 (min. 0-1-8), 3=212/12-11-0 (min. 0-1-8), 4=508/12-11-0 (min. 0-1-8)
 Max Horz 1=-45(LC 10)
 Max Uplift1=-19(LC 12), 3=-19(LC 12)
 Max Grav 1=215(LC 23), 3=215(LC 24), 4=508(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-4=-337/154


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-7-9 to 3-7-9, Interior(1) 3-7-9 to 6-5-8, Exterior(2R) 6-5-8 to 9-5-8, Interior(1) 9-5-8 to 12-3-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V07	Valley	1	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:39 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-ufM6WKV8aibPS4lqjk_mCccQY4ldAFRL9R_Gx0yTraY



Scale: 3/4"=1'

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.28	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.15	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 28 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=155/8-10-0 (min. 0-1-8), 3=155/8-10-0 (min. 0-1-8), 4=302/8-10-0 (min. 0-1-8)
 Max Horz 1=29(LC 11)
 Max Uplift 1=-19(LC 12), 3=-19(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-7-9 to 3-7-9, Interior(1) 3-7-9 to 4-5-8, Exterior(2R) 4-5-8 to 7-5-8, Interior(1) 7-5-8 to 8-3-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job KELLY 22-52-09	Truss V08	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
-----------------------	--------------	----------------------	----------	----------	--------------------------

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:40 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-MrwVjWmL?jF3Et0HRV?lp9eXUeavikVO5jpTSyTraX




Plate Offsets (X,Y)-- [2:0-2-0,Edge]		4-11-0		4-10-8	
LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.07	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.17	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 13 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-11-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=146/4-10-0 (min. 0-1-8), 3=146/4-10-0 (min. 0-1-8)
Max Horz 1=14(LC 11)
Max Uplift 1=-5(LC 12), 3=-5(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V09	Valley	1	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:41 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-q1Utw?WP6Jr6hOSDq90EH1hnqu?Te9_edlTN?vyTraW



Scale = 1:14.8

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.23	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.00	BC 0.12	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2018/TPI2014			Weight: 26 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=142/8-2-0 (min. 0-1-8), 3=142/8-2-0 (min. 0-1-8), 4=276/8-2-0 (min. 0-1-8)
Max Horz 1=27(LC 11)
Max Uplift 1=-17(LC 12), 3=-17(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-


- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) 0-7-9 to 3-7-9, Interior(1) 3-7-9 to 4-1-8, Exterior(2R) 4-1-8 to 7-1-8, Interior(1) 7-1-8 to 7-7-7 zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
KELLY 22-52-09	V10	Valley	1	1	

Carolina Structural Systems, Star, NC 27356

Run: 8.420 s Feb 10 2021 Print: 8.420 s Feb 10 2021 MiTek Industries, Inc. Wed Oct 13 12:03:42 2021 Page 1
ID:KceFwG7y3lLnKoF4owlohVyTryG-IE2F8LX1tdzzJY1POsXTqEE?MHLxNcqorPCwYLyTraV



Scale = 1:7.8

LOADING (psf)		SPACING-		CSI.		DEFL.				PLATES	GRIP	
TCLL	20.0	2-0-0	Plate Grip DOL	1.00	TC	0.05	in	(loc)	l/defl	L/d	MT20	244/190
TCDL	10.0	Lumber DOL	1.15	BC	0.11	Vert(LL)	n/a	-	n/a	999		
BCLL	0.0 *	Rep Stress Incr	YES	WB	0.00	Vert(CT)	n/a	-	n/a	999		
BCDL	10.0	Code IRC2018/TPI2014		Matrix-P		Horz(CT)	0.00	3	n/a	n/a		
											Weight: 11 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-3-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=120/4-2-0 (min. 0-1-8), 3=120/4-2-0 (min. 0-1-8)
Max Horz 1=12(LC 11)
Max Uplift 1=-4(LC 12), 3=-4(LC 12)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-16; Vult=125mph (3-second gust) Vasd=99mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional) and C-C Exterior(2E) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Gable requires continuous bottom chord bearing.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
- This truss is designed in accordance with the 2018 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard