

■ = HUS26 (Qty. 11)■ = HJC26 (Qty. 1)

LOAD CHART FOR JACK STUDS

(MASE) ON LABOR (\$502.51) A (A)

NUMBER OF JACK STUDS ACCURAGE (A CAS) OF

FEADER (\$670.62)

2550 1 5100 2

7650 3

10200 4

12750 5

15300 6

3400 1

10200 3

13600 4

17000 5

6600 2

1700 1 3400 2

▲ = Denotes Left End of Truss (Reference Engineered Truss Drawing)

Truss Placement Plan SCALE: 1/4" = 1'-0"

G + G O NY HEASE	BUILDER	Cates Building	CITY / CO.	Cameron / Harnett	THIS IS A These truss the building sheets for ea is responsible the overall si walls, and co regarding broor online @: Bearing rea prescriptive (derived frof foundations than 3000# be retained specified in retained to
	JOB NAME	Lot 696 Manors at Lexington Plantation	ADDRESS	123 Bow Common Way	
	PLAN	CC-2308 K	MODEL	Roof	
	SEAL DATE	6/17/20	DATE REV.	/ /	
	QUOTE #	Quote #	DRAWN BY	Christine Shivy	
	JOB #	J0721-4255	SALES REP.	Scot Duncan	

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.

These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Christine Shivy

Christine Shivy

ROOF & FLOOR TRUSSES & BEAMS Reilly Road Industrial Park

Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444