## Harnett County Department of Public Health

## Improvement Permit

A building permit cannot be issued with only an Improvement Permit

ICCIED TO: IS I BUILDARE		nont Creek Place (L	
ISSUED TO: JSJ Builders	SUBDIVISION Williams Farr		LOT # 33
NEW REPAIR EXPANSION	Site Improvements r	equired prior to Construction Author	orization Issuance:
Type of Structure: 43' x 52' SFD	-		
Proposed Wastewater System Type: 25% reduction	-		
Projected Daily Flow: 360 GPD			
Number of bedrooms: 3Number of Occupants: 6	max		
Basement Yes No	service and almost on all facilities		
Pump Required: ☐Yes ☐ No ☒ May be required based on final lo Type of Water Supply: ☐ Community ☒ Public ☐ Well Distan	ce from wellfeet	Permit valid for:	Five years
Permit conditions:	ce nom wenreet	Termit valid for.	No expiration
remit conditions.			III No expiration
, 1/			
Authorized State Agent: Mah Che REHV	Date: 11-17-21	SEE A	TACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issuance of other		hecking with appropriate governing bodies	in meeting their requirements. This
site is subject to revocation if the site plan, plat, or the intended use changes. The Improvement	Permit shall not be affected by a change in ow	mership of the site. This permit is subject	o compliance with the provisions of
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this permit.			
Constr	uction Authorization		
(Rec	uired for Building Permit)		
The construction and installation requirements of Rules .1950, .1952, .1954, .1955, .1956, .1957,		es into this permit and shall be met. System	ns shall be installed in accordance
with the attached system layout.			
ISSUED TO: JSJ Builders	DRODERTY LOCATION. SO (	Slenmont Creek Pla	00 (119 4019)
ISSUED TO: 355 Builders			
131 ·· F31 CED	A STATE OF THE STA	Farm	LOT # <u>33</u>
Facility Type: 43' x 52' SFD New	Expansion Repair	r	
Basement? Yes No Basement Fixtures? Yes	× N <sub>0</sub>		2/4
Type of Wastewater System** 25% reduction		(Initial) Wastewater Flow	GPD GPD
(See note below, if applicable )			
25% reduction	(Repair)		
Installation Requirements/Conditions Number of trenc	hes 3		
	each trench 60 feet	Trench Spacing: 9	Feet on Center
, and the second		Soil Cover: 6	
	installed on contour at a	JULI COVEL. O	inches
,	e installed on contour at a	and the second s	_inches
Maximum Trench	Depth of: 18" - 24" inches	(Maximum soil cover shall	not exceed
Maximum Trench (Trench bottoms		and the second s	not exceed
Maximum Trench (Trench bottoms in all directions)	Depth of: 18" - 24" inches	(Maximum soil cover shall	not exceed ottom)
Maximum Trench (Trench bottoms in all directions)	Depth of: 18" - 24" inches	(Maximum soil cover shall 36" above the trench bo	not exceed ottom) inches below pipe
Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM	Depth of: 18" - 24" inches	(Maximum soil cover shall 36" above the trench bo	not exceed oftom)  inches below pipe inches above pipe
Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM	Depth of: 18" - 24" inches	(Maximum soil cover shall 36" above the trench bo	not exceed ottom) inches below pipe
Maximum Trench (Trench bottoms in all directions) Pump Requirements:ft. TDH vsGPM  Conditions:	Depth of: 18" - 24" inches shall be level to +/-1/4"	(Maximum soil cover shall 36" above the trench bo	not exceed oftom)  inches below pipe inches above pipe
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:	Depth of: 18" - 24" inches shall be level to +/-1/4"	(Maximum soil cover shall 36" above the trench bo	not exceed ottom) inches below pipe inches above pipe
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR	(Maximum soil cover shall 36" above the trench bo	not exceed ottom) inches below pipe inches above pipe
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR	(Maximum soil cover shall 36" above the trench bo	not exceed ottom) inches below pipe inches above pipe inches total
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR	(Maximum soil cover shall 36" above the trench bo	not exceed ottom) inches below pipe inches above pipe inches total
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA  **If applicable: understand the system type specified is different from	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR	(Maximum soil cover shall 36" above the trench both Aggregate Depth:  REPAIR AREA.	not exceed ottom) inches below pipe inches above pipe inches total
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD AREA  **If applicable:tunderstand_the_system_type_specified_is_different_from  Owner/Legal Representative_Signature:	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR A.  the type specified on the application	(Maximum soil cover shall 36" above the trench bo Aggregate Depth:  REPAIR AREA.	not exceed  ottom)  inches below pipe inches above pipe inches total  of this permit.
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE.  **If applicable:tunderstand the system type specified is different from  Owner/Legal Representative Signature:  This Construction Authorization is subject to revocation if the site plan, plat, or the intended use	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR A.  the type specified on the application shall no changes. The Construction Authorization shall no	(Maximum soil cover shall 36" above the trench both Aggregate Depth:  Aggregate Depth:  REPAIR AREA.  Date:  Date:  t be transferred when there is a change in	not exceed oftom)  inches below pipe inches above pipe inches total  f this permit.
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR A.  the type specified on the application shall no changes. The Construction Authorization shall no	(Maximum soil cover shall 36" above the trench both Aggregate Depth:  Aggregate Depth:  REPAIR AREA.  Date:  Date:  t be transferred when there is a change in	not exceed  ottom)  inches below pipe inches above pipe inches total  of this permit.
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE.  **If applicable:	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR A.  the type specified on the application shall no changes. The Construction Authorization shall no	(Maximum soil cover shall 36" above the trench both Aggregate Depth:  Aggregate Depth:  REPAIR AREA.  Date:  Date:  t be transferred when there is a change in	not exceed oftom)  inches below pipe inches above pipe inches total  f this permit.
Maximum Trench (Trench bottoms in all directions)  Pump Requirements:ft. TDH vsGPM  Conditions:  WATER LINES (INCLUDING IRRIGATION) MUST BE 10FT. FROM A NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN FIELD ARE.  **If applicable:	Depth of: 18" - 24" inches shall be level to +/-1/4"  NY PART OF SEPTIC SYSTEM OR A.  the type specified on the application shall no Sewage Treatment and Disposal and to the conditions.	(Maximum soil cover shall 36" above the trench both and a specifications of the specifications of the transferred when there is a change in the transferred when the transferred when there is a change in the transferred when the transferred	not exceed oftom)  inches below pipe inches above pipe inches total  f this permit.

## Harnett County Department of Public Health Site Sketch

Property Location: 80 Glenmont Creek Place (US 401S)

Issued To: JSJ Builders Subdivision Williams Farm Lot # 33

Authorized State Agent: Act Reflection Date: 11-17-21

