


Job 26153	Truss G1	Truss Type GABLE	Qty 1	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	---------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:31 2021 Page 1

ID:sGsAqvGWbCg24bWoi?O8uJysxnY-fF_k6guyjskZ_AwUSA?MrDrlW5bA2lJShrFOiymsic



4x4 =

Scale = 1:35.9




Plate Offsets (X,Y)-- [2:0-1-13,0-0-12], [8:0-1-11,0-0-12]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.10	Vert(LL)	-0.00	9	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	-0.00	9	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	8	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S							
									Weight: 82 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3
 SLIDER Left 2x4 SP No.3 ~ 1-9-8, Right 2x4 SP No.3 ~ 1-9-8

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 13-8-0.
 (lb) - Max Horz 2=139(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 8, 14, 15, 12, 11
 Max Grav All reactions 250 lb or less at joint(s) 2, 8, 13, 14, 15, 12, 11

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 1.5x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8, 14, 15, 12, 11.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 26153	Truss G2	Truss Type GABLE	Qty 1	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	---------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:32 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-7RY1YShWj1_bB8I629iEv2m1KwRJVT0sgxapx9ymcrl



Scale = 1:57.8

Plate Offsets (X,Y)-- [6:0-2-13,Edge], [12:0-2-13,Edge], [24:0-3-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.04	Vert(LL)	-0.00	17	n/r	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.02	Vert(CT)	-0.00	17	n/r		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.15	Horz(CT)	0.00	16	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2015/TPI2014						Weight: 185 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 9-23

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 24-0-0.
 (lb) - Max Horz 2=-229(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 24, 25, 26, 27, 28, 22, 21, 20, 19, 18
 Max Grav All reactions 250 lb or less at joint(s) 2, 16, 23, 24, 25, 26, 27, 28, 22, 21, 20, 19, 18

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=24ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 1.5x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Gable studs spaced at 2-0-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 24, 25, 26, 27, 28, 22, 21, 20, 19, 18.
 - 10) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
26153	G3	GABLE	1	1	Job Reference (optional)

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:33 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-bd6Ploi8UK6SolKlbtDTRGJC3KnJeww0vbKMTbmycjq



Scale: 3/16"=1'

Plate Offsets (X,Y)-- [6:0-3-0,0-3-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.04	Vert(LL)	-0.00	1	n/r	120	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	-0.00	1	n/r	120		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.13	Horz(CT)	0.00	19	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S							
									Weight: 259 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 10-28, 9-29, 11-27

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 34-0-0.
 (lb) - Max Horz 2=228(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 29, 31, 32, 33, 34, 35, 36, 27, 25, 24, 23, 22, 21, 20
 Max Grav All reactions 250 lb or less at joint(s) 2, 19, 28, 29, 31, 32, 33, 34, 35, 36, 27, 25, 24, 23, 22, 21 except 20=252(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=34ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 29, 31, 32, 33, 34, 35, 36, 27, 25, 24, 23, 22, 21, 20.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 26153	Truss G4	Truss Type GABLE	Qty 1	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	---------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:35 2021 Page 1

ID:sGsAqvGWBcg24bWoi?O8uJysxnY-X0EAAUjP0yMA2cUjhJfXxhOYZ8Sy6qPJmvpTXUymjco




Plate Offsets (X,Y)-- [6:0-3-0,0-3-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.04	Vert(LL)	-0.00	1	n/r	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	-0.00	1	n/r		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.13	Horz(CT)	0.00	19	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						
								Weight: 259 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 WEBS 1 Row at midpt 10-28, 9-29, 11-27

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 34-0-0.
 (lb) - Max Horz 2=228(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 29, 31, 32, 33, 34, 35, 36, 27, 25, 24, 23, 22, 21, 20
 Max Grav All reactions 250 lb or less at joint(s) 2, 19, 28, 29, 31, 32, 33, 34, 35, 36, 27, 25, 24, 23, 22, 21 except 20=252(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=34ft; eave=2ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 29, 31, 32, 33, 34, 35, 36, 27, 25, 24, 23, 22, 21, 20.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 26153	Truss GR1	Truss Type Common Girder	Qty 1	Ply 2	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	--------------	-----------------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:36 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-?CoYNqk1nFU1fm3tH?mA3uxfXXfEr4JSbZY04wymcfn



Scale = 1:35.1

Plate Offsets (X,Y)-- [7:0-4-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.29	Vert(LL) -0.05	7-8	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.60	Vert(CT) -0.10	7-8	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.99	Horz(CT) 0.02	5	n/a	n/a		
BCDL 10.0	Rep Stress Incr NO	Matrix-MS	Wind(LL) 0.04	7-8	>999	240		
	Code IRC2015/TPI2014						Weight: 176 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x6 SP No.1 , Right: 2x6 SP No.1

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-8 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (lb/size) 1=4420/0-3-8 (min. 0-2-10), 5=4705/0-3-8 (min. 0-2-12)
 Max Horz 1=119(LC 24)
 Max Uplift 1=-378(LC 8), 5=-403(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-5832/523, 2-3=-4229/427, 3-4=-4231/427, 4-5=-5909/529
 BOT CHORD 1-15=-366/4590, 8-15=-366/4590, 8-16=-366/4590, 16-17=-366/4590, 7-17=-366/4590,
 7-18=-372/4657, 6-18=-372/4657, 6-19=-372/4657, 5-19=-372/4657
 WEBS 3-7=-441/4774, 4-7=-1732/209, 4-6=-142/1994, 2-7=-1643/202, 2-8=-133/1899

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-7-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=378, 5=403.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 1339 lb down and 124 lb up at 2-0-12, 1339 lb down and 124 lb up at 4-0-12, 1339 lb down and 124 lb up at 6-0-12, 1339 lb down and 124 lb up at 8-0-12, and 1339 lb down and 124 lb up at 10-0-12, and 1339 lb down and 124 lb up at 12-0-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

Job 26153	Truss GR1	Truss Type Common Girder	Qty 1	Ply 2	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13 Job Reference (optional)
--------------	--------------	-----------------------------	----------	-----------------	------------------------------------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:36 2021 Page 2
ID:sGsAqvGWBcg24bWoi?O8uJysxnY-?CoYNqk1nFU1fm3tH?mA3uxfXXfEr4JSbZY04wymcin

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-60, 3-5=-60, 9-12=-20


Concentrated Loads (lb)

Vert: 6=-1339(F) 15=-1339(F) 16=-1339(F) 17=-1339(F) 18=-1339(F) 19=-1339(F)

Job 26153	Truss T1	Truss Type Common	Qty 6	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:37 2021 Page 1
ID:sGsAqvGWbCg24bWoi?O8uJysxnY-TOLwb9lFYZduHve3qiHPc6Ts9x5yajLbqDlacMymcim



Scale = 1:57.5

Plate Offsets (X,Y)-- [2:0-6-0,0-0-3], [8:0-6-0,0-0-3]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.17	Vert(LL)	-0.08 10-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.25	Vert(CT)	-0.11 10-12	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.23	Horz(CT)	0.02 8	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS	Wind(LL)	0.02 12	>999	240		
								Weight: 150 lb	FT = 20%

LUMBER-

TOP CHORD 2x4 SP 2400F 2.0E

BOT CHORD 2x6 SP No.1

WEBS 2x4 SP No.3

WEDGE

Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-

TOP CHORD

Structural wood sheathing directly applied.

BOT CHORD

Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1032/0-3-8 (min. 0-1-8), 8=1032/0-3-8 (min. 0-1-8)

Max Horz 2=229(LC 7)

Max Uplift 2=-115(LC 8), 8=-115(LC 8)

Max Grav 2=1055(LC 13), 8=1055(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1315/136, 3-4=-1220/184, 4-5=-1125/222, 5-6=-1125/222, 6-7=-1220/184,

7-8=-1316/136

BOT CHORD 2-12=0/1128, 11-12=0/751, 10-11=0/751, 8-10=0/1003

WEBS 3-12=-328/179, 5-12=-77/646, 5-10=-77/646, 7-10=-328/179

NOTES-

1) Unbalanced roof live loads have been considered for this design.

2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60

3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.

5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=115, 8=115.

6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.


LOAD CASE(S) Standard

Job 26153	Truss T2	Truss Type Common	Qty 4	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:37 2021 Page 1

ID:sGsAqvGWBcg24bWoi?O8uJysxnY-TOLwb9fYZduHve3qiHPc6Ts8x5_ajHbqDlaciMymcim



Scale = 1:57.4




Plate Offsets (X,Y)-- [1:0-0-0,0-0-1], [5:Edge,0-1-1]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.17	Vert(LL)	-0.07	6-8	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.24	Vert(CT)	-0.11	6-8	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.24	Horz(CT)	0.02	5	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.02	8-11	>999		
	Code IRC2015/TPI2014						Weight: 145 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=955/0-3-8 (min. 0-1-8), 5=955/0-2-0 (min. 0-1-8)
 Max Horz 1=-207(LC 6)
 Max Uplift 1=-74(LC 8), 5=-74(LC 8)
 Max Grav 1=982(LC 13), 5=981(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1317/142, 2-3=-1224/231, 3-4=-1199/228, 4-5=-1288/143
 BOT CHORD 1-8=-31/1118, 7-8=0/736, 6-7=0/736, 5-6=-28/973
 WEBS 2-8=-331/181, 3-8=-83/656, 3-6=-80/627, 4-6=-317/176


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 26153	Truss T3	Truss Type Common	Qty 2	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:38 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-ybvloVmHJtlv3DGOQoe8J01uLRDJAXI3t178pymcl



Scale = 1:57.4




Plate Offsets (X,Y)-- [1:0-0-0,0-0-1], [5:Edge,0-1-1]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.17	Vert(LL)	-0.07	6-8	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.24	Vert(CT)	-0.11	6-8	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.24	Horz(CT)	0.02	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS	Wind(LL)	0.02	8-11	>999	240		
									Weight: 145 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=955/0-3-8 (min. 0-1-8), 5=955/0-2-0 (min. 0-1-8)
 Max Horz 1=-207(LC 6)
 Max Uplift 1=-74(LC 8), 5=-74(LC 8)
 Max Grav 1=982(LC 13), 5=981(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1317/142, 2-3=-1224/231, 3-4=-1199/228, 4-5=-1288/143
 BOT CHORD 1-8=-31/1118, 7-8=0/736, 6-7=0/736, 5-6=-28/973
 WEBS 2-8=-331/181, 3-8=-83/656, 3-6=-80/627, 4-6=-317/176

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate at joint(s) 5.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard


Job 26153	Truss T4	Truss Type Common	Qty 6	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:39 2021 Page 1

ID:sGsAqvGWBcg24bWoi?O8uJysxnY-QnTh0rmv4AtcWDoSy7KthXZCVljp2ZEuHXnggFymcck

Job Reference (optional)



4x6 ||

Scale: 3/16"=1'




Plate Offsets (X,Y)-- [2:0-2-9,Edge], [10:0-2-9,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.18	Vert(LL)	-0.24	11-14	>999	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.48	Vert(CT)	-0.33	11-14	>999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.40	Horz(CT)	0.05	10	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Wind(LL)	0.06	11-20	>999		
	Code IRC2015/TPI2014						Weight: 211 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1434/0-3-8 (min. 0-1-12), 10=1359/Mechanical
 Max Horz 2=228(LC 7)
 Max Uplift 2=-147(LC 8), 10=-104(LC 8)
 Max Grav 2=1462(LC 13), 10=1395(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2328/232, 3-4=-2032/182, 4-5=-1957/200, 5-6=-2063/316, 6-7=-2067/319,
 7-8=-1964/203, 8-9=-2037/185, 9-10=-2336/237
 BOT CHORD 2-14=-126/2108, 14-21=0/1295, 13-21=0/1295, 12-13=0/1295, 11-22=0/1295,
 10-11=-132/1953
 WEBS 5-14=-344/165, 7-11=-342/164, 3-14=-356/142, 6-14=-117/1074, 6-11=-122/1080,
 9-11=-361/146

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=34ft; eave=4ft; Cat. II; Exp B; Enclosed; MWF RS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BC DL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=147, 10=104.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.


LOAD CASE(S) Standard

Job 26153	Truss T5	Truss Type Common	Qty 2	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:40 2021 Page 1

ID:sGsAqvGWBcg24bWoi?O8uJysxnY-uz13DBnXrU?T8NMeWrr6Ek5N294in?62WBWEDhymcjj



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.19	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.43	Vert(LL) -0.19 12-15 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.49	Vert(CT) -0.27 12-15 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.02 11 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.04 15-18 >999 240		
				Weight: 216 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.
 WEBS 1 Row at midpt 6-12

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1134/0-3-8 (min. 0-1-8), 11=1659/0-3-8 (min. 0-1-15), 11=1659/0-3-8 (min. 0-1-15)
 Max Horz 2=228(LC 7)
 Max Uplift 2=-124(LC 8), 11=-127(LC 8)
 Max Grav 2=1174(LC 13), 11=1659(LC 1), 11=1659(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1769/186, 3-4=-1470/135, 4-5=-1396/153, 5-6=-1502/269, 6-7=-922/235,
 7-8=-842/124, 8-9=-914/95, 9-10=-67/467
 BOT CHORD 2-15=-87/1626, 15-22=0/804, 14-22=0/804, 13-14=0/804, 13-23=0/804, 12-23=0/804,
 11-12=-322/71, 10-11=-322/71
 WEBS 5-15=-344/165, 7-12=-331/156, 3-15=-359/143, 6-15=-111/1086, 9-12=-0/1201,
 9-11=-1550/161

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=34ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFERS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=124, 11=127.
 - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied DIRECTLY to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.


LOAD CASE(S) Standard

Job 26153	Truss T6	Truss Type COMMON	Qty 9	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:41 2021 Page 1

ID:sGsAqvGWbCg24bWof?O8uJysxnY-MAbRQXo9bo7JmXxr3YMLmyeXeYPzWRsBlrGnl7ymci



LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.20	Vert(LL) -0.19 13-16 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.43	Vert(CT) -0.27 13-16 >999 240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.52	Horz(CT) 0.02 12 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-AS	Wind(LL) 0.04 16-19 >999 240		Weight: 218 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied.
 BOT CHORD Rigid ceiling directly applied.
 WEBS 1 Row at midpt 6-13

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1116/0-3-8 (min. 0-1-8), 12=1749/0-3-8 (min. 0-2-1), 12=1749/0-3-8 (min. 0-2-1)
 Max Horz 2=-232(LC 6)
 Max Uplift 2=-114(LC 8), 12=-179(LC 8)
 Max Grav 2=1163(LC 13), 12=1749(LC 1), 12=1749(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1748/166, 3-4=-1449/115, 4-5=-1374/133, 5-6=-1480/249, 6-7=-862/196, 7-8=-790/84, 8-9=-862/55, 9-10=-115/622
 BOT CHORD 2-16=-37/1616, 16-23=0/794, 15-23=0/794, 14-15=0/794, 14-24=0/794, 13-24=0/794, 12-13=-457/176, 10-12=-457/176
 WEBS 5-16=-344/165, 7-13=-331/156, 3-16=-360/144, 6-16=-111/1086, 9-13=-55/1259, 9-12=-1625/217


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=34ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFERS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=114, 12=179.
 - 6) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
26153	T7	Common	11	1	Job Reference (optional)

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:42 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-qM9petpoM5FANhW1dGtaJ9BckylUFwSKzV?LHaymcih



Scale = 1:60.8

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.62	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.41	Vert(LL) -0.17 10-12 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.43	Vert(CT) -0.24 10-12 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.02 9 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.03 12-15 >999 240		Weight: 181 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied, except end verticals.
 BOT CHORD Rigid ceiling directly applied.
 WEBS 1 Row at midpt 6-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1068/0-3-8 (min. 0-1-8), 9=992/Mechanical
 Max Horz 2=316(LC 7)
 Max Uplift 2=-116(LC 8), 9=-79(LC 8)
 Max Grav 2=1088(LC 13), 9=1108(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1605/172, 3-4=-1299/118, 4-5=-1221/136, 5-6=-1330/253, 6-7=-628/199,
 7-8=-551/108, 8-9=-1255/76
 BOT CHORD 2-12=-130/1478, 12-16=-53/649, 11-16=-53/649, 11-17=-53/649, 10-17=-53/649
 WEBS 3-12=-367/145, 5-12=-350/167, 6-12=-111/1078, 6-10=-403/57, 7-10=-293/115,
 8-10=-7/1080


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=25ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6'-0" between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9 except (jt=lb) 2=116.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job	Truss	Truss Type	Qty	Ply	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
26153	T8	Common	1	1	Job Reference (optional)

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:42 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-qM9petpoM5FANhW1dGtaJ9BckylUFwSKzV?LHaymcih



Scale = 1:60.8

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.62	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.41	Vert(LL) -0.17 10-12 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.43	Vert(CT) -0.24 10-12 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.02 9 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.03 12-15 >999 240		Weight: 181 lb FT = 20%

LUMBER-
 TOP CHORD 2x4 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.1
 WEBS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied, except end verticals.
 BOT CHORD Rigid ceiling directly applied.
 WEBS 1 Row at midpt 6-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 2=1068/0-3-8 (min. 0-1-8), 9=992/Mechanical
 Max Horz 2=316(LC 7)
 Max Uplift 2=-116(LC 8), 9=-79(LC 8)
 Max Grav 2=1088(LC 13), 9=1108(LC 13)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1605/172, 3-4=-1299/118, 4-5=-1221/136, 5-6=-1330/253, 6-7=-628/199,
 7-8=-551/108, 8-9=-1255/76
 BOT CHORD 2-12=-130/1478, 12-16=-53/649, 11-16=-53/649, 11-17=-53/649, 10-17=-53/649
 WEBS 3-12=-367/145, 5-12=-350/167, 6-12=-111/1078, 6-10=-403/57, 7-10=-293/115,
 8-10=-7/1080


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TCDL=6.0psf; BCDL=6.0psf; h=20ft; B=45ft; L=25ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9 except (jt=lb) 2=116.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.

LOAD CASE(S) Standard

Job 26153	Truss V1	Truss Type Valley	Qty 1	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------


C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:43 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-YjBrDqQ7PN1?r5DBzOprNjt5MAT_TzUC9lup0ymcg



4x4 =

Scale = 1:18.7



LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.20	Vert(LL) n/a - n/a 999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.11	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P		Weight: 26 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=146/7-4-7 (min. 0-1-8), 3=146/7-4-7 (min. 0-1-8), 4=232/7-4-7 (min. 0-1-8)
 Max Horz 1=-57(LC 6)
 Max Uplift 1=-29(LC 8), 3=-29(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 26153	Truss V2	Truss Type Valley	Qty 1	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------


C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:44 2021 Page 1

ID:sGsAqvGWBcg24bWof?O8uJysxnY-mIGa3Zq2ujVud_gPIhv2OaG5DmXxjwVdRpURMSymcfc

4-3-12
2-1-14

Scale = 1:10.6



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
	Code IRC2015/TPI2014			Weight: 14 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 4-3-12 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=77/4-3-2 (min. 0-1-8), 3=77/4-3-2 (min. 0-1-8), 4=122/4-3-2 (min. 0-1-8)
Max Horz 1=-30(LC 6)
Max Uplift 1=-15(LC 8), 3=-15(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job 26153	Truss V3	Truss Type Valley	Qty 1	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:44 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-mlGa3Zq2ujVud_gPlhv2OaG36mWWjwdRpURMSymcfc
 11-3-7



Scale = 1:25.9

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.18	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.12	Vert(LL) n/a - n/a 999		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.06	Vert(CT) n/a - n/a 999		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 44 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. All bearings 11-2-12.
 (lb) - Max Horz 1=-90(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5, 8, 6
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=254(LC 1), 8=318(LC 13), 6=318(LC 14)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-8=-259/138, 4-6=-259/138


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWF RS (directional); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5, 8, 6.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 26153	Truss V4	Truss Type Valley	Qty 1	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:45 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?08uJysxnY-ExqyGurgf0dF8FclOQHxopDIArXSNNngTE?uvymc
 8-2-2



Scale = 1:20.1



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.26	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.14	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.04	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 29 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=163/8-2-2 (min. 0-1-8), 3=163/8-2-2 (min. 0-1-8), 4=259/8-2-2 (min. 0-1-8)
 Max Horz 1=-63(LC 6)
 Max Uplift1=-33(LC 8), 3=-33(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard


Job 26153	Truss V5	Truss Type Valley	Qty 1	Ply 1	FREEDOM CONSTRUCTORS/WILDWOOD LOT 13
--------------	-------------	----------------------	----------	----------	--------------------------------------

C&R Building Supply, Autryville NC

8.430 s Jan 20 2021 MiTek Industries, Inc. Wed Aug 18 13:26:45 2021 Page 1
 ID:sGsAqvGWBcg24bWoi?O8uJysxnY-ExqyGurgf0dF8FclOQHxopFYAtxSNhngTE?uyvmc



Scale = 1:14.0



LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.08	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.05	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.02	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					Weight: 17 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-0-12 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS. (lb/size) 1=93/5-0-12 (min. 0-1-8), 3=93/5-0-12 (min. 0-1-8), 4=148/5-0-12 (min. 0-1-8)
 Max Horz 1=36(LC 7)
 Max Uplift 1=-19(LC 8), 3=-19(LC 8)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=140mph Vasd=111mph; TC DL=6.0psf; BC DL=6.0psf; h=20ft; B=45ft; L=24ft; eave=4ft; Cat. II; Exp B; Enclosed; MWFRS (directional); cantilever left and right exposed ; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard