


Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	AT01	Attic	4	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:47 2021 Page 1  
 ID: xXVn1g\_eg3NzLwT48PmhGczX1xV-W54n5527M8BmqcuidA6PrQuX45WcJmsRW?J5\_XyKzKz



Scale = 1:74.0

Plate Offsets (X,Y)-- [2:0-0-0,0-0-2], [3:0-4-0,0-6-0], [9:0-4-0,0-6-0], [10:0-0-0,0-0-6], [13:0-2-12,0-2-0], [17:0-6-0,0-3-0], [18:0-3-8,0-2-0], [22:0-3-8,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.50	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.95	Vert(LL) -0.27 12 >725 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.86	Vert(CT) -0.43 12 >464 240		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.04 10 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014		Attic -0.19 13-26 1004 360		
				Weight: 277 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x8 SP DSS *Except* T3: 2x4 SP DSS	TOP CHORD Structural wood sheathing directly applied or 5-6-1 oc purlins.
BOT CHORD 2x4 SP No.2 *Except* B2: 2x4 SP DSS, B3: 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 21-22, 19-21 4-4-9 oc bracing: 17-19 6-0-0 oc bracing: 23-26, 16-23, 13-16
WEBS 2x4 SP No.3 *Except* W8, W1: 2x4 SP No.2	JOINTS 1 Brace at Jt(s): 29, 23, 16
WEDGE Right: 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1248/0-5-8 (min. 0-1-11), 21=971/0-3-8 (min. 0-1-15), 10=1242/0-5-8 (min. 0-1-12)  
 Max Horz 2=267(LC 13)  
 Max Uplift 2=-44(LC 16), 10=-32(LC 17)  
 Max Grav 2=1438(LC 2), 21=1644(LC 31), 10=1464(LC 32)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-2012/125, 3-4=-1680/121, 4-36=-1427/189, 5-36=-1209/229, 5-6=-37/577,  
 6-7=-52/663, 7-37=-1128/236, 8-37=-1385/200, 8-9=-1825/105, 9-10=-2262/99  
 BOT CHORD 2-28=-151/1747, 27-28=-150/1753, 24-27=-20/1551, 22-24=-22/711, 21-22=-1298/221,  
 19-21=-1298/221, 17-19=-1298/221, 15-17=0/1829, 12-15=0/1555, 11-12=-23/1801,  
 10-11=-24/1795, 25-26=-301/104, 23-25=-400/265, 20-23=-154/1730, 18-20=-148/2580,  
 16-18=-369/899, 14-16=-510/177, 13-14=-296/95  
 WEBS 12-13=0/575, 8-13=0/731, 26-27=0/258, 4-26=0/362, 5-29=-2025/336, 7-29=-2025/336,  
 6-29=-24/264, 20-21=-987/0, 18-19=-560/0, 20-22=-46/888, 22-23=-1242/37,  
 23-24=-115/923, 17-18=0/2052, 16-17=-1130/44, 15-16=-676/228, 14-15=-115/393,  
 12-14=-400/192, 9-12=-841/219, 3-27=-647/233

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load); Lumber DOL=1.15 Plate DOL=1.15; Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow); Lumber DOL=1.15 Plate DOL=1.15; Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Ceiling dead load (5.0 psf) on member(s). 4-5, 7-8, 5-29, 7-29; Wall dead load (5.0psf) on member(s). 8-13, 4-26
  - Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 25-26, 23-25, 20-23, 18-20, 16-18

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	Job Reference (optional)
21-6482-A	AT01	Attic	4	1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:47 2021 Page 2  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-W54n5527M8BmqcuidA6PrQuX45WcJmsRW?J5\_XyKxzk

**NOTES-**


- 10) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job 21-6482-A	Truss AT02	Truss Type ATTIC GIRDER	Qty 1	Ply 4	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
------------------	---------------	----------------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MITek Industries, Inc. Tue Nov 9 11:08:48 2021 Page 1  
ID:XXVN1g\_eg3NzLwT48PmhGczX1xV-HeAIQ2I7RjCStvBudeOdQ61UtG2Daalf3fW\_yKxzj



Scale = 1:74.0

Plate Offsets (X,Y)-- [3:0-2-0,0-3-0], [9:0-2-0,0-3-0], [13:0-2-12,0-2-0], [17:0-4-4,0-3-0], [18:0-3-8,0-2-0], [22:0-5-8,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	6-0-0	TC 0.49	Vert(LL)	-0.29	12	>683	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.86	Vert(CT)	-0.44	12	>449		
TCDL 10.0	Lumber DOL 1.15	WB 0.89	Horz(CT)	0.02	10	n/a		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS	Attic	-0.19	13-26	1008		
BCDL 10.0	Code IRC2015/TPI2014					360		
							Weight: 1151 lb	FT = 20%

**LUMBER-**  
**TOP CHORD** 2x8 SP DSS \*Except\*  
T3: 2x4 SP DSS  
**BOT CHORD** 2x4 SP No.1 \*Except\*  
B2: 2x4 SP DSS  
**WEBS** 2x4 SP No.3 \*Except\*  
W8,W1: 2x4 SP No.2  
**WEDGE**  
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

**BRACING-**  
**TOP CHORD** 2-0-0 oc purlins (6-0-0 max.)  
(Switched from sheeted: Spacing > 2-0-0).  
**BOT CHORD** Rigid ceiling directly applied or 10-0-0 oc bracing, Except:  
6-0-0 oc bracing: 21-22,19-21,17-19.  
6-0-0 oc bracing: 23-26, 16-23, 13-16  
**JOINTS** 1 Brace at Jt(s): 6, 29, 23, 16

**REACTIONS.** (lb/size) 2=3861/0-5-8 (min. 0-1-8), 10=4893/0-3-8 (min. 0-1-15), 21=3155/0-3-8 (min. 0-1-9)  
Max Horz 2=799(LC 13)  
Max Uplift 2=-165(LC 16), 10=-299(LC 17)  
Max Grav 2=4465(LC 31), 10=6525(LC 32), 21=5306(LC 31)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**TOP CHORD** 2-3=-6375/403, 3-4=-5633/391, 4-36=-5048/604, 5-36=-4356/736, 5-6=-160/2054,  
6-7=-242/2738, 7-37=-3750/726, 8-37=-4761/615, 8-9=-7013/399, 9-10=-9631/493  
**BOT CHORD** 2-28=-453/5647, 27-28=-454/5640, 24-27=-25/4730, 22-24=-34/1766, 21-22=-4457/781,  
19-21=-4457/781, 17-19=-4457/781, 15-17=0/6657, 12-15=0/6267, 11-12=-260/7628,  
10-11=-258/7643, 25-26=-710/364, 23-25=-627/1115, 20-23=-618/6163, 18-20=-620/8993,  
16-18=-1134/2650, 14-16=-2356/385, 13-14=-1351/333  
**WEBS** 12-13=0/2498, 8-13=0/3104, 26-27=-145/607, 4-26=-136/868, 5-29=-7443/1153,  
7-29=-7443/1153, 6-29=-89/953, 9-11=0/535, 9-12=-4517/824, 3-28=0/442, 3-27=-1713/634,  
18-19=-1780/0, 20-21=-3174/0, 20-22=-134/2938, 22-23=-3670/119, 23-24=-388/3182,  
24-25=-847/236, 25-27=-469/969, 17-18=0/7530, 16-17=-3934/222, 15-16=-1732/1006,  
14-15=-192/1714, 12-14=-1635/238

- NOTES-**
- 4-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x8 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.  
Bottom chords connected as follows: 2x4 - 1 row at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.  
Attach TC w/ 1/2" diam. bolts (ASTM A-307) in the center of the member w/washers at 4-0-0 oc.  
Attach BC w/ 1/2" diam. bolts (ASTM A-307) in the center of the member w/washers at 4-0-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TC LL: ASCE 7-10; Pr=30.0 psf (roof live load); Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow); Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	AT02	ATTIC GIRDER	1	4	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:48 2021 Page 2  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-\_HeAIQ2I7RjCStvBudeOdQ61UtG2Daalf3fW\_yKxzj

**NOTES-**


- 6) Unbalanced snow loads have been considered for this design.
- 7) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
- 8) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 9) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 10) Ceiling dead load (5.0 psf) on member(s). 4-5, 7-8, 5-29, 7-29; Wall dead load (5.0psf) on member(s).8-13, 4-26
- 11) Bottom chord live load (40.0 psf) and additional bottom chord dead load (5.0 psf) applied only to room. 25-26, 23-25, 20-23, 18-20, 16-18, 14-16, 13-14
- 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=165, 10=299.
- 13) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 14) Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
  - Uniform Loads (plf)
    - Vert: 1-4=-199, 4-5=-229, 5-6=-199, 30-33=-60, 13-26=-90, 5-7=-30
    - Drag: 8-13=-30, 4-26=-30
  - Trapezoidal Loads (plf)
    - Vert: 6=-199-to-7=-225, 7=-255-to-8=-330, 8=-300-to-10=-399

Job 21-6482-A	Truss ATGE01	Truss Type GABLE	Qty 1	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
Riverside Roof Truss, LLC, Danville, VA. 24541					Job Reference (optional)

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MITek Industries, Inc. Tue Nov 9 11:08:49 2021 Page 1  
 ID: xXVN1g\_eg3NzLwT48PmhGczX1xV-SUBYWM3NuIRt3v15b8twrZNEuQ3nspk\_JoC3QyKxzI



Scale = 1:76.6

Plate Offsets (X,Y)-- [3:0-4-0-0-6-0], [9:0-4-0-0-6-0], [16:0-2-12,0-2-0], [20:0-2-8,0-3-0], [25:0-3-8,0-3-0]											
<b>LOADING</b> (psf)		<b>SPACING-</b>	2-0-0	<b>CSI.</b>		<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof)	30.0	Plate Grip DOL	1.15	TC	0.08	Vert(LL)	0.00	1	n/r	MT20	244/190
Snow (Pf/Pg)	23.1/30.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	0.00	1	n/r		
TCDL	10.0	Rep Stress Incr	YES	WB	0.12	Horz(CT)	0.02	10	n/a		
BCLL	0.0 *	Code IRC2015/TPI2014		Matrix-S							
BCDL	10.0									Weight: 297 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x8 SP DSS *Except* T3: 2x4 SP DSS	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP DSS	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing. Except:
WEBS 2x4 SP No.3 *Except* W8: 2x4 SP No.1, W1: 2x4 SP No.2	10-0-0 oc bracing: 26-29, 19-26, 16-19
OTHERS 2x4 SP No.3	1 Brace at Jt(s): 35, 26, 19
WEDGE Left: 2x4 SP No.3, Right: 2x4 SP No.3	MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 31-0-0.  
 (lb) - Max Horz 2=269(LC 13)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 10, 13, 32 except 15=337(LC 17), 30=240(LC 16)  
 Max Grav All reactions 250 lb or less at joint(s) 24, 22, 25, 20, 31, 33, 34, 14, 12, 11 except 2=579(LC 2), 15=323(LC 36), 30=378(LC 35), 27=357(LC 7), 18=396(LC 7), 10=488(LC 2), 13=473(LC 2), 32=462(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-675/93, 3-4=-785/88, 4-4=-903/166, 5-4=-705/196, 5-6=-254/34, 6-7=-254/42, 7-45=-714/196, 8-45=-903/166, 8-9=-787/76, 9-10=-654/38  
 BOT CHORD 2-34=-43/482, 33-34=-43/482, 32-33=-43/482, 31-32=-42/458, 30-31=-42/458, 27-30=-16/373, 25-27=0/435, 18-20=0/460, 15-18=-11/423, 14-15=0/445, 13-14=0/445, 12-13=0/471, 11-12=0/471, 10-11=0/471, 23-26=0/271, 21-23=0/367, 19-21=0/267  
 WEBS 15-16=-569/164, 8-16=-592/204, 29-30=-588/171, 4-29=-596/216, 5-35=-443/231, 7-35=-443/231, 28-30=0/296, 17-18=-281/0, 15-17=0/285, 9-13=-464/64, 3-32=-455/80

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	ATGE01	GABLE	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:50 2021 Page 2  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-wglwj64?f2ZKh3cHJf6T2WYzImIWl3tCzYlbsyKxzh

**NOTES-**


- 11) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 12) Ceiling dead load (5.0 psf) on member(s). 4-5, 7-8, 5-35, 7-35; Wall dead load (5.0psf) on member(s).8-16, 4-29
- 13) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10, 13, 32 except (jt=lb) 15=337, 30=240.
- 14) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 15) Attic room checked for L/360 deflection.

**LOAD CASE(S)** Standard

Job 21-6482-A	Truss ATSGE01	Truss Type GABLE	Qty 1	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
------------------	------------------	---------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:51 2021 Page 1  
ID: xXVN1g\_eg3NzLwT48PmhGczX1xV-OsJlwS5eQMhBJDBUs0BL?G2cZiwhFbG0RdHJ7lyKxzg



Scale = 1:69.2




Plate Offsets (X,Y)-- [4:0-3-0,0-2-4], [6:0-2-0,0-0-0], [8:0-3-0,0-2-4], [27:0-2-0,0-1-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.53	Vert(LL) -0.14	18-19	>999	360	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.82	Vert(CT) -0.25	18-19	>982	240		
TCDL 10.0	Lumber DOL 1.15	WB 0.77	Horz(CT) 0.02	17	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 324 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x6 SP No.2  
 WEBS 2x4 SP No.3  
 OTHERS 2x4 SP No.3  
 WEDGE  
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-3-7 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.  
 WEBS 1 Row at midpt 6-18

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 10-5-8 except (jt=length) 2=0-5-8, 17=0-3-8.  
 (lb) - Max Horz 2=272(LC 15)  
 Max Uplift All uplift 100 lb or less at joint(s) 10, 13 except 2=-130(LC 16), 14=-117(LC 17), 15=-474(LC 30), 12=-122(LC 17), 17=-187(LC 17)  
 Max Grav All reactions 250 lb or less at joint(s) 10, 15, 13, 10 except 2=1305(LC 2), 14=1380(LC 31), 12=291(LC 31), 17=1190(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-1665/206, 3-4=-1358/188, 4-5=-1236/221, 5-55=-1369/340, 6-55=-1355/370, 6-56=-630/241, 7-56=-644/211, 7-8=-535/92, 8-9=-636/59  
 BOT CHORD 2-21=-211/1420, 20-21=-211/1420, 19-20=-211/1420, 19-57=-14/680, 57-58=-14/680, 18-58=-14/680  
 WEBS 6-18=-497/89, 7-18=-435/235, 9-18=0/725, 9-14=-1137/146, 6-19=-299/1259, 5-19=-435/234, 3-19=-340/170

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 4) TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 5) Unbalanced snow loads have been considered for this design.
  - 6) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - 7) All plates are 2x4 MT20 unless otherwise indicated.
  - 8) Gable studs spaced at 2-0-0 oc.
  - 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 10) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 10, 13, 10 except (jt=lb) 2=130, 14=117, 15=474, 12=122, 17=187.

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	ATSGE01	GABLE	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:51 2021 Page 2  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-OsJlwS5eQMhBJDBUs0BL?G2cZiwhFbG0RdHJ7lyKxzg

**NOTES-**

12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard


- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15
- Uniform Loads (plf)
  - Vert: 1-6=-66, 6-11=-66, 19-49=-20, 18-19=-60, 18-52=-20



Job 21-6482-A	Truss G01	Truss Type Common Girder	Qty 1	Ply 2	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
------------------	--------------	-----------------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:52 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-s3tg8o6GBgp2wNmGQkiaYTbt6Lc\_7gAgH1sflyKxzf



Scale: 3/8"=1'

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.18	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.45	Vert(LL) -0.03 7-8 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.44	Vert(CT) -0.05 7-8 >999 240		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.01 5 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 153 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x6 SP No.2  
WEBS 2x4 SP No.3  
WEDGE  
Left: 2x4 SP No.3 , Right: 2x4 SP No.3

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (lb/size) 1=1949/0-5-8 (min. 0-1-8), 5=2291/0-5-8 (min. 0-1-9)  
Max Horz 1=-103(LC 12)  
Max Uplift 1=-164(LC 16), 5=-189(LC 17)  
Max Grav 1=2230(LC 2), 5=2619(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-2=-2880/280, 2-15=-2205/247, 3-15=-2152/258, 3-16=-2152/258, 4-16=-2206/247,  
4-5=-2882/280  
BOT CHORD 1-17=-206/2323, 8-17=-206/2323, 8-18=-206/2323, 18-19=-206/2323, 7-19=-206/2323,  
7-20=-182/2329, 6-20=-182/2329, 6-21=-182/2329, 5-21=-182/2329  
WEBS 3-7=-197/2104, 4-7=-705/137, 4-6=-39/633, 2-7=-698/136, 2-8=-40/633

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.  
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=164, 5=189.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 1-11-4 from the left end to 11-11-4 to connect truss(es) M02 (1 ply 2x4 SP), M02A (1 ply 2x4 SP) to back face of bottom chord.
  - Fill all nail holes where hanger is in contact with lumber.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	G01	Common Girder	1	2	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:52 2021 Page 2  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-s3tg8o6GBgp2wNmgQkiaYTbtt6Lc\_7gAgH1sflyKxzf

**LOAD CASE(S)** Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-66, 3-5=-66, 9-12=-20


Concentrated Loads (lb)

Vert: 14=-522(B) 17=-531(B) 18=-531(B) 19=-531(B) 20=-531(B) 21=-518(B)

Job 21-6482-A	Truss G02	Truss Type Common Girder	Qty 1	Ply 2	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
------------------	--------------	-----------------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:53 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-LFR3L86uyzvxYXLs\_RDp5h72cVhpjasJuxmQCByKxe



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.18	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.45	Vert(LL) -0.03 7-8 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.44	Vert(CT) -0.05 7-8 >999 240		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.01 5 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 153 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	
WEDGE	
Left: 2x4 SP No.3 , Right: 2x4 SP No.3	

**REACTIONS.** (lb/size) 1=2308/0-5-8 (min. 0-1-9), 5=1957/0-5-8 (min. 0-1-8)  
 Max Horz 1=-103(LC 12)  
 Max Uplift 1=-191(LC 16), 5=-165(LC 17)  
 Max Grav 1=2638(LC 2), 5=2239(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-2915/282, 2-15=-2223/249, 3-15=-2169/259, 3-16=-2169/259, 4-16=-2222/249, 4-5=-2893/281  
 BOT CHORD 1-17=-208/2355, 8-17=-208/2355, 8-18=-208/2355, 7-18=-208/2355, 7-19=-183/2334, 19-20=-183/2334, 6-20=-183/2334, 6-21=-183/2334, 5-21=-183/2334  
 WEBS 3-7=-198/2122, 4-7=-693/136, 4-6=-39/628, 2-7=-720/137, 2-8=-41/653

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.  
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=191, 5=165.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
  - Use Simpson Strong-Tie HUS26 (14-10d Girder, 4-10d Truss) or equivalent spaced at 2-0-0 oc max. starting at 0-8-4 from the left end to 10-6-12 to connect truss(es) M02 (1 ply 2x4 SP) to back face of bottom chord.
  - Fill all nail holes where hanger is in contact with lumber.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	G02	Common Girder	1	2	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:53 2021 Page 2  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-LFR3L86uyzXvYXLS\_RDP5h72cVhpjasJuxmQCBYKxze

**LOAD CASE(S)** Standard

1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-66, 3-5=-66, 9-12=-20


Concentrated Loads (lb)

Vert: 11=-534(B) 17=-531(B) 18=-531(B) 19=-531(B) 20=-531(B) 21=-531(B)

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	M01	Monopitch Supported Gable	2	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:54 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-pR?RZU7WiH3mAgw2X8k2dug3ov4SS4FT7bWzkdyKxz



Scale = 1:52.4

Plate Offsets (X,Y)-- [9:Edge,0-1-8], [16:0-2-3,0-0-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.79	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.24	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.24	Horz(CT)	-0.00	9	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-R						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 92 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 OTHERS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 8-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 12-4-0.  
 (lb) - Max Horz 16=323(LC 13)  
 Max Uplift All uplift 100 lb or less at joint(s) 9, 13, 14, 12, 11, 10 except 16=188(LC 14), 15=214(LC 16)  
 Max Grav All reactions 250 lb or less at joint(s) 9, 13, 14, 12, 11, 10 except 16=322(LC 13), 15=256(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-16=374/326, 1-2=540/488, 2-3=420/384, 3-4=364/338, 4-5=301/287


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 3) TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) All plates are 2x4 MT20 unless otherwise indicated.
  - 6) Gable requires continuous bottom chord bearing.
  - 7) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
  - 8) Gable studs spaced at 2-0-0 oc.
  - 9) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 10) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 11) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 13, 14, 12, 11, 10 except (jt=lb) 16=188, 15=214.
  - 12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	M02	Monopitch	10	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:54 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-pR?RZU7Wih3mAgw2X8k2dug1yv2BSysT7bWzkyKxz



Scale = 1:52.7

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.91	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.38	Vert(LL) -0.04 5-6 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.71	Vert(CT) -0.08 5-6 >999 240		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.02 1 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 76 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
SLIDER Left 2x4 SP No.3 - 2-6-0

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS 1 Row at midpt 4-5

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=538/Mechanical, 5=538/0-3-8 (min. 0-1-8)  
Max Horz 1=326(LC 15)  
Max Uplift1=-30(LC 16), 5=-152(LC 16)  
Max Grav 1=624(LC 2), 5=649(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 1-2=-278/0, 2-3=-507/126, 3-11=-253/166  
BOT CHORD 1-6=-282/562, 5-6=-282/562  
WEBS 3-6=0/281, 3-5=-631/232


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 3) Unbalanced snow loads have been considered for this design.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Refer to girder(s) for truss to truss connections.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 5=152.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	M02A	Monopitch	2	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:55 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-HeZpmq88TbDnqVF5sFHA6DDLJOhBQscMFFWG4yKxzp



Scale = 1:51.7

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.87	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.36	Vert(LL) -0.04 5-6 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.66	Vert(CT) -0.07 5-6 >999 240		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.02 1 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 74 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 ~ 2-6-0

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 4-5

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=525/Mechanical, 5=525/Mechanical  
 Max Horz 1=319(LC 15)  
 Max Uplift 1=-30(LC 16), 5=-149(LC 16)  
 Max Grav 1=609(LC 2), 5=634(LC 29)


**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-269/0, 2-3=-493/123  
 BOT CHORD 1-6=-277/549, 5-6=-277/549  
 WEBS 3-6=0/274, 3-5=-615/228

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 3) Unbalanced snow loads have been considered for this design.
  - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 5) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 6) Refer to girder(s) for truss to truss connections.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 5=149.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 21-6482-A	Truss M03	Truss Type Monopitch	Qty 5	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
Riverside Roof Truss, LLC, Danville, VA. 24541					Job Reference (optional)

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:56 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-lq7B\_A9mEuJUP\_4RfZmWiJINOjjYwtmmbv?4oWYKxzB



Scale = 1:52.7

Plate Offsets (X,Y)-- [8:Edge,0-6-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.91	Vert(LL) -0.04	6-7	>999	360	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.39	Vert(CT) -0.08	6-7	>999	240		
TCDL 10.0	Lumber DOL 1.15	WB 0.68	Horz(CT) 0.01	6	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 83 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 7-8-9 oc bracing.  
WEBS 1 Row at midpt 5-6

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 8=611/0-5-8 (min. 0-1-8), 6=528/0-3-8 (min. 0-1-8)  
Max Horz 8=343(LC 13)  
Max Uplift 8=54(LC 16), 6=151(LC 16)  
Max Grav 8=713(LC 2), 6=639(LC 30)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-708/93, 3-4=-488/114, 4-9=-254/164, 2-8=-658/171  
BOT CHORD 7-8=-572/695, 6-7=-273/546  
WEBS 4-7=0/275, 4-6=-606/220, 2-7=-150/301

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 3) Unbalanced snow loads have been considered for this design.
  - 4) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 8 except (jt=lb) 6=151.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard



Job 21-6482-A	Truss T01	Truss Type Common	Qty 2	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
------------------	--------------	----------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:57 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-D0gZBV9O?CRL18fdDHHIFXlbV7yJfP2vpZkdLyyKxza



Scale = 1:50.6

Plate Offsets (X,Y)-- [6:Edge,0-0-9]

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.76	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.87	Vert(LL) -0.19 9-10 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.36	Vert(CT) -0.33 9-10 >876 240		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.04 6 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 144 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x6 SP No.2  
 WEBS 2x4 SP No.3  
 WEDGE  
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-8-2 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1280/0-5-8 (min. 0-1-12), 6=1279/0-5-8 (min. 0-1-12)  
 Max Horz 2=214(LC 15)  
 Max Uplift 2=-153(LC 16), 6=-153(LC 17)  
 Max Grav 2=1489(LC 2), 6=1486(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-2044/289, 3-18=-1896/359, 4-18=-1757/382, 4-19=-1761/382, 5-19=-1900/359,  
 5-6=-2049/290  
 BOT CHORD 2-11=-207/1663, 10-11=-207/1663, 10-20=-37/1088, 20-21=-37/1088, 9-21=-37/1088,  
 8-9=-131/1599, 6-8=-131/1599  
 WEBS 3-10=-412/240, 4-10=-188/935, 4-9=-189/941, 5-9=-413/240

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCCL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=153, 6=153.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard  
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-4=-66, 4-7=-66, 10-12=-20, 9-10=-60, 9-15=-20

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T01GE	GABLE	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:58 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-hDEyOrA1mWZCelDqm\_p\_nkrwoWU3Ouk22DUBtOyKxzZ

1-0-0	11-11-14	24-0-0	24-11-12
1-0-0	11-11-14	12-0-2	0-11-12

Scale = 1:54.1




Plate Offsets (X,Y)-- [9:0-3-0,Edge], [16:Edge,0-3-14]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.09	Vert(LL) -0.00	17	n/r	180	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT) -0.00	17	n/r	120		
TCDL 10.0	Lumber DOL 1.15	WB 0.21	Horz(CT) 0.01	16	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S						
BCDL 10.0	Code IRC2015/TPI2014							
							Weight: 157 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 OTHERS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 - 0-10-3, Right 2x4 SP No.3 - 0-10-6

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 24-0-0.  
 (lb) - Max Horz 2=214(LC 15)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 24, 25, 27, 28, 29, 22, 21, 20, 19, 16 except 30=-177(LC 16), 18=-160(LC 17)  
 Max Grav All reactions 250 lb or less at joint(s) 25, 27, 28, 29, 30, 23, 22, 21, 20, 19, 18 except 2=284(LC 32), 24=261(LC 30), 16=259(LC 33)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-369/236, 15-16=-333/235


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 24, 25, 27, 28, 29, 22, 21, 20, 19, 16 except (jt=lb) 30=177, 18=160.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T02	Common	11	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:08:59 2021 Page 1  
 ID: xXVN1g\_eg3NzLwT48PmhGczX1xV-9PoKcBBfXph3GSo0KiKDKyNw3wen7JWCHtdkPryKxzY



Scale = 1:50.1

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.76	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.87	Vert(LL) -0.19 8-9 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.36	Vert(CT) -0.33 8-9 >876 240		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.04 6 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 143 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x6 SP No.2  
 WEBS 2x4 SP No.3  
 WEDGE  
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-7-8 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1281/0-5-8 (min. 0-1-12), 6=1212/0-5-8 (min. 0-1-11)  
 Max Horz 2=209(LC 15)  
 Max Uplift 2=-153(LC 16), 6=-132(LC 17)  
 Max Grav 2=1489(LC 2), 6=1406(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-2045/290, 3-17=-1896/361, 4-17=-1757/383, 4-18=-1763/384, 5-18=-1902/361,  
 5-6=-2050/291  
 BOT CHORD 2-10=-218/1655, 9-10=-218/1655, 9-19=-48/1080, 19-20=-48/1080, 8-20=-48/1080,  
 7-8=-153/1600, 6-7=-153/1600  
 WEBS 4-8=-191/944, 5-8=-414/240, 4-9=-188/935, 3-9=-412/240


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=153, 6=132.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard  
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-4=-66, 4-6=-66, 9-11=-20, 8-9=-60, 8-14=-20

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T02A	Common	2	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:00 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-ebMipXCHI7pvubNCuPrSt9w6fK\_Zsk0LVXzHxHyKxzX



Scale = 1:50.4

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.70	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.83	Vert(LL) -0.18 9-10 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.48	Vert(CT) -0.30 9-10 >938 240		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS	Horz(CT) 0.03 7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 151 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x6 SP No.2  
 WEBS 2x4 SP No.3  
 WEDGE  
 Left: 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 3-8-4 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 5-7

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=1250/0-5-8 (min. 0-1-11), 7=1190/Mechanical  
 Max Horz 2=224(LC 15)  
 Max Uplift 2=151(LC 16), 7=127(LC 17)  
 Max Grav 2=1453(LC 2), 7=1381(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-1984/282, 3-15=-1836/355, 4-15=-1696/375, 4-16=-1654/372, 5-16=-1794/349,  
 5-6=-400/149, 6-7=-358/128  
 BOT CHORD 2-11=-209/1611, 10-11=-209/1611, 10-17=-39/1038, 17-18=-39/1038, 9-18=-39/1038,  
 8-9=-160/1460, 7-8=-160/1460  
 WEBS 3-10=-414/240, 4-10=-189/928, 4-9=-181/864, 5-9=-314/241, 5-7=-1569/144

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Refer to girder(s) for truss to truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=151, 7=127.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard  
 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T02A	Common	2	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:00 2021 Page 2  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-ebMipXCH17pvubNCuPrSt9w6fK\_Zsk0LVzHxHyKxzX

**LOAD CASE(S)** Standard


Uniform Loads (plf)

Vert: 1-4=-66, 4-6=-66, 10-12=-20, 9-10=-60, 7-9=-20

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T02GE	GABLE	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MTEK Industries, Inc. Tue Nov 9 11:09:00 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-ebMipXCHI7pvubNCuPrSt9wE7K9asoBLVXzHxHyKxzX



Scale = 1:53.4




Plate Offsets (X,Y)-- [9:0-3-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.16	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.13	Vert(LL) -0.00 1 n/r 180		
TCDL 10.0	Lumber DOL 1.15	WB 0.21	Vert(CT) -0.00 1 n/r 120		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.01 17 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 154 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 OTHERS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 ~ 0-8-1

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 23-11-12.  
 (lb) - Max Horz 2=220(LC 13)  
 Max Uplift All uplift 100 lb or less at joint(s) 24, 25, 27, 28, 29, 22, 21, 20, 19 except 17=163(LC 15), 2=118(LC 14), 30=206(LC 16), 18=299(LC 17)  
 Max Grav All reactions 250 lb or less at joint(s) 25, 27, 28, 29, 30, 22, 21, 20, 19, 18 except 17=382(LC 17), 2=293(LC 32), 24=267(LC 30), 23=251(LC 6)


**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-381/240, 15-16=-302/206

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 24, 25, 27, 28, 29, 22, 21, 20, 19 except (jt=lb) 17=163, 2=118, 30=206, 18=299.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 21-6482-A	Truss T03	Truss Type Common	Qty 5	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
Riverside Roof Truss, LLC, Danville, VA. 24541					Job Reference (optional)

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:01 2021 Page 1  
 ID: xXVN1g\_eg3NzLwT48PmhGczX1xV-6nw41tCv3RxmVlyPS7MhPNTHnkLXbDMVkBirUjyKxzW



Scale = 1:55.0




Plate Offsets (X,Y)-- [2:Edge,0-2-0], [10:Edge,0-2-0]

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.68	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.72	Vert(LL) -0.24 11-13 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.34	Vert(CT) -0.32 11-13 >935 240		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.05 10 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 151 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP DSS  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 5-3-0 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
 WEBS 1 Row at midpt 4-14, 6-10

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 10=1141/0-5-8 (min. 0-1-9), 14=1141/0-5-8 (min. 0-1-9)  
 Max Horz 14=-243(LC 14)  
 Max Uplift10=-128(LC 17), 14=-128(LC 16)  
 Max Grav 10=1327(LC 2), 14=1327(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-675/180, 3-4=-502/201, 4-15=-1485/303, 5-15=-1333/326, 5-16=-1333/326,  
 6-16=-1485/303, 6-7=-503/201, 7-8=-675/180, 2-14=-627/202, 8-10=-627/202  
 BOT CHORD 13-14=-165/1356, 13-17=0/909, 12-17=0/909, 12-18=0/909, 11-18=0/909, 10-11=-90/1272  
 WEBS 5-11=-139/655, 6-11=-401/256, 5-13=-139/655, 4-13=-401/256, 4-14=-1055/77,  
 6-10=-1055/77


- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 4) Unbalanced snow loads have been considered for this design.
  - 5) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 7) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 10=128, 14=128.
  - 9) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T03GE	Common Supported Gable	2	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MITek Industries, Inc. Tue Nov 9 11:09:02 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-a\_USEDdXqk4d7vXb?qtwyba?bo8sYKIDezqSO0AyKxzV



Scale = 1:29.0




Plate Offsets (X,Y)-- [6:0-3-0,Edge], [10:Edge,0-3-10]

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	Plate Grip DOL	1.15	TC 0.09	Vert(LL)	-0.00	11	n/r	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Lumber DOL	1.15	BC 0.03	Vert(CT)	-0.00	11	n/r		
TCDL 10.0	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	10	n/a		
BCLL 0.0 *	Code IRC2015/TPI2014		Matrix-S						
BCDL 10.0								Weight: 71 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 OTHERS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 ~ 1-4-15, Right 2x4 SP No.3 ~ 1-4-15

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** All bearings 12-6-0.  
 (lb) - Max Horz 2=-120(LC 14)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 10, 15, 16, 17, 14, 13, 12  
 Max Grav All reactions 250 lb or less at joint(s) 2, 10, 15, 16, 17, 14, 13, 12

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - 4) TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 5) Unbalanced snow loads have been considered for this design.
  - 6) This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - 7) All plates are 2x4 MT20 unless otherwise indicated.
  - 8) Gable requires continuous bottom chord bearing.
  - 9) Gable studs spaced at 2-0-0 oc.
  - 10) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 11) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 12) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10, 15, 16, 17, 14, 13, 12.
  - 13) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



Job 21-6482-A	Truss T04	Truss Type ROOF SPECIAL GIRDER	Qty 1	Ply 3	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
------------------	--------------	-----------------------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MITek Industries, Inc. Tue Nov 9 11:09:03 2021 Page 1  
ID: xXVN1g\_eg3NzLwT48PmhGczX1xV-2A2rSZE9b2CUI36nZOX09UoYa4X9v306oCUBxYcyKxzU

-1-0-03-4-12	6-9-8	11-4-6	15-11-4	20-6-2	24-6-4	28-6-5	31-0-0
1-0-03-4-12	3-4-12	4-6-14	4-6-14	4-6-14	4-0-2	4-0-2	2-5-11

Scale = 1:112.6




Plate Offsets (X,Y)-- [16:0-4-0,0-4-8], [20:0-5-4,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	6-0-0	TC 0.88	Vert(LL)	-0.13 16-18	>999	360	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.21	Vert(CT)	-0.22 16-18	>999	240		
TCDL 10.0	Lumber DOL 1.15	WB 0.77	Horz(CT)	0.11 13	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr NO	Matrix-MS						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 1037 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x8 SP DSS  
BOT CHORD 2x8 SP DSS  
WEBS 2x4 SP No.3

**BRACING-**  
TOP CHORD 2-0-0 oc purlins (6-0-0 max.), except end verticals (Switched from sheeted: Spacing > 2-0-0).  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.  
WEBS 1 Row at midpt 12-13

**REACTIONS.** (lb/size) 2=4191/0-5-8 (min. 0-1-10), 13=3986/0-3-8 (min. 0-1-9)  
Max Horz 2=1698(LC 13)  
Max Uplift 2=318(LC 16), 13=985(LC 16)  
Max Grav 2=4872(LC 2), 13=4624(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-6922/523, 3-4=-6558/593, 4-5=-6212/631, 5-6=-9012/1398, 6-7=-9692/1835,  
7-8=-8427/1653, 8-9=-8070/1725, 9-10=-4002/948, 10-11=-1469/671, 11-12=-1391/784,  
12-13=-4344/1175  
BOT CHORD 2-21=-1895/5701, 20-21=-1895/5701, 19-20=-2064/6494, 18-19=-2857/8933,  
17-18=-3109/9464, 16-17=-3028/9526, 15-16=-2279/6720, 14-15=-1226/3365,  
13-14=-352/397  
WEBS 3-20=-347/206, 5-20=-2970/1108, 5-19=-670/2083, 6-19=-1718/813, 6-18=-253/651,  
7-18=-106/358, 7-16=-1176/517, 9-16=-1581/5689, 9-15=-5320/1669, 10-15=-1196/4527,  
10-14=-4774/1475, 11-14=-610/1048, 12-14=-1119/3670

- NOTES-**
- 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
Top chords connected as follows: 2x8 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.  
Bottom chords connected as follows: 2x8 - 2 rows staggered at 0-9-0 oc.  
Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=318, 13=985.

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T04	ROOF SPECIAL GIRDER	1	3	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:03 2021 Page 2  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-2A2rSZE9b2CUI36nZXO9UoYa4X9v306oCUBxYcyKxzU

**NOTES-**


11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard



Job 21-6482-A	Truss T06	Truss Type Roof Special	Qty 7	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
Riverside Roof Truss, LLC, Danville, VA. 24541					Job Reference (optional)

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:04 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-WMbDfvFnMMKLMdhz7FvO1?511xPPoUNxQ8xV42yKxzT



Scale = 1:119.6

Plate Offsets (X,Y)-- [10:0-2-0,0-3-0], [13:0-5-8,0-5-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.87	Vert(LL)	-0.10 11-12	>999	360	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.58	Vert(CT)	-0.19 11-12	>999	240		
TCDL 10.0	Lumber DOL 1.15	WB 0.71	Horz(CT)	0.11 9	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 239 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2 \*Except\*  
 B2,B4: 2x4 SP No.3  
 WEBS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-4-1 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 5-8-1 oc bracing. Except:  
 1 Row at midpt 6-10  
 WEBS 1 Row at midpt 2-15, 3-12, 5-12, 10-12, 7-10, 8-9, 7-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 16=1051/0-5-8 (min. 0-1-8), 9=1051/0-3-8 (min. 0-1-10)  
 Max Horz 16=563(LC 13)  
 Max Uplift 16=-18(LC 16), 9=-300(LC 16)  
 Max Grav 16=1219(LC 2), 9=1401(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-494/45, 2-3=-1361/549, 3-4=-1171/186, 4-5=-880/212, 5-6=-1067/253, 6-7=-1064/399,  
 1-16=-1186/92  
 BOT CHORD 15-16=-719/662, 3-13=-466/404, 12-13=-1070/1609, 6-10=-453/248, 10-18=-201/347,  
 18-19=-201/347, 9-19=-201/347  
 WEBS 2-15=-1591/826, 13-15=-1203/1518, 2-13=-720/1362, 3-12=-763/675, 5-12=-499/234,  
 10-12=-650/1313, 7-10=-634/1687, 1-15=-64/896, 7-9=-1277/559


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16 except (jt=lb) 9=300.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T06A	Roof Special	2	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:05 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-\_Z9bsFGQ7fSC\_NGAhyRdaDdvCLgXym4fog2dVyKxzS



Scale = 1:119.6




Plate Offsets (X,Y)-- [10:0-2-4,0-3-0], [13:0-5-8,0-5-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.91	Vert(LL)	-0.09 11-12	>999	360	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.58	Vert(CT)	-0.18 11-12	>999	240		
TCDL 10.0	Lumber DOL 1.15	WB 0.70	Horz(CT)	0.11 9	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 239 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2 \*Except\*  
 B2,B4: 2x4 SP No.3  
 WEBS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-4-9 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 5-7-14 oc bracing. Except:  
 1 Row at midpt 6-10  
 WEBS 1 Row at midpt 2-15, 3-12, 5-12, 10-12, 7-10, 8-9, 7-9

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 16=1038/0-5-8 (min. 0-1-8), 9=1038/Mechanical  
 Max Horz 16=566(LC 13)  
 Max Uplift 16=-14(LC 16), 9=-305(LC 16)  
 Max Grav 16=1204(LC 2), 9=1390(LC 29)


**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-488/40, 2-3=-1341/544, 3-4=-1150/182, 4-5=-858/208, 5-6=-1019/246, 6-7=-1016/393,  
 1-16=-1171/89  
 BOT CHORD 15-16=-730/673, 3-13=-478/418, 12-13=-1077/1607, 6-10=-453/248, 10-18=-192/321,  
 18-19=-192/321, 9-19=-192/321  
 WEBS 2-15=-1568/826, 13-15=-1216/1525, 2-13=-721/1343, 3-12=-775/686, 5-12=-477/227,  
 10-12=-647/1284, 7-10=-637/1668, 1-15=-61/884, 7-9=-1273/577

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Refer to girder(s) for truss connections.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 16 except (jt=lb) 9=305.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 21-6482-A	Truss T07	Truss Type Common	Qty 2	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
Riverside Roof Truss, LLC, Danville, VA. 24541					Job Reference (optional)

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:06 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-Sljz4aG2uza3cXrMEgys6QAC8I2rGWyEuSQc9xyKxzR



Scale = 1:44.0




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [8:0-5-5,Edge], [10:0-4-0,0-3-0]

<b>LOADING</b> (psf)	<b>SPACING-</b>	2-0-0	<b>CSI.</b>	<b>DEFL.</b>	in (loc)	I/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	Plate Grip DOL	1.15	TC 0.45	Vert(LL)	-0.12 10-13	>999	360	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Lumber DOL	1.15	BC 0.77	Vert(CT)	-0.24 10-13	>961	240		
TCDL 10.0	Rep Stress Incr	YES	WB 0.26	Horz(CT)	0.03 8	n/a	n/a		
BCLL 0.0 *	Code IRC2015/TPI2014		Matrix-MS						
BCDL 10.0								Weight: 103 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3  
SLIDER Left 2x4 SP No.3 ~ 2-6-0, Right 2x4 SP No.3 ~ 2-6-0

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 5-3-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=907/0-3-8 (min. 0-1-8), 8=907/0-3-8 (min. 0-1-8)  
Max Horz 2=-177(LC 14)  
Max Uplift 2=-103(LC 16), 8=-103(LC 17)  
Max Grav 2=1055(LC 2), 8=1055(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-698/0, 3-4=-1098/215, 4-19=-968/171, 5-19=-854/190, 5-20=-854/190, 6-20=-968/171, 6-7=-1098/215, 7-8=-698/0  
BOT CHORD 2-10=-141/968, 8-10=-80/968  
WEBS 5-10=-75/559, 6-10=-348/192, 4-10=-348/192


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=103, 8=103.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T07GE	GABLE	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:07 2021 Page 1  
 ID: xXVn1g\_eg3NzLwT48PmhGczX1xV-wxHLHwHgfHwDgPYoNT5fejNu9N4?zCN6699hNyKxzQ



4x4 =

Scale = 1:44.0




Plate Offsets (X,Y)-- [2:0-3-8,Edge], [8:0-5-5,Edge], [10:0-4-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.45	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.77	Vert(LL) -0.12 10-33 >999 360		
TCDL 10.0	Lumber DOL 1.15	WB 0.26	Vert(CT) -0.24 10-33 >961 240		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS	Horz(CT) 0.03 8 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 141 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3  
 OTHERS 2x4 SP No.3  
 SLIDER Left 2x4 SP No.3 ~ 2-6-0, Right 2x4 SP No.3 ~ 2-6-0

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 5-3-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 2=907/0-3-8 (min. 0-1-8), 8=907/0-3-8 (min. 0-1-8)  
 Max Horz 2=-177(LC 14)  
 Max Uplift 2=-103(LC 16), 8=-103(LC 17)  
 Max Grav 2=1055(LC 2), 8=1055(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-698/0, 3-4=-1098/215, 4-39=-968/171, 5-39=-854/190, 5-40=-854/190, 6-40=-968/171, 6-7=-1098/215, 7-8=-698/0  
 BOT CHORD 2-10=-141/968, 8-10=-80/968  
 WEBS 5-10=-75/559, 6-10=-348/192, 4-10=-348/192

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=103, 8=103.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T08	Common	4	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:07 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-wxHLHwHgfHwDgPYoNT5fejM89Le?uXN6699hNyKxzQ




Plate Offsets (X,Y)-- [1:Edge,0-2-0], [5:Edge,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.50	Vert(LL)	-0.18	7-9	>999	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.93	Vert(CT)	-0.36	6-7	>657		
TCDL 10.0	Lumber DOL 1.15	WB 0.55	Horz(CT)	0.03	6	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 110 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 5-5-3 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 2-2-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 6=839/0-5-8 (min. 0-1-8), 9=839/0-5-8 (min. 0-1-8)  
 Max Horz 9=-178(LC 12)  
 Max Uplift 6=-81(LC 17), 9=-81(LC 16)  
 Max Grav 6=973(LC 2), 9=973(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 1-2=-506/68, 2-10=-986/172, 3-10=-865/190, 3-11=-865/190, 4-11=-986/172, 4-5=-506/68,  
 1-9=-395/77, 5-6=-395/77  
 BOT CHORD 8-9=-155/982, 7-8=-155/982, 6-7=-124/982  
 WEBS 3-7=-82/589, 4-7=-349/210, 2-7=-349/210, 2-9=-804/166, 4-6=-804/166

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load; Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow; Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 9.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard



Job 21-6482-A	Truss T09	Truss Type Common	Qty 5	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
------------------	--------------	----------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:08 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-P8rkVGIIPaqrq\_IM5\_KBrFV3YidKlgXLmviEpyKxzP



Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T10	Roof Special Structural Gable	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:09 2021 Page 1  
 ID:xxVN1g\_eg3NzLwT48PmhGczX1xV-tKP6icJwAuyeT\_ZxwoVzk3ocDy3?TgGgaQeGmGyKxzO

-1-0-0	5-3-12	10-7-8	17-9-4	24-11-0	28-6-5	31-0-0
1-0-0	5-3-12	5-3-12	7-1-12	7-1-12	3-7-5	2-5-11

Scale = 1:116.0




Plate Offsets (X,Y)-- [9:0-1-0,0-1-8], [12:0-2-4,Edge], [18:Edge,0-6-4], [25:0-1-9,0-1-0], [29:0-1-9,0-1-0], [41:0-1-13,0-1-0], [45:0-1-13,0-1-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.84	Vert(LL)	-0.16 14-15	>999	360	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.81	Vert(CT)	-0.32 14-15	>999	240		
TCDL 10.0	Lumber DOL 1.15	WB 0.99	Horz(CT)	0.11 11	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 392 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2 \*Except\*  
 B2,B4: 2x4 SP No.3  
 WEBS 2x4 SP No.3  
 OTHERS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-10-4 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:  
 6-6-14 oc bracing: 17-18  
 6-3-9 oc bracing: 14-15.  
 1 Row at midpt 8-12  
 1 Row at midpt 5-14, 7-14, 9-12, 10-11, 9-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 18=1401/0-5-8 (min. 0-1-15), 11=1322/0-3-8 (min. 0-2-0)  
 Max Horz 18=582(LC 13)  
 Max Uplift 18=-103(LC 16), 11=-332(LC 16)  
 Max Grav 18=1629(LC 2), 11=1679(LC 30)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-2140/159, 3-4=-1985/176, 4-5=-3066/497, 5-6=-1703/261, 6-7=-1411/286,  
 7-8=-1350/294, 8-9=-1320/440, 2-18=-1572/202  
 BOT CHORD 17-18=-814/932, 5-15=-277/1062, 14-15=-867/2620, 8-12=-450/248, 12-55=-188/381,  
 55-56=-188/381, 11-56=-188/381  
 WEBS 4-17=-1083/416, 15-17=-699/2011, 4-15=-260/873, 5-14=-1452/491, 7-14=-304/249,  
 12-14=-593/1831, 7-12=-371/188, 9-12=-589/2131, 2-17=-12/1321, 9-11=-1559/523

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 18=103 11=332.

Continued on page 2

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T10	Roof Special Structural Gable	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MITek Industries, Inc. Tue Nov 9 11:09:10 2021 Page 2  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-LWzUwyJYxC4V4887TW0oHGLnzMPEC7Wpp4OplyKxzN

**NOTES-**

12) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	T11	Roof Special	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:10 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-LWzUwyJYxC4V4887TW0oHGLnzMPEC7Wpp4OplyKxzN

-1-0-0	5-3-12	10-7-8	17-9-4	24-11-0	28-6-5	31-0-0
1-0-0	5-3-12	5-3-12	7-1-12	7-1-12	3-7-5	2-5-11

Scale = 1:111.4




Plate Offsets (X,Y)-- [12:0-2-4,Edge], [18:Edge,0-6-4]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.84	Vert(LL)	-0.16 14-15	>999	360	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.81	Vert(CT)	-0.32 14-15	>999	240		
TCDL 10.0	Lumber DOL 1.15	WB 0.99	Horz(CT)	0.11 11	n/a	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-MS						
BCDL 10.0	Code IRC2015/TPI2014						Weight: 258 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2 \*Except\*  
 B2,B4: 2x4 SP No.3  
 WEBS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-10-4 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:  
 6-6-14 oc bracing: 17-18  
 6-3-9 oc bracing: 14-15.  
 1 Row at midpt 8-12  
 1 Row at midpt 5-14, 7-14, 9-12, 10-11, 9-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 18=1401/0-5-8 (min. 0-1-15), 11=1322/0-3-8 (min. 0-2-0)  
 Max Horz 18=582(LC 13)  
 Max Uplift 18=-103(LC 16), 11=-332(LC 16)  
 Max Grav 18=1629(LC 2), 11=1679(LC 30)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-2140/159, 3-4=-1985/176, 4-5=-3066/497, 5-6=-1703/261, 6-7=-1411/286,  
 7-8=-1350/294, 8-9=-1320/440, 2-18=-1572/202  
 BOT CHORD 17-18=-814/932, 5-15=-277/1062, 14-15=-867/2620, 8-12=-450/248, 12-20=-188/381,  
 20-21=-188/381, 11-21=-188/381  
 WEBS 4-17=-1083/416, 15-17=-699/2011, 4-15=-260/873, 5-14=-1452/491, 7-14=-304/249,  
 12-14=-593/1831, 7-12=-371/188, 9-12=-589/2131, 2-17=-12/1321, 9-11=-1559/523


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCCL: ASCE 7-10; Pr=30.0 psf (roof live load); Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow); Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - This truss has been designed for greater of min roof live load of 12.0 psf or 1.00 times flat roof load of 23.1 psf on overhangs non-concurrent with other live loads.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 18=103, 11=332.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	V01	Valley	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:11 2021 Page 1  
ID:xXVn1g\_eg3NzLwT48PmhGczX1xV-pjXs7IKAiVCMiljK1DY1pUt5dmvBxm?z1k7Nq8yKxzM



Scale = 1:43.6

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.27	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.19	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.20	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 93 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.3

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 21-3-8.  
(lb) - Max Horz 1=168(LC 12)  
Max Uplift All uplift 100 lb or less at joint(s) 1, 7 except 11=144(LC 16), 13=107(LC 16), 9=144(LC 17), 8=107(LC 17)  
Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 10=430(LC 32), 11=494(LC 29), 13=341(LC 2), 9=494(LC 30), 8=341(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
**WEBS** 3-11=-357/194, 2-13=-270/147, 5-9=-357/194, 6-8=-270/147


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 7 except (jt=lb) 11=144, 13=107, 9=144, 8=107.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	V02	Valley	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:12 2021 Page 1  
 ID: xXVN1g\_eg3NzLwT48PmhGczX1xV-Hv4ELeLpTpKCKSIWbw3GMhQGhAF1gFR6G0twNbyKxzL



Scale = 1:37.2

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.32	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.15	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.13	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 70 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 OTHERS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 17-3-8.  
 (lb) - Max Horz 1=-135(LC 12)  
 Max Uplift All uplift 100 lb or less at joint(s) 1 except 9=-160(LC 16), 6=-160(LC 17)  
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=382(LC 29), 9=505(LC 29), 6=505(LC 30)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 2-9=-387/207, 4-6=-387/207


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 9=160, 6=160.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	V03	Valley	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:12 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-Hv4ELeLpTpKCKSIWbw3GMhQHyaAGSgF46G0twNbyKxzL



Scale = 1:27.4

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.23	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.12	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.09	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 5 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 51 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 OTHERS 2x4 SP No.3

**BRACING-**  
 TOP CHORD  
 BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** All bearings 13-3-8.  
 (lb) - Max Horz 1=-102(LC 12)  
 Max Uplift All uplift 100 lb or less at joint(s) 1 except 8=-128(LC 16), 6=-128(LC 17)  
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=326(LC 2), 8=382(LC 33), 6=382(LC 34)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 2-8=-314/169, 4-6=-314/169


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 8=128, 6=128.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	V04	Valley	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:13 2021 Page 1  
ID: xXVN1g\_eg3NzLwT48PmhGczX1xV-l5edY\_MRE7S3xbti9eaVuvzQlZasPidGV2cTv1yKxzK



Scale = 1:20.1

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.32	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.17	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.07	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 33 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.3

**BRACING-**  
TOP CHORD  
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.  
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=178/9-3-8 (min. 0-1-8), 3=178/9-3-8 (min. 0-1-8), 4=363/9-3-8 (min. 0-1-8)  
Max Horz 1=-69(LC 14)  
Max Uplift 1=-30(LC 16), 3=-40(LC 17), 4=-11(LC 16)  
Max Grav 1=208(LC 2), 3=208(LC 2), 4=417(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
WEBS 2-4=-286/78

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


**LOAD CASE(S)** Standard



Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	V05	Valley	2	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:14 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-DIC?IJN3?QawZISuiL5kR6VaczwG8A\_PjiM1RTyKxzJ



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.42	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.16	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.06	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 31 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.3

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=188/8-11-4 (min. 0-1-8), 3=188/8-11-4 (min. 0-1-8), 4=316/8-11-4 (min. 0-1-8)  
Max Horz 1=-66(LC 12)  
Max Uplift 1=-39(LC 16), 3=-47(LC 17)  
Max Grav 1=221(LC 2), 3=221(LC 2), 4=361(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
WEBS 2-4=-261/70


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 21-6482-A	Truss V06	Truss Type Valley	Qty 2	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF Job Reference (optional)
------------------	--------------	----------------------	----------	----------	---


Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:14 2021 Page 1  
ID: xXVN1g\_eg3NzLwT48PmhGczX1xV-DIC?IJN3?QawZISuiL5kR6VfzyA8AWPjim1RTyKxzJ



4x4 =

Scale = 1:12.7



<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	Plate Grip DOL 1.15	TC 0.09	Vert(LL) n/a - n/a 999	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Lumber DOL 1.15	BC 0.04	Vert(CT) n/a - n/a 999		
TCDL 10.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 3 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 16 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.3

**BRACING-**  
TOP CHORD  
BOT CHORD

Structural wood sheathing directly applied or 5-0-0 oc purlins.  
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=95/4-11-4 (min. 0-1-8), 3=95/4-11-4 (min. 0-1-8), 4=159/4-11-4 (min. 0-1-8)  
Max Horz 1=-33(LC 14)  
Max Uplift1=-19(LC 16), 3=-24(LC 17)  
Max Grav 1=111(LC 2), 3=111(LC 2), 4=181(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	V07	Valley	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:15 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-hUmNzfNhmkinBv15G3cz\_K2kINF\_td9ZyM5azvyKxzI



Scale = 1:18.1

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.42	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.20	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 18 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
WEBS 2x4 SP No.3

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 4-8-0 oc purlins, except end verticals.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=174/4-8-0 (min. 0-1-8), 3=174/4-8-0 (min. 0-1-8)  
Max Horz 1=102(LC 13)  
Max Uplift 1=12(LC 16), 3=47(LC 16)  
Max Grav 1=202(LC 2), 3=208(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 3) Unbalanced snow loads have been considered for this design.
  - 4) Gable requires continuous bottom chord bearing.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard




Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	V09	Valley	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:16 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-AgKIA?OJX2qeo3bHqm7CWXa\_Anec4PiB0r8WMyKxzH

2-7-8  
2-7-8

Scale = 1:11.4



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.09	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.04	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 9 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 2-7-8 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=86/2-7-8 (min. 0-1-8), 3=86/2-7-8 (min. 0-1-8)  
 Max Horz 1=50(LC 13)  
 Max Uplift 1=-6(LC 16), 3=-23(LC 16)  
 Max Grav 1=100(LC 2), 3=103(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 3) Unbalanced snow loads have been considered for this design.
  - 4) Gable requires continuous bottom chord bearing.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job	Truss	Truss Type	Qty	Ply	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
21-6482-A	V10	Valley	1	1	Job Reference (optional)

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:17 2021 Page 1  
 ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-esu7OLPxILzVQDATOUeR3i74wByXLXfrQgah2oyKxzG



Scale = 1:17.9

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	2-0-0	TC 0.41	in (loc) l/defl L/d	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.19	Vert(LL) n/a - n/a 999		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Vert(CT) n/a - n/a 999		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P	Horz(CT) 0.00 3 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014			Weight: 18 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x4 SP No.2  
 BOT CHORD 2x4 SP No.2  
 WEBS 2x4 SP No.3

**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 4-7-8 oc purlins, except end verticals.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=172/4-7-8 (min. 0-1-8), 3=172/4-7-8 (min. 0-1-8)  
 Max Horz 1=101(LC 13)  
 Max Uplift 1=12(LC 16), 3=47(LC 16)  
 Max Grav 1=200(LC 2), 3=206(LC 29)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - 3) Unbalanced snow loads have been considered for this design.
  - 4) Gable requires continuous bottom chord bearing.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - 8) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 21-6482-A	Truss V11	Truss Type Valley	Qty 1	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF
------------------	--------------	----------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:17 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-esu7OLPxILzVQDATOUeR3I7AyB\_eLXfrQgah2oyKxzG



Scale = 1:7.9

Plate Offsets (X,Y)-- [2:0-2-0,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof) 30.0	2-0-0	TC 0.03	Vert(LL)	n/a	-	n/a	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Plate Grip DOL 1.15	BC 0.06	Vert(CT)	n/a	-	n/a		
TCDL 10.0	Lumber DOL 1.15	WB 0.00	Horz(CT)	0.00	3	n/a		
BCLL 0.0 *	Rep Stress Incr YES	Matrix-P					Weight: 9 lb	FT = 20%
BCDL 10.0	Code IRC2015/TPI2014							

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 3-2-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=95/3-2-0 (min. 0-1-8), 3=95/3-2-0 (min. 0-1-8)  
Max Horz 1=-18(LC 14)  
Max Uplift 1=-9(LC 16), 3=-9(LC 17)  
Max Grav 1=110(LC 2), 3=110(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.


- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard

Job 21-6482-A	Truss V12	Truss Type Valley	Qty 1	Ply 1	POSTON-KATIE LASSEK RES PLAN 24376 ROOF Job Reference (optional)
------------------	--------------	----------------------	----------	----------	---

Riverside Roof Truss, LLC, Danville, VA. 24541

Run: 8.500 s May 17 2021 Print: 8.500 s May 17 2021 MiTek Industries, Inc. Tue Nov 9 11:09:18 2021 Page 1  
ID:xXVN1g\_eg3NzLwT48PmhGczX1xV-63SVbhQZ3f5M2NlgxBAGbygKPaK04\_T?eKKEaEyKxzF



Scale = 1:13.2

<b>LOADING</b> (psf)	<b>SPACING-</b> 2-0-0	<b>CSI.</b>	<b>DEFL.</b> in (loc) l/defl L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL (roof) 30.0	Plate Grip DOL 1.15	TC 0.11	Vert(LL) n/a - n/a 999	MT20	244/190
Snow (Pf/Pg) 23.1/30.0	Lumber DOL 1.15	BC 0.05	Vert(CT) n/a - n/a 999		
TCDL 10.0	Rep Stress Incr YES	WB 0.03	Horz(CT) 0.00 3 n/a n/a		
BCLL 0.0 *	Code IRC2015/TPI2014	Matrix-P			
BCDL 10.0				Weight: 17 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x4 SP No.2  
BOT CHORD 2x4 SP No.2  
OTHERS 2x4 SP No.3

**BRACING-**  
TOP CHORD  
BOT CHORD

Structural wood sheathing directly applied or 5-3-8 oc purlins.  
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

**REACTIONS.** (lb/size) 1=101/5-3-8 (min. 0-1-8), 3=101/5-3-8 (min. 0-1-8), 4=170/5-3-8 (min. 0-1-8)  
Max Horz 1=-36(LC 12)  
Max Uplift 1=-21(LC 16), 3=-26(LC 17)  
Max Grav 1=119(LC 2), 3=119(LC 2), 4=194(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - TCLL: ASCE 7-10; Pr=30.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=30.0 psf (ground snow); Pf=23.1 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Partially Exp.; Ct=1.10
  - Unbalanced snow loads have been considered for this design.
  - Gable requires continuous bottom chord bearing.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.
  - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

**LOAD CASE(S)** Standard