



Phone: (919) 363-4956 Fax: (919) 387-8565 https://www.bldr.com

General Notes: - Per ANSI/TPI 1-2002 all " Truss to Wall" connections are the responsibility of the Building

- Designer, not the Truss Manufacturer.
 Dimensions are Feet-Inches- Sixteenths.
 Trusses are to be 24" o.c. unless noted otherwise (U.N.O.)
- Trusses are not designed to support brick U.N.O.
- Do not cut or modify trustes without first contacting Builders FirstSource.
 Immediately contact Builders FirstSource if trusses are damaged.


- Connection Notes: All hangers are to be Simpson or equivalent U.N.O. Use Manufacturer's specifications for all hanger
- connections U.N.O. Use 10d x 1 1/2" Nails in hanger connections to single ply roof girder trusses.

Ploor notes: - Shift truss as required to avoid plumbing traps. - Installation Contractor and/or Field Supervisor are to verify all dimensions, trap locations, and options prior to installation

Dimension Notes:

- Drawing not to scale. Do not scale dimensions

 $\bigtriangleup \triangleleft \bigtriangledown \triangleright$ Left end of truss as shown on truss detail drawings are indicated by triangle icons.



<u>HANGER LIST</u>					ALL TIE DOWNS H2.5A UNLESS NOTED			
4				L 4	SPECIAL ITEMS LIST			
9		ITU26		<u>M</u> _6				
2	L	_GT2		J L				
					MISC MATERIAL			
				IATTAI	1Y HOMES			
REDWOOD						ELEV: CRAFTSMAN		
PROVIDENCE CREEK								
NC				NC	LOT:		99	
					<u>APPWRIGHT #</u>			
GARAGE RH				4	XXXXXXX			
 SCREENED PORCH 					CODE		IRC 2015	
					LOADING:			
					T.C.L.	L.	20 PSF	
DESIGNED BY:			A	3S	T.C.D.	.L. 10 PSF		
LAY	AYQUT:			B.C.L.L.		0 PSF		
L/Q	DATE:	1/:	18/2	022	B.C.D.	L.	10 PSF	
REVISION HISTORY					<u>WIND:</u>			
RE	V1:	XX	K/XX	/XX	M.P.H	M.P.H. 115 MPH		
RE	V2:	XX	K/XX	/XX	EXPO	EXPOSURE CATEGORY		
RE	V3:	XX	K/XX	/XX	B (WO	B (WOODED AREAS/OTHERS)		
PICK TICKET:				JOB NO:				
SALES NO:				ACCT NO:				
<u>HATCH LEGEND</u>								
* *	ττΑ		TIC ROOM					
	VOLUME C		EILING					
\mathbb{Z}		STIC	CK FR/	AMING				