

Truss Placement Plan SCALE: 1/4"=1'

(BASED ON TABLES R502.5(1) & (b)) NUMBER OF JACK STUDS REQUIRED ⊕ EA END OF HEADER/GIRDER

END REACTION
(UP TO)
REQ'D STUDS FOR
(3) PLY HEADER

2550 1

5100 2

7650 3

10200 4

12750 5

15300 6

8500 5 10200 6

11900 7 13600 8

15300 9

🛕 = Indicates Left End of Truss (Reference Engineered Truss Drawing) Do NOT Erect Truss Backwards

i(1) & (b)) ED @ EA END OF	BUILDER	Signature Home Builders	CITY / CO.	Erwin / Harnett	These trusses are designed as individual building components to be inco the building design at the specification of the building designer. See individual sheets for each truss design identified on the placement drawing. The buil
3400 1 6800 2 10200 3 13600 4 17000 5	JOB NAME	Lot 16 Wildwood	ADDRESS	Lot 16 Wildwood	is responsible for temporary and permanent bracing of the roof and floor of the overall structure. The design of the truss support structure including he walls, and columns is the responsibility of the building designer. For gene regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss of
		Dorchester B GR2 (Full FP)	MODEL	Roof	or online @ sbcindustry.com Bearing reactions less than or equal to 3000# are deemed to comp prescriptive Code requirements. The contractor shall refer to the a
	SEAL DATE	4/8/2020	DATE REV.	02/04/22	(derived from the prescriptive Code requirements) to determine it foundation size and number of wood studs required to support reathan 3000# but not greater than 15000#. A registered design profes be retained to design the support system for any reaction that exc specified in the attached Tables. A registered design professional retained to design the support system for all reactions that exceed the support of the suppor
	QUOTE#	B1020-4902	DRAWN BY	Marshall Naylor	
	JOB#	J0222-0556	SALES REP.	Anthony Williams	Marshall Naylor



Fayetteville, N.C. 28309

Phone: (910) 864-8787

Fax: (910) 864-4444