

Trenco  
818 Soundside Rd  
Edenton, NC 27932

Re: J0222-0556  
Lot 16 Wildwood

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Comtech, Inc - Fayetteville.

Pages or sheets covered by this seal: I50071073 thru I50071094

My license renewal date for the state of North Carolina is December 31, 2022.

North Carolina COA: C-0844



February 4, 2022

Gilbert, Eric

**IMPORTANT NOTE:** The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071073
J0222-0556	A01	GABLE	1	1	Job Reference (optional)	


Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:33 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-gDj6DRMl0m9ZV5m8MI5yHRIGyJTCV7ciToQibhzoYJS

-0-10-8 19-0-0 38-0-0 38-10-8  
 0-10-8 19-0-0 19-0-0 0-10-8

Scale: 3/16"=1'



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	2-0-0	TC 0.07	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) 0.00 22 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.15	Vert(CT) 0.00 22 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.01 22 n/a n/a		
	Code IRC2015/TPI2014			Weight: 259 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.2	

**REACTIONS.** All bearings 38-0-0.  
 (lb) - Max Horz 2=168(LC 12)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 22, 34, 35, 37, 38, 39, 40, 41, 42, 32, 31, 29, 28, 27, 26, 25, 24  
 Max Grav All reactions 250 lb or less at joint(s) 2, 22, 33, 34, 35, 37, 38, 39, 40, 41, 42, 32, 31, 29, 28, 27, 26, 25, 24

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 10-11=-89/265, 11-12=-105/308, 12-13=-105/309, 13-14=-89/266

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 3-6-5, Exterior(2) 3-6-5 to 19-0-0, Corner(3) 19-0-0 to 23-4-13, Exterior(2) 23-4-13 to 38-10-8 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - All plates are 2x4 MT20 unless otherwise indicated.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 40.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 22, 34, 35, 37, 38, 39, 40, 41, 42, 32, 31, 29, 28, 27, 26, 25, 24.



February 4, 2022

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071074
J0222-0556	A02	COMMON	16	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:35 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-dbrse700YNQHIPwWTA8QM870Vz??x6vpgazoYjQ

0-10-8 9-7-2 19-0-0 28-4-14 38-0-0 38-10-8  
 0-10-8 9-7-2 9-4-14 9-4-14 9-7-2 0-10-8

Scale = 1:65.8



<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	2-0-0	TC 0.41	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.62	Vert(LL) -0.30 10-13 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.28	Vert(CT) -0.47 10-13 >970 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.08 8 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.09 2-13 >999 240	Weight: 233 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 3-11-13 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

**REACTIONS.** (size) 2=0-3-8, 8=0-3-8  
 Max Horz 2=98(LC 12)  
 Max Uplift 2=107(LC 12), 8=107(LC 13)  
 Max Grav 2=1559(LC 1), 8=1559(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-3064/658, 3-5=-2696/612, 5-7=-2696/612, 7-8=-3064/658  
 BOT CHORD 2-13=-493/2755, 10-13=-215/1799, 8-10=-501/2755  
 WEBS 5-10=-124/981, 7-10=-614/329, 5-13=-124/981, 3-13=-614/329

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 19-0-0, Exterior(2) 19-0-0 to 23-4-13, Interior(1) 23-4-13 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 2=107, 8=107.



February 4, 2022

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071075
J0222-0556	A03	COMMON	2	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:36 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-5oPErSPeJhY8MZV1tffv4wivXLeIRQ89meMC0zoYjP

0-10-8 9-7-2 19-0-0 28-4-14 38-0-0 38-10-8  
 0-10-8 9-7-2 9-4-14 9-4-14 9-7-2 0-10-8

Scale = 1:67.2




LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.41	Vert(LL) -0.18	2-15	>999	360		MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.69	Vert(CT) -0.39	8-10	>999	240			
BCLL 0.0 *	Rep Stress Incr YES	WB 0.27	Horz(CT) 0.08	8	n/a	n/a			
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.09	2-15	>999	240			
								Weight: 252 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 3-9-11 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2 *Except* 12-13: 2x6 SP No.1	

**REACTIONS.** (size) 2=0-3-8, 8=0-3-8  
 Max Horz 2=98(LC 12)  
 Max Uplift 2=-7(LC 12), 8=-7(LC 13)  
 Max Grav 2=1659(LC 1), 8=1659(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-3327/394, 3-5=-2960/346, 5-7=-2960/346, 7-8=-3327/394  
 BOT CHORD 2-15=-251/2995, 10-15=-49/1964, 8-10=-259/2995  
 WEBS 5-10=0/1086, 7-10=-608/335, 5-15=0/1086, 3-15=-608/335

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 19-0-0, Exterior(2) 19-0-0 to 23-4-13, Interior(1) 23-4-13 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 200.0lb AC unit load placed on the bottom chord, 19-0-0 from left end, supported at two points, 3-0-0 apart.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8.



February 4, 2022

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071076
J0222-0556	A04	COMMON	1	1		

Comtech, Inc., Fayetteville, NC - 28314,


8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:37 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-Z\_zd3oPG4\_g?\_j4vbaAuRHStfwhRugHOQOwkTzoYJO

Job Reference (optional)

0-10-8 9-7-2 19-0-0 28-4-14 38-0-0 38-10-8  
 0-10-8 9-7-2 9-4-14 9-4-14 9-7-2 0-10-8

Scale = 1:67.2



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.41	Vert(LL) -0.18	2-15	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.69	Vert(CT) -0.39	8-10	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.27	Horz(CT) 0.08	8	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.09	2-15	>999	240		
							Weight: 252 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 12-13: 2x6 SP No.1

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 3-9-11 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.**


(size) 2=0-3-8, 8=0-3-8  
 Max Horz 2=98(LC 12)  
 Max Uplift 2=-7(LC 12), 8=-7(LC 13)  
 Max Grav 2=1659(LC 1), 8=1659(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-3327/394, 3-5=-2960/346, 5-7=-2960/346, 7-8=-3327/394  
 BOT CHORD 2-15=-251/2995, 10-15=-49/1964, 8-10=-259/2995  
 WEBS 5-10=0/1086, 7-10=-608/335, 5-15=0/1086, 3-15=-608/335

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 19-0-0, Exterior(2) 19-0-0 to 23-4-13, Interior(1) 23-4-13 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 200.0lb AC unit load placed on the bottom chord, 19-0-0 from left end, supported at two points, 3-0-0 apart.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071077
J0222-0556	A05	COMMON	1	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:38 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-1AX?G8Qurlscf58lh7\_V?2HK1PALmRd47THvzoYjN

0-10-8 9-7-2 19-0-0 28-4-14 38-0-0 38-10-8  
 0-10-8 9-7-2 9-4-14 9-4-14 9-7-2 0-10-8

Scale = 1:67.2



	12-8-12 12-8-12	15-0-0 2-3-4	18-4-0 3-4-0	23-0-0 4-8-0	25-3-4 2-3-4	38-0-0 12-8-12
<b>LOADING</b> (psf)	<b>SPACING-</b>		<b>CSI.</b>	<b>DEFL.</b>		<b>PLATES</b>
TCLL 20.0	2-0-0		TC 0.42	in (loc) l/defl L/d		<b>GRIP</b>
TCDL 10.0	Plate Grip DOL 1.15		BC 0.60	Vert(LL) -0.19 2-16 >999 360		MT20 244/190
BCLL 0.0 *	Lumber DOL 1.15		WB 0.28	Vert(CT) -0.45 2-16 >486 240		
BCDL 10.0	Rep Stress Incr YES		Matrix-S	Horz(CT) 0.05 8 n/a n/a		
	Code IRC2015/TPI2014			Wind(LL) 0.10 2-16 >999 240		Weight: 252 lb FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 12-14: 2x6 SP No.1

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 4-6-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.**

(size) 2=0-3-8, 8=0-3-8, 13=0-3-8  
 Max Horz 2=98(LC 12)  
 Max Uplift 2=-97(LC 12), 8=-98(LC 13)  
 Max Grav 2=1296(LC 1), 8=1316(LC 1), 13=799(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2357/533, 3-5=-1983/486, 5-7=-2038/479, 7-8=-2411/526  
 BOT CHORD 2-16=-379/2108, 13-16=-139/1391, 10-13=-138/1385, 8-10=-379/2158  
 WEBS 5-10=-55/739, 7-10=-628/332, 5-16=-67/670, 3-16=-629/331

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 19-0-0, Exterior(2) 19-0-0 to 23-4-13, Interior(1) 23-4-13 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 200.0lb AC unit load placed on the bottom chord, 19-0-0 from left end, supported at two points, 3-0-0 apart.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932




Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071078
J0222-0556	A06	COMMON	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:39 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-VN5NUURWccwjD0EHi?CMXiYDDkNbvoKarkt1pLzoYjM



Scale = 1:75.7





Plate Offsets (X,Y)-- [6:0-3-0,0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.41	Vert(LL) -0.20	2-18	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.61	Vert(CT) -0.46	2-18	>480	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.26	Horz(CT) 0.05	10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.10	2-18	>999	240	Weight: 250 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2 \*Except\*  
 14-16: 2x6 SP No.1

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 4-4-12 oc purlins, except 2-0-0 oc purlins (5-6-3 max.): 5-7.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.**

(size) 2=0-3-8, 10=0-3-8, 15=0-3-8  
 Max Horz 2=93(LC 12)  
 Max Uplift 2=86(LC 12), 10=87(LC 13)  
 Max Grav 2=1303(LC 1), 10=1322(LC 1), 15=772(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2362/567, 3-5=-2002/505, 7-9=-2055/498, 9-10=-2414/560, 5-6=-1724/526, 6-7=-1774/520  
 BOT CHORD 2-18=-430/2110, 15-18=-176/1419, 12-15=-175/1413, 10-12=-422/2157  
 WEBS 6-12=-54/715, 9-12=-579/345, 6-18=-63/649, 3-18=-584/344

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 18-0-0, Exterior(2) 18-0-0 to 26-2-11, Interior(1) 26-2-11 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 200.0lb AC unit load placed on the bottom chord, 19-0-0 from left end, supported at two points, 5-0-0 apart.
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 10.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSITPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071079
J0222-0556	A07	COMMON	1	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:40 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-zZflhqS8Nv2arApUGjib3w4Nq8joeFUk4NcaLnzoYJL



Scale = 1:70.9




<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	2-0-0	TC 0.48	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.61	Vert(LL) -0.32 9-11 >724 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.27	Vert(CT) -0.56 9-11 >413 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.05 9 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.17 9-11 >999 240	Weight: 243 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 4-2-10 oc purlins, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (5-11-1 max.): 5-6.
WEBS 2x4 SP No.2 *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
13-15: 2x6 SP No.1	

**REACTIONS.** (size) 2=0-3-8, 9=0-3-8, 14=0-3-8  
 Max Horz 2=83(LC 12)  
 Max Uplift 2=-69(LC 12), 9=-83(LC 13)  
 Max Grav 2=1318(LC 1), 9=1336(LC 1), 14=811(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-2391/586, 3-5=-2049/541, 6-8=-2089/541, 8-9=-2436/611, 5-6=-1621/535  
 BOT CHORD 2-17=-446/2132, 14-17=-250/1640, 11-14=-250/1635, 9-11=-466/2175  
 WEBS 6-11=-22/589, 8-11=-596/332, 5-17=-17/510, 3-17=-583/335

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 16-0-0, Exterior(2) 16-0-0 to 28-2-11, Interior(1) 28-2-11 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 200.0lb AC unit load placed on the bottom chord, 19-0-0 from left end, supported at two points, 5-0-0 apart.
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 9.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 4, 2022



Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071080
J0222-0556	A08	COMMON	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:41 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-RIC7uASm8DARTK0gqQFqc7dXQY01NvtJ1M7IEzoYjK

0-10-8 9-7-2 14-0-0 19-0-0 24-0-0 28-4-14 38-0-0 38-10-8  
 0-10-8 9-7-2 4-4-14 5-0-0 5-0-0 4-4-14 9-7-2 0-10-8

Scale = 1:70.9




Plate Offsets (X,Y)--	[12:0-6-0,0-5-0], [16:0-2-12,0-5-4]
-----------------------	-------------------------------------

LOADING (psf)	SPACING-	CSL	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.55	Vert(LL) -0.25	11-12	>934	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.80	Vert(CT) -0.36	11-12	>640	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.51	Horz(CT) 0.04	9	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.12	11-12	>999	240		
							Weight: 250 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 4-8-13 oc purlins, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (5-8-1 max.): 5-6.
WEBS 2x4 SP No.2 *Except* 13-15: 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 2=0-3-8, 9=0-3-8, 14=0-3-8  
 Max Horz 2=73(LC 12)  
 Max Uplift 2=-65(LC 12), 9=-89(LC 13)  
 Max Grav 2=1103(LC 1), 9=1133(LC 1), 14=1200(LC 2)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-1955/508, 3-5=-1347/479, 6-8=-1359/470, 8-9=-2053/546, 5-6=-1198/464  
 BOT CHORD 2-17=-369/1702, 16-17=-369/1702, 14-16=-211/1232, 12-14=-212/1223, 11-12=-402/1793,  
 9-11=-402/1793  
 WEBS 8-11=0/464, 3-17=0/392, 3-16=-831/273, 8-12=-906/267

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
  - 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-8-7 to 3-8-6, Interior(1) 3-8-6 to 14-0-0, Exterior(2) 14-0-0 to 20-2-11, Interior(1) 20-2-11 to 24-0-0, Exterior(2) 24-0-0 to 30-2-11, Interior(1) 30-2-11 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 3) 200.0lb AC unit load placed on the bottom chord, 19-0-0 from left end, supported at two points, 5-0-0 apart.
  - 4) Provide adequate drainage to prevent water ponding.
  - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 6) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
  - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 9.
  - 8) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**  
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

**ENGINEERING BY**  
**TRENCO**  
 A MiTek Affiliate  
 818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071081
J0222-0556	A09	HIP	1	1		

Comtech, Inc., Fayetteville, NC - 28314,


8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:42 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-wymW6WTPvXIH5UzsN8m38LAgAxU066P1Yh5hQgzoYjJ

Job Reference (optional)

-0-10-8	6-1-2	12-0-0	18-6-12	26-0-0	31-10-14	38-0-0	38-10-8
0-10-8	6-1-2	5-10-14	6-6-12	7-5-4	5-10-14	6-1-2	0-10-8

Scale = 1:66.4



9-4-8	18-6-12	28-2-4	38-0-0
9-4-8	9-2-4	9-7-8	9-9-12

<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.62	Vert(LL) -0.06	8-10	>999	360		MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.31	Vert(CT) -0.13	8-10	>999	240			
BCLL 0.0 *	Rep Stress Incr YES	WB 0.50	Horz(CT) 0.02	8	n/a	n/a			
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.02	8-10	>999	240			
								Weight: 212 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 5-10-1 oc purlins, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (10-0-0 max.): 4-6.
WEBS 2x4 SP No.2	Rigid ceiling directly applied or 10-0-0 oc bracing.
	T-Brace: 2x4 SPF No.2 - 4-12, 6-12
	Fasten (2X) T and I braces to narrow edge of web with 10d (0.131"x3") nails, 6in o.c., with 3in minimum end distance.
	Brace must cover 90% of web length.

**REACTIONS.** (size) 2=0-5-8, 12=0-5-8, 8=0-3-8  
 Max Horz 2=-64(LC 17)  
 Max Uplift 2=-65(LC 12), 12=-117(LC 8), 8=-72(LC 13)  
 Max Grav 2=647(LC 23), 12=1871(LC 1), 8=687(LC 24)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-931/263, 3-4=-601/157, 4-5=-65/596, 5-6=-65/596, 6-7=-680/173, 7-8=-1036/297  
 BOT CHORD 2-14=-179/790, 12-14=0/262, 10-12=0/374, 8-10=-208/888  
 WEBS 3-14=-387/272, 4-14=-52/538, 4-12=-981/291, 5-12=-482/249, 6-12=-1080/310, 6-10=-32/545, 7-10=-398/279

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-10-8 to 3-6-5, Interior(1) 3-6-5 to 12-0-0, Exterior(2) 12-0-0 to 18-2-11, Interior(1) 18-2-11 to 26-0-0, Exterior(2) 26-0-0 to 32-0-11, Interior(1) 32-0-11 to 38-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8 except (jt=lb) 12=117.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - Warning: Additional permanent and stability bracing for truss system (not part of this component design) is always required.




February 4, 2022

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071082
J0222-0556	A10	HIP	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:43 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-O8KuJsU1gqQ8ieX3xHlhYituLpnrZDAmLrEy6zoYjl



Scale = 1:69.6




Plate Offsets (X,Y)-- [4:0-4-0-0-4-8]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.49	Vert(LL) -0.06	2-12	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.34	Vert(CT) -0.14	2-12	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.46	Horz(CT) 0.01	6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.05	6-8	>999	240		
							Weight: 232 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
BOT CHORD 2x6 SP No.1  
WEBS 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.); 3-5.  
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.**


(size) 2=0-5-8, 10=0-5-8, 6=0-3-8  
Max Horz 2=-53(LC 17)  
Max Uplift 2=-72(LC 12), 10=-108(LC 8), 6=-78(LC 13)  
Max Grav 2=737(LC 23), 10=1611(LC 1), 6=774(LC 24)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-968/279, 3-4=-795/343, 4-5=-904/366, 5-6=-1083/302  
BOT CHORD 2-12=-142/787, 6-8=-161/896  
WEBS 4-12=-229/970, 4-10=-1438/468, 4-8=-246/1070

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 10-0-0, Exterior(2) 10-0-0 to 16-2-11, Interior(1) 16-2-11 to 28-0-0, Exterior(2) 28-0-0 to 34-2-11, Interior(1) 34-2-11 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6 except (jt=1b) 10=108.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071083
J0222-0556	A11	ROOF SPECIAL	1	1	Job Reference (optional)	


Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:45 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-KXSekXWHCSgsyxhR3GJmmzoE29WJJO1TEfKL0?zoYJg



Scale = 1:69.6



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.38	Vert(LL) -0.05	2-18	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.24	Vert(CT) -0.11	2-18	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.82	Horz(CT) 0.01	10	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.03	2-18	>999	240		
							Weight: 240 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.): 5-9.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.**


All bearings 0-5-8 except (jt=length) 10=0-3-8.  
 (lb) - Max Horz 2=51(LC 12)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 17, 10 except 15=108(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) except 2=479(LC 23), 17=784(LC 1), 15=1208(LC 24), 10=706(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-358/103, 4-5=-164/632, 4-7=-122/584, 7-8=-86/634, 8-9=-548/189, 9-10=-1099/249  
 BOT CHORD 15-17=-490/185, 13-15=-32/421, 12-13=-161/850, 10-12=-135/928  
 WEBS 5-18=0/352, 3-5=-505/287, 5-17=-981/274, 7-15=-415/156, 8-15=-1253/318, 8-13=-4/390, 9-13=-366/159, 9-12=0/317

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-8-7 to 3-8-6, Interior(1) 3-8-6 to 9-6-0, Exterior(2) 9-6-0 to 11-0-0, Interior(1) 11-0-0 to 30-0-0, Exterior(2) 30-0-0 to 34-4-13, Interior(1) 34-4-13 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 17, 10 except (jt=lb) 15=108.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071084
J0222-0556	A12	ROOF SPECIAL	1	1		

Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:46 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-oj00ytWvylojZ5Gdczq?JBKPAZrC2yRcSJ4uZRzoYjF

0-10-8	9-6-0	13-0-0	18-6-12	25-3-6	32-0-0	38-0-0	38-10-8
0-10-8	9-6-0	3-6-0	5-6-12	6-8-10	6-8-10	6-0-0	0-10-8

Scale = 1:69.6




Plate Offsets (X,Y)-- [4:0-2-1,0-4-0], [9:0-3-0,0-2-15]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.42	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.29	Vert(LL) -0.05 2-18 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.37	Vert(CT) -0.13 2-18 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.02 10 n/a n/a		
	Code IRC2015/TPI2014		Wind(LL) 0.04 12-13 >999 240	Weight: 239 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except 2-0-0 oc purlins (6-0-0 max.); 5-9.  
 BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.**


All bearings 0-5-8.  
 (lb) - Max Horz 2=51(LC 17)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 17, 10 except 15=101(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) except 2=651(LC 1), 17=349(LC 1), 15=1324(LC 1), 10=791(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-769/161, 3-4=-728/209, 4-7=-476/118, 7-8=-1269/367, 8-9=-1236/356, 9-10=-1400/345  
 BOT CHORD 2-18=-33/607, 17-18=-30/589, 12-13=-236/1269, 10-12=-233/1225  
 WEBS 5-18=0/342, 3-5=0/321, 4-17=-581/197, 7-17=-74/612, 7-15=-1159/335, 7-13=-337/1491, 8-13=-409/205, 9-12=0/278

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TC DL=6.0psf; BC DL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) 0-8-7 to 3-8-6, Interior(1) 3-8-6 to 9-6-0, Exterior(2) 9-6-0 to 12-6-13, Interior(1) 12-6-13 to 32-0-0, Exterior(2) 32-0-0 to 36-4-13, Interior(1) 36-4-13 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Provide adequate drainage to prevent water ponding.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 17, 10 except (jt=lb) 15=101.
- Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932



Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071085
J0222-0556	A13	ROOF SPECIAL	1	1		


Comtech, Inc. Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:47 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-GvaP9DXj3waBFrqAhLErOta5yAvnMQmhzpS5uzoYjE

0-10-8	9-6-0	15-0-0	18-6-12	26-3-6	34-0-0	38-0-0	38-10-8
0-10-8	9-6-0	5-6-0	3-6-12	7-8-10	7-8-10	4-0-0	0-10-8

Scale = 1:69.6



9-6-0	12-10-4	18-6-12	26-3-6	34-0-0	38-0-0
9-6-0	3-4-4	5-8-8	7-8-10	7-8-10	4-0-0

Plate Offsets (X,Y)-- [4:0-10-0,0-4-0], [7:0-3-8,0-2-0], [9:0-3-0,0-2-15], [13:0-3-8,0-2-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.41	Vert(LL) -0.10 12-13 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.32	Vert(CT) -0.20 12-13 >999 240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.57	Horz(CT) 0.02 10 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.08 12-13 >999 240	Weight: 245 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x6 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except
BOT CHORD 2x6 SP No.1	2-0-0 oc purlins (5-9-0 max.): 5-9.
WEBS 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

**REACTIONS.** All bearings 0-5-8 except (jt=length) 10=0-3-8.  
 (lb) - Max Horz 2=51(LC 13)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 17, 10 except 15=139(LC 13)  
 Max Grav All reactions 250 lb or less at joint(s) except 2=559(LC 1), 17=479(LC 1), 15=1333(LC 1), 10=746(LC 24)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-551/148, 3-4=-497/173, 4-5=-139/717, 4-7=-64/539, 7-8=-1725/468, 8-9=-1387/389, 9-10=-1522/391  
 BOT CHORD 2-18=-10/406, 17-18=-10/407, 13-15=-539/166, 12-13=-367/1725, 10-12=-291/1365  
 WEBS 5-18=0/367, 5-17=-796/155, 4-15=-427/132, 7-15=-949/312, 7-13=-544/2310, 8-13=-381/224, 8-12=-347/83, 9-12=0/324

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 9-6-0, Exterior(2) 9-6-0 to 13-10-13, Interior(1) 13-10-13 to 34-0-0, Exterior(2) 34-0-0 to 38-4-13, Interior(1) 38-4-13 to 38-8-7 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 17, 10 except (jt=lb) 15=139.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 4, 2022




Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071086
J0222-0556	B1	COMMON SUPPORTED GAB	1	1		

Comtech, Inc., Fayetteville, NC - 28314,


8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:48 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-k57nNZY9UN2RpPQ0kOtTOcQrWMbzWx9vwdZ?dKzoYjD

Job Reference (optional)



Scale = 1:33.3



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.05	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.01	Vert(LL) -0.00 12 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.03	Vert(CT) -0.00 13 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 12 n/a n/a		
	Code IRC2015/TPI2014			Weight: 104 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x6 SP No.1  
 OTHERS 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.**

All bearings 19-0-0.  
 (lb) - Max Horz 2=-87(LC 13)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 20, 21, 22, 23, 18, 17, 16, 14, 12  
 Max Grav All reactions 250 lb or less at joint(s) 2, 19, 20, 21, 22, 23, 18, 17, 16, 14, 12

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 3-6-0, Exterior(2) 3-6-0 to 9-6-0, Corner(3) 9-6-0 to 13-10-13, Exterior(2) 13-10-13 to 19-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 20, 21, 22, 23, 18, 17, 16, 14, 12.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071087
J0222-0556	B2	Common	3	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:49 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-C1h9avZoFgAIQZ?Cl6Oixpyv2mnoFNN29HIY9mzoYjC



Scale = 1:34.4




Plate Offsets (X,Y)-- [6:0-4-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.51	Vert(LL) -0.14	2-6	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.68	Vert(CT) -0.30	4-6	>750	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.10	Horz(CT) 0.03	4	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.05	2-6	>999	240	Weight: 87 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x4 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 5-11-5 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.**


(size) 4=0-3-8, 2=0-3-8  
 Max Horz 2=-51(LC 17)  
 Max Uplift 4=-59(LC 13), 2=-59(LC 12)  
 Max Grav 4=799(LC 1), 2=799(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-1154/279, 3-4=-1154/279  
 BOT CHORD 2-6=-135/987, 4-6=-135/987  
 WEBS 3-6=0/433

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 9-6-0, Exterior(2) 9-6-0 to 13-10-13, Interior(1) 13-10-13 to 19-8-7 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071088
J0222-0556	B3	Common	1	1		

Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:00:50 2022 Page 1  
ID:R1p83C19U58uRV3x1R7mxyBybj-hUFXnFZQ0\_I92jaPrpvxT1V4xA9q\_q1CNx26iCzoYjB



Scale: 3/8"=1'




Plate Offsets (X,Y)-- [6:0-4-0,0-3-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.50	Vert(LL) -0.17	2-6	>870	360		MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.57	Vert(CT) -0.38	2-6	>402	240			
BCLL 0.0 *	Rep Stress Incr YES	WB 0.07	Horz(CT) 0.02	4	n/a	n/a			
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.05	2-6	>999	240		Weight: 84 lb	FT = 20%

**LUMBER-**  
TOP CHORD 2x6 SP No.1  
BOT CHORD 2x4 SP No.1  
WEBS 2x4 SP No.2

**BRACING-**  
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 4=0-5-8, 2=0-5-8, 5=0-5-8  
Max Horz 2=53(LC 12)  
Max Uplift 4=-61(LC 13), 2=-71(LC 12), 5=REL  
Max Grav 4=660(LC 1), 2=758(LC 1), 5=143(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
TOP CHORD 2-3=-1013/288, 3-4=-1018/300  
BOT CHORD 2-6=-161/857, 5-6=-161/857, 4-5=-161/857  
WEBS 3-6=0/316

**NOTES-**

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-8-7 to 3-8-6, Interior(1) 3-8-6 to 9-6-0, Exterior(2) 9-6-0 to 13-10-13, Interior(1) 13-10-13 to 18-6-12 zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 4) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 4, 2.
- 6) "Λ" indicates Released bearing: allow for upward movement at joint(s) 5.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
Edenton, NC 27932


Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071089
J0222-0556	C01	Half Hip Girder	1	2	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:01:00 2022 Page 1  
ID:R1p83C19U58uRV3x1R7mxyBybj-OPsJughhf3ZkFFLKRw4Ht8vslCe4KlrggVTe2dzoYj1



Scale = 1:35.1



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.16	Vert(LL) -0.07 9-11 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.25	Vert(CT) -0.15 9-11 >999 240		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.31	Horz(CT) 0.02 8 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL) 0.07 9-11 >999 240	Weight: 246 lb	FT = 20%

**LUMBER-**  
 TOP CHORD 2x6 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2


**BRACING-**  
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 3-7.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.** (size) 8=0-5-8, 2=0-5-8  
 Max Horz 2=47(LC 23)  
 Max Uplift 8=-139(LC 5), 2=-173(LC 4)  
 Max Grav 8=847(LC 1), 2=995(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 TOP CHORD 2-3=-2053/349, 3-4=-3157/536, 4-6=-3157/536  
 BOT CHORD 2-12=-328/1830, 11-12=-329/1866, 9-11=-428/2588, 8-9=-428/2588  
 WEBS 3-12=-10/332, 3-11=-216/1323, 4-11=-326/153, 6-11=-111/584, 6-8=-2453/406

- NOTES-**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:  
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.  
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.  
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
  - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope); Lumber DOL=1.60 plate grip DOL=1.60
  - Provide adequate drainage to prevent water ponding.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 8=139, 2=173.
  - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
  - Use USP HJC26 (With 16-16d nails into Girder & 10d nails into Truss) or equivalent at 2-10-6 from the left end to connect truss(es) to back face of bottom chord, skewed 0.0 deg.to the left, sloping 0.0 deg. down.
  - Fill all nail holes where hanger is in contact with lumber.
  - "NAILED" indicates 3-10d (0.148"x3") or 3-12d (0.148"x3.25") toe-nails per NDS guidelines.

**LOAD CASE(S)** Standard  
 1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15  
 Uniform Loads (plf)  
 Vert: 1-3=-60, 3-7=-60, 2-8=-20



Continued on page 2

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**  
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

**ENGINEERING BY**  
**TRENCO**  
 A MiTek Affiliate  
 818 Soundside Road  
 Edenton, NC 27932

Job J0222-0556	Truss C01	Truss Type Half Hip Girder	Qty 1	Ply <b>2</b>	Lot 16 Wildwood Job Reference (optional)	I50071089
-------------------	--------------	-------------------------------	----------	-----------------	---------------------------------------------	-----------

Comtech, Inc, Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:01:00 2022 Page 2  
ID:R1p83C19U58uRV3x1R7mxsyBybj-OPsJughhf3ZkFFLKRw4Ht8vslCe4KIrggVTe2dzoYj1

**LOAD CASE(S)** Standard

Concentrated Loads (lb)

Vert: 12=-164(B) 13=-3(B) 14=-3(B) 15=-3(B) 16=-3(B) 17=-3(B) 18=-3(B) 19=-3(B) 20=-14(B) 21=-6(B) 22=-6(B) 23=-6(B) 24=-6(B) 25=-6(B) 26=-6(B) 27=-6(B)  
28=-9(B)

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071090
J0222-0556	CJ1	Diagonal Hip Girder	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:01:01 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-scQh50iJQMhbsPvW?dcWQLS0vc1Z3pspv9CBb4zoYj0



Scale = 1:11.1


<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	in	(loc)	l/defl	L/d	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	Plate Grip DOL 1.15	TC 0.20	Vert(LL) -0.00	2-6	>999	360		MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.04	Vert(CT) -0.00	2-6	>999	240			
BCLL 0.0 *	Rep Stress Incr NO	WB 0.00	Horz(CT) 0.00		n/a	n/a			
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P	Wind(LL) 0.00	2	****	240		Weight: 18 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 3-10-9 oc purlins, except end verticals.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

**REACTIONS.** (size) 6=Mechanical, 2=0-7-4  
 Max Horz 2=52(LC 8)  
 Max Uplift 6=-18(LC 12), 2=-75(LC 8)  
 Max Grav 6=122(LC 1), 2=246(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Corner(3) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 2.



February 4, 2022




Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071091
J0222-0556	J1	Jack-Open	8	1	Job Reference (optional)	

Comtech, Inc, Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:01:01 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-scQh50iJQMhbsPvW?dcWQLS35c1t3pspv9CBb4zoYj0



Scale = 1:11.4

LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.06	Vert(LL) -0.00	2	>999	360		MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.02	Vert(CT) -0.00	2-4	>999	240			
BCLL 0.0 *	Rep Stress Incr YES	WB 0.00	Horz(CT) -0.00	3	n/a	n/a			
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P	Wind(LL) 0.00	2	****	240			
								Weight: 13 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x4 SP No.1  
BOT CHORD 2x6 SP No.1

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 2-10-0 oc purins.  
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.**

(size) 3=Mechanical, 2=0-5-4, 4=Mechanical  
Max Horz 2=48(LC 12)  
Max Uplift 3=-33(LC 12), 2=-29(LC 8)  
Max Grav 3=62(LC 1), 2=182(LC 1), 4=51(LC 3)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

**NOTES-**

- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- 4) Refer to girder(s) for truss to truss connections.
- 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 3, 2.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**




818 Soundside Road  
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071092
J0222-0556	J2	Jack-Closed	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:01:02 2022 Page 1  
 ID:R1p83C19U58uRV3x1R7mxyBybj-Ko\_3JLjyBgpSUZUiYK7lyZ?Et?NBoG6z8pyl7WzoYj?



Scale = 1:11.4

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.06	Vert(LL) -0.00	2	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.02	Vert(CT) -0.00	2	>999	240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.00	Horz(CT) 0.00		n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-P	Wind(LL) 0.00	2	****	240	Weight: 14 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 2-10-0 oc purlins, except end verticals.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.2	

**REACTIONS.** (size) 6=Mechanical, 2=0-5-4  
 Max Horz 2=48(LC 12)  
 Max Uplift 6=-19(LC 12), 2=-29(LC 8)  
 Max Grav 6=90(LC 1), 2=174(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) zone;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - 3) \* This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - 4) Refer to girder(s) for truss to truss connections.
  - 5) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 6, 2.



Job J0222-0556	Truss P1	Truss Type Common Supported Gable	Qty 1	Ply 1	Lot 16 Wildwood Job Reference (optional)	150071093
-------------------	-------------	--------------------------------------	----------	----------	---------------------------------------------	-----------


Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:01:03 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-o\_XSWhjay\_xJ6i3v62e\_VmXODPJEXjd6NThlFyzoYj\_



Scale = 1:21.4




<b>LOADING</b> (psf)	<b>SPACING-</b>	<b>CSI.</b>	<b>DEFL.</b>	<b>PLATES</b>	<b>GRIP</b>
TCLL 20.0	2-0-0	TC 0.08	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.03	Vert(LL) 0.00 6 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Vert(CT) 0.00 6 n/r 120		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.00 6 n/a n/a		
	Code IRC2015/TPI2014			Weight: 49 lb	FT = 20%

<b>LUMBER-</b>	<b>BRACING-</b>
TOP CHORD 2x4 SP No.1	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x6 SP No.1	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.2	

**REACTIONS.** All bearings 10-0-0.  
 (lb) - Max Horz 2=50(LC 13)  
 Max Uplift All uplift 100 lb or less at joint(s) 2, 6, 10, 8  
 Max Grav All reactions 250 lb or less at joint(s) 2, 6, 9, 10, 8

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.  
 WEBS 3-10=-168/271, 5-8=-168/271

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
  - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 3-6-5, Exterior(2) 3-6-5 to 5-0-0, Corner(3) 5-0-0 to 9-4-13, Exterior(2) 9-4-13 to 10-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
  - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
  - Gable requires continuous bottom chord bearing.
  - Gable studs spaced at 2-0-0 oc.
  - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
  - \* This truss has been designed for a live load of 40.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
  - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6, 10, 8.



February 4, 2022

Job	Truss	Truss Type	Qty	Ply	Lot 16 Wildwood	150071094
J0222-0556	P2	Common	3	1		


Comtech, Inc., Fayetteville, NC - 28314,

8.430 s Aug 16 2021 MiTek Industries, Inc. Fri Feb 4 10:01:04 2022 Page 1

ID:R1p83C19U58uRV3x1R7mxyBybj-GA5qj1kCjH3Ajse5gl9D2\_4XEp12GAnGbRrAOzoYiz



Scale = 1:21.4



LOADING (psf)	SPACING-	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.19	Vert(LL)	-0.01	6	>999	360	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.12	Vert(CT)	-0.02	4-6	>999	240		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Horz(CT)	0.00	4	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Wind(LL)	0.01	4-6	>999	240		
	Code IRC2015/TPI2014							Weight: 45 lb	FT = 20%

**LUMBER-**

TOP CHORD 2x4 SP No.1  
 BOT CHORD 2x6 SP No.1  
 WEBS 2x4 SP No.2

**BRACING-**

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.  
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

**REACTIONS.**


(size) 2=0-3-8, 4=0-3-8  
 Max Horz 2=-29(LC 17)  
 Max Uplift 2=-39(LC 12), 4=-39(LC 13)  
 Max Grav 2=450(LC 1), 4=450(LC 1)

**FORCES.** (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-578/221, 3-4=-578/221  
 BOT CHORD 2-6=-103/467, 4-6=-103/467

**NOTES-**

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) and C-C Exterior(2) -0-10-8 to 3-6-5, Interior(1) 3-6-5 to 5-0-0, Exterior(2) 5-0-0 to 9-4-13, Interior(1) 9-4-13 to 10-10-8 zone; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.60
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- \* This truss has been designed for a live load of 40.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.



February 4, 2022

**WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.**

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

**ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component**

**Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road  
 Edenton, NC 27932

# Symbols

## PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.

\* Plate location details available in **MITek 20/20 software** or upon request.

## PLATE SIZE

**4 X 4**

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

## LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

## BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

### Industry Standards:

ANSI/TFP 1: National Design Specification for Metal Plate Connected Wood Truss Construction.  
DSB-89: Design Standard for Bracing, Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

# Numbering System

6-4-8  
dimensions shown in ft-in-sixteenths  
(Drawings not to scale)



**JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.**

**CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.**

## PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988  
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TFP 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITteK® All Rights Reserved



MITek Engineering Reference Sheet: Mill-7473 rev. 5/19/2020



# General Safety Notes

## Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TFP 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TFP 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Rewriting pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TFP 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.