

Hatch Legend 1st Floor Walls Dropped 1' 2nd Floor Bearing Walls @ 9' 1-1/2" Bonus Room, 40 lbs. Live Load Tray Ceiling Cathedral Ceiling

HANGER LEGEND	
	= USP THD28-2 / Double 2x Hanger
	= USP HUS26 / Single 2x Hanger
	= USP HJC26 / Hip Hanger

= Denotes Left End of Truss (Reference Engineered Truss Drawing) Do Not Erect Trusses Backwards

Truss Placement Plan SCALE: 1/4" = 1'

соттесн **ROOF & FLOOR TRUSSES & BEAMS** 

Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787

Fax: (910) 864-4444 THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.
These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

earing reactions less than or equal to 3000# are beemed to comply with the prescriptive Code quirements. The contractor shall refer to the tached Tables ( derived from the prescriptive Code quirements ) to determine the minimum foundation ze and number of wood studs required to support eactions greater than 3000# but not greater than 5000#. A registered design professional shall be tained to design the support system for any eaction that exceeds those specified in the attached ables. A registered design professional shall be

Curtis Quick

Curtis Quick