

Trenco
818 Soundside Rd
Edenton, NC 27932

Re: Master_FT
John Dove; Brooke; Master.FT

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Builders FirstSource-Apex,NC.

Pages or sheets covered by this seal: I50770164 thru I50770176

My license renewal date for the state of North Carolina is December 31, 2022.

North Carolina COA: C-0844



March 15, 2022

Gilbert, Eric

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770164
MASTER_FT	F01	ROOF TRUSS	2	1	Job Reference (optional)	


Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:33 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-VS0Dcd2lIcensPK?hpkUuWf_g2wjt5yxytLJ0Szb_qs

0-1/8

0-1/8

Scale = 1:30.2



18-2-8
18-2-8

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.09	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.02	Vert(CT)	n/a	-	n/a		
BCLL 0.0	Rep Stress Incr	NO	WB 0.03	Horz(CT)	0.00	17	n/a		
BCDL 5.0	Code IRC2015/TPI2014		Matrix-R					Weight: 76 lb	FT = 20%F, 11%E

LUMBER-

TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

All bearings 18-2-8.

(lb) - Max Grav All reactions 250 lb or less at joint(s) 32, 17, 31, 30, 28, 27, 26, 25, 24, 23, 22, 21, 20, 19, 18

FORCES.

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- All plates are 1.5x3 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



March 15, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770165
MASTER_FT	F02	ROOF TRUSS	6	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:34 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-zeabqz3wWWmeUZvCEWfJRkCznR00cQK45c5tYuzb_qR



2-9-0	5-3-0	10-5-8	12-11-8	15-5-8	18-2-8
2-9-0	2-6-0	5-2-8	2-6-0	2-6-0	2-9-0


Plate Offsets (X,Y)-- [6:0-1-8,Edge], [17:0-1-8,Edge]					
LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.84	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.97	Vert(LL) -0.34 15-16 >628 480	MT20HS	187/143
BCLL 0.0	Rep Stress Incr YES	WB 0.54	Vert(CT) -0.47 15-16 >458 360		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S	Horz(CT) 0.08 12 n/a n/a		
				Weight: 91 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat) *Except*	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 16-17,15-16.
12-19: 2x4 SP No.1(flat)	
WEBS 2x4 SP No.3(flat)	

REACTIONS. (size) 21=0-3-8, 12=0-3-8
Max Grav 21=981(LC 1), 12=981(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2094/0, 3-4=-3422/0, 4-5=-4214/0, 5-6=-4214/0, 6-7=-4110/0, 7-8=-3438/0, 8-10=-2090/0
BOT CHORD 20-21=0/1230, 18-20=0/2919, 17-18=0/3918, 16-17=0/4214, 15-16=0/4214, 14-15=0/3939, 13-14=0/2914, 12-13=0/1232
WEBS 10-12=-1542/0, 2-21=-1540/0, 10-13=0/1117, 2-20=0/1125, 8-13=-1072/0, 3-20=-1074/0, 8-14=0/682, 3-18=0/654, 7-14=-652/0, 4-18=-646/0, 7-15=-1/381, 4-17=-50/641, 6-15=-427/183

- NOTES-**
- Unbalanced floor live loads have been considered for this design.
 - All plates are MT20 plates unless otherwise indicated.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



March 15, 2022

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770166
MASTER_FT	F03	ROOF TRUSS	1	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:36 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-v1hMFf5A270Mjt3aMxlBW9HI7Fly4GtNZwa_dnbz_qp




Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge], [10:0-1-8,Edge], [11:0-1-8,Edge], [14:0-3-0,0-0-0], [16:0-2-0,Edge], [20:0-3-0,0-0-0]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.85	Vert(LL) -0.34	19	>625	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.82	Vert(CT) -0.47	19	>451	360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr NO	WB 0.79	Horz(CT) 0.03	13	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S						
							Weight: 119 lb	FT = 20%F, 11%E

LUMBER-

TOP CHORD 2x4 SP SS(flat) *Except*
7-12: 2x4 SP No.1(flat)
BOT CHORD 2x4 SP SS(flat) *Except*
18-25: 2x4 SP No.1(flat)
WEBS 2x4 SP No.3(flat) *Except*
10-16: 2x4 SP No.2(flat)

BRACING-

TOP CHORD Structural wood sheathing directly applied or 4-4-1 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS.

(size) 25=0-3-8, 13=0-3-8
Max Grav 25=1114(LC 1), 13=1483(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

TOP CHORD 2-3=-2496/0, 3-4=-4210/0, 4-5=-5174/0, 5-6=-5598/0, 6-8=-5545/0, 8-9=-4875/0, 9-10=-4875/0, 10-11=-2568/0
BOT CHORD 24-25=0/1515, 22-24=0/3515, 21-22=0/5174, 20-21=0/5174, 19-20=0/5174, 17-19=0/5758, 16-17=0/5350, 15-16=0/2568, 14-15=0/2568, 13-14=0/2549
WEBS 9-16=-843/0, 2-25=-1805/0, 2-24=0/1249, 3-24=-1295/0, 3-22=0/883, 8-16=-583/0, 6-17=-270/0, 6-19=-415/32, 4-22=-1203/0, 5-19=0/841, 5-20=-579/0, 4-21=0/617, 10-16=0/2791, 10-15=-1395/0, 11-13=-3023/0, 11-14=0/1179

NOTES-

- Unbalanced floor live loads have been considered for this design.
- All plates are MT20 plates unless otherwise indicated.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
- CAUTION, Do not erect truss backwards.
- Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 715 lb down at 14-3-8 on top chord. The design/selection of such connection device(s) is the responsibility of others.
- In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

- Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
Uniform Loads (plf)
Vert: 13-25=-10, 1-12=-100
Concentrated Loads (lb)
Vert: 9=-635(F)



March 15, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601





818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770167
MASTER_FT	F04	ROOF TRUSS	2	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:36 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-v1hMF5A270Mjt3aMxIBW9HP8F164NINZwa_dnbz_qp



2-9-0 2-9-0	5-3-0 2-6-0	9-0-8 3-9-8	11-6-8 2-6-0	14-3-8 2-9-0
Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge]				


LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 40.0	Plate Grip DOL	1.00	TC 0.40	Vert(LL)	-0.13	12-13	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.81	Vert(CT)	-0.18	12-13	>911	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.38	Horz(CT)	0.04	9	n/a	n/a		
BCDL 5.0	Code	IRC2015/TPI2014	Matrix-S							
									Weight: 73 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (size) 16=0-3-8, 9=Mechanical
Max Grav 16=766(LC 1), 9=766(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1553/0, 3-4=-2372/0, 4-5=-2605/0, 5-6=-2372/0, 6-7=-1553/0
BOT CHORD 15-16=0/946, 14-15=0/2126, 13-14=0/2605, 12-13=0/2605, 11-12=0/2605, 10-11=0/2126, 9-10=0/946
WEBS 7-9=-1184/0, 2-16=-1184/0, 7-10=0/790, 2-15=0/790, 6-10=-746/0, 3-15=-746/0, 6-11=0/375, 3-14=0/375, 5-11=-437/0, 4-14=-437/0

- NOTES-**
- Unbalanced floor live loads have been considered for this design.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - Refer to girder(s) for truss to truss connections.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.





March 15, 2022

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770168
MASTER_FT	F05	ROOF TRUSS	3	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:37 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-NDFkS?6opR9DL1enwfpQ2MqaVf42ppMWOaJX9Dzb_qO



2-9-0	5-3-0	9-4-0	11-10-0	14-7-0
2-9-0	2-6-0	4-1-0	2-6-0	2-9-0


Plate Offsets (X,Y)-- [4:0-1-8,Edge], [5:0-1-8,Edge]										
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 40.0	Plate Grip DOL	1.00	TC 0.42	Vert(LL)	-0.15	12-13	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.89	Vert(CT)	-0.20	12-13	>859	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.39	Horz(CT)	0.04	9	n/a	n/a		
BCDL 5.0	Code	IRC2015/TPI2014	Matrix-S							
									Weight: 74 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (size) 16=0-3-8, 9=0-3-8
Max Grav 16=782(LC 1), 9=782(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1593/0, 3-4=-2450/0, 4-5=-2705/0, 5-6=-2450/0, 6-7=-1593/0
BOT CHORD 15-16=0/967, 14-15=0/2185, 13-14=0/2705, 12-13=0/2705, 11-12=0/2705, 10-11=0/2185, 9-10=0/967
WEBS 7-9=-1210/0, 2-16=-1210/0, 7-10=0/815, 2-15=0/815, 6-10=-770/0, 3-15=-770/0, 6-11=0/402, 3-14=0/402, 5-11=-478/0, 4-14=-478/0


- NOTES-**
- Unbalanced floor live loads have been considered for this design.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770169
MASTER_FT	F06	ROOF TRUSS	6	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:38 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-rPp6fL6RakH4yADzTMKfbaNfh3PsYEVg0E34hgzb_qN



2-9-0	5-3-0	10-2-0	12-8-0	15-2-0	17-11-0
2-9-0	2-6-0	4-11-0	2-6-0	2-6-0	2-9-0

Plate Offsets (X,Y)-- [6:0-1-8,Edge], [17:0-1-8,Edge]


LOADING (psf)	SPACING-	CSL.	DEFL.	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.78	Vert(LL) -0.32 15-16 >667 480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.92	Vert(CT) -0.44 15-16 >486 360	MT20HS	187/143
BCLL 0.0	Rep Stress Incr YES	WB 0.52	Horz(CT) 0.07 12 n/a n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S			
				Weight: 91 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 4-4-5 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat) *Except* 12-19: 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 2-2-0 oc bracing: 15-16.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (size) 21=0-3-8, 12=Mechanical
Max Grav 21=965(LC 1), 12=965(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-2054/0, 3-4=-3345/0, 4-5=-4084/0, 5-6=-4084/0, 6-7=-3993/0, 7-8=-3359/0,
8-10=-2050/0
BOT CHORD 20-21=0/1209, 18-20=0/2860, 17-18=0/3820, 16-17=0/4084, 15-16=0/4084, 14-15=0/3840,
13-14=0/2855, 12-13=0/1211
WEBS 10-12=-1516/0, 2-21=-1514/0, 10-13=0/1093, 2-20=0/1100, 8-13=-1048/0, 3-20=-1050/0,
8-14=0/657, 3-18=0/631, 7-14=-625/0, 4-18=-618/0, 7-15=-23/355, 4-17=-70/584,
6-15=-386/182

- NOTES-**
- Unbalanced floor live loads have been considered for this design.
 - All plates are MT20 plates unless otherwise indicated.
 - All plates are 3x4 MT20 unless otherwise indicated.
 - Refer to girder(s) for truss to truss connections.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



March 15, 2022

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770170
MASTER_FT	F08	ROOF TRUSS	1	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:39 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-JcNUtg73L2PxaKo914ru7nvohStmHm1pFuoeD6zb_qM




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [3:0-1-8,Edge]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.95	Vert(LL) -0.01	7	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.42	Vert(CT) -0.02	7	>999	360		
BCLL 0.0	Rep Stress Incr NO	WB 0.25	Horz(CT) 0.01	5	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S					Weight: 25 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.1(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 4-4-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 8=Mechanical, 5=0-4-8
 Max Grav 8=735(LC 1), 5=1062(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 4-5=-463/0, 2-3=-862/0
 BOT CHORD 7-8=0/862, 6-7=0/862, 5-6=0/862
 WEBS 3-5=-1031/0, 2-8=-1058/0

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) Refer to girder(s) for truss to truss connections.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 700 lb down at 1-8-8, and 749 lb down at 3-8-8 on top chord. The design/selection of such connection device(s) is the responsibility of others.
 - 6) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard
 1) Dead + Floor Live (balanced): Lumber Increase=1.00, Plate Increase=1.00
 Uniform Loads (plf)
 Vert: 5-8=-10, 1-4=-100
 Concentrated Loads (lb)
 Vert: 2=-666(F) 11=-694(F)



March 15, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770171
MASTER_FT	F09	ROOF TRUSS	1	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:40 2022 Page 1

ID:srh1Bnhll_muC_Z4WU9buzzeKC9-noxs408h6LXoCUNMbnM7g?SAXsHK0GMZUYbMzYzb_qL




Plate Offsets (X,Y)-- [2:0-1-8,Edge], [3:0-1-8,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.12	Vert(LL)	-0.00	7	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.08	Vert(CT)	-0.00	7	>999	360		
BCLL 0.0	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	5	n/a	n/a		
BCDL 5.0	Code	IRC2015/TPI2014	Matrix-S						Weight: 24 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 3-11-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 8=0-3-8, 5=0-3-8
 Max Grav 8=195(LC 1), 5=195(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 3) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



March 15, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770172
MASTER_FT	F10	GABLE	1	1	Job Reference (optional)	


Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:40 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-noxs408h6LXoCUNMbnM7g?SAwslP0GhzUYyBmYzb_qL

0-1-8

0-1-8

Scale = 1:19.2



1-4-0	2-8-0	4-0-0	5-4-0	6-8-0	8-0-0	9-4-0	10-8-0	11-8-8
1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-0-8

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(oc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL	1.00	TC 0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.00	BC 0.01	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0	Rep Stress Incr	NO	WB 0.03	Horz(CT)	0.00	11	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014		Matrix-R						Weight: 50 lb	FT = 20%F, 11%E


LUMBER-
TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 11-8-8.
(lb) - Max Grav All reactions 250 lb or less at joint(s) 20, 11, 19, 18, 17, 16, 15, 14, 13, 12

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- All plates are 1.5x3 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



March 15, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770173
MASTER_FT	F11	ROOF TRUSS	3	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:41 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-G_VFIM9JsfppY9UtMDC?ljGXylf76iCHll?zb_qk





Plate Offsets (X,Y)--	[11:0-1-8,Edge], [12:0-1-8,Edge]
-----------------------	----------------------------------

LOADING (psf)	SPACING-	CSL.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.28	Vert(LL) -0.07	11-12	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.51	Vert(CT) -0.09	11-12	>999	360		
BCLL 0.0	Rep Stress Incr YES	WB 0.28	Horz(CT) 0.02	9	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S					Weight: 61 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 14=0-3-8, 9=0-3-8
 Max Grav 14=640(LC 1), 9=640(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1231/0, 3-4=-1800/0, 4-5=-1800/0, 5-6=-1800/0, 6-7=-1231/0
 BOT CHORD 13-14=0/787, 12-13=0/1640, 11-12=0/1800, 10-11=0/1640, 9-10=0/787
 WEBS 7-9=-984/0, 2-14=-984/0, 7-10=0/579, 2-13=0/579, 6-10=-533/0, 3-13=-533/0, 6-11=-17/383, 3-12=-17/383

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



March 15, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770174
MASTER_FT	F12	ROOF TRUSS	6	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:42 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-kB2dV9xdznWRoWkiCPbIQXTbgtuU6XFxs1qRzb_qJ





Plate Offsets (X,Y)--	[11:0-1-8,Edge], [12:0-1-8,Edge]	2-9-0 2-9-0	8-11-8 6-2-8	11-8-8 2-9-0
-----------------------	----------------------------------	----------------	-----------------	-----------------


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.27	Vert(LL) -0.06	12	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.46	Vert(CT) -0.09	12	>999	360		
BCLL 0.0	Rep Stress Incr YES	WB 0.26	Horz(CT) 0.02	9	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S					Weight: 61 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (size) 14=Mechanical, 9=0-3-8
Max Grav 14=624(LC 1), 9=624(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1191/0, 3-4=-1716/0, 4-5=-1716/0, 5-6=-1716/0, 6-7=-1191/0
BOT CHORD 13-14=0/765, 12-13=0/1582, 11-12=0/1716, 10-11=0/1582, 9-10=0/765
WEBS 7-9=-957/0, 2-14=-957/0, 7-10=0/554, 2-13=0/554, 6-10=-508/0, 3-13=-508/0, 6-11=-39/341, 3-12=-39/341

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Refer to girder(s) for truss to truss connections.
 - 4) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.





March 15, 2022

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770175
MASTER_FT	F13	ROOF TRUSS	10	1	Job Reference (optional)	

Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:42 2022 Page 1
ID:srh1Bnhll_muC_Z4WU9buzzeKC9-kB2dV9xdznWRoWkiCPblQXTbgtuU6XFxs1qRzb_qJ



2-9-0	8-11-8	11-8-8
2-9-0	6-2-8	2-9-0
Plate Offsets (X,Y)--	[11:0-1-8,Edge], [12:0-1-8,Edge]	


LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.27	Vert(LL) -0.06	12	>999	480	MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.46	Vert(CT) -0.09	12	>999	360		
BCLL 0.0	Rep Stress Incr YES	WB 0.26	Horz(CT) 0.02	9	n/a	n/a		
BCDL 5.0	Code IRC2015/TPI2014	Matrix-S					Weight: 61 lb	FT = 20%F, 11%E

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	

REACTIONS. (size) 14=0-3-8, 9=Mechanical
Max Grav 14=624(LC 1), 9=624(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1191/0, 3-4=-1716/0, 4-5=-1716/0, 5-6=-1716/0, 6-7=-1191/0
BOT CHORD 13-14=0/765, 12-13=0/1582, 11-12=0/1716, 10-11=0/1582, 9-10=0/765
WEBS 7-9=-957/0, 2-14=-957/0, 7-10=0/554, 2-13=0/554, 6-10=-508/0, 3-13=-508/0, 6-11=-39/341, 3-12=-39/341

- NOTES-**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x4 MT20 unless otherwise indicated.
 - 3) Refer to girder(s) for truss to truss connections.
 - 4) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



March 15, 2022

Job	Truss	Truss Type	Qty	Ply	John Dove; Brooke; Master.FT	150770176
MASTER_FT	F14	GABLE	1	1	Job Reference (optional)	


Builders FirstSource (Apex, NC), Apex, NC - 27523,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Mar 14 14:28:43 2022 Page 1
 ID:srh1Bnhll_muC_Z4WU9buzzeKC9-CNc?j2AZOGvN3y5wGvwqld4h94K0DdQPAWmrMtzbl_ql

0:1:8

0:1:8

Scale = 1:18.7



1-4-0	2-8-0	4-0-0	5-4-0	6-8-0	8-0-0	9-4-0	10-8-0	11-5-0		
1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	1-4-0	0-9-0		
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 40.0	Plate Grip DOL 1.00	TC 0.09	Vert(LL) n/a - n/a	999					MT20	244/190
TCDL 10.0	Lumber DOL 1.00	BC 0.02	Vert(CT) n/a - n/a	999						
BCLL 0.0	Rep Stress Incr NO	WB 0.03	Horz(CT) 0.00 11 n/a	n/a						
BCDL 5.0	Code IRC2015/TPI2014	Matrix-R							Weight: 49 lb	FT = 20%F, 11%E

LUMBER-
 TOP CHORD 2x4 SP No.2(flat)
 BOT CHORD 2x4 SP No.2(flat)
 WEBS 2x4 SP No.3(flat)
 OTHERS 2x4 SP No.3(flat)

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 11-5-0.
 (lb) - Max Grav All reactions 250 lb or less at joint(s) 20, 11, 19, 18, 17, 16, 15, 14, 13, 12

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



March 15, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Symbols

PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.

* Plate location details available in **MITek 20/20 software** or upon request.

PLATE SIZE

4 X 4

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TPI 1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-89: Design Standard for Bracing, Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate Connected Wood Trusses.

Numbering System

6-4-8
dimensions shown in ft-in-sixteenths
(Drawings not to scale)



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TPI 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITteK® All Rights Reserved



MITek Engineering Reference Sheet: Mill-7473 rev. 5/19/2020



General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TPI 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TPI 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TPI 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.