


Job Lamco_Kristie Bonus_Engr	Truss A	Truss Type Piggyback Base	Qty 3	Ply 1	Job Reference (optional)
------------------------------------	------------	------------------------------	----------	----------	--------------------------



Scale = 1:81.3

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP		
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.83	Vert(LL)	-0.41	14-16	>888	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.89	Vert(CT)	-0.65	14-16	>566	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.82	Horz(CT)	0.02	11	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 303 lb	FT = 20%

LUMBER
 TOP CHORD 2x6 SP No.2 *Except* T3:2x6 SP 2400F 2.0E
 BOT CHORD 2x4 SP No.2 *Except* B2:2x4 SP 2400F 2.0E
 WEBS 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except
 2-0-0 oc purlins (6-0-0 max.); 5-6.
 BOT CHORD Rigid ceiling directly applied or 4-1-1 oc bracing.
 WEBS 1 Row at midpt 5-16, 5-14, 6-12, 3-17, 8-11

REACTIONS (lb/size) 11=1956/0-3-8, (min. 0-2-12), 17=1489/0-3-8, (min. 0-2-1)
 Max Horiz 17=215 (LC 13)
 Max Grav 11=2343 (LC 44), 17=1732 (LC 53)


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-24=-325/587, 3-24=-276/758, 3-25=-1028/103, 4-25=-999/110, 4-5=-844/165, 5-26=-765/133, 26-27=-765/133, 6-27=-765/133, 6-7=-136/436, 8-28=-366/917, 9-28=-420/721
 BOT CHORD 2-17=-507/365, 16-17=-135/714, 16-29=-58/822, 15-29=-58/822, 15-30=-58/822, 14-30=-58/822, 14-31=-15/599, 13-31=-15/599, 13-32=-15/599, 12-32=-15/599, 11-12=-623/448, 11-33=-623/448, 9-33=-623/448
 WEBS 6-14=-16/634, 6-12=-1225/324, 3-16=-3/519, 3-17=-1860/412, 8-12=-24/1308, 8-11=-2129/427

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT16A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 17. This connection is for uplift only and does not consider lateral forces.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 11. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss AA	Truss Type Piggyback Base	Qty 6	Ply 1	Job Reference (optional)
------------------------------------	-------------	------------------------------	----------	----------	--------------------------



Scale = 1:81.3

Loading (psf)	Spacing 2-0-0	CSI	DEFL in (loc) l/defl L/d	PLATES	GRIP
TCLL (roof) 20.0	Plate Grip DOL 1.15	TC 0.77	Vert(LL) -0.19 12-14 >999 240	MT20	244/190
Snow (Pf/Pg) 18.9/20.0	Lumber DOL 1.15	BC 0.82	Vert(CT) -0.33 12-14 >999 180		
TCDL 10.0	Rep Stress Incr YES	WB 0.68	Horz(CT) 0.08 11 n/a n/a		
BCLL 0.0*	Code IRC2015/TPI2014	Matrix-MSH			
BCDL 10.0					Weight: 332 lb FT = 20%

LUMBER
TOP CHORD 2x6 SP No.2 *Except* T3:2x6 SP 2400F 2.0E
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.2

REACTIONS (lb/size) 2=1545/0-3-8, (min. 0-2-3), 11=1899/0-3-8, (min. 0-2-10)
Max Horiz 2=215 (LC 14)
Max Grav 2=1871 (LC 46), 11=2199 (LC 38)

BRACING
TOP CHORD Structural wood sheathing directly applied or 3-0-3 oc purlins, except
2-0-0 oc purlins (6-0-0 max.): 5-6.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
6-0-0 oc bracing: 9-11.
WEBS 1 Row at midpt 5-14, 6-12, 8-11


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-23=-3080/428, 3-23=-2919/459, 3-24=-2882/463, 4-24=-2841/464, 4-5=-2697/520, 5-25=-1816/399, 25-26=-1816/399, 6-26=-1816/399, 6-7=-1865/399, 7-27=-2014/344, 8-27=-2038/338, 8-28=-189/578, 9-28=-243/432
BOT CHORD 2-29=-264/2764, 29-30=-264/2764, 16-30=-264/2764, 16-31=-59/1852, 15-31=-59/1852, 15-32=-59/1852, 14-32=-59/1852, 14-33=-20/1577, 13-33=-20/1577, 13-34=-20/1577, 12-34=-20/1577, 11-12=-69/1495, 9-11=-373/305
WEBS 5-16=-125/1147, 3-16=-696/283, 6-14=0/592, 8-12=-25/496, 8-11=-2643/526

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TC DL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2 and 11. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss AB	Truss Type Piggyback Base	Qty 5	Ply 1	Job Reference (optional)
------------------------------------	-------------	------------------------------	----------	----------	--------------------------



Scale = 1:81.3

Plate Offsets (X, Y): [3:0-3-6,0-3-0]

Loading	(psf)	Spacing	2-0-0	CSI	0.73	DEFL	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.73	Vert(LL)	-0.17 11-13	>999	240	MT20	244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.80	Vert(CT)	-0.29 13-15	>999	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.48	Horz(CT)	0.07 9	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH							
BCDL	10.0									Weight: 330 lb	FT = 20%

LUMBER	BRACING
TOP CHORD 2x6 SP No.2 *Except* T3:2x6 SP 2400F 2.0E	TOP CHORD Structural wood sheathing directly applied or 3-2-15 oc purlins, except
BOT CHORD 2x6 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 2-16.
WEBS 2x4 SP No.2	WEBS 1 Row at midpt 3-16, 5-15, 6-13
REACTIONS (lb/size) 9=1468/0-3-8, (min. 0-2-2), 16=1977/0-3-8, (min. 0-2-11)	
Max Horiz 16=215 (LC 14)	
Max Grav 9=1786 (LC 48), 16=2289 (LC 38)	

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.


FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-23=-305/556, 3-23=-252/709, 3-24=-1545/221, 4-24=-1514/227, 4-5=-1363/283, 5-25=-1618/354, 25-26=-1618/354, 6-26=-1618/354, 6-7=-2533/480, 7-27=-2677/424, 8-27=-2718/423, 8-28=-2755/420, 9-28=-2916/388
BOT CHORD	2-16=-481/353, 15-16=-86/1010, 15-29=0/1362, 14-29=0/1362, 14-30=0/1362, 13-30=0/1362, 13-31=-21/1659, 12-31=-21/1659, 12-32=-21/1659, 11-32=-21/1659, 11-33=-227/2462, 33-34=-227/2462, 9-34=-227/2462
WEBS	3-16=-2444/518, 3-15=0/772, 5-15=-486/124, 5-13=0/683, 6-13=-266/145, 6-11=-125/1150, 8-11=-697/283

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 16 and 9. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss AD1	Truss Type Jack-Closed	Qty 11	Ply 1	Job Reference (optional)
------------------------------------	--------------	---------------------------	-----------	----------	--------------------------

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Wed Apr 01 08:15:44 Page: 1
ID:0h7OQyXRoGFn2FhS8f17v5zVDtg-evUgltWkySa5zJgDIVS0vTIJdyoS2rGCm1f2nzzV9UE



Scale = 1:63.9

Plate Offsets (X, Y): [2:0-2-9,Edge], [5:0-2-14,0-2-0], [6:Edge,0-3-8]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.91	Vert(LL)	-0.11	9-15	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.52	Vert(CT)	-0.24	9-15	>999	180	MT20HS	187/143
TCDL	10.0	Rep Stress Incr	YES	WB	0.51	Horz(CT)	0.01	6	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 170 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP No.2
BOT CHORD 2x6 SP No.2
WEBS 2x4 SP No.2 *Except* W5:2x4 SP No.1, W4:2x4 SP No.3

REACTIONS (lb/size) 2=766/0-3-8, (min. 0-1-8), 6=731/ Mechanical, (min. 0-1-8)
Max Horiz 2=376 (LC 14)
Max Uplift 6=54 (LC 15)
Max Grav 2=909 (LC 29), 6=946 (LC 29)

FORCES

(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1146/173, 3-4=-1232/369, 4-16=-1132/399, 5-16=-1129/432, 6-11=-867/323, 5-11=-868/335
BOT CHORD 2-17=-359/1001, 9-17=-359/1001
WEBS 3-9=-794/428, 9-10=-430/1493, 5-10=-401/1511

NOTES

- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- All plates are MT20 plates unless otherwise indicated.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- Refer to girder(s) for truss to truss connections.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.


LOAD CASE(S) Standard

BRACING

TOP CHORD Structural wood sheathing directly applied or 5-8-14 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 1 Row at midpt 5-6, 5-9, 10-11

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

Job Lamco_Kristie Bonus_Engr	Truss ADE	Truss Type Monopitch Supported Gable	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	--------------	---	----------	----------	--------------------------



Scale = 1:68.2

Plate Offsets (X, Y): [2:0-3-8,Edge]

Loading	(psf)	Spacing	1-11-4	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.84	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.41	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.12	Horz(CT)	-0.01	14	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 169 lb	FT = 20%

LUMBER

TOP CHORD	2x4 SP No.2
BOT CHORD	2x4 SP No.2
WEBS	2x4 SP No.1
OTHERS	2x4 SP No.2 *Except* ST4,ST3,ST2,ST1:2x4 SP No.3
WEDGE	Left: 2x4 SP No.3

BRACING

TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	1 Row at midpt 13-15, 10-18, 11-17, 12-16

REACTIONS

- All bearings 20-9-8.
 (lb) - Max Horiz 2=368 (LC 14), 26=368 (LC 14)
 Max Uplift All uplift 100 (lb) or less at joint(s) 2, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26 except 14=-173 (LC 11), 15=-310 (LC 14)
 Max Grav All reactions 250 (lb) or less at joint(s) 2, 14, 16, 17, 18, 19, 20, 21, 22, 24, 25, 26 except 15=279 (LC 11)

FORCES

TOP CHORD	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown. 2-3=-617/569, 3-4=-549/503, 4-5=-507/471, 5-6=-458/409, 6-7=-451/430, 7-8=-411/390, 8-9=-363/351, 9-10=-315/311, 10-11=-266/270, 13-15=-322/259
BOT CHORD	2-25=-286/283


NOTES

- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
- Unbalanced snow loads have been considered for this design.
- This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Bearing at joint(s) 14 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14, 15, 2, 20, 21, 22, 24, 25, 19, 18, 17, and 16. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss AE	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	-------------	--	----------	----------	--------------------------

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Wed Apr 01 08:15:44 Page: 1
ID:8TxkjCuFkU1Wfs_DuyrA6QzVDtC-6522yDXMjmixbTFPzCzFSgHckL8mMLM?hPcJPzV9UD



Scale = 1:81.3

Plate Offsets (X, Y): [2:0-3-8,Edge], [13:0-3-0,0-1-12], [19:0-3-0,0-1-12], [30:0-3-8,Edge]

Loading	(psf)	Spacing	1-11-4	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.44	Vert(LL)	0.09	55	>994	240	MT20 244/190
Snow (Pf/Pg)	18.9/20.0	Lumber DOL	1.15	BC	0.54	Vert(CT)	-0.18	55	>492	180	
TCDL	10.0	Rep Stress Incr	YES	WB	0.20	Horz(CT)	0.02	2	n/a	n/a	
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH							
BCDL	10.0										Weight: 375 lb FT = 20%

LUMBER	BRACING
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except
BOT CHORD 2x4 SP No.2	2-0-0 oc purlins (6-0-0 max.): 13-19.
OTHERS 2x4 SP No.2 *Except* ST4,ST3,ST2,ST1:2x4 SP No.3	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEDGE Left: 2x4 SP No.3	1 Row at midpt 16-44, 15-45, 14-46, 12-47, 11-49,
Right: 2x4 SP No.3	17-43, 18-42, 20-41, 21-39

REACTIONS All bearings 40-3-8. except 2=0-5-8
 (lb) - Max Horiz 2=-210 (LC 13)
 Max Uplift All uplift 100 (lb) or less at joint(s) 30, 32, 33, 34, 35, 36, 37, 38, 39, 43, 44, 45, 49, 50, 51, 53, 60 except 52=-153 (LC 29)
 Max Grav All reactions 250 (lb) or less at joint(s) 30, 32, 33, 34, 35, 36, 37, 38, 39, 41, 42, 43, 44, 45, 46, 47, 49, 50, 52, 60 except 2=363 (LC 2), 51=276 (LC 38), 53=696 (LC 29)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 9-10=-254/179, 10-11=-289/224, 11-12=-341/280, 12-13=-298/253, 13-14=-303/264, 14-15=-303/264, 15-65=-303/264, 16-65=-303/264, 16-66=-303/264, 17-66=-303/264, 17-18=-303/264, 18-19=-303/264, 19-20=-298/253, 20-21=-341/280, 21-22=-290/225, 22-23=-251/178
 WEBS 7-53=-361/136


- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=18.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10, Lu=50-0-0; Min. flat roof snow load governs. Rain surcharge applied to all exposed surfaces with slopes less than 0.500/12 in accordance with IBC 1608.3.4.
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 30, 44, 45, 46, 47, 49, 50, 51, 52, 53, 43, 42, 41, 39, 38, 37, 36, 35, 34, 33, and 32. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

Job Lamco_Kristie Bonus_Engr	Truss AE	Truss Type Piggyback Base Supported Gable	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	-------------	--	----------	----------	--------------------------

13) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss B	Truss Type Attic	Qty 8	Ply 1	Job Reference (optional)
------------------------------------	------------	---------------------	----------	----------	--------------------------



Scale = 1:66.5

Plate Offsets (X, Y): [4:0-3-0,Edge], [9:0-5-0,Edge], [10:0-5-0,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.64	Vert(LL)	-0.35	9-10	>705	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.42	Vert(CT)	-0.51	9-10	>484	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.61	Horz(CT)	0.01	8	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.18	9-10	>809	360		
BCDL	10.0											
											Weight: 170 lb	FT = 20%

LUMBER
TOP CHORD 2x6 SP 2400F 2.0E
BOT CHORD 2x6 SP No.2 *Except* B2:2x10 SP 2400F 2.0E
WEBS 2x4 SP No.3 *Except* W4,W2:2x4 SP No.2

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 8=887/0-3-8, (min. 0-1-8), 11=887/0-3-8, (min. 0-1-8)
Max Horiz 11=211 (LC 10)
Max Grav 8=1289 (LC 26), 11=1289 (LC 25)


MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-517/144, 2-3=-921/152, 3-4=-110/866, 4-5=-110/866, 5-6=-920/152, 6-7=-517/144, 1-11=-581/128, 7-8=-581/128
BOT CHORD 10-11=0/814, 9-10=0/851, 8-9=0/802
WEBS 6-9=0/676, 2-10=0/676, 3-5=-1885/347, 2-11=-1022/0, 6-8=-1021/0

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - Ceiling dead load (5.0 psf) on member(s). 2-3, 5-6, 3-5; Wall dead load (5.0psf) on member(s).6-9, 2-10
 - Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 9-10
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 11 and 8. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss BE	Truss Type Attic	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	-------------	---------------------	----------	----------	--------------------------



Scale = 1:68.3

Plate Offsets (X, Y): [1:0-1-12,0-1-8], [5:0-3-0,Edge], [9:0-2-0,0-1-12], [10:Edge,0-3-8], [12:0-4-12,0-3-8], [13:0-4-12,0-3-8]

Loading	(psf)	Spacing	1-11-4	CSI	0.58	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.58	Vert(LL)	-0.30	12-13	>833	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.39	Vert(CT)	-0.44	12-13	>569	180		
TCDL	10.0	Rep Stress Incr	YES	WB	0.82	Horz(CT)	0.00	10	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.15	12-13	>935	360		
BCDL	10.0										Weight: 173 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.2 *Except* B2:2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.3 *Except* W4:2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING

TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
 JOINTS 1 Brace at Jt(s): 15

REACTIONS (lb/size) 10=858/0-3-8, (min. 0-1-8), 14=858/0-3-8, (min. 0-1-8)
 Max Horiz 14=204 (LC 10)
 Max Grav 10=1247 (LC 26), 14=1247 (LC 25)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-1244/0, 2-3=-1210/1, 3-4=-899/148, 4-5=-105/820, 5-6=-106/835, 6-7=-885/147, 7-8=-1364/13, 8-9=-1143/0, 1-14=-1232/0, 9-10=-1052/0
 BOT CHORD 13-14=-195/286, 12-13=0/842
 WEBS 7-12=-14/796, 3-13=-45/537, 4-6=-1830/334, 1-15=0/769, 13-15=0/742, 12-16=0/734, 9-16=0/745, 8-16=-481/57, 11-16=-449/41


NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed ; end vertical left and right exposed;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- Gable studs spaced at 2-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 3-4, 6-7, 4-6; Wall dead load (5.0psf) on member(s).7-12, 3-13
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 12-13
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 14 and 10. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss BG	Truss Type Common	Qty 1	Ply 2	Job Reference (optional)
------------------------------------	-------------	----------------------	----------	----------	--------------------------

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Wed Apr 01 08:15:45 Page: 1
ID:H4JRy5RHbMqdp1z2kmHD2mzVCIE-alcQAZX_U3qoCdqBQwUU?uqlvVYWmsVEL89rrzV9UC



Scale = 1:56

Plate Offsets (X, Y): [1:0-0-1,Edge], [5:0-0-1,Edge], [6:0-5-0,0-4-12], [8:0-5-0,0-4-12]

Loading	(psf)	Spacing	1-11-4	CSI	0.54	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.54	Vert(LL)	-0.09	6-8	>999	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.48	Vert(CT)	-0.18	6-8	>999	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.44	Horz(CT)	0.02	5	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0											
											Weight: 266 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x6 SP 2400F 2.0E
WEBS 2x4 SP No.2 *Except* W1:2x4 SP No.3
WEDGE Left: 2x4 SP No.3
Right: 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 4-10-7 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=5511/0-3-8, (min. 0-2-5), 5=5267/0-3-8, (min. 0-2-4)
Max Horiz 1=167 (LC 29)
Max Uplift 1=-316 (LC 9), 5=-300 (LC 10)
Max Grav 1=5609 (LC 2), 5=5367 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 1-2=-5587/344, 2-3=-5474/432, 3-4=-5514/435, 4-5=-5623/346
BOT CHORD 1-15=-266/4270, 15-16=-266/4270, 16-17=-266/4270, 8-17=-266/4270, 8-18=-132/2942, 18-19=-132/2942,
7-19=-132/2942, 7-20=-132/2942, 20-21=-132/2942, 6-21=-132/2942, 6-22=-210/4247, 22-23=-210/4247,
23-24=-210/4247, 24-25=-210/4247, 5-25=-210/4247
WEBS 3-6=-307/3609, 4-6=-304/136, 3-8=-301/3528, 2-8=-304/144

- NOTES**
- 2-ply truss to be connected together with 10d (0.131"x3") nails as follows:
Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc.
Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 5. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Use USP THD26 (With 18-16d nails into Girder & 12-10d x 1-1/2 nails into Truss) or equivalent spaced at 2-0-0 oc max. starting at 2-2-8 from the left end to 20-2-8 to connect truss(es) AD1 (1 ply 2x6 SP) to back face of bottom chord.
 - Fill all nail holes where hanger is in contact with lumber.

Job Lamco_Kristie Bonus_Engr	Truss BG	Truss Type Common	Qty 1	Ply 2	Job Reference (optional)
------------------------------------	-------------	----------------------	----------	----------	--------------------------

- 11) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 851 lb down and 66 lb up at 0-0-0 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard

- 1) Dead + Snow (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (lb/ft)


Vert: 1-3=-52, 3-5=-52, 9-12=-19

Concentrated Loads (lb)

Vert: 9=-851, 15=-843, 16=-843, 17=-843, 18=-843, 20=-843, 21=-843, 22=-843, 23=-843, 24=-843, 25=-846

Job Lamco_Kristie Bonus_Engr	Truss BG2	Truss Type Attic Girder	Qty 1	Ply 3	Job Reference (optional)
------------------------------------	--------------	----------------------------	----------	----------	--------------------------

Run: 8.32 S Nov 19 2019 Print: 8.320 S Nov 19 2019 MiTek Industries, Inc. Wed Apr 01 08:15:45 Page: 1
ID:r4uTDIYQKRAm5214b?UejtzVCvg-alcQAZX_U3qoCdqBqWUU?uqkflWeWoLVEL89rrzV9UC



Scale = 1:66.6

Plate Offsets (X, Y): [1:0-2-12,0-1-8], [3:0-2-1,0-2-0], [4:0-3-0,Edge], [5:0-2-1,0-2-0], [7:0-2-12,0-1-8], [9:0-4-12,0-3-8], [10:0-4-12,0-3-8]

Loading	(psf)	Spacing	6-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.62	Vert(LL)	-0.32	9-10	>773	240	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.41	Vert(CT)	-0.46	9-10	>533	180		
TCDL	10.0	Rep Stress Incr	NO	WB	0.28	Horz(CT)	0.00	8	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH		Attic	-0.17	9-10	>842	360		
BCDL	10.0											
											Weight: 497 lb	FT = 20%

LUMBER

TOP CHORD 2x6 SP 2400F 2.0E
 BOT CHORD 2x6 SP No.2 *Except* B2:2x10 SP 2400F 2.0E
 WEBS 2x4 SP No.3 *Except* W4,W1:2x4 SP No.2

BRACING

TOP CHORD 2-0-0 oc purlins (6-0-0 max.), except end verticals (Switched from sheeted: Spacing > 2-0-0).
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 8=2655/0-3-8, (min. 0-1-8), 11=2655/0-3-8, (min. 0-1-8)
 Max Horiz 11=632 (LC 6)
 Max Grav 8=3862 (LC 22), 11=3862 (LC 21)




FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-3924/0, 2-3=-2754/75, 3-4=-11/2256, 4-5=-11/2256, 5-6=-2754/75, 6-7=-3923/0, 1-11=-3808/0, 7-8=-3809/0
 BOT CHORD 10-11=-610/919, 9-10=0/2589, 8-9=-56/452
 WEBS 6-9=-216/1553, 2-10=-216/1553, 3-5=-5242/11, 1-10=0/2317, 7-9=0/2324

NOTES

- 3-ply truss to be connected together with 10d (0.131"x3") nails as follows:
 Top chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 2x6 - 2 rows staggered at 0-9-0 oc, 2x10 - 2 rows staggered at 0-9-0 oc.
 Web connected as follows: 2x4 - 1 row at 0-9-0 oc.
- All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope); cantilever left and right exposed; end vertical left and right exposed; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- Ceiling dead load (5.0 psf) on member(s). 2-3, 5-6, 3-5; Wall dead load (5.0psf) on member(s).6-9, 2-10
- Bottom chord live load (40.0 psf) and additional bottom chord dead load (0.0 psf) applied only to room. 9-10
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 11 and 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- Attic room checked for L/360 deflection.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss PB	Truss Type Piggyback	Qty 14	Ply 1	Job Reference (optional)
------------------------------------	-------------	-------------------------	-----------	----------	--------------------------



Scale = 1:27.2

Plate Offsets (X, Y): [2:0-1-5,0-1-0], [4:0-1-5,0-1-0]

Loading	(psf)	Spacing	2-0-0	CSI	0.25	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.25	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.26	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horz(CT)	0.00	2	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 36 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.




REACTIONS All bearings 9-2-1.
(lb) - Max Horiz 2=59 (LC 14), 7=59 (LC 14)
Max Uplift All uplift 100 (lb) or less at joint(s) 2, 4, 7, 11
Max Grav All reactions 250 (lb) or less at joint(s) 2, 4, 7, 11 except 6=350 (LC 2)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 4-0-0 oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 4, and 6. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss PBE	Truss Type Piggyback	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	--------------	-------------------------	----------	----------	--------------------------



Scale = 1:26.8

Loading	(psf)	Spacing	1-11-4	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.07	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.06	Vert(CT)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.03	Horz(CT)	n/a	-	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-MSH								
BCDL	10.0										Weight: 40 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.


REACTIONS All bearings 9-2-1.
(lb) - Max Horiz 2=-57 (LC 13), 11=-57 (LC 13)
Max Uplift All uplift 100 (lb) or less at joint(s) 8, 10
Max Grav All reactions 250 (lb) or less at joint(s) 2, 6, 8, 9, 10, 11, 15

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
 - Unbalanced snow loads have been considered for this design.
 - This truss has been designed for greater of min roof live load of 12.0 psf or 2.00 times flat roof load of 13.9 psf on overhangs non-concurrent with other live loads.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 2-0-0 oc.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
 - One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 2, 6, 9, 10, and 8. This connection is for uplift only and does not consider lateral forces.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss VD	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	-------------	----------------------	----------	----------	--------------------------



Scale = 1:34.2

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	I/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.27	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.21	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.07	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-SH								
BCDL	10.0										Weight: 37 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS (lb/size) 1=167/9-7-15, (min. 0-1-8), 3=169/9-7-15, (min. 0-1-8),
4=321/9-7-15, (min. 0-1-8)
Max Horiz 1=-73 (LC 11)
Max Uplift 3=-2 (LC 14)
Max Grav 1=197 (LC 2), 3=199 (LC 2), 4=371 (LC 2)


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 3, and 4. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss VE	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	-------------	----------------------	----------	----------	--------------------------



Scale = 1:39.6

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.03	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.04	Horiz(TL)	0.00	7	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-SH								
BCDL	10.0										Weight: 60 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6'-0-0 oc purlins.
Rigid ceiling directly applied or 10'-0-0 oc bracing.

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

REACTIONS All bearings 12-4-8.
(lb) - Max Horiz 1=96 (LC 9)
Max Uplift All uplift 100 (lb) or less at joint(s) 1, 8, 9, 11, 12
Max Grav All reactions 250 (lb) or less at joint(s) 1, 7, 8, 9, 10, 11, 12


FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Gable studs spaced at 2'-0-0 oc.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3'-06-00 tall by 2'-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1, 7, 10, 11, 12, 9, and 8. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss VG	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	-------------	----------------------	----------	----------	--------------------------



Scale = 1:27

Plate Offsets (X, Y): [2:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.19	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.35	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	0.00	3	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-P								
BCDL	10.0										Weight: 22 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 6-0-0 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=225/6-10-6, (min. 0-1-8), 3=225/6-10-6, (min. 0-1-8)
Max Horiz 1=50 (LC 12)
Max Grav 1=263 (LC 2), 3=263 (LC 2)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.



FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 3. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard

Job Lamco_Kristie Bonus_Engr	Truss VI	Truss Type Valley	Qty 1	Ply 1	Job Reference (optional)
------------------------------------	-------------	----------------------	----------	----------	--------------------------



Scale = 1:26.4

Plate Offsets (X, Y): [2:0-2-8,Edge]

Loading	(psf)	Spacing	2-0-0	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL (roof)	20.0	Plate Grip DOL	1.15	TC	0.05	Vert(LL)	n/a	-	n/a	999	MT20	244/190
Snow (Pf/Pg)	13.9/20.0	Lumber DOL	1.15	BC	0.10	Vert(TL)	n/a	-	n/a	999		
TCDL	10.0	Rep Stress Incr	YES	WB	0.00	Horiz(TL)	n/a	-	n/a	n/a		
BCLL	0.0*	Code	IRC2015/TPI2014	Matrix-P								
BCDL	10.0										Weight: 13 lb	FT = 20%

LUMBER
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING
TOP CHORD
BOT CHORD

Structural wood sheathing directly applied or 4-1-6 oc purlins.
Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS (lb/size) 1=122/4-0-12, (min. 0-1-8), 3=122/4-0-12, (min. 0-1-8)
Max Horiz 1=-27 (LC 11)
Max Grav 1=142 (LC 2), 3=142 (LC 2)

MiTek recommends that Stabilizers and required cross bracing be installed during truss erection, in accordance with Stabilizer Installation guide.

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=130mph (3-second gust) Vasd=103mph; TCDL=6.0psf; BCDL=6.0psf; h=25ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) and C-C Exterior (2) zone; cantilever left and right exposed; end vertical left and right exposed; C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.60 plate grip DOL=1.33
- TCLL: ASCE 7-10; Pr=20.0 psf (roof live load: Lumber DOL=1.15 Plate DOL=1.15); Pg=20.0 psf (ground snow); Pf=13.9 psf (flat roof snow: Lumber DOL=1.15 Plate DOL=1.15); Category II; Exp B; Fully Exp.; Ct=1.10
- Gable requires continuous bottom chord bearing.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas where a rectangle 3-06-00 tall by 2-00-00 wide will fit between the bottom chord and any other members.
- One RT7A USP connectors recommended to connect truss to bearing walls due to UPLIFT at jt(s) 1 and 3. This connection is for uplift only and does not consider lateral forces.
- This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.

LOAD CASE(S) Standard