



NOTES:

- 1'-4" TOP CHORD OVERHANG (TYP.)
- TRUSSES 24" O.C. UNLESS NOTED.

Note: All dimensions shown 00-00-00 are in Feet-Inches-Sixteenths

THIS LAYOUT IS INTENDED FOR THE PURPOSE OF TRUSS LOCATION AND PLACEMENT ONLY.
REFER TO THE BUILDING PLANS FOR THE ACTUAL BUILDING CONSTRUCTION.

GENERAL NOTES:
 - DO NOT CUT, DRILL, NOTCH OR MODIFY TRUSSES WITHOUT APPROVAL FROM A CARTER LUMBER TRUSS ASSOCIATE
 - TRUSSES ARE SPACED AT 24" O.C. UNLESS NOTED OTHERWISE
 - REFER TO INDIVIDUAL TRUSS DESIGN DRAWINGS FOR THE LOCATION OF LATERAL BRACING AND MULTI-PLY CONNECTION REQUIREMENTS
 - PER AND TPI 1, 2002 THE TRUSS ENGINEER IS RESPONSIBLE FOR TRUSS TO TRUSS CONNECTIONS AND TRUSS PLY TO PLY CONNECTIONS
 - THIS TRUSS PLACEMENT PLAN RECOMMENDS TRUSS TO BEARING CONNECTIONS AND TRUSS TO BEAM CONNECTIONS WHICH SHALL BE REVIEWED BY THE BUILDING DESIGNER
 - IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER TO RESOLVE ALL ROOF FORCES ADEQUATELY TO THE FOUNDATION

**747 OLD HARGRAVE RD
LEXINGTON, NC 27295**

Project: 2100 - A
 Customer: Adams Homes
 Job Name: L23 CAMERON WOODS
 Options: GARAGE left
 Revision: ---
 Ship Date: x/x/xx
 Scale: NTS
 Drawn Date: 3-22-22
 Drawn By: SB
 Order No.: 22020382

HARDWARE LIST		
QTY	MARK	TYPE
.	.	.
.	.	.
.	.	.
.	.	.
.	.	.
.	.	.
.	.	.
.	.	.

CARTER Lumber
COMPONENTS DIVISION