

Trenco
818 Soundside Rd
Edenton, NC 27932

Re: 22010478
WAG-10

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by The Building Center.

Pages or sheets covered by this seal: I49984751 thru I49984782

My license renewal date for the state of North Carolina is December 31, 2022.

North Carolina COA: C-0844




February 1, 2022

Gilbert, Eric


IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job 22010478	Truss A	Truss Type PIGGYBACK BASE	Qty 19	Ply 1	WAG-10	149984751
-----------------	------------	------------------------------	-----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052, 8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:27 2022 Page 1
 ID:ZLxyDKeGfLTRFJhi639XsazhgKy-rBjIPSRVoM6zPdxglZHDPGummlOCoaWmoKP_ngzppjw



Scale = 1:87.7



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.97	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.73	Vert(LL) -0.78 17-19 >763 360	MT20HS	187/143
BCLL 0.0 *	Lumber DOL 1.15	WB 0.47	Vert(CT) -1.22 13-15 >491 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.20 12 n/a n/a		
	Code IRC2015/TPI2014			Weight: 288 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2 *Except* 9-12: 2x4 SP DSS	TOP CHORD Structural wood sheathing directly applied, except 2-0-0 oc purlins (3-3-5 max.): 6-7.
BOT CHORD 2x4 SP DSS	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 5-17, 7-17, 8-15
OTHERS 2x4 SP No.3	
WEDGE Left: 2x4 SP No.3	
SLIDER Right 2x4 SP No.3 2-6-0	

REACTIONS. (size) 2=0-3-8, 12=Mechanical
 Max Horz 2=165(LC 10)
 Max Uplift 2=-181(LC 10), 12=-163(LC 11)
 Max Grav 2=2182(LC 2), 12=2144(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-4134/412, 3-5=-3890/406, 5-6=-2956/412, 6-7=-2574/412, 7-8=-2952/412,
 8-10=-3793/406, 10-12=-3980/411
 BOT CHORD 2-19=-368/3610, 17-19=-220/3127, 15-17=-105/2569, 13-15=-215/3098, 12-13=-290/3480
 WEBS 3-19=-389/196, 5-19=-28/672, 5-17=-812/238, 6-17=-44/970, 7-15=-88/968,
 8-15=-780/237, 8-13=-24/594, 10-13=-318/186

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 17-9-1, Exterior(2) 17-9-1 to 32-2-15, Interior(1) 32-2-15 to 46-8-8, Exterior(2) 46-8-8 to 49-8-8 zone; cantilever left and right exposed ;C:C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - Provide adequate drainage to prevent water ponding.
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 181 lb uplift at joint 2 and 163 lb uplift at joint 12.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.




February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job 22010478	Truss A1	Truss Type PIGGYBACK BASE	Qty 1	Ply 1	WAG-10	149984752
-----------------	-------------	------------------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052, 8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:29 2022 Page 1
 ID:ZLxyDKeGfLTRFJhi639XsazhgKy-naqVg8tKzMhfx53tZjUhZ6064gGU?2Geu5rZzppju



Scale = 1:87.8




Plate Offsets (X, Y)-- [2:0-0-0,0-0-5], [6:0-3-0,0-2-8], [7:0-5-8,0-2-4], [11:0-0-0,0-0-5]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.98	Vert(LL)	-0.80	13-15	>752	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.73	Vert(CT)	-1.24	13-15	>484	240	MT20HS	187/143
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.47	Horz(CT)	0.20	11	n/a	n/a		
BCDL 10.0	Code IRC2015/TP12014		Matrix-AS							
									Weight: 288 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP DSS
 WEBS 2x4 SP No.3
 OTHERS 2x4 SP No.3
 WEDGE
 Left: 2x4 SP No.3 , Right: 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied, except 2-0-0 oc purlins (3-3-4 max.): 6-7.
 BOT CHORD Rigid ceiling directly applied.
 WEBS 1 Row at midpt 5-17, 7-17, 8-15

REACTIONS. (size) 2=0-3-8, 11=0-3-8
 Max Horz 2=156(LC 10)
 Max Uplift 2=181(LC 10), 11=181(LC 11)
 Max Grav 2=2195(LC 2), 11=2196(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-4160/412, 3-5=-3916/406, 5-6=-2983/412, 6-7=-2599/412, 7-8=-2984/412, 8-10=-3918/406, 10-11=-4163/412
 BOT CHORD 2-19=-360/3633, 17-19=-212/3151, 15-17=-82/2599, 13-15=-191/3153, 11-13=-270/3635
 WEBS 3-19=-388/196, 5-19=-28/671, 5-17=-811/238, 6-17=-45/983, 7-15=-90/990, 8-15=-813/238, 8-13=-28/672, 10-13=-388/196

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 17-9-1, Exterior(2) 17-9-1 to 32-2-15, Interior(1) 32-2-15 to 47-10-8, Exterior(2) 47-10-8 to 50-10-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) Provide adequate drainage to prevent water ponding.
 - 4) All plates are MT20 plates unless otherwise indicated.
 - 5) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 6) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 7) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 181 lb uplift at joint 2 and 181 lb uplift at joint 11.
 - 8) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.
 - 9) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601


ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job 22010478	Truss AGE	Truss Type GABLE	Qty 2	Ply 1	WAG-10	149984753
-----------------	--------------	---------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:33 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-gL40gVwGOCs77YQ6pOdeX8?bjbXCnreAGsJ_Kzppjq



Scale = 1:87.5




Plate Offsets (X,Y)--	[19:0-3-0,0-2-0], [25:0-3-0,0-2-0], [42:Edge,0-3-8]
-----------------------	---

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.11	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.09	Vert(LL) -0.00 1 n/r 120		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.10	Vert(CT) 0.00 1 n/r 90		
BCDL 10.0	Rep Stress Incr YES	Matrix-S	Horz(CT) 0.01 43 n/a n/a		
	Code IRC2015/TPI2014			Weight: 497 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 19-25.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 22-62, 21-64, 20-65, 18-66, 17-67, 16-68, 15-69, 23-61, 24-60, 26-59, 27-58, 28-57, 29-56
OTHERS 2x4 SP No.3	

REACTIONS. All bearings 49-8-8.
 (lb) - Max Horz 2=167(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 62, 64, 67, 68, 69, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 61, 58, 57, 56, 54, 53, 52, 51, 50, 49, 48, 47, 46, 45, 44, 2
 Max Grav All reactions 250 lb or less at joint(s) 43, 62, 64, 65, 66, 67, 68, 69, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 61, 60, 59, 58, 57, 56, 54, 53, 52, 51, 50, 49, 48, 47, 46, 45, 44, 2

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 16-17=-94/260, 17-18=-104/303, 18-19=-107/320, 19-20=-97/311, 20-21=-97/311, 21-22=-97/311, 22-23=-97/311, 23-24=-97/311, 24-25=-97/311, 25-26=-107/320, 26-27=-104/303, 27-28=-94/260

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 2-4-0, Exterior(2) 2-4-0 to 19-0-0, Corner(3) 19-0-0 to 31-0-0, Exterior(2) 31-0-0 to 46-4-0, Corner(3) 46-4-0 to 49-6-12 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 1-4-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 62, 64, 67, 68, 69, 71, 72, 73, 74, 75, 76, 77, 78, 79, 80, 81, 61, 58, 57, 56, 54, 53, 52, 51, 50, 49, 48, 47, 46, 45, 44, 2.
 - Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601


ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job 22010478	Truss B1GE	Truss Type COMMON SUPPORTED GAB	Qty 1	Ply 1	WAG-10	149984754
-----------------	---------------	------------------------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:35 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-ckCm5BxWwp6qNsYDDEQ5kyDM4Xl8gInXeaLQ3Czppjo



Scale = 1:29.3




Plate Offsets (X,Y)--	[2:0-6-10,0-1-8], [8:0-6-10,0-1-8]
-----------------------	------------------------------------


LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.05	Vert(LL)	-0.00	9	n/r	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.02	Vert(CT)	-0.00	9	n/r		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.03	Horz(CT)	0.00	8	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						
								Weight: 53 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	
SLIDER Left 2x8 SP No.2 0-10-12, Right 2x8 SP No.2 0-10-12	

REACTIONS. All bearings 7-5-0.
 (lb) - Max Horz 2--85(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 8, 13, 14, 11, 10
 Max Grav All reactions 250 lb or less at joint(s) 2, 8, 12, 13, 14, 11, 10

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Gable requires continuous bottom chord bearing.
 - Gable studs spaced at 1-4-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 8, 13, 14, 11, 10.
 - Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 2.




Job 22010478	Truss BGE	Truss Type GABLE	Qty 1	Ply 1	WAG-10 Job Reference (optional)	149984755
-----------------	--------------	---------------------	----------	----------	------------------------------------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:36 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-4wm9lXy8h7Eh_07PnyxKG9mSpxdwPJ4tE5zbfzppjn



4x5 =

Scale: 3/16"=1'




Plate Offsets (X,Y)-- [16:0-2-8,0-3-0]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.37	Vert(LL)	-0.00	20-21	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.11	Vert(CT)	-0.01	20-21	>999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.19	Horz(CT)	0.00	9	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS						
								Weight: 192 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3 *Except*
3-18: 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied, excepting end verticals.
BOT CHORD Rigid ceiling directly applied.
WEBS 1 Row at midpt 4-16

REACTIONS. All bearings 13-2-0 except (jt=length) 21=0-3-8, 19=0-3-8.
(lb) - Max Horz 21=204(LC 8)
Max Uplift All uplift 100 lb or less at joint(s) 21, 9 except 18=136(LC 10), 12=218(LC 11), 10=113(LC 11)
Max Grav All reactions 250 lb or less at joint(s) 18, 9, 17, 15, 14, 13, 11, 10, 19 except 21=425(LC 1),
16=347(LC 17), 12=362(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-366/73, 2-21=-388/81
BOT CHORD 19-20=-98/322, 18-19=-98/322
WEBS 3-18=-322/192, 4-16=-286/12, 5-12=-314/232

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 7-1-12, Exterior(2) 7-1-12 to 13-1-12, Interior(1) 13-1-12 to 18-1-12, Exterior(2) 18-1-12 to 21-2-0 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable studs spaced at 1-4-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 21, 9 except (jt=lb) 18=136, 12=218, 10=113.
 - 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY
TRENCO
A MiTek Affiliate
818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss BGR	Truss Type COMMON GIRDER	Qty 1	Ply 3	WAG-10	149984756
-----------------	--------------	-----------------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:38 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-0JtvjDzPCKUPEJHnvM_oLarkkkf1tR_NKYa4fXzppj



4x8 ||

Scale = 1:63.1




Plate Offsets (X, Y)--	[2:Edge,0-3-4], [6:0-0-0,0-3-4], [7:0-7-4,0-1-8], [8:0-6-0,0-9-8], [9:0-7-4,0-1-8]
------------------------	--

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.60	Vert(LL)	-0.10	8	>999	MT20	137/130
TCDL 10.0	Lumber DOL	1.15	BC 0.26	Vert(CT)	-0.18	7-8	>999		
BCLL 0.0 *	Rep Stress Incr	NO	WB 0.94	Horz(CT)	0.02	6	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-MSH						
								Weight: 628 lb	FT = 20%


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 1-1/2X11-7/8 LP-LSL TC 1.75E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3 *Except* 4-8: 2x4 SP No.2	

REACTIONS. (size) 6=0-3-8, 2=0-3-8
 Max Horz 2=199(LC 26)
 Max Uplift 6=933(LC 9), 2=922(LC 8)
 Max Grav 6=11492(LC 2), 2=11208(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-11791/998, 3-4=-8743/822, 4-5=-8742/822, 5-6=-12009/1014
 BOT CHORD 2-9=-754/8624, 8-9=-754/8624, 7-8=-689/8785, 6-7=-689/8785
 WEBS 4-8=-1000/11456, 5-8=-3403/430, 5-7=-335/4409, 3-8=-3174/408, 3-9=-306/4101

- NOTES-**
- 3-ply truss to be connected together with 10d (0.148"x3") nails as follows:
 Top chords connected as follows: 2x4 - 1 row at 0-9-0 oc.
 Bottom chords connected as follows: 1-1/2x11-7/8 - 3 rows staggered at 0-5-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed; Lumber DOL=1.33 plate grip DOL=1.33
 - The Fabrication Tolerance at joint 8 = 0%
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 6=933, 2=922.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 2124 lb down and 183 lb up at 1-4-12, 2124 lb down and 183 lb up at 3-4-12, 2124 lb down and 183 lb up at 5-4-12, 2124 lb down and 183 lb up at 7-4-12, 2124 lb down and 183 lb up at 9-4-12, 2124 lb down and 183 lb up at 11-4-12, 2124 lb down and 183 lb up at 13-4-12, 2124 lb down and 183 lb up at 15-4-12, and 2124 lb down and 183 lb up at 17-0-4, and 2124 lb down and 183 lb up at 19-0-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard



Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job 22010478	Truss BGR	Truss Type COMMON GIRDER	Qty 1	Ply 3	WAG-10 Job Reference (optional)	I49984756
-----------------	--------------	-----------------------------	----------	-----------------	------------------------------------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:39 2022 Page 2
ID:ZLxyDKeGfLTRFJhi639XsazhgKy-UVRHxY_1z2cGrTr_S4V1uoOvU8bGcuEXZBJdC_zppjk

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-4=-60, 4-6=-60, 10-13=-20

Concentrated Loads (lb)

Vert: 9=-1968(F) 16=-1968(F) 17=-1968(F) 18=-1968(F) 19=-1968(F) 20=-1968(F) 21=-1968(F) 22=-1968(F) 23=-1968(F) 24=-1968(F)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss C	Truss Type COMMON	Qty 1	Ply 1	WAG-10	149984757
-----------------	------------	----------------------	----------	----------	--------	-----------


The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:40 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-zh?f8u?fkLk7TdQA0n0GR?xALYqSLW6gnr3BkQzppj



Scale = 1:34.0



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.21	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.71	Vert(LL) -0.10 8-11 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.19	Vert(CT) -0.21 8-11 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.02 6 n/a n/a		
	Code IRC2015/TPI2014			Weight: 83 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS. (size) 2=0-3-8, 6=0-3-8
Max Horz 2=-67(LC 11)
Max Uplift 2=-81(LC 10), 6=-81(LC 11)
Max Grav 2=773(LC 1), 6=773(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1167/182, 3-4=-879/141, 4-5=-879/141, 5-6=-1167/182
BOT CHORD 2-8=-126/996, 6-8=-88/996
WEBS 4-8=-4/508, 5-8=-321/140, 3-8=-321/140

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 6-0-0, Exterior(2) 6-0-0 to 12-0-0, Interior(1) 12-0-0 to 15-10-8, Exterior(2) 15-10-8 to 18-10-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601


ENGINEERING BY
TRENCO
A MiTek Affiliate
818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss CGE	Truss Type COMMON SUPPORTED GAB	Qty 1	Ply 1	WAG-10 Job Reference (optional)	149984758
-----------------	--------------	------------------------------------	----------	----------	------------------------------------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:41 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-RuZ2ME0HVfs_5n?MaVXVzDYOYxLE40op0VokGszppji



Scale = 1:33.0





Plate Offsets (X,Y)--	[21:0-2-8,0-3-0]				
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.05	Vert(LL) -0.00 14 n/r 120	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.04	Vert(CT) 0.00 14 n/r 90		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.04	Horz(CT) 0.00 14 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S			
				Weight: 103 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

REACTIONS. All bearings 18-0-0.
 (lb) - Max Horz 2=67(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) 14, 22, 23, 24, 25, 26, 20, 19, 18, 17, 16, 2
 Max Grav All reactions 250 lb or less at joint(s) 14, 21, 22, 23, 24, 25, 26, 20, 19, 18, 17, 16, 2

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) 0-10-8 to 2-4-0, Exterior(2) 2-4-0 to 6-0-0, Corner(3) 6-0-0 to 12-0-0, Exterior(2) 12-0-0 to 15-8-0, Corner(3) 15-8-0 to 18-10-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Gable studs spaced at 1-4-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 14, 22, 23, 24, 25, 26, 20, 19, 18, 17, 16, 2.
 - 10) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 14.



February 1, 2022

<p>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job 22010478	Truss CGR	Truss Type COMMON GIRDER	Qty 1	Ply 3	WAG-10	149984759
-----------------	--------------	-----------------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:43 2022 Page 1

ID:ZLxyDKeGfLTrfJhi639XsazhgKy-NGhomw1X1G7iK59lhWZz2eZbtv5Yi?6UpHrLlzpjjg



Scale = 1:33.0




Plate Offsets (X, Y)--	[1:0-7-0,0-0-7], [5:0-7-0,0-0-7], [7:0-9-4,0-5-0]
------------------------	---

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.64	in (loc) l/defl L/d	MT20	137/130
TCDL 10.0	Plate Grip DOL 1.15	BC 0.46	Vert(LL) -0.12 7-12 >999 360	MT20HS	110/93
BCLL 0.0 *	Lumber DOL 1.15	WB 0.95	Vert(CT) -0.23 7-12 >908 240		
BCDL 10.0	Rep Stress Incr NO	Matrix-MSH	Horz(CT) 0.04 5 n/a n/a		
	Code IRC2015/TPI2014			Weight: 474 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 5-5-7 oc purlins.
BOT CHORD 1-1/2X11-7/8 LP-LSL TC 1.75E	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3 *Except* 3-7: 2x4 SP No.2	

REACTIONS. (size) 1=0-3-8, 5=0-3-8
 Max Horz 1=-74(LC 28)
 Max Uplift 1=-940(LC 8), 5=-924(LC 9)
 Max Grav 1=10543(LC 2), 5=10210(LC 2)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 1-2=-13574/1247, 2-3=-13315/1182, 3-4=-13315/1184, 4-5=-13572/1244
 BOT CHORD 1-7=-1126/12149, 5-7=-1056/12146
 WEBS 3-7=-978/11627, 4-7=-364/154, 2-7=-368/155

- NOTES-**
- 3-ply truss to be connected together with 10d (0.148"x3") nails as follows:
 Top chords connected as follows: 2x4 - 2 rows staggered at 0-6-0 oc.
 Bottom chords connected as follows: 1-1/2x11-7/8 - 4 rows staggered at 0-4-0 oc.
 Webs connected as follows: 2x4 - 1 row at 0-9-0 oc.
 - All loads are considered equally applied to all plies, except if noted as front (F) or back (B) face in the LOAD CASE(S) section. Ply to ply connections have been provided to distribute only loads noted as (F) or (B), unless otherwise indicated.
 - Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone; cantilever left and right exposed ; Lumber DOL=1.33 plate grip DOL=1.33
 - All plates are MT20 plates unless otherwise indicated.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) except (jt=lb) 1=940, 5=924.
 - Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 2164 lb down and 200 lb up at 1-0-4, 2162 lb down and 201 lb up at 2-9-4, 2162 lb down and 201 lb up at 4-9-4, 2162 lb down and 201 lb up at 6-9-4, 2162 lb down and 201 lb up at 8-9-4, 2162 lb down and 201 lb up at 10-9-4, 2162 lb down and 201 lb up at 12-9-4, and 2162 lb down and 201 lb up at 14-9-4, and 2162 lb down and 201 lb up at 16-9-4 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.

LOAD CASE(S) Standard



Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job 22010478	Truss CGR	Truss Type COMMON GIRDER	Qty 1	Ply 3	WAG-10 Job Reference (optional)	I49984759
-----------------	--------------	-----------------------------	----------	-----------------	------------------------------------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:43 2022 Page 2
ID:ZLxyDKeGfLTRFJhi639XsazhgKy-NGhomw1X1G7iK59IhwZz2eZbtIv5Yi?6UpHrLzppjg

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-3=-60, 3-6=-60, 1-5=-20

Concentrated Loads (lb)

Vert: 7=-2021(B) 13=-2023(B) 14=-2021(B) 15=-2021(B) 16=-2021(B) 17=-2021(B) 18=-2021(B) 19=-2021(B) 20=-2021(B)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss D	Truss Type Monopitch	Qty 6	Ply 1	WAG-10	149984760
-----------------	------------	-------------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:44 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-rSEA_G29oaFZyEkxFd4Cbr5rj9IRHN6GiT1OtBzppjf





Plate Offsets (X,Y)--		[4:Edge,0-1-14]								
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15		TC 0.31	Vert(LL) -0.02	4-7	>999	360		MT20	244/190
TCDL 10.0	Lumber DOL 1.15		BC 0.26	Vert(CT) -0.05	4-7	>999	240			
BCLL 0.0 *	Rep Stress Incr YES		WB 0.00	Horz(CT) 0.00	2	n/a	n/a			
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS						Weight: 20 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	3-0-0 oc bracing.
WEBS	2x4 SP No.3		

REACTIONS. (size) 2=0-3-8, 4=0-1-8
 Max Horz 2=75(LC 10)
 Max Uplift 2=-32(LC 10), 4=-41(LC 10)
 Max Grav 2=260(LC 1), 4=187(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 4) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
 - 7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord.



February 1, 2022

Job 22010478	Truss D1	Truss Type Monopitch	Qty 3	Ply 1	WAG-10	149984761
-----------------	-------------	-------------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:45 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-JfoYBc3oZuNQZOJ8pLcR83e1JZgC0qMPx7mxPdppje



Scale = 1:13.2




Plate Offsets (X, Y)--	[4:Edge,0-1-14]				
LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.19	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.16	Vert(LL) -0.01 4-7 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.00	Vert(CT) -0.02 4-7 >999 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-MP	Horz(CT) 0.00 2 n/a n/a		
	Code IRC2015/TPI2014			Weight: 16 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-11-12 oc purlins, except end verticals.
BOT CHORD 3-0-0 oc bracing.

REACTIONS. (size) 2=0-3-8, 4=0-1-8
Max Horz 2=62(LC 10)
Max Uplift 2=-30(LC 10), 4=-32(LC 10)
Max Grav 2=221(LC 1), 4=146(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 2) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 3) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 4) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 5) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss DGE	Truss Type GABLE	Qty 1	Ply 1	WAG-10	149984762
-----------------	--------------	---------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:46 2022 Page 1

ID:ZLxYDKeGfLTRFJhi639XsazhgKy-nrMxPy4QKBVHBYuKN27ggGABDy_vlHcZAnWVvy4zppjd



Scale = 1:15.2


Plate Offsets (X, Y)--		[4:Edge,0-1-14]								
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.31	Vert(LL)	-0.02	4-11	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.26	Vert(CT)	-0.05	4-11	>999	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	2	n/a	n/a		
BCDL 10.0	Code	IRC2015/TPI2014	Matrix-AS						Weight: 23 lb	FT = 20%

LUMBER-		BRACING-	
TOP CHORD	2x4 SP No.2	TOP CHORD	Structural wood sheathing directly applied, except end verticals.
BOT CHORD	2x4 SP No.2	BOT CHORD	3-0-0 oc bracing.
WEBS	2x4 SP No.3		
OTHERS	2x4 SP No.3		

REACTIONS. (size) 2=0-3-8, 4=0-1-8
 Max Horz 2=75(LC 10)
 Max Uplift 2=-32(LC 10), 4=-41(LC 10)
 Max Grav 2=260(LC 1), 4=187(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 2) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 3) Gable studs spaced at 1-4-0 oc.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 6) Bearing at joint(s) 4 considers parallel to grain value using ANSI/TPI 1 angle to grain formula. Building designer should verify capacity of bearing surface.
 - 7) Provide mechanical connection (by others) of truss to bearing plate at joint(s) 4.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
 - 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord.




February 1, 2022

Job 22010478	Truss E	Truss Type Common	Qty 3	Ply 1	WAG-10	149984763
-----------------	------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:46 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-nrMxPy4QKBVHBYuKN27ggGAAoysJIDfZAnWVy4zppjd



Scale = 1:39.0




Plate Offsets (X,Y)--	[8:0-4-0,0-3-4]
-----------------------	-----------------

LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.34	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.81	Vert(LL) -0.21 8-14 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.32	Vert(CT) -0.43 8-14 >626 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.03 6 n/a n/a		
	Code IRC2015/TPI2014			Weight: 102 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	
WEDGE	
Left: 2x4 SP No.3 , Right: 2x4 SP No.2	

REACTIONS. (size) 2=0-3-0, 6=0-3-0
 Max Horz 2=83(LC 10)
 Max Uplift 2=-99(LC 10), 6=-99(LC 11)
 Max Grav 2=952(LC 1), 6=952(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1471/207, 3-4=-1100/159, 4-5=-1100/159, 5-6=-1471/207
 BOT CHORD 2-8=-160/1260, 6-8=-98/1260
 WEBS 4-8=0/643, 5-8=-414/177, 3-8=-414/177

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -1-0-0 to 2-0-0, Interior(1) 2-0-0 to 8-1-12, Exterior(2) 8-1-12 to 14-1-12, Interior(1) 14-1-12 to 20-3-8, Exterior(2) 20-3-8 to 23-3-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



February 1, 2022

Job 22010478	Truss E1	Truss Type Common	Qty 1	Ply 1	WAG-10	149984764
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:47 2022 Page 1
ID:ZLxyDKeGfLTRFJhi639XsazhgKy-F1wJcl425Vd8piTWwlevDUJkPmARUgtiORF2UWzppjc



Scale = 1:38.5





Plate Offsets (X, Y)--	[2:0-0-0,0-1-1], [7:0-2-12,0-1-3], [8:0-4-0,0-3-4]				
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.39	Vert(LL) -0.23 8-15 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.95	Vert(CT) -0.48 8-15 >537 240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.32	Horz(CT) 0.04 7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-AS		Weight: 102 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.2 *Except* 2-8: 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	
WEDGE Left: 2x4 SP No.3	
SLIDER Right 2x6 SP No.1 2-6-0	

REACTIONS. (size) 7=Mechanical, 2=0-3-0
 Max Horz 2=97(LC 10)
 Max Uplift 7=75(LC 11), 2=97(LC 10)
 Max Grav 7=858(LC 1), 2=921(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1402/208, 3-4=-1029/161, 4-5=-1012/162, 5-7=-1228/198
 BOT CHORD 2-8=-173/1200, 7-8=-115/1055
 WEBS 3-8=-416/176, 4-8=-5/579, 5-8=-285/149

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -1-0-0 to 2-0-0, Interior(1) 2-0-0 to 8-1-12, Exterior(2) 8-1-12 to 14-1-12, Interior(1) 14-1-12 to 18-5-12, Exterior(2) 18-5-12 to 21-5-12 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Refer to girder(s) for truss to truss connections.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 2.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



February 1, 2022


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601

ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job 22010478	Truss EGE	Truss Type GABLE	Qty 1	Ply 1	WAG-10	149984765
-----------------	--------------	---------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:49 2022 Page 1
ID:ZLxyDKeGfLTRFJhi639XsazhgKy-CQ231z6ld6tr20cv2AgNlvog1At0yZO?slk9YPzppja



Scale = 1:39.0




Plate Offsets (X, Y)--	[3:0-2-0,0-0-6], [5:0-2-0,0-0-6], [8:0-4-0,0-3-4], [9:0-1-15,0-1-0], [12:0-1-15,0-1-0], [15:0-1-15,0-1-0], [27:0-1-15,0-1-0], [30:0-1-15,0-1-0], [33:0-1-15,0-1-0]
------------------------	--


LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.34	Vert(LL)	-0.21	8-46	>999	360	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.81	Vert(CT)	-0.43	8-46	>626	240		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.32	Horz(CT)	0.03	6	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS							
									Weight: 159 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied.
BOT CHORD 2x4 SP No.1	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	
OTHERS 2x4 SP No.3	
WEDGE	
Left: 2x4 SP No.3 , Right: 2x4 SP No.3	

REACTIONS. (size) 2=0-3-0, 6=0-3-0
 Max Horz 2=83(LC 10)
 Max Uplift 2=-99(LC 10), 6=-99(LC 11)
 Max Grav 2=952(LC 1), 6=952(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1471/207, 3-4=-1100/159, 4-5=-1100/159, 5-6=-1471/207
 BOT CHORD 2-8=-160/1260, 6-8=-98/1260
 WEBS 4-8=0/643, 5-8=-414/177, 3-8=-414/177

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -1-0-0 to 2-0-0, Interior(1) 2-0-0 to 8-1-12, Exterior(2) 8-1-12 to 14-1-12, Interior(1) 14-1-12 to 20-3-8, Exterior(2) 20-3-8 to 23-3-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable studs spaced at 1-4-0 oc.
 - 6) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 7) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 8) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.
 - 9) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.




February 1, 2022

Job 22010478	Truss F	Truss Type COMMON	Qty 5	Ply 1	WAG-10	149984766
-----------------	------------	----------------------	----------	----------	--------	-----------


The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:50 2022 Page 1

ID:ZLxyDKeGfLTrfJhi639XsazhgKy-gccREJ7wOQ?ig9B5cuBcr6LsJaAbh0S85PUI5rzppjZ



Scale = 1:36.9



LOADING (psf)	SPACING-	CSI.	DEFL.	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.31	in (loc) l/defl L/d	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.98	Vert(LL) -0.18 8-14 >999 360		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.27	Vert(CT) -0.38 8-14 >667 240		
BCDL 10.0	Rep Stress Incr YES	Matrix-AS	Horz(CT) 0.03 6 n/a n/a		
	Code IRC2015/TPI2014			Weight: 96 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
WEDGE
Left: 2x4 SP No.3 , Right: 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied.
BOT CHORD Rigid ceiling directly applied.

REACTIONS. (size) 2=0-3-8, 6=0-3-8
Max Horz 2=-78(LC 11)
Max Uplift 2=-92(LC 10), 6=-92(LC 11)
Max Grav 2=893(LC 1), 6=893(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1382/202, 3-4=-1035/155, 4-5=-1035/155, 5-6=-1382/202
BOT CHORD 2-8=-150/1183, 6-8=-99/1183
WEBS 4-8=-2/603, 5-8=-388/166, 3-8=-388/166

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 7-6-0, Exterior(2) 7-6-0 to 13-6-0, Interior(1) 13-6-0 to 18-10-8, Exterior(2) 18-10-8 to 21-10-8 zone; cantilever left and right exposed ;C:C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 6.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



February 1, 2022

Job 22010478	Truss FGE	Truss Type COMMON SUPPORTED GAB	Qty 1	Ply 1	WAG-10 Job Reference (optional)	149984767
-----------------	--------------	------------------------------------	----------	----------	------------------------------------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:52 2022 Page 1
ID:ZLxyDKeGfLTrFJhi639XsazhgKy-c?jCf?8Bv1FQvTLUjJE4wXQGkN5z9_KRYjzp9jzppjX





Plate Offsets (X,Y)--	[27:0-2-8,0-3-0]				
LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.05	Vert(LL) -0.00 18 n/r 120	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.03	Vert(CT) -0.00 19 n/r 90		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.05	Horz(CT) 0.00 18 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S		Weight: 130 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

REACTIONS. All bearings 21-0-0.
 (lb) - Max Horz 2=-78(LC 11)
 Max Uplift All uplift 100 lb or less at joint(s) 2, 28, 29, 30, 31, 32, 33, 34, 26, 25, 24, 23, 22, 21, 20, 18
 Max Grav All reactions 250 lb or less at joint(s) 2, 27, 28, 29, 30, 31, 32, 33, 34, 26, 25, 24, 23, 22, 21, 20, 18

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 2-1-8, Exterior(2) 2-1-8 to 7-6-0, Corner(3) 7-6-0 to 13-6-0, Exterior(2) 13-6-0 to 18-10-8, Corner(3) 18-10-8 to 21-10-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - 4) All plates are 2x4 MT20 unless otherwise indicated.
 - 5) Gable requires continuous bottom chord bearing.
 - 6) Gable studs spaced at 1-4-0 oc.
 - 7) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 8) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 28, 29, 30, 31, 32, 33, 34, 26, 25, 24, 23, 22, 21, 20, 18.
 - 10) Beveled plate or shim required to provide full bearing surface with truss chord at joint(s) 2.



February 1, 2022


<p>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job 22010478	Truss PB1	Truss Type Piggyback	Qty 22	Ply 1	WAG-10	149984768
-----------------	--------------	-------------------------	-----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:53 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-4BHatL9pgLNHXdwgH0JSlzRRnOOuRLanNiNhAzppjW



Scale = 1:11.8




Plate Offsets (X,Y)--	[3:0-2-0,Edge]							
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d
TCLL 20.0	Plate Grip DOL	1.15	TC 0.06	Vert(LL)	0.00	5	n/r	120
TCDL 10.0	Lumber DOL	1.15	BC 0.21	Vert(CT)	0.00	5	n/r	90
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	4	n/a	n/a
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P					
								PLATES
								MT20
								GRIP
								244/190
								Weight: 16 lb
								FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 2=4-0-14, 4=4-0-14
Max Horz 2=18(LC 10)
Max Uplift 2=-27(LC 10), 4=-27(LC 11)
Max Grav 2=201(LC 1), 4=201(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 2, 4.
 - 7) See Standard Industry Piggyback Truss Connection Detail for Connection to base truss as applicable, or consult qualified building designer.



February 1, 2022

<p>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>ENGINEERING BY</p> <p>TRENCO</p> <p>A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job 22010478	Truss R1	Truss Type COMMON	Qty 2	Ply 1	WAG-10	149984769
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:54 2022 Page 1

ID:ZLxyDKeGfLTrFJhi639XsazhgKy-YOry4hARRfV88nVsrjGY?yWQmBaXdrFk?1SwEczzpjV



4x4 =

Scale = 1:56.4




Plate Offsets (X,Y)--	[8:0-4-0,0-3-0]
-----------------------	-----------------

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.79	Vert(LL)	-0.17	7-8	>999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.85	Vert(CT)	-0.33	8-9	>722		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.21	Horz(CT)	0.02	7	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-AS						
								Weight: 104 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied.
WEBS 2x4 SP No.3	

REACTIONS. (size) 9=0-3-8, 7=0-3-8
 Max Horz 9=177(LC 7)
 Max Uplift 9=-71(LC 10), 7=-54(LC 11)
 Max Grav 9=851(LC 1), 7=787(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-910/130, 3-4=-699/146, 4-5=-700/147, 5-6=-912/132, 2-9=-750/154, 6-7=-685/119
 BOT CHORD 8-9=-114/645, 7-8=-34/617
 WEBS 4-8=-78/525

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 7-0-0, Exterior(2) 7-0-0 to 13-0-0, Interior(1) 13-0-0 to 16-10-4, Exterior(2) 16-10-4 to 19-10-4 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 9, 7.
 - This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



February 1, 2022

<p>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>ENGINEERING BY</p> <p>TRENCO</p> <p>A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job 22010478	Truss R2	Truss Type COMMON	Qty 1	Ply 1	WAG-10	149984770
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:55 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-0aPK11B3Cyd?mx43ORnnYA2bgbxYMIzEhBTm2zppjJ



4x4 =

Scale = 1:56.4




Plate Offsets (X, Y)-- [7:Edge,0-0-0], [8:0-4-0,0-3-0]

LOADING (psf)	SPACING- 2-0-0	CSI.	DEFL. in (loc) l/defl L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.78	Vert(LL) -0.18 8-9 >999 360	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.80	Vert(CT) -0.35 8-9 >663 240		
BCLL 0.0 *	Rep Stress Incr YES	WB 0.21	Horz(CT) 0.02 7 n/a n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-AS			
				Weight: 110 lb	FT = 20%


LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
WEBS 2x4 SP No.3
SLIDER Right 2x8 SP No.2 2-6-0

BRACING-
TOP CHORD Structural wood sheathing directly applied, except end verticals.
BOT CHORD Rigid ceiling directly applied.

REACTIONS. (size) 7=Mechanical, 9=0-3-8
Max Horz 9=177(LC 7)
Max Uplift 7=-53(LC 11), 9=-71(LC 10)
Max Grav 7=781(LC 1), 9=845(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-902/131, 3-4=-691/148, 4-5=-688/149, 5-7=-836/130, 2-9=-745/155
BOT CHORD 8-9=-116/639, 7-8=-28/597
WEBS 4-8=-80/520

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) -0-10-8 to 2-1-8, Interior(1) 2-1-8 to 7-0-0, Exterior(2) 7-0-0 to 13-0-0, Interior(1) 13-0-0 to 16-8-8, Exterior(2) 16-8-8 to 19-8-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 4) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 5) Refer to girder(s) for truss to truss connections.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7, 9.
 - 7) This truss design requires that a minimum of 7/16" structural wood sheathing be applied directly to the top chord and 1/2" gypsum sheetrock be applied directly to the bottom chord.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss RGE	Truss Type COMMON SUPPORTED GAB	Qty 1	Ply 1	WAG-10	149984771
-----------------	--------------	------------------------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:56 2022 Page 1
ID:ZLxyDKeGfLTrFJhi639XsazhgKy-VmzjVMBhzGlsO4Fy8I04Nbw5_Rm5nT1TLx11VzppjT



Scale = 1:54.5

Plate Offsets (X,Y)--	[28:0-2-8,0-3-0]							
LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.16	Vert(LL) -0.00	19	n/r	120	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.10	Vert(CT) -0.00	19	n/r	90		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.10	Horz(CT) 0.00	20	n/a	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-R					Weight: 173 lb	FT = 20%
	Code IRC2015/TPI2014							


LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3	WEBS 1 Row at midpt 10-28
OTHERS 2x4 SP No.3	

REACTIONS. All bearings 20-0-0.
 (lb) - Max Horz 36=-183(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 20, 29, 30, 31, 32, 33, 34, 27, 26, 25, 24, 23, 22 except 36=-160(LC 8), 35=-206(LC 10), 21=-178(LC 11)
 Max Grav All reactions 250 lb or less at joint(s) 20, 28, 29, 30, 31, 32, 33, 34, 35, 27, 26, 25, 24, 23, 22, 21 except 36=253(LC 10)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- Unbalanced roof live loads have been considered for this design.
- Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Corner(3) -0-10-8 to 2-0-0, Exterior(2) 2-0-0 to 7-0-0, Corner(3) 7-0-0 to 13-0-0, Exterior(2) 13-0-0 to 17-10-8, Corner(3) 17-10-8 to 20-10-8 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
- Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
- All plates are 2x4 MT20 unless otherwise indicated.
- Gable requires continuous bottom chord bearing.
- Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
- Gable studs spaced at 1-4-0 oc.
- This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
- Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 20, 29, 30, 31, 32, 33, 34, 27, 26, 25, 24, 23, 22 except (jt=lb) 36=160, 35=206, 21=178.



February 1, 2022


<p>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE. Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>ENGINEERING BY TRENCO A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
--	--

Job 22010478	Truss V1	Truss Type GABLE	Qty 1	Ply 1	WAG-10	149984772
-----------------	-------------	---------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:58 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-R95Tw2DxVt0adOod4ZLU9ogFjo6sYheKwfQ7NNzppjR



Scale = 1:54.2


Plate Offsets (X,Y)--	[10:0-2-8,0-3-0]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.21	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.19	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.12	Horz(CT)	0.00	7	n/a	n/a		
BCDL 10.0	Code	IRC2015/TPI2014	Matrix-S						Weight: 93 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	WEBS 1 Row at midpt 4-10

REACTIONS. All bearings 18-11-11.
 (lb) - Max Horz 1=-169(LC 8)
 Max Uplift All uplift 100 lb or less at joint(s) 7 except 1=-105(LC 8), 11=-171(LC 10), 12=-124(LC 10), 9=-171(LC 11), 8=-124(LC 11)
 Max Grav All reactions 250 lb or less at joint(s) 1, 7 except 10=375(LC 20), 11=432(LC 17), 12=269(LC 17), 9=432(LC 18), 8=270(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 3-11=-290/212, 5-9=-290/212

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-4-8 to 3-4-8, Interior(1) 3-4-8 to 6-5-13, Exterior(2) 6-5-13 to 12-5-13, Interior(1) 12-5-13 to 15-7-3, Exterior(2) 15-7-3 to 18-7-3 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 7 except (jt=lb) 1=105, 11=171, 12=124, 9=171, 8=124.




February 1, 2022

<p>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job 22010478	Truss V2	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984773
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:01 2022 Page 1
ID:ZLxyDKeGfLTRFJhi639XsazhgKy-rkmcY4FqooO8UsXCliuBnRlM?8d1ymcodeozippjO



Scale = 1:49.5

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.24	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.18	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.15	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 78 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 16-8-15.
(lb) - Max Horz 1=149(LC 7)
Max Uplift All uplift 100 lb or less at joint(s) 1 except 9=187(LC 10), 6=187(LC 11)
Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=357(LC 20), 9=465(LC 17), 6=465(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-9=-308/223, 4-6=-308/223

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-4-8 to 3-4-8, Interior(1) 3-4-8 to 5-4-12, Exterior(2) 5-4-12 to 11-4-12, Interior(1) 11-4-12 to 13-5-0, Exterior(2) 13-5-0 to 16-5-0 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members, with BCDL = 10.0psf.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1 except (jt=lb) 9=187, 6=187.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss V3	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984774
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:02 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-JwK_mQGSZ6W?606PJPPQKeryCPUxUVmvrGOLW8zppjN



Scale = 1:41.7

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.18	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.11	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.12	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 66 lb	FT = 20%

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. All bearings 14-6-12.
 (lb) - Max Horz 1=-128(LC 6)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 8=-162(LC 10), 6=-162(LC 11)
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except 8=350(LC 17), 6=350(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 WEBS 2-8=-270/197, 4-6=-270/196

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-4-8 to 3-3-11, Interior(1) 3-3-11 to 4-3-11, Exterior(2) 4-3-11 to 10-3-11, Interior(1) 10-3-11 to 11-2-13, Exterior(2) 11-2-13 to 14-2-13 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=162, 6=162.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
 Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601


ENGINEERING BY
TRENCO
 A MiTek Affiliate
 818 Soundside Road
 Edenton, NC 27932

Job 22010478	Truss V4	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984775
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:03 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-n6uMzmH4KQesk9hbs6wfsO61pq1DyV34w7u2bzppjM



Scale = 1:35.8

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.18	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.12	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.08	Horz(CT)	0.00	5	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 54 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

REACTIONS. All bearings 12-4-9.
 (lb) - Max Horz 1=108(LC 7)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 5 except 8=149(LC 10), 6=149(LC 11)
 Max Grav All reactions 250 lb or less at joint(s) 1, 5, 7 except 8=315(LC 17), 6=315(LC 18)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
WEBS 2-8=-251/184, 4-6=-251/184

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - Gable requires continuous bottom chord bearing.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 5 except (jt=lb) 8=149, 6=149.



February 1, 2022


<p>WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.</p> <p>Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601</p>	<p>ENGINEERING BY</p> <p>TRENCO</p> <p>A MiTek Affiliate</p> <p>818 Soundside Road Edenton, NC 27932</p>
--	---

Job 22010478	Truss V5	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984776
-----------------	-------------	----------------------	----------	----------	--------	-----------


The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:03 2022 Page 1

ID:ZLxYdKeGfLTRFJhi639XsazhgKy-n6uMzmH4KQesk9hbs6wfssO3kpoODyb34w7u2bzppjM



Scale = 1:29.5



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.32	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.23	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.08	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S					Weight: 40 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3


BRACING-
 TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=10-2-7, 3=10-2-7, 4=10-2-7
 Max Horz 1=88(LC 7)
 Max Uplift 1=30(LC 11), 3=35(LC 11), 4=2(LC 10)
 Max Grav 1=207(LC 1), 3=207(LC 1), 4=345(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TC DL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932


Job 22010478	Truss V6	Truss Type Valley	Qty 1	Ply 1	WAG-10 Job Reference (optional)	149984777
-----------------	-------------	----------------------	----------	----------	------------------------------------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:04 2022 Page 1
ID:ZLxyDKeGfLTRFJhi639XsazhgKy-GJSkA6li5jmjLJGnQqRuP3wFVD94yQRCJatSa1zppjL



Scale = 1:24.7



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.26	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.14	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.04	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 31 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=8-0-4, 3=8-0-4, 4=8-0-4
Max Horz 1=-68(LC 6)
Max Uplift 1=-31(LC 11), 3=-35(LC 11)
Max Grav 1=172(LC 1), 3=172(LC 1), 4=240(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss V7	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984778
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,


8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:06 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-ChaVbnJzcLORbdQAYFUMUU0e90scQKDVmuMZfvzppjJ



4x4 =

Scale = 1:19.4



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.12	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.07	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.02	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-P					Weight: 22 lb	FT = 20%
	Code IRC2015/TPI2014							

LUMBER-
 TOP CHORD 2x4 SP No.2
 BOT CHORD 2x4 SP No.2
 OTHERS 2x4 SP No.3

BRACING-
 TOP CHORD Structural wood sheathing directly applied or 5-10-9 oc purlins.
 BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=5-10-1, 3=5-10-1, 4=5-10-1
 Max Horz 1=48(LC 6)
 Max Uplift 1=22(LC 11), 3=25(LC 11)
 Max Grav 1=121(LC 1), 3=121(LC 1), 4=169(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
 Edenton, NC 27932

Job 22010478	Truss V8	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984779
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:06 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-ChaVbnJzclORbdQAYFUMUU0fU0s3QKZVmuMZfvzppjJ



Scale = 1:11.3

Plate Offsets (X,Y)--	[2:0-2-0,Edge]									
LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL	1.15	TC 0.04	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.10	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 12 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 3-8-7 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=3-7-14, 3=3-7-14
Max Horz 1=27(LC 7)
Max Uplift 1=8(LC 10), 3=8(LC 11)
Max Grav 1=118(LC 1), 3=118(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.



February 1, 2022


WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.
Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



Job 22010478	Truss V9	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984780
-----------------	-------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:07 2022 Page 1
ID:ZLxyDKeGfLTRFJhi639XsazhgKy-gu7tp7KbNe8lCn_M5y?b1Y06QC19n?e?Y56BMzppjI




LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.17	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.12	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.05	Horz(CT)	0.00	5	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-S						Weight: 49 lb	FT = 20%

LUMBER-	BRACING-
TOP CHORD 2x4 SP No.2	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD 2x4 SP No.2	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
OTHERS 2x4 SP No.3	

REACTIONS. All bearings 13-10-0.
 (lb) - Max Horz 1=43(LC 10)
 Max Uplift All uplift 100 lb or less at joint(s) 1, 8, 6
 Max Grav All reactions 250 lb or less at joint(s) 1, 5 except 7=285(LC 1), 8=307(LC 21), 6=307(LC 22)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES-**
- 1) Unbalanced roof live loads have been considered for this design.
 - 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TC DL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) 0-7-9 to 3-7-9, Interior(1) 3-7-9 to 3-11-8, Exterior(2) 3-11-8 to 9-11-8, Interior(1) 9-11-8 to 10-3-7, Exterior(2) 10-3-7 to 13-3-7 zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
 - 3) Gable requires continuous bottom chord bearing.
 - 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
 - 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
 - 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 8, 6.




February 1, 2022

Job 22010478	Truss V10	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984781
-----------------	--------------	----------------------	----------	----------	--------	-----------


The Building Center, Gastonia, NC - 28052,

8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:50:59 2022 Page 1

ID:ZLxyDKeGfLTrFJhi639XsazhgKy-vLer7OEaGB8RFYNqdHsjj0DPkCS6H9?T9J9hvpzppjQ



Scale = 1:18.2



LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	2-0-0	TC 0.26	Vert(LL)	n/a	-	n/a	MT20	244/190
TCDL 10.0	Plate Grip DOL 1.15	BC 0.19	Vert(CT)	n/a	-	n/a		
BCLL 0.0 *	Lumber DOL 1.15	WB 0.05	Horz(CT)	0.00	3	n/a		
BCDL 10.0	Rep Stress Incr YES	Matrix-S						
	Code IRC2015/TPI2014						Weight: 32 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2
OTHERS 2x4 SP No.3


BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=9-10-0, 3=9-10-0, 4=9-10-0
Max Horz 1=30(LC 14)
Max Uplift 1=25(LC 10), 3=31(LC 11), 4=13(LC 10)
Max Grav 1=160(LC 21), 3=160(LC 22), 4=377(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TC DL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3, 4.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
Edenton, NC 27932

Job 22010478	Truss V11	Truss Type Valley	Qty 1	Ply 1	WAG-10	149984782
-----------------	--------------	----------------------	----------	----------	--------	-----------

The Building Center, Gastonia, NC - 28052,


8.430 s Aug 16 2021 MiTek Industries, Inc. Mon Jan 31 13:51:00 2022 Page 1

ID:ZLxyDKeGfLTRFJhi639XsazhgKy-NXCDLkFC1VGHtiy0B_NyFDmd5cmx0c4cOzvERgzppjP



3x4 =

Scale: 1"=1'



2x4 =

2x4 =

5-10-8
5-10-8

5-11-0
0-0-8

Plate Offsets (X,Y)-- [2:0-2-0,Edge]

LOADING (psf)	SPACING-	2-0-0	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP	
TCLL 20.0	Plate Grip DOL	1.15	TC 0.09	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL 10.0	Lumber DOL	1.15	BC 0.28	Vert(CT)	n/a	-	n/a	999		
BCLL 0.0 *	Rep Stress Incr	YES	WB 0.00	Horz(CT)	0.00	3	n/a	n/a		
BCDL 10.0	Code IRC2015/TPI2014		Matrix-P						Weight: 16 lb	FT = 20%

LUMBER-
TOP CHORD 2x4 SP No.2
BOT CHORD 2x4 SP No.2

BRACING-
TOP CHORD Structural wood sheathing directly applied or 5-11-0 oc purlins.
BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.

REACTIONS. (size) 1=5-10-0, 3=5-10-0
Max Horz 1=16(LC 10)
Max Uplift 1=-17(LC 10), 3=-17(LC 11)
Max Grav 1=186(LC 1), 3=186(LC 1)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

NOTES-

- 1) Unbalanced roof live loads have been considered for this design.
- 2) Wind: ASCE 7-10; Vult=115mph Vasd=91mph; TCDL=5.0psf; BCDL=5.0psf; h=35ft; Cat. II; Exp B; Enclosed; MWFRS (envelope) gable end zone and C-C Exterior(2) zone; cantilever left and right exposed ;C-C for members and forces & MWFRS for reactions shown; Lumber DOL=1.33 plate grip DOL=1.33
- 3) Gable requires continuous bottom chord bearing.
- 4) This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.
- 5) * This truss has been designed for a live load of 20.0psf on the bottom chord in all areas with a clearance greater than 6-0-0 between the bottom chord and any other members.
- 6) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 100 lb uplift at joint(s) 1, 3.



February 1, 2022

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component


Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601




818 Soundside Road
Edenton, NC 27932

Symbols

PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.

* Plate location details available in **MITek 20/20 software or upon request.**

PLATE SIZE

4 X 4

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING




Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TFP 1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-89: Design Standard for Bracing, Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate
Connected Wood Trusses.

Numbering System

6-4-8
dimensions shown in ft-in-sixteenths
(Drawings not to scale)



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TFP 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITteK® All Rights Reserved



MITek Engineering Reference Sheet: MII-7473 rev. 5/19/2020



General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TFP 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TFP 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Reviewing pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TFP 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.