

Trenco
818 Soundside Rd
Edenton, NC 27932

Re: J0322-1386
Parker Residence

The truss drawing(s) referenced below have been prepared by Truss Engineering Co. under my direct supervision based on the parameters provided by Comtech, Inc - Fayetteville.

Pages or sheets covered by this seal: I53984927 thru I53984927

My license renewal date for the state of North Carolina is December 31, 2022.

North Carolina COA: C-0844



September 1, 2022


Gilbert, Eric

IMPORTANT NOTE: The seal on these truss component designs is a certification that the engineer named is licensed in the jurisdiction(s) identified and that the designs comply with ANSI/TPI 1. These designs are based upon parameters shown (e.g., loads, supports, dimensions, shapes and design codes), which were given to MiTek or TRENCO. Any project specific information included is for MiTek's or TRENCO's customers file reference purpose only, and was not taken into account in the preparation of these designs. MiTek or TRENCO has not independently verified the applicability of the design parameters or the designs for any particular building. Before use, the building designer should verify applicability of design parameters and properly incorporate these designs into the overall building design per ANSI/TPI 1, Chapter 2.

Job J0322-1386	Truss A2SGX	Truss Type GABLE	Qty 1	Ply 1	Parker Residence Job Reference (optional)	I53984927
-------------------	----------------	---------------------	----------	----------	--	-----------

Comtech, Inc., Fayetteville, NC 28309

8,430 s Jan 6 2022 MiTek Industries, Inc. Thu Sep 1 11:56:15 2022 Page 1
ID:23qSx45WzNy51_KH?FehmwybPjb-3nAkIPaQ7hMSvibpJDGRJj_OnbwN?m0yyc5aJjyirE



REPAIR: CRACK ON BOTTOM CHORD 2-30 AT 1'-7" LEFT OF JOINT 30.
PLATE DAMAGE AT JOINTS 2 AND 30.

Scale = 1:84.1




Plate Offsets (X,Y)-- [21:0-5-12,0-4-0], [23:0-4-0,0-4-12]

LOADING (psf)	SPACING-	CSI.	DEFL.	in (loc)	l/defl	L/d	PLATES	GRIP
TCLL 20.0	Plate Grip DOL 1.15	TC 0.74	Vert(LL)	-0.09	21-22	>999	MT20	244/190
TCDL 10.0	Lumber DOL 1.15	BC 0.52	Vert(CT)	-0.21	21-22	>999		
BCLL 0.0 *	Rep Stress Incr NO	WB 0.77	Horz(CT)	0.08	21	n/a		
BCDL 10.0	Code IRC2015/TPI2014	Matrix-S	Wind(LL)	0.08	21-22	>999		
							Weight: 403 lb	FT = 20%


LUMBER-
TOP CHORD 2x6 SP No.1
BOT CHORD 2x6 SP No.1 *Except*
2-30: 2x8 SP No.1
WEBS 2x4 SP No.2 *Except*
5-30: 2x6 SP No.1
OTHERS 2x4 SP No.2
SLIDER Right 2x4 SP No.2 4-10-10

BRACING-
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals, and 2-0-0 oc purlins (6-0-0 max.): 5-30, 9-14. Except: 6-0-0 oc bracing: 3-5
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 1 Row at midpt 14-21, 16-21
JOINTS 1 Brace at Jt(s): 31, 32, 36, 38
ATTACH 1/2" PLYWOOD OR OSB GUSSET (15/32" RATED SHEATHING 32/16 EXP 1) TO EACH FACE OF TRUSS WITH (0.131" X 2.5" MIN.) NAILS PER THE FOLLOWING NAIL SCHEDULE: 2 X 3'S - 2 ROWS, 2 X 4'S - 3 ROWS, 2 X 6'S AND LARGER - 4 ROWS: SPACED @ 4" O.C. NAILS TO BE DRIVEN FROM BOTH FACES. STAGGER SPACING FROM FRONT TO BACK FACE FOR A NET 2" O.C. SPACING IN EACH COVERED TRUSS MEMBER. USE 2" MEMBER END DISTANCE.

REACTIONS. All bearings 13-1-8 except (jt=length) 30=0-3-8, 20=0-3-8.
(lb) - Max Horz 30=411(LC 7)
Max Uplift All uplift 100 lb or less at joint(s) except 30=766(LC 4), 21=277(LC 5), 18=297(LC 28), 19=144(LC 28), 20=499(LC 3)
Max Grav All reactions 250 lb or less at joint(s) except 30=2050(LC 1), 21=2003(LC 1), 18=401(LC 16), 19=533(LC 16)

FORCES. (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-40=542/790, 3-40=520/841, 3-30=712/361, 3-5=577/170, 5-6=558/182, 6-7=578/266, 7-8=555/325, 8-9=636/457, 9-10=620/318, 10-11=621/320, 11-12=621/320, 12-13=621/320, 13-14=621/320, 14-15=191/692, 15-16=246/534, 16-17=226/411, 17-18=282/372
BOT CHORD 2-41=751/574, 30-41=751/574, 29-30=789/836, 29-42=715/785, 28-42=702/794, 27-28=571/762, 26-27=367/635, 25-26=382/758, 24-25=369/753, 23-24=414/940, 21-22=250/158
WEBS 5-39=46/572, 38-39=51/640, 37-38=52/626, 27-37=38/621, 27-36=410/222, 35-36=418/217, 9-35=436/270, 9-34=144/581, 23-34=162/612, 23-33=489/990, 32-33=431/918, 31-32=437/917, 14-31=456/947, 14-21=1084/398, 16-21=441/264, 22-33=240/266, 10-34=381/85, 24-34=416/104, 6-38=320/164, 28-38=277/169

- NOTES-**
- Unbalanced roof live loads have been considered for this design.
 - Wind: ASCE 7-10; Vult=130mph Vasd=103mph; TCCL=6.0psf; BCCL=6.0psf; h=15ft; Cat. II; Exp C; Enclosed; MWFRS (envelope) gable end zone; cantilever left exposed; Lumber DOL=1.60 plate grip DOL=1.60
 - Truss designed for wind loads in the plane of the truss only. For studs exposed to wind (normal to the face), see Standard Industry Gable End Details as applicable, or consult qualified building designer as per ANSI/TPI 1.
 - Provide adequate drainage to prevent water ponding.
 - All plates are 2x4 MT20 unless otherwise indicated.
 - Gable studs spaced at 2-0-0 oc.
 - This truss has been designed for a 10.0 psf bottom chord live load nonconcurrent with any other live loads.



September 1, 2022

Continued on page 2

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see

ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component

Safety Information available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
Edenton, NC 27932

Job	Truss	Truss Type	Qty	Ply	Parker Residence	I53984927
J0322-1386	A2SGX	GABLE	1	1	Job Reference (optional)	

Comtech, Inc., Fayetteville, NC 28309

8,430 s Jan 6 2022 MiTek Industries, Inc. Thu Sep 1 11:56:15 2022 Page 2
 ID:23qSx45WzNy51_KH?FehmwybPjb-3nAkIPaQ7hMSvibpJDGRJ_OnbwN?m0yyc5aJjyi?rE

NOTES-

- 8) * This truss has been designed for a live load of 30.0psf on the bottom chord in all areas where a rectangle 3-6-0 tall by 2-0-0 wide will fit between the bottom chord and any other members, with BCDL = 10.0psf.
- 9) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 766 lb uplift at joint 30, 277 lb uplift at joint 21, 297 lb uplift at joint 18, 144 lb uplift at joint 19 and 499 lb uplift at joint 20.
- 10) Following joints to be plated by qualified designer: Joint(s) 30, not plated.
- 11) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
- 12) Graphical purlin representation does not depict the size or the orientation of the purlin along the top and/or bottom chord.
- 13) Hanger(s) or other connection device(s) shall be provided sufficient to support concentrated load(s) 421 lb down and 252 lb up at 6-8-8, and 154 lb down and 92 lb up at 8-5-12 on bottom chord. The design/selection of such connection device(s) is the responsibility of others.
- 14) In the LOAD CASE(S) section, loads applied to the face of the truss are noted as front (F) or back (B).

LOAD CASE(S) Standard

1) Dead + Roof Live (balanced): Lumber Increase=1.15, Plate Increase=1.15

Uniform Loads (plf)

Vert: 1-40=-60, 3-40=-20, 4-5=-60, 5-9=-60, 9-14=-60, 14-18=-60, 2-30=-20, 23-30=-20, 21-23=-20, 18-21=-20

Concentrated Loads (lb)

Vert: 30=-421(B) 42=-154(B)

WARNING - Verify design parameters and READ NOTES ON THIS AND INCLUDED MITEK REFERENCE PAGE MII-7473 rev. 5/19/2020 BEFORE USE.

Design valid for use only with MiTek® connectors. This design is based only upon parameters shown, and is for an individual building component, not a truss system. Before use, the building designer must verify the applicability of design parameters and properly incorporate this design into the overall building design. Bracing indicated is to prevent buckling of individual truss web and/or chord members only. Additional temporary and permanent bracing is always required for stability and to prevent collapse with possible personal injury and property damage. For general guidance regarding the fabrication, storage, delivery, erection and bracing of trusses and truss systems, see **ANSI/TPI1 Quality Criteria, DSB-89 and BCSI Building Component Safety Information** available from Truss Plate Institute, 2670 Crain Highway, Suite 203 Waldorf, MD 20601



818 Soundside Road
 Edenton, NC 27932

Symbols

PLATE LOCATION AND ORIENTATION



Center plate on joint unless x, y offsets are indicated. Dimensions are in ft-in-sixteenths. Apply plates to both sides of truss and fully embed teeth.



For 4 x 2 orientation, locate plates 0- 1/16" from outside edge of truss.



This symbol indicates the required direction of slots in connector plates.

* Plate location details available in **MITek 20/20 software** or upon request.

PLATE SIZE

4 X 4

The first dimension is the plate width measured perpendicular to slots. Second dimension is the length parallel to slots.

LATERAL BRACING LOCATION



Indicated by symbol shown and/or by text in the bracing section of the output. Use T or I bracing if indicated.

BEARING



Indicates location where bearings (supports) occur. Icons vary but reaction section indicates joint number where bearings occur. Min size shown is for crushing only.

Industry Standards:

ANSI/TFP 1: National Design Specification for Metal Plate Connected Wood Truss Construction.
DSB-89: Design Standard for Bracing, Building Component Safety Information, Guide to Good Practice for Handling, Installing & Bracing of Metal Plate
BCSI: Connected Wood Trusses.

Numbering System

6-4-8
dimensions shown in ft-in-sixteenths
(Drawings not to scale)



JOINTS ARE GENERALLY NUMBERED/LETTERED CLOCKWISE AROUND THE TRUSS STARTING AT THE JOINT FARTHEST TO THE LEFT.

CHORDS AND WEBS ARE IDENTIFIED BY END JOINT NUMBERS/LETTERS.

PRODUCT CODE APPROVALS

ICC-ES Reports:

ESR-1311, ESR-1352, ESR1988
ER-3907, ESR-2362, ESR-1397, ESR-3282

Trusses are designed for wind loads in the plane of the truss unless otherwise shown.

Lumber design values are in accordance with ANSI/TFP 1 section 6.3 These truss designs rely on lumber values established by others.

© 2012 MITteK® All Rights Reserved



MITek Engineering Reference Sheet: MII-7473 rev. 5/19/2020



General Safety Notes

Failure to Follow Could Cause Property Damage or Personal Injury

1. Additional stability bracing for truss system, e.g. diagonal or X-bracing, is always required. See BCSI.
2. Truss bracing must be designed by an engineer. For wide truss spacing, individual lateral braces themselves may require bracing, or alternative Tor I bracing should be considered.
3. Never exceed the design loading shown and never stack materials on inadequately braced trusses.
4. Provide copies of this truss design to the building designer, erection supervisor, property owner and all other interested parties.
5. Cut members to bear tightly against each other.
6. Place plates on each face of truss at each joint and embed fully. Knots and wane at joint locations are regulated by ANSI/TFP 1.
7. Design assumes trusses will be suitably protected from the environment in accord with ANSI/TFP 1.
8. Unless otherwise noted, moisture content of lumber shall not exceed 19% at time of fabrication.
9. Unless expressly noted, this design is not applicable for use with fire retardant, preservative treated, or green lumber.
10. Camber is a non-structural consideration and is the responsibility of truss fabricator. General practice is to camber for dead load deflection.
11. Plate type, size, orientation and location dimensions indicated are minimum plating requirements.
12. Lumber used shall be of the species and size, and in all respects, equal to or better than that specified.
13. Top chords must be sheathed or purlins provided at spacing indicated on design.
14. Bottom chords require lateral bracing at 10 ft. spacing, or less, if no ceiling is installed, unless otherwise noted.
15. Connections not shown are the responsibility of others.
16. Do not cut or alter truss member or plate without prior approval of an engineer.
17. Install and load vertically unless indicated otherwise.
18. Use of green or treated lumber may pose unacceptable environmental, health or performance risks. Consult with project engineer before use.
19. Review all portions of this design (front, back, words and pictures) before use. Rewriting pictures alone is not sufficient.
20. Design assumes manufacture in accordance with ANSI/TFP 1 Quality Criteria.
21. The design does not take into account any dynamic or other loads other than those expressly stated.