



▲ = Denotes Left End of Truss  
(Reference Engineered Truss Drawing)  
Do Not Erect Trusses Backwards

Hatch Legend	
	1st Floor Bearing Walls @ 11' 1-1/2"
	2nd Floor Bearing Walls @ 8' 1-1/2"

Truss Placement Plan  
SCALE: 1/4" = 1'

HANGER LEGEND	
	= USP HUS26 / Single 2x Hanger

LOAD CHART FOR JACK STUDS			
REACTION	SPACING	REACTION	SPACING
(UP TO 1000#)	(IN FT)	(UP TO 1000#)	(IN FT)
1700	1	2550	1
3400	2	5100	2
5100	3	7650	3
6800	4	10200	4
8500	5	12750	5
10200	6	15300	6
11900	7		
13600	8		
15300	9		

BUILDER	Wellco Contractors	CITY / CO.	Spring Lake / Cumberland
JOB NAME	463 Old Salem Dr.	ADDRESS	463 Old Salem Dr.
PLAN	BBH-1650	MODEL	Model
SEAL DATE	Seal Date	DATE REV.	04/12/22
QUOTE #	Quote #	DRAWN BY	Curtis Quick
JOB #	J0422-2008	SALES REP.	Lenny Norris

<p>THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSH-B1 and BCSH-B3 provided with the truss delivery package or online @ sbcindustry.com</p> <p>Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.</p>			
Signature _____		Curtis Quick	
		Curtis Quick	

<p>Signature _____</p> <p>Curtis Quick</p>	
--	--

**comtech**  
ROOF & FLOOR  
TRUSSES & BEAMS  
Reilly Road Industrial Park  
Fayetteville, N.C. 28309  
Phone: (910) 864-8787  
Fax: (910) 864-4444