



THF25140	USP	32	NA	10d/3"	10d/3"
THF25140-2	USP	01	NA	10d/3"	10d/3"

Products					
PlotID	Length	Product	Plies	Net Qty	Fab Type
Bk1	2-0-0	14" NI-40x	1	1	FF
DB1	7-0-0	1-3/4"x 9-1/4" LVL Kerto-S	2	2	FF
DB2	10-0-0	1-3/4"x 11-7/8" LVL Kerto-S	2	2	FF
FB1	12-0-0	1-3/4"x 14" LVL Kerto-S	2	2	FF
FB2	24-0-0	1-3/4"x 23-7/8" LVL Kerto-S	4	4	FF
FB3	13-0-0	1-3/4"x 14" LVL Kerto-S	2	2	FF
FJ1	35-3-6	14" NI-40x	1	8	FF
FJ1A	35-5-4	14" NI-40x	1	1	FF
FJ2	19-10-8	14" NI-40x	1	1	FF
FJ3	19-7-14	14" NI-40x	1	5	FF
FJ4	16-0-12	14" NI-40x	1	1	FF
FJ5	15-11-13	14" NI-40x	1	6	FF
FJ6	15-9-9	14" NI-40x	1	5	FF
FJ7	15-9-3	14" NI-40x	1	6	FF
FJ8	4-1-2	14" NI-40x	1	1	FF
FJ9	3-9-9	14" NI-40x	1	1	FF
GDH	24-0-0	1-3/4"x 11-7/8" LVL Kerto-S	3	3	FF
RIM1	12-0-0	1 1/8" x 14" Rim Board	1	11	FF

Truss Placement Plan
SCALE: 1/4"=1'

△ = Indicates Left End of Truss
(Reference Engineered Truss Drawing)
Do NOT Erect Truss Backwards

LOAD CHART FOR JACK STUDS

(BASED ON TABLES R502.5(1) & (2))
NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADS/GIRDER

END REACTION (UP TO) HEADS/GIRDER	END REACTION (UP TO) HEADS/GIRDER	END REACTION (UP TO) HEADS/GIRDER
1700	2550	3400
3400	5100	6800
5100	7650	10200
6800	10200	13600
8500	12750	17000
10200	15300	
11900		
13600		
15300		

BUILDER	Cates Building, Inc.	CITY / CO.	Cameron / Harnett
JOB NAME	Lot 739 Lexington Plantation	ADDRESS	148 Old Montague Way
PLAN	CC-2136 2nd FLOOR I-JOIST	MODEL	31500
SEAL DATE	5/21/21	DATE REV.	04/21/22
QUOTE #	\$2136 I-J KN SL	DRAWN BY	Marshall Naylor
JOB #	J0322-1507	SALES REP.	Scot Duncan

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.
These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature: Marshall Naylor
Marshall Naylor

comTECH
ROOF & FLOOR TRUSSES & BEAMS
Reilly Road Industrial Park
Fayetteville, N.C. 28309
Phone: (910) 864-8787
Fax: (910) 864-4444