

Products								
PlotID	Length	Product	Plies	Net Qty	Fab Type			
Bk1	2-0-0	11 7/8" NI-40x	1	6	FF			
DB1	20-0-0	2x10 SP No.2	3	6	FF			
FB1	10-0-0	1-3/4"x 11-7/8" LVL Kerto-S	2	2	FF			
FJ1	33-8-13	11 7/8" NI-40x	1	12	MFD			
FJ2	14-6-6	11 7/8" NI-40x	1	3	MFD			
FJ3	11-8-13	11 7/8" NI-40x	1	2	MFD			
FJ4	10-0-6	11 7/8" NI-40x	1	11	MFD			
FJ5	4-9-12	11 7/8" NI-40x	1	1	MFD			
RIM1	12-0-0	1 1/8" x 11 7/8" Rim Board	1	13	FF			

<u>Truss</u> <u>Placement</u> <u>Plan</u> SCALE: 1/4"=1'

-	LOAD CHART FOR JACK STUDS (BASED ON TABLES R502.5(1) 4 (b)) NUMBER OF JACK STUDS REQUIRED @ EA END OF		BUILDER	Cates Building, Inc.	CITY / CO.	Cameron / Harnett	THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer	
	HEADER/GIRDE	R	JOB NAME	Lot 739 Lexington Plantation	ADDRESS	148 Old Montague Way	Is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#. <u>Marshall Naylor</u>	COMTECH ROOF & FLOOR RUSSES & BEAMS Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444
	END RE (UP (2) PLY (2) PLY (2) PLY (UP (UP (UP (UP (3) PLY) (3) PLY	END RE (UP REQ'D S	PLAN	CC 2136 Crawl RF2	MODEL	31500		
$\begin{array}{cccc} 1700 & 1 \\ 3400 & 2 \\ 5100 & 3 \\ 6800 & 4 \\ 8500 & 5 \\ 10200 & 6 \\ 11900 & 7 \\ 13600 & 8 \\ 15300 & 9 \end{array}$	3400 2 5100 2 5100 3 7650 3	3400 1 6800 2 10200 3	² ₃ SEAL DATE	5/21/2021	DATE REV.	04/21/22		
	8500 5 12750 5 10200 6 15300 6	13600 4 17000 5		MOORE A&B RP3C	DRAWN BY	Marshall Naylor		
	13600 8		JOB #	J0422-2241	SALES REP.	Scot Duncan		

= Indicates Left End of Truss
 (Reference Engineered Truss Drawing)
 Do NOT Erect Truss Backwards