

**FRONT ELEVATION 5**  
SCALE: 1/8" = 1'-0"



**REAR ELEVATION 5**  
SCALE: 1/8" = 1'-0"


MASTER PLAN INFORMATION		UPDATED DATE
REVISION	DATE	2-17-22
R2-RALE	3-6-19	

DRAWN BY:	ITS
DATE:	05/27/2022
PLAN NO.	2695




HOUSE NAME:	DRAYTON
DRAWING TITLE	FRONT & REAR ELEVATIONS

SHEET No.  
**A.I.**



**RIGHT ELEVATION 5**

SCALE: 1/8" = 1'-0"



**LEFT ELEVATION 5**

SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION DATE	UPDATED DATE
R2-RALE 3-6-19	2-17-22

DRAWN BY:	ITS
DATE:	05/27/2022
PLAN NO.	2695




HOUSE NAME:	DRAYTON
DRAWING TITLE	RIGHT & LEFT ELEVATIONS

SHEET No.	A1.2
-----------	------









ELEVATION 5  
 FIRST FLOOR PLAN  
 SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION	DATE
R2-RALE	3-6-19
UPDATED DATE	2-17-22


DRAWN BY:	ITS
DATE:	05/27/2022
PLAN NO.	2695



HOUSE NAME:	DRAYTON
DRAWING TITLE	FIRST FLOOR PLAN

SHEET No.	A3.1
-----------	------

FILE: Lot 00.0077.dwg DATE: 5/27/2022 10:32 AM



ELEVATION 5  
SECOND FLOOR PLAN  
SCALE: 1/8" = 1'-0"


MASTER PLAN INFORMATION	
REVISION	DATE
R2-RALE	3-6-19
UPDATED DATE	2-17-22

DRAWN BY:	ITS
DATE:	05/27/2022
PLAN NO.	2695




HOUSE NAME:	DRAYTON
DRAWING TITLE	SECOND FLOOR PLAN

SHEET No.	A3.2
-----------	------



**SECTION 1**  
SCALE: 1/8" = 1'-0"



**SECTION 2**  
SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION	DATE
R2-RALE	3-6-19
UPDATED DATE	2-17-22

DRAWN BY:	ITS
DATE:	05/27/2022
PLAN NO.	2695




HOUSE NAME:	DRAYTON
DRAWING TITLE	BUILDING SECTION

SHEET No.  
**A4.1**

**ELECTRICAL LEGEND**

- Ⓢ SINGLE POLE SWITCH
- Ⓢ<sub>3</sub> THREE WAY SWITCH
- Ⓢ<sub>4</sub> FOUR WAY SWITCH
- ⓈⓈ DUPLEX AFCI RECEPTACLE
- ⓈⓈ<sub>B</sub> DUPLEX AFCI RECEPTACLE - BOTTOM HALF SWITCHED
- ⓈⓈ<sub>F</sub> DUPLEX AFCI RECEPTACLE - FLOOR MOUNTED
- 220V Ⓢ RECEPTACLE - 220V
- GFI Ⓢ DUPLEX AFCI RECEPTACLE - GFI
- WP/GFI Ⓢ DUPLEX AFCI RECEPTACLE - WATERPROOF GFI
- Ⓢ(SD) SMOKE DETECTOR - WIRED IN SERIES
- Ⓢ(EF) EXHAUST FAN MOTOR
- Ⓢ(CO) CO DETECTOR
- Ⓢ(DC) DOOR CHIME
- Ⓢ(L) LIGHT FIXTURE - WALL MOUNTED
- Ⓢ(C) LIGHT FIXTURE - CEILING MOUNTED
- Ⓢ(R) LIGHT FIXTURE - RECESSED CAN
- LED Ⓢ LIGHT FIXTURE - LED SURFACE MOUNTED
- Ⓢ(P) FULLCHAIN LAMPHOLDER
- Ⓢ(K) KEYLESS LAMPHOLDER

NOTE: ALL ELECTRICAL WORK SHALL CONFORM TO THE REQUIREMENTS OF THE ADOPTED VERSION OF THE NATIONAL ELECTRICAL CODE, THE LOCAL POWER COMPANY AND TO ALL APPLICABLE LOCAL REGULATIONS.



**ELECTRICAL PLAN  
FIRST FLOOR - ELEV. 5**  
SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION		UPDATED DATE
REVISION	DATE	2-17-22
R2-RALE	3-6-19	

DRAWN BY:	ITS
DATE:	05/27/2022
PLAN NO.	2695



HOUSE NAME:	DRAYTON
DRAWING TITLE	FIRST FLOOR ELECTRICAL


SHEET No.	E.1
-----------	-----

FILE: Lot 00.0077.dwg DATE: 5/27/2022 10:32 AM

**ELECTRICAL LEGEND**

- Ⓢ SINGLE POLE SWITCH
- Ⓢ<sub>3</sub> THREE WAY SWITCH
- Ⓢ<sub>4</sub> FOUR WAY SWITCH
- ⓈⓈ DUPLEX AFCI RECEPTACLE
- ⓈⓈ<sub>B</sub> DUPLEX AFCI RECEPTACLE - BOTTOM HALF SWITCHED
- ⓈⓈ<sub>F</sub> DUPLEX AFCI RECEPTACLE - FLOOR MOUNTED
- 220V Ⓢ RECEPTACLE - 220V
- ⓈⓈ<sub>GFI</sub> DUPLEX AFCI RECEPTACLE - GFI
- ⓈⓈ<sub>WP/GFI</sub> DUPLEX AFCI RECEPTACLE - WATERPROOF GFI
- ⓈⓈ<sub>SD</sub> SMOKE DETECTOR - WIRED IN SERIES
- ⓈⓈ<sub>EF</sub> EXHAUST FAN MOTOR
- ⓈⓈ<sub>CO</sub> CO DETECTOR
- ⓈⓈ<sub>DC</sub> DOOR CHIME
- ⓈⓈ<sub>LM</sub> LIGHT FIXTURE - WALL MOUNTED
- ⓈⓈ<sub>CM</sub> LIGHT FIXTURE - CEILING MOUNTED
- ⓈⓈ<sub>RC</sub> LIGHT FIXTURE - RECESSED CAN
- ⓈⓈ<sub>LSM</sub> LIGHT FIXTURE - LED SURFACE MOUNTED
- ⓈⓈ<sub>PL</sub> FULLCHAIN LAMPHOLDER
- ⓈⓈ<sub>K</sub> KEYLESS LAMPHOLDER

NOTE: ALL ELECTRICAL WORK SHALL CONFORM TO THE REQUIREMENTS OF THE ADOPTED VERSION OF THE NATIONAL ELECTRICAL CODE, THE LOCAL POWER COMPANY AND TO ALL APPLICABLE LOCAL REGULATIONS.



**ELECTRICAL PLAN**  
**SECOND FLOOR - ELEV. 5**  
 SCALE: 1/8" = 1'-0"

MASTER PLAN INFORMATION	
REVISION	DATE
R2-RALE	3-6-19
UPDATED DATE	2-17-22

DRAWN BY:  
 ITS  
 DATE: 05/27/2022  
 PLAN NO.  
 2695




HOUSE NAME:  
**DRAYTON**  
 DRAWING TITLE  
**SECOND FLOOR ELECTRICAL**

SHEET No.  
**E1.2**

FILE: Lot\_00:0077.dwg DATE: 5/27/2022 10:32 AM





MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING  
10000 W. HARRIS RD. SUITE 100  
DRAYTON, NC 27585  
919-854-8888  
www.mulhernkulp.com



MLK project number:  
126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21

REVISIONS:  
date: initial



FOUNDATION PLANS  
DRAYTON  
RALEIGH, NC

SO.0

### GENERAL STRUCTURAL NOTES

#### FOUNDATION

- DESIGN IS BASED ON 2018 NORTH CAROLINA STATE BUILDING CODE: RESIDENTIAL CODE.
- FOOTING DESIGN - 2,000 PSF ALLOWABLE SOIL BEARING PRESSURE IS ASSUMED. BUILDER/CONTRACTOR MUST VERIFY.
- FASTEN 2x4/6 SILL PLATES TO FND WITH A MINIMUM OF 2 ANCHORS PER PLATE, 12" MAX. FROM PLATE ENDS - UTILIZING:
  - 1/2" DIA. ANCHOR BOLTS @ 6'-0" O.C. 7" MIN. EMBEDMENT (CONG), 15" MIN. EMBEDMENT (CMU)
  - SIMPSON MASA ANCHOR STRAPS @ 6'-0" O.C. (CONG)
  - SIMPSON MAB23 ANCHOR STRAPS @ 2'-8" O.C. (CMU)
 (REFER TO DETAILS FOR 10' TALL MALL ANCHOR REQUIREMENTS)
- ALL LUMBER EXPOSED TO WEATHER OR IN CONTACT W/ CONCRETE OR CMU SHALL BE PRESERVATIVE TREATED SOUTHERN PINE #2.
- BUILDER TO VERIFY CORROSION-RESISTANCE COMPATIBILITY OF HARDWARE & FASTENERS IN CONTACT W/ PRESERVATIVE-TREATED WOOD. CONTACT LUMBER & HARDWARE SUPPLIERS TO COORD.
- BASEMENT INTERIOR BEARING WALLS & EXTERIOR WALK-OUT BASEMENT WALLS SHALL BE 2x6 @ 16" O.C. SFF OR STP, 'STUD' GRADE OR BETTER.
- CONCRETE DESIGN BASED ON ACI 318. CONCRETE SHALL ATTAIN THE FOLLOWING MIN. COMPRESSIVE STRENGTHS IN 28 DAYS, UN.O.:
  - f<sub>c</sub> = 4000 psi: ..... FOUNDATION WALLS
  - 2500 psi: ..... FOOTINGS & INTERIOR SLABS ON GRADE
  - 3000 psi: ..... GARAGE & EXTERIOR SLABS ON GRADE
  - f<sub>y</sub> = 60,000 psi
- BASEMENT FOUNDATION WALL DESIGN BASED ON:
  - 9' OR 10' HEIGHT (AS NOTED ON PLANS)
  - TALLER WALLS MUST BE ENGINEERED.
  - NOMINAL WIDTH (9 1/2") FOR 10' THICK WALL.
- BASEMENT WALL DESIGN IS BASED ON 60 PCF BACKFILL SOIL TYPE CLASSIFICATIONS (SG, ML, CL, OR CL).
- BASEMENT WALLS SHALL BE BRACED, PRIOR TO BACKFILLING, BY ADEQUATE TEMPORARY BRACING OR INSTALL 1st FLOOR DECK.
- PROVIDE (2) #5 BARS AROUND ALL SIDES OF OPENINGS IN CONCRETE BSMT. FND. WALL WITH 2" CLEAR. REINFORCEMENT SHALL EXTEND 12" PAST CORNER OF OPENING IN ALL DIRECTIONS.
  - FOR OPENINGS UP TO 36", PROVIDE MINIMUM 10' CONCRETE DEPTH OVER OPENING OR (3)2x10 W/ (2)2x6 JACK STUDS, UN.O.
  - LARGER OPENINGS SHALL BE PER PLAN.
- ALL CONCRETE EXPOSED TO THE WEATHER SHALL NOT HAVE LESS THAN 5% OR MORE THAN 7% AIR ENTRAINMENT.
- ALL FOOTINGS SHALL BEAR AT LEAST 12" BELOW FINISH GRADE.
- FOOTINGS AND SLABS ON GRADE SHALL BEAR ON VIRGIN SOIL OR 95% COMPACTED FILL.
- PROVIDE CONTROL JOINTS AT ALL INSIDE CORNERS OF SLAB EDGES, AND OTHER LOCATIONS WHERE SLAB CRACKS ARE LIKELY TO DEVELOP.
  - JOINTS SHALL BE LOCATED @ 10'-0" O.C. (RECOMMENDED) OR 15'-0" O.C. (MAXIMUM)
  - JOINT GRID PATTERN SHALL BE AS CLOSE TO SQUARES AS POSSIBLE (1:1 RATIO), WITH A MAXIMUM OF 1:1.5 RATIO
  - CONTROL JOINTS SHALL NOT BE INSTALLED IN STRUCTURAL SLABS
- CONCRETE MASONRY UNITS (CMU) SHALL BE ASTM C90 WITH A MIN. COMPRESSIVE STRENGTH OF 1900 psi (F<sub>m</sub>=1500 psi). MORTAR SHALL BE ASTM C270, TYPE S. CMU DESIGN PER ACI 530 & 530.1.
- CMU FOUNDATION WALLS SHALL HAVE 'DUR-O-WALL' HORIZONTAL JOINT REINFORCEMENT (OR EQUAL) - 9 GA. MINIMUM @ 16" O.C.
- PROVIDE 2x8 x 16" LONG P.T. PLATE ON TOP OF ALL CRAWL SPACE PIERS. ALL PIERS SHALL BE GROUTED SOLID.
- PROVIDE 2x6 P.T. PLATE ON INTERIOR CRAWL SPACE WALLS, FASTENED PER ANCHORAGE SPECIFICATION NOTED ABOVE.
- DIMENSIONS BY OTHERS, BUILDER TO VERIFY.
- BUILDER TO VERIFY THAT MODEL HAS BEEN ADEQUATELY TREATED BY A LICENSED AND BONDED PEST CONTROL COMPANY FOR SUBTERRANEAN TERMITES. METHOD AND TYPE OF TREATMENT TO BE DETERMINED BY BEST CONTROL COMPANY.

### VENEER LINTEL SCHEDULE

SPAN (MAX)	HEIGHT OF VENEER ABOVE LINTEL	STEEL ANGLE SIZE
3'-0"	20 FT. MAX	L3"x3"x1/2"
6'-0"	3 FT. MAX	L3"x3"x1/2"
	12 FT. MAX	L4"x3"x1/2"
8'-0"	20 FT. MAX	L3"x3"x3/8"
	3 FT. MAX	L4"x4"x1/2"
	12 FT. MAX	L3"x3"x3/8"
9'-0"	16 FT. MAX	L6"x3"x3/8"
	12 FT. MAX	L6"x3"x3/8"
16'-0"	2 FT. MAX	L7"x4"x3/2"
	3 FT. MAX	L8"x4"x3/2"

ALL LINTELS:  
 - SHALL SUPPORT 2 1/2" - 3 1/2" VENEER w/ 40 psf MAXIMUM HEIGHT.  
 - 1/2" SHALL HAVE 4" MIN BEARING  
 - 1/4" SHALL HAVE 8" MIN BEARING  
 - 1/2" SHALL NOT BE FASTENED BACK TO HEADER  
 - 1/4" SHALL BE FASTENED BACK TO WOOD HEADER IN WALL @ 48" O.C. W/ 3/8" DIA. x 3 1/2" LONG LAG SCREWS IN 2" LOW VERTICALLY SLOTTED HOLES.  
 - MAX VENEER HT. APPLIES TO ANY PORTION OF BRICK OVER THE OPENING.  
 - ALL LINTELS SHALL BE LOW LEG VERTICAL.  
 - NEAR SUPPORTING VENEER @ 3" FROM THE EXTERIOR TOE OF THE HORIZONTAL LEG MAY BE CUT IN THE FIELD TO BE 3/4" DEEP OVER THE BEARING LENGTH ONLY. THIS IS TO ALLOW FOR PORTLAND JOINT FINISHING.  
 - SEE STRUCTURAL PLANS FOR ANY LINTEL CONDITION NOT ENCOMPASSED BY THE ABOVE PARAMETERS.  
 - FOR GREEN VENEER USE L-ANCHOR.  
 - FOR 3/4" VENEER ONLY. SEE PLAN FOR VENEER SUPPORT IN VENEER @ 6" THICK.

### LEGEND

- ▬ INTERIOR BEARING WALL
- ▬ BEARING WALL ABOVE
- ▬ BEAM / HEADER
- ▬ INDICATES SHEAR WALL & EXTENT
- ▬ EXTENT OF OVERFRAMING
- JL METAL HANGER
  - INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
- ▶ INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

### NON-BEARING HEADER SCHEDULE

SPAN	2x4 NON-BEARING PARTITION WALL	2x6 NON-BEARING PARTITION WALL
UP TO 3'-0"	(1)2x4 FLAT	(1)2x6 FLAT
UP TO 6'-0"	(2)2x4	(3)2x4
UP TO 8'-0"	(2)2x6	(3)2x6

NOTES:  
 • ALL NON-BEARING INTERIOR STUD WALLS SHALL BE CONSTRUCTED WITH 2x 'STUD' GRADE MEMBERS SPACED @ 24" O.C. (MAX.)

### LATERAL BRACING & SHEAR WALL SHEATHING SPECIFICATIONS

THIS MODEL HAS BEEN DESIGNED TO RESIST LATERAL FORCES RESULTING FROM:  
**120 MPH WIND IN 2018 NCSEBG:RC**  
 (120 MPH WIND SPEED IN ASCE 7-10 WIND MAP, PER IRC R301.2.1.1) EXP. B, RISK CAT. 2 & SEISMIC CAT. A/B.

THE DESIGN WAS COMPLETED PER 2015 IBC (SECTION 1604) & ASCE 7-10, AS PERMITTED BY R301.1.3 OF THE 2018 NCSEBG:RC, OR THE SIMPLIFIED PRESCRIPTIVE PROCEDURE IN ACCORDANCE WITH THE 2015 IRC IF THE PARAMETERS OF SECTION R602.12 COMPLY. ACCORDINGLY, THIS MODEL, AS DOCUMENTED AND DETAILED HEREIN, IS ADEQUATE TO RESIST THE CODE REQUIRED LATERAL FORCES.

DESIGN WIND UPLIFT LOADS HAVE BEEN CALCULATED UTILIZING ASCE 7-10 (ACCEPTED ENGINEERING PRACTICE) AS ALLOWED PER 2018 NCSEBG:RC SECTION R802.1.1.1. THIS MODEL HAS BEEN DETAILED WHERE REQUIRED & ENGINEERED TO RESIST THE WIND UPLIFT LOAD PATH PER SECTIONS R602.3.5 & R802.11.

### EXT. WALL SHEATHING SPECIFICATION

- 7/16" OSB OR 15/32" PLYWOOD:  
FASTEN SHEATHING W/ 8d NAILS @ 6" O.C. AT EDGES & @ 12" O.C. IN THE PANEL FIELD. TYP. UN.O.
- HORIZONTAL BLOCKING OF EXT. WALLS/SHEAR WALL PANEL EDGES IS NOT REQUIRED BY THIS DESIGN EXCEPT FOR THOSE AREAS SPECIFICALLY NOTED.
- ALL EXT. WALLS SHALL BE CONTINUOUSLY SHEATHED AND ARE CONSIDERED SHEAR WALLS.
- ALT. STAPLE CONNECTION SPEC: 1 1/2" 16 GA STAPLES (3/4" CROWN) @ 3" O.C. AT EDGES & @ 6" O.C. IN FIELD.

### BLOCKED PANEL EDGES

- AT DESIGNATED AREAS - FASTEN SHEATHING W/ 8d NAILS @ 6" O.C. AT ALL PANEL EDGES AND 12" O.C. IN THE PANEL FIELD OR 1 1/2" 16 GA STAPLES (3/4" CROWN) @ 3" O.C. AT EDGES & @ 6" O.C. IN FIELD. ALL SHEATHING PANELS SHALL BE ORIENTED AND INSTALLED FULL HEIGHT OF SHEAR WALL OR 2x HORIZONTAL BLOCKING SHALL BE PROVIDED TO SUPPORT ALL UNSUPPORTED PANEL EDGES & EDGE FASTENINGS.

### 3" O.C. EDGE NAILING

- AT DESIGNATED AREAS - FASTEN PANEL EDGES OF WOOD STRUCTURAL WALL SHEATHING TO FRAMING W/ 8d NAILS @ 3" O.C. NO STAPLE ALTERNATIVE AVAILABLE AT THIS SPEC. ALL SHEATHING PANELS SHALL BE ORIENTED AND INSTALLED FULL HEIGHT OF SHEAR WALL OR 2x HORIZONTAL BLOCKING SHALL BE PROVIDED TO SUPPORT UNSUPPORTED PANEL EDGES AND 3" O.C. EDGE FASTENING.

### NOTES

- SEE CONNECTION SPECIFICATIONS CHART FOR STANDARD SHEAR TRANSFER DETAILING. IF ADDITIONAL CAPACITY IS REQUIRED BY DESIGN, IT WILL BE SPECIFICALLY NOTED ON PLAN.
- DESIGN ASSUMES 16" O.C. MAX. STUD SPACING, UN.O.
- ALL STRUCTURAL PANELS ARE TO BE DIRECTLY APPLIED TO STUD FRAMING.
- PRE-MANUFACTURED PANELIZED WALLS:  
FASTEN TOGETHER END STUDS OF WALL PANELS SHEATHED W/ OSB OR PLYWOOD W/ 10d NAILS @ 4" O.C. (THRU ONE SIDE ONLY)

- ▬ INDICATES EXTENT OF INT. OSB SHEARWALL OR 3" O.C. OSB SHEARWALL.
- ▶ INDICATES HOLD-DOWN BELOW

### FLOOR FRAMING

- I-JOISTS/TRUSSES SHALL BE DESIGNED BY MANUF. TO MEET OR EXCEED L/480 LIVE LOAD DEFLECTION CRITERIA. (EXCLUDES MARBLE FLOORS - CONTACT MKK FOR MARBLE FLOOR DESIGNS)
- AT I-JOIST FLOORS, PROVIDE 1 1/8" MIN. OSB RIM BOARD.
- METAL HANGERS SHALL BE SPECIFIED BY MANUFACTURER, UN.O.
- I-JOIST/TRUSS SHOP DWGS. SHALL BE SUBMITTED TO ARCH. & ENG. FOR REVIEW AND APPROVAL PRIOR TO FABRICATION OR DELIVERY.
- FLOOR SHEATHING SHALL BE 23/32" A.P.A. RATED STURD-I-FLOOR 24" O.C. EXPOSURE 1 (OR APPROVED EQUAL) WITH TONGUE AND GROOVE EDGES. FASTEN TO FRAMING MEMBERS W/ GLUE AND - 2 1/2" x 0.131" NAILS @ 6" O.C. @ PANEL EDGES & @ 12" O.C. FIELD. - 2 3/8" x 0.120" NAILS @ 4" O.C. @ PANEL EDGES & @ 8" O.C. FIELD. - 2 3/8" x 0.113" NAILS @ 3" O.C. @ PANEL EDGES & @ 6" O.C. IN FIELD.

### ROOF FRAMING

- BAY WINDOWS & SHED ROOFS (UP TO 6' SPAN) CAN BE 2x4 OR 2x6 RAFTERS & CEILING JOISTS @ 16/24" O.C.
- FASTEN EACH ROOF TRUSS TO TOP PLATE W/ SIMPSON H2.5T CLIP (OR APPROVED EQUAL) @ ALL BEARING POINTS. PROVIDE (2) H2.5T CLIPS AT 2-PLY GIRDER TRUSSES, (3) H2.5T CLIPS AT 3-PLY GIRDER TRUSSES & ROOF BEAMS - AT ALL BEARING POINTS.
- METAL HANGERS SHALL BE SPECIFIED BY THE MANUFACTURER, UN.O.
- ROOF TRUSS SHOP DWGS. SHALL BE SUBMITTED TO ARCH & ENG. FOR REVIEW AND APPROVAL PRIOR TO FABRICATION OR DELIVERY.
- ERECT AND INSTALL ROOF TRUSSES PER WTCA & TP15 BCSI 1-08 'GUIDE TO GOOD PRACTICE FOR HANDLING, INSTALLING & BRACING OF METAL PLATE CONNECTED WOOD TRUSSES.'
- SUPPORT PORCH & SHORT SPAN ROOF TRUSSES W/ 2x4 LEDGER FASTENED TO FRAMING W/ (2) 3"x0.131" NAILS @ 16" O.C. (MAX. 1' SPAN)
- ROOF SHEATHING SHALL BE 7/16" A.P.A. RATED SHEATHING 24/16 EXPOSURE 1 (OR APPROVED EQUAL). FASTEN TO FRAMING MEMBERS - W/ 2 1/2" x 0.131" NAILS @ 6" O.C. @ PANEL EDGES & @ 12" O.C. FIELD. - W/ 2 3/8" x 0.120" NAILS @ 4" O.C. @ PANEL EDGES & @ 8" O.C. FIELD. - W/ 2 3/8" x 0.113" NAILS @ 3" O.C. @ PANEL EDGES & @ 6" O.C. FIELD.

### GENERAL STRUCTURAL NOTES

- DESIGN IS BASED ON 2018 NORTH CAROLINA STATE BUILDING CODE: RESIDENTIAL CODE.
- WOOD FRAME ENGINEERING IS BASED ON NDS, 'NATIONAL DESIGN SPECIFICATION FOR WOOD CONSTRUCTION' - LATEST EDITION.
- DESIGN LOADS:  
ROOF DEAD = 7 PSF T.C., 10 PSF B.G.  
LIVE = 16 PSF  
LOAD DURATION FACTOR = 1.25  
  
FLOOR LIVE = 40 PSF @ SLEEPING AREAS  
DEAD = 10 PSF (I-JOISTS & SOLID SAMN)  
10 PSF T.C., 5 PSF B.G. (TRUSSES)  
(ADD'L 10 PSF @ TILE)  
  
LATERAL 120 MPH, EXPOSURE B. SEISMIC A/B.  
  
SOIL 2,000 PSF ASSUMED ALLOWABLE BEARING PRESSURE (TO BE VERIFIED BY BUILDER)

### GENERAL FRAMING

- ALL TYP. NAIL FASTENER REQUIREMENTS ARE NOTED IN STANDARD CONNECTIONS TABLE OR ON PLANS. ALL NAILS SPECIFIED ARE MIN DIAMETER AND LENGTH REQUIRED FOR CONNECTION. ALL HANGER NAILS SHALL BE INSTALLED PER MANUFACTURER'S REQUIREMENTS FOR MAX CHARTED CAPACITY. NOTE: HANGERS USE COMMON NAIL DIAMETERS NOT TYPICAL FRAMING GUN NAILS.
- REFER TO FASTENING SCHEDULE TABLE R602.3(1) FOR ALL CONNECTIONS, TYP. UN.O.
- EXT. & INT. BRG WALLS SHALL BE 2x4 OR 2x6 (AS SHOWN ON PLANS) @ 16" O.C. SFF OR STP 'STUD' GRADE LUMBER, OR BETTER, UN.O.  
• WALLS OVER 12' TALL SHALL BE PER PLAN.
- ALL HEADERS, BEAMS & OTHER STRUCTURAL MEMBERS SHALL BE SPRUCE-PINE-FIR #2 (SFF) OR SOUTHERN PINE #2 (STP) LUMBER, OR BETTER (KILN-DRIED). ALL HEADERS HAVE BEEN DESIGNED BASED ON CALCULATED LOADS & SIZED ACCORDINGLY. CODE TABLES HAVE NOT BEEN USED.
- ALL NON-BEARING INTERIOR STUD WALLS SHALL BE CONSTRUCTED WITH 2x 'STUD' GRADE MEMBERS SPACED @ 16" O.C. (MAX, UN.O.)  
• HEADERS IN NON-LOAD BEARING WALLS SHALL BE: (1)2x4/6 FLAT @ OPENINGS UP TO 4'; (2)2x4/6 FLAT UP TO 8';  
• ALL FRAMING LUMBER SHALL BE DRIED TO 19% MC (KD-15).
- ENGINEERED LUMBER TO MEET OR EXCEED THE FOLLOWING:  
• LSL' - F<sub>b</sub>=2325 psi; F<sub>v</sub>=310 psi; E=155x10<sup>6</sup> psi  
• LVL' - F<sub>b</sub>=2600 psi; F<sub>v</sub>=285 psi; E=2.0x10<sup>6</sup> psi
- FOR 2 & 3 PLY BEAMS OF EQUAL WIDTH, FASTEN PLYS TOGETHER WITH 3 ROWS OF 3"x0.120" NAILS @ 8" O.C. OR 2 ROWS 1/4"x3/8" SIMPSON SDS SCREWS (OR 3/8" TRUSSLOK SCREWS) @ 16" O.C. USE A MINIMUM OF 3 ROWS FOR BEAM DEPTHS OF 14" OR GREATER. APPLY FASTENING AT BOTH FACES FOR 3-PLY CONDITION. LOCATE TOP & BOTTOM NAILS/SCREWS 2" FROM EDGE. SOLID 3 1/2" OR 5 1/4" BEAMS ARE ACCEPTABLE. USE 2 ROWS OF NAILS FOR 2x6 & 2x8 MEMBERS.
- FOR 4 PLY BEAMS OF EQUAL WIDTH, FASTEN PLYS TOGETHER WITH 3 ROWS OF 1/4"x6" SIMPSON SDS SCREWS (OR 6 3/8" TRUSSLOK SCREWS) @ 16" O.C. USE A MINIMUM OF 4 ROWS FOR BEAM DEPTHS OF 14" OR GREATER. APPLY FASTENING AT BOTH FACES (ONE SIDE ONLY FOR TRUSSLOK SCREWS). LOCATE TOP AND BOTTOM SCREWS 2" FROM EDGE. A SOLID 7" BEAM IS ACCEPTABLE.
- ALL HEADERS SHALL BE SUPPORTED BY (1)2x JACK STUD & (1)2x KING STUD, MINIMUM.  
- THE NUMBER OF STUDS SPECIFIED AT A SUPPORT INDICATES THE NUMBER OF JACK STUDS REQUIRED, UN.O..
- ALL MULTI-PLY STUDS TO BE FASTENED TOGETHER W/ 3"x0.131" NAILS @ 24" O.C. (MIN), EACH PLY.
- PROVIDE SOLID BLOCKING IN FLOOR SYSTEM UNDER ALL POSTS CONTINUOUS TO FND/BEARING. BLOCKING TO MATCH POST ABOVE.
- FASTEN 2x WOOD PLATES TO TOP FLANGE OF STEEL BEAMS WITH P.A.F.'s (HILT' X-CF PINS OR EQUAL) @ 16" O.C. STAGGERED, OR 1/2" DIA. BOLTS @ 48" O.C. STAGGERED.
- ALL EXTERIOR 4x4 WOOD POSTS SHALL HAVE SIMPSON BC52-2/4 CAP & ABW44Z BASE, UN.O.


### MEANS & METHODS NOTES

THE STRUCTURE IS DESIGNED TO BE SELF SUPPORTING AND STABLE AFTER THE BUILDING IS FINISHED AND ALL PLAN, DETAIL, AND NOTE SPECIFICATIONS HAVE BEEN COMPLETED. IT IS THE CONTRACTOR'S SOLE RESPONSIBILITY TO DETERMINE THE ERECTION PROCEDURES AND SEQUENCE TO INSURE THE SAFETY OF THE BUILDING AND ITS COMPONENTS DURING CONSTRUCTION. THIS INCLUDES, BUT IS NOT LIMITED TO, THE ADDITION OF NECESSARY SHORING, SHEETING, TEMPORARY BRACING, GUYS, AND TIE-DOWNS. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL SHORING AND BRACING REQUIRED TO STABILIZE AND PROTECT EXISTING AND ADJACENT STRUCTURES AND SYSTEMS DURING COURSE OF DEMOLITION AND CONSTRUCTION OF THE PROJECT.

STRUCTURAL DESIGN AND SPECIFICATIONS ASSUME THAT ALL SUPPORTING AND NON-SUPPORTING ELEMENTS IN CONTACT WITH FLOOR FRAMING ARE LEVEL, INCLUDING, BUT NOT LIMITED TO; FOUNDATIONS, SLABS ON GRADE, BEAMS, WALLS, AND NON-BEARING ELEMENTS. IT IS THE CONTRACTOR'S RESPONSIBILITY TO VERIFY LEVELNESS AND MAKE ADJUSTMENTS AS NECESSARY, INCLUDING CONSIDERATION OF THOSE AREAS THAT MAY BE WITHIN CONTRACTUAL, INDUSTRY, OR WARRANTY TOLERANCES.

### ADDITIONAL NOTES FOR TRUSS & I-JOIST MANUFACTURER

- ROOF TRUSS, FLOOR TRUSS AND ENGINEERED JOISTS SHALL BE DESIGNED TO MEET THE DIFFERENTIAL DEFLECTION CRITERIA BELOW, UNLESS NOTED OTHERWISE ON PLAN. MULHERN & KULP CANNOT BE HELD RESPONSIBLE FOR ANY STRUCTURAL ISSUES RELATED TO ANY BUILDING COMPONENT IF COMPONENT SHOP DRAWINGS ARE NOT SUBMITTED TO MKK FOR REVIEW PRIOR TO FABRICATION, DELIVERY, OR INSTALLATION.
  - TRUSSES/JOISTS SHALL BE DESIGNED SO THAT DIFFERENTIAL DEFLECTION BETWEEN ADJACENT PARALLEL TRUSSES/JOISTS OR GIRDER TRUSSES/FLUSH BEAMS DO NOT EXCEED THE FOLLOWING:
    - ROOF TRUSSES:
      - 1/4" DEAD LOAD
      - 1/8" DEAD LOAD
    - FLOOR TRUSSES, ATTIC TRUSSES, & I-JOISTS:
      - 1/8" DEAD LOAD
    - FLOOR TRUSSES & ATTIC TRUSSES ADJACENT TO FLOOR FRAMING BY OTHERS:
      - LIMIT ABSOLUTE TRUSS DEFLECTION TO 3/16" DEAD LOAD. (NOT DIFFERENTIAL DEFLECTION)



**MULHERN+KUL**  
RESIDENTIAL STRUCTURAL ENGINEERING  
3800 Shiloh Ave. Building 4 - Jamboree, PA 15228  
724-864-8888 - mulhern@mulhernk.com  
N.C. #0-3025



M&K project number:  
126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21

REVISIONS:  
date: initia:




FOUNDATION PLANS  
DRAYTON  
RALEIGH, NC


LEFT HAND  
**S1.0**

LEGEND	
	INTERIOR BEARING WALL
	BEARING WALL ABOVE
	BEAM / HEADER
	INDICATES SHEAR WALL & EXTENT
	EXTENT OF OVERFRAMING
	JL METAL HANGER
	* INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
	INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

REFER TO S0.0 FOR  
TYPICAL STRUCTURAL NOTES  
& SCHEDULES




**3 PARTIAL MONO SLAB FOUNDATION PLAN**  
SCALE: 1/8"=1'-0"  
OPTIONAL EXT. BREAKFAST



**1 MONO SLAB FOUNDATION PLAN**  
SCALE: 1/8"=1'-0"  
ELEVATION #1





**MULHERN+KUL**  
 REGISTERED STRUCTURAL ENGINEERING  
 2800 Southside Ave. Building 4 - Jackson, NC 28540  
 252-345-8888 - mulhern@mulhern.com  
 N.C. # 3025


LEGEND	
	INTERIOR BEARING WALL
	BEARING WALL ABOVE
	BEAM / HEADER
	INDICATES SHEAR WALL & EXTENT
	EXTENT OF OVERFRAMING
	METAL HANGER
	INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
	INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

**REFER TO SO.0 FOR  
 TYPICAL STRUCTURAL NOTES  
 & SCHEDULES**

M&K project number:  
 126-21020

project mgr: JTR  
 drawn by: KL  
 issue date: 06-12-21


REVISIONS:  
 date: initial:



**4 PARTIAL MONO SLAB FOUNDATION PLAN**  
 SCALE: 1/8"=1'-0"  
 ELEVATION #5

FOUNDATION PLANS  
 DRAYTON  
 RALEIGH, NC

Sheet LEFT HAND  
**S1.1**



**1 2ND FLOOR FRAMING PLAN**  
SCALE: 1/8"=1'-0" ELEVATIONS #1 + #2

REFER TO SO.O FOR TYPICAL STRUCTURAL NOTES & SCHEDULES

SD2.0 & SD2.1 REFERS TO SD2.0J & SD2.1J FOR I-JOIST FLOOR FRAMING OR SD2.0T & SD2.1T FOR TRUSS FLOOR FRAMING

SD2.1J/SD2.1T REFERS TO SD2.1JA/SD2.1TA FOR LVL/PSL/LSL BEAMS OR SD2.1JB/SD2.1TB FOR FLITCH BEAMS OR SD2.1JC/SD2.1TC FOR STEEL BEAMS

**LEGEND**

- INTERIOR BEARING WALL
- BEARING WALL ABOVE
- BEAM / HEADER
- INDICATES SHEAR WALL & EXTENT
- EXTENT OF OVERFRAMING
- J.L. METAL HANGER
- INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMBS ABOVE.
- INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

**ENGINEERED BEAM MATERIAL SCHEDULE**

BEAM NUMBER	LVL OPTION	PSL OPTION	LSL OPTION	FLITCH OPTION	STEEL OPTION
001	(2)3/4"x14" - F	3/2"x14" - F	(2)3/4"x14" - F	(2)2x12 + (1)1/2"x10" STEEL FLITCH PLATES - FB	M2x14 - F
002	(2)3/4"x14" - F	3/2"x14" - F	(2)3/4"x14" - F	(2)2x12 + (1)1/2"x10" STEEL FLITCH PLATES - FB	M2x14 - F
003	(2)3/4"x18" - FB or (2)3/4"x20" - FB	3/4"x18" - FB	NA	(2)2x12 + (2)3/4"x10" STEEL FLITCH PLATES - FB	M2x26 - F
004	(2)3/4"x14" - F	3/2"x14" - F	(2)3/4"x14" - F	(2)2x12 + (1)1/2"x10" STEEL FLITCH PLATES - FB	M2x14 - F
005	(2)3/4"x17 1/2" - H cont.	3/2"x17 1/2" - H cont.	(2)3/4"x17 1/2" - H cont.	(2)2x12 + (2)3/4"x10" STEEL FLITCH PLATES - H cont.	NA
005A	(2)3/4"x14" - H cont.	3/4"x14" - H cont.	NA	(2)2x12 + (2)3/4"x10" STEEL FLITCH PLATES - H cont.	NA
006	(1)3/4"x14" - F	3/2"x14" - F	(2)3/4"x14" - F	(2)2x12 + (1)1/2"x10" STEEL FLITCH PLATES - FB	M2x14 - F
007	(2)3/4"x17 1/2" - D	3/2"x17 1/2" - D	(2)3/4"x17 1/2" - D	(2)2x12 + (2)3/4"x10" STEEL FLITCH PLATES - D	M10x12 - D
008	(2)3/4"x18" - H cont.	3/2"x18" - H cont.	(2)3/4"x18" - H cont.	(2)2x12 + (2)3/4"x10" STEEL FLITCH PLATES - H cont.	NA
009	(2)3/4"x14" - F	3/2"x14" - F	(2)3/4"x14" - F	(2)2x10 + (1)1/2"x10" STEEL FLITCH PLATES - F	M8x10 - F
010	(2)3/4"x14" - F	3/2"x14" - F	(2)3/4"x14" - F	(2)2x12 + (1)1/2"x10" STEEL FLITCH PLATES - FB	M2x14 - F
011	(2)3/4"x14" - F	3/2"x14" - F	(2)3/4"x14" - F	(2)2x12 + (1)1/2"x10" STEEL FLITCH PLATES - FB	M2x14 - F
012	(2)3/4"x17 1/2" - D	3/2"x17 1/2" - D	(2)3/4"x17 1/2" - D	(2)2x12 + (1)1/2"x10" STEEL FLITCH PLATES - D	M10x12 - D

**\*\* BEAM NOTATION:**


- "F" INDICATES FLUSH BEAM
- "FT" INDICATES FLUSH TOP BEAM
- "FB" INDICATES FLUSH BOTTOM BEAM
- "D" INDICATES DROPPED BEAM
- "H" INDICATES DROPPED OPENING HEADER

**\*\* REFER TO DETAIL D/SD2.0 FOR TYPICAL FLITCH BEAM CONNECTIONS**

**\*\* REFER TO DETAIL E/SD2.0 FOR TYPICAL STEEL BEAM CONNECTIONS**

**\*\* FOR FLUSH TOP BEAMS PROVIDE 2X STACKED PLATES BENEATH BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.**

**\*\* FOR FLUSH BOTTOM BEAMS PROVIDE 2X STACKED PLATES ATOP BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.**



**MULHERTN+KULL**  
RESIDENTIAL STRUCTURAL ENGINEERING  
3800 Bechtel Ave. Raleigh, NC 27607  
919.876.8888 • mulhertn+kull.com  
N.C. Lic. #S-3025



M&K project number: 126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21  
REVISIONS:  
date: initial



FLOOR FRAMING PLANS  
DRAYTON  
RALEIGH, NC

LEFT HAND  
**S3.0J**

REFER TO S.O. FOR  
TYPICAL STRUCTURAL NOTES  
& SCHEDULES

SD2.0 & SD2.1 REFERS TO SD2.0J  
& SD2.1J FOR I-JOIST FLOOR  
FRAMING OR SD2.0T & SD2.1T  
FOR TRUSS FLOOR FRAMING

SD2.1J/SD2.1T REFERS TO  
SD2.1JA/SD2.1TA FOR LVL/PSL/LSL  
BEAMS OR SD2.1JB/SD2.1TB FOR  
FLITCH BEAMS OR  
SD2.1JC/SD2.1TC FOR STEEL  
BEAMS


**LEGEND**

- [Symbol] INTERIOR BEARING WALL
- [Symbol] BEARING WALL ABOVE
- [Symbol] BEAM / HEADER
- [Symbol] INDICATES SHEAR WALL & EXTENT
- [Symbol] EXTENT OF OVERFRAMING
- JL METAL HANGER
- \* INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
- ▶ INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.


**ENGINEERED BEAM MATERIAL SCHEDULE**

BEAM NUMBER	LVL OPTION	PSL OPTION	LSL OPTION	FLITCH OPTION	STEEL OPTION
001	(2) 3/4" x 14" - F	3/2" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
002	(2) 3/4" x 14" - F	3/2" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
003	(3) 3/4" x 10" - FB or (2) 3/4" x 20" - FB	3/4" x 10" - FB	N/A	(3) 2x12 + (2) 3/4" x 14" STEEL FLITCH PLATES - FB	M2x10 - F
004	(2) 3/4" x 14" - F	3/2" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
005	(2) 3/4" x 11 1/2" - H cont.	3/2" x 11 1/2" - H cont.	(2) 3/4" x 11 1/2" - H cont.	(3) 2x12 + (2) 3/4" x 11 1/2" STEEL FLITCH PLATES - H cont.	N/A
005A	(3) 3/4" x 14" - H cont.	3/2" x 14" - H cont.	N/A	(3) 2x12 + (2) 3/4" x 11 1/2" STEEL FLITCH PLATES - H cont.	N/A
006	(1) 3/4" x 14" - F	3/2" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
007	(2) 3/4" x 11 1/2" - D	3/2" x 11 1/2" - D	(2) 3/4" x 11 1/2" - D	(2) 2x12 + (1) 1/2" x 11 1/2" STEEL FLITCH PLATES - D	M10x12 - D
008	(2) 3/4" x 10" - H cont.	3/2" x 10" - H cont.	(3) 3/4" x 10" - H cont.	(3) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - H cont.	N/A
009	(2) 3/4" x 9 1/2" - F	3/2" x 9 1/2" - F	(2) 3/4" x 9 1/2" - F	(2) 2x10 + (1) 1/2" x 9 1/2" STEEL FLITCH PLATES - F	M8x10 - F
010	(2) 3/4" x 14" - F	3/2" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
011	(2) 3/4" x 14" - F	3/2" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
012	(2) 3/4" x 11 1/2" - D	3/2" x 11 1/2" - D	(2) 3/4" x 11 1/2" - D	(2) 2x12 + (1) 1/2" x 11 1/2" STEEL FLITCH PLATES - D	M10x12 - D

- \*\* BEAM NOTATION:  
 - "F" INDICATES FLUSH BEAM  
 - "FB" INDICATES FLUSH TOP BEAM  
 - "FB" INDICATES FLUSH BOTTOM BEAM  
 - "D" INDICATES DROPPED BEAM  
 - "H" INDICATES DROPPED OPENING HEADER
- \*\* REFER TO DETAIL D/SD2.0 FOR TYPICAL FLITCH BEAM CONNECTIONS  
 \*\* REFER TO DETAIL E/SD2.0 FOR TYPICAL STEEL BEAM CONNECTIONS  
 \*\* FOR FLUSH TOP BEAMS PROVIDE 2X STACKED PLATES BENEATH BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.  
 \*\* FOR FLUSH BOTTOM BEAMS PROVIDE 2X STACKED PLATES ATOP BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.



**2 PARTIAL 2ND FLOOR FRAMING PLAN**  
 SCALE: 1/8"=1'-0"  
 ELEVATION #5



**MULHERN+KULICH**  
 REGISTERED STRUCTURAL ENGINEERING  
 3000 Southside Ave., Raleigh, NC 27608  
 P: 919.876.8888 F: 919.876.8889  
 M.L. #5-3025



MLK project number:  
 126-21020  
 project mgr: JTR  
 drawn by: KL  
 issue date: 06-12-21

REVISIONS:  
 date: init:



FLOOR FRAMING PLANS  
 DRAYTON  
 RALEIGH, NC

LEFT HAND  
**S3.1J**


**LEGEND**

- ▬ INTERIOR BEARING WALL
- ▬ BEARING WALL ABOVE
- ▬ BEAM / HEADER
- ▬ INDICATES SHEAR WALL & EXTENT
- ▬ EXTENT OF OVERFRAMING
- JL METAL HANGER
- \* INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
- ▶ INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

REFER TO 50.0 FOR TYPICAL STRUCTURAL NOTES & SCHEDULES

SD2.0 & SD2.1 REFERS TO SD2.0J & SD2.1J FOR 1-JOIST FLOOR FRAMING OR SD2.0T & SD2.1T FOR TRUSS FLOOR FRAMING

SD2.1J/SD2.1T REFERS TO SD2.1JA/SD2.1TA FOR LVL/PSL/LSL BEAMS OR SD2.1JB/SD2.1TB FOR FLITCH BEAMS OR SD2.1JC/SD2.1TC FOR STEEL BEAMS




**MULHERN+KULCZYNSKI**  
RESIDENTIAL STRUCTURAL ENGINEERING  
300 Peninsula Ave. Building 4 - Asheville, NC 28806  
919.252.9450  
ML.E. #C-2625

**ENGINEERED BEAM MATERIAL SCHEDULE**

BEAM NUMBER	LVL OPTION	PSL OPTION	LSL OPTION	FLITCH OPTION	STEEL OPTION
001	(2) 3/4"x14" - F	3/4"x14" - F	(2) 3/4"x14" - F	(2) 2x12 + (1) 1/2"x10" STEEL FLITCH PLATES - FB	W12x14 - F
002	(2) 3/4"x14" - F	3/4"x14" - F	(2) 3/4"x14" - F	(2) 2x12 + (1) 1/2"x10" STEEL FLITCH PLATES - FB	W12x14 - F
003	(2) 3/4"x18" - FB or (2) 3/4"x20" - FB	3/4"x18" - FB	N/A	(2) 2x12 + (2) 3/4"x10" STEEL FLITCH PLATES - FB	W12x26 - F
004	(2) 3/4"x14" - F	3/4"x14" - F	(2) 3/4"x14" - F	(2) 2x12 + (1) 1/2"x10" STEEL FLITCH PLATES - FB	W12x14 - F
005	(2) 3/4"x11 1/2" - H cont.	3/4"x11 1/2" - H cont.	(2) 3/4"x11 1/2" - H cont.	(2) 2x12 + (2) 3/4"x10 1/2" STEEL FLITCH PLATES - H cont.	N/A
005A	(2) 3/4"x14" - H cont.	3/4"x14" - H cont.	N/A	(2) 2x12 + (2) 3/4"x10 1/2" STEEL FLITCH PLATES - H cont.	N/A
006	(1) 3/4"x14" - F	3/4"x14" - F	(2) 3/4"x14" - F	(2) 2x12 + (1) 1/2"x10" STEEL FLITCH PLATES - FB	W12x14 - F
007	(2) 3/4"x11 1/2" - D	3/4"x11 1/2" - D	(2) 3/4"x11 1/2" - D	(2) 2x12 + (1) 1/2"x10" STEEL FLITCH PLATES - D	W10x12 - D
008	(2) 3/4"x16" - H cont.	3/4"x16" - H cont.	(2) 3/4"x16" - H cont.	(2) 2x12 + (2) 3/4"x10" STEEL FLITCH PLATES - H cont.	N/A
009	(2) 3/4"x9" - F	3/4"x9" - F	(2) 3/4"x9" - F	(2) 2x10 + (1) 1/2"x8" STEEL FLITCH PLATES - F	W6x10 - F
010	(2) 3/4"x14" - F	3/4"x14" - F	(2) 3/4"x14" - F	(2) 2x12 + (1) 1/2"x10" STEEL FLITCH PLATES - FB	W12x14 - F
011	(2) 3/4"x14" - F	3/4"x14" - F	(2) 3/4"x14" - F	(2) 2x12 + (1) 1/2"x10" STEEL FLITCH PLATES - FB	W12x14 - F
012	(2) 3/4"x11 1/2" - D	3/4"x11 1/2" - D	(2) 3/4"x11 1/2" - D	(2) 2x12 + (1) 1/2"x10" STEEL FLITCH PLATES - D	W10x12 - D

\*\* BEAM NOTATION:  
 - "F" INDICATES FLUSH BEAM  
 - "FT" INDICATES FLUSH TOP BEAM  
 - "FB" INDICATES FLUSH BOTTOM BEAM  
 - "D" INDICATES DROPPED BEAM  
 - "H" INDICATES DROPPED OPENING HEADER  
 \*\* REFER TO DETAIL D/SD2.0 FOR TYPICAL FLITCH BEAM CONNECTIONS  
 \*\* REFER TO DETAIL E/SD2.0 FOR TYPICAL STEEL BEAM CONNECTIONS  
 \*\* FOR FLUSH TOP BEAMS PROVIDE 2X STACKED PLATES BENEATH BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.  
 \*\* FOR FLUSH BOTTOM BEAMS PROVIDE 2X STACKED PLATES ATOP BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.



**5 PARTIAL SECOND FLOOR FRAMING PLAN  
 OPTIONAL EXT. BREAKFAST**  
 SCALE: 1/8"=1'-0" ELEV. #1 SHOWN - ALL ELEV. SIM.

M&K project number:  
12621020  
 project mgr: JTR  
 drawn by: KL  
 issue date: 06-12-21


REVISIONS:  
 date: initial



OPTION FRAMING PLANS  
**DRAYTON**  
 RALEIGH, NC

sheet: LEFT HAND  
**S5.0J**





**1 2ND FLOOR FRAMING PLAN**  
 SCALE: 1/8"=1'-0"  
 ELEVATIONS #1 + #2

REFER TO S.O. FOR  
 TYPICAL STRUCTURAL NOTES  
 & SCHEDULES

SD2.0 & SD2.1 REFERS TO SD2.0J  
 & SD2.1J FOR I-JOIST FLOOR  
 FRAMING OR SD2.0T & SD2.1T  
 FOR TRUSS FLOOR FRAMING

SD2.1J/SD2.1T REFERS TO  
 SD2.1JA/SD2.1TA FOR LVL/PSL/LSL  
 BEAMS OR SD2.1JB/SD2.1TB FOR  
 FLITCH BEAMS OR  
 SD2.1JC/SD2.1TC FOR STEEL  
 BEAMS


**LEGEND**

- INTERIOR BEARING WALL
- BEARING WALL ABOVE
- BEAM / HEADER
- - - INDICATES SHEAR WALL & EXTENT
- EXTENT OF OVERFRAMING
- J.L. METAL HANGER
- \* INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
- ▷ INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

**ENGINEERED BEAM MATERIAL SCHEDULE**

BEAM NUMBER	LVL OPTION	PSL OPTION	LSL OPTION	FLITCH OPTION	STEEL OPTION
001	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	M2x14 - F
002	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	M2x14 - F
003	(3) 3/4" x 18" - FB or (2) 3/4" x 20" - FB	3/4" x 18" - FB	NA	(3) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - FB	M2x26 - F
004	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	M2x14 - F
005	(2) 3/4" x 17 1/2" - H cont.	3/4" x 17 1/2" - H cont.	(2) 3/4" x 17 1/2" - H cont.	(3) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - H cont.	NA
005A	(3) 3/4" x 14" - H cont.	3/4" x 14" - H cont.	NA	(3) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - H cont.	NA
006	(1) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	M2x14 - F
007	(2) 3/4" x 17 1/2" - D	3/4" x 17 1/2" - D	(2) 3/4" x 17 1/2" - D	(3) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - D	M10x12 - D
008	(2) 3/4" x 18" - H cont.	3/4" x 18" - H cont.	(3) 3/4" x 18" - H cont.	(3) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - H cont.	NA
009	(2) 3/4" x 9 1/2" - F	3/4" x 9 1/2" - F	(2) 3/4" x 9 1/2" - F	(2) 2x10 + (1) 1/2" x 9 1/2" STEEL FLITCH PLATES - F	M6x10 - F
010	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	M2x14 - F
011	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	M2x14 - F
012	(2) 3/4" x 17 1/2" - D	3/4" x 17 1/2" - D	(2) 3/4" x 17 1/2" - D	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - D	M10x12 - D

**\*\* BEAM NOTATION:**  
 - "F" INDICATES FLUSH BEAM  
 - "FT" INDICATES FLUSH TOP BEAM  
 - "FB" INDICATES FLUSH BOTTOM BEAM  
 - "D" INDICATES DROPPED BEAM  
 - "H" INDICATES DROPPED OPENING HEADER  
 \*\* REFER TO DETAIL D/SD2.0 FOR TYPICAL FLITCH BEAM CONNECTIONS  
 \*\* REFER TO DETAIL E/SD2.0 FOR TYPICAL STEEL BEAM CONNECTIONS  
 \*\* FOR FLUSH TOP BEAMS PROVIDE 2X STACKED PLATES BENEATH BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.  
 \*\* FOR FLUSH BOTTOM BEAMS PROVIDE 2X STACKED PLATES ATOP BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.



**MULHERTN+KULL**  
 RESIDENTIAL STRUCTURAL ENGINEERING  
 3800 Bechtel Ave. Raleigh, NC 27607  
 P: 919.876.8888 F: 919.876.8889  
 M: 919.876.8885



M&K project number:  
 126-21020  
 project mgr: JTR  
 drawn by: KL  
 issue date: 06-12-21

**REVISIONS:**

date:	initial:



FLOOR FRAMING PLANS  
 DRAYTON  
 RALEIGH, NC

LEFT HAND  
**S3.0T**

REFER TO S.O. FOR  
TYPICAL STRUCTURAL NOTES  
& SCHEDULES

SD2.0 & SD2.1 REFERS TO SD2.0J  
& SD2.1J FOR I-JOIST FLOOR  
FRAMING OR SD2.0T & SD2.1T  
FOR TRUSS FLOOR FRAMING

SD2.1J/SD2.1T REFERS TO  
SD2.1JA/SD2.1TA FOR LVL/PSL/LSL  
BEAMS OR SD2.1JB/SD2.1TB FOR  
FLITCH BEAMS OR  
SD2.1JC/SD2.1TC FOR STEEL  
BEAMS

**LEGEND**


- ▬ INTERIOR BEARING WALL
- ▬ BEARING WALL ABOVE
- ▬ BEAM / HEADER
- ▬ INDICATES SHEAR WALL & EXTENT
- ▬ EXTENT OF OVERFRAMING
- JL METAL HANGER
- \* INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
- ▶ INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

**ENGINEERED BEAM MATERIAL SCHEDULE**

BEAM NUMBER	LVL OPTION	PSL OPTION	LSL OPTION	FLITCH OPTION	STEEL OPTION
001	(2) 1/2" x 14" - F	3/2" x 14" - F	(2) 1/2" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
002	(2) 1/2" x 14" - F	3/2" x 14" - F	(2) 1/2" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
003	(3) 1/2" x 10" - FB or (2) 3/4" x 20" - FB	3/4" x 10" - FB	N/A	(3) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - FB	M2x20 - F
004	(2) 1/2" x 14" - F	3/2" x 14" - F	(2) 1/2" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
005	(2) 1/2" x 11 1/2" - H cont.	3/2" x 11 1/2" - H cont.	(2) 1/2" x 11 1/2" - H cont.	(3) 2x12 + (2) 1/2" x 11 1/2" STEEL FLITCH PLATES - H cont.	N/A
005A	(3) 1/2" x 14" - H cont.	3/2" x 14" - H cont.	N/A	(3) 2x12 + (2) 1/2" x 11 1/2" STEEL FLITCH PLATES - H cont.	N/A
006	(1) 1/2" x 14" - F	3/2" x 14" - F	(2) 1/2" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
007	(2) 1/2" x 11 1/2" - D	3/2" x 11 1/2" - D	(2) 1/2" x 11 1/2" - D	(2) 2x12 + (1) 1/2" x 11 1/2" STEEL FLITCH PLATES - D	M10x12 - D
008	(2) 1/2" x 10" - H cont.	3/2" x 10" - H cont.	(3) 1/2" x 10" - H cont.	(3) 2x12 + (2) 1/2" x 10" STEEL FLITCH PLATES - H cont.	N/A
009	(2) 1/2" x 9 1/2" - F	3/2" x 9 1/2" - F	(2) 1/2" x 9 1/2" - F	(2) 2x10 + (1) 1/2" x 9 1/2" STEEL FLITCH PLATES - F	M8x10 - F
010	(2) 1/2" x 14" - F	3/2" x 14" - F	(2) 1/2" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
011	(2) 1/2" x 14" - F	3/2" x 14" - F	(2) 1/2" x 14" - F	(2) 2x12 + (1) 1/2" x 14" STEEL FLITCH PLATES - FB	M2x14 - F
012	(2) 1/2" x 11 1/2" - D	3/2" x 11 1/2" - D	(2) 1/2" x 11 1/2" - D	(2) 2x12 + (1) 1/2" x 11 1/2" STEEL FLITCH PLATES - D	M10x12 - D

**\*\* BEAM NOTATION:**  
 - "F" INDICATES FLUSH BEAM  
 - "FB" INDICATES FLUSH TOP BEAM  
 - "FB" INDICATES FLUSH BOTTOM BEAM  
 - "D" INDICATES DROPPED BEAM  
 - "H" INDICATES DROPPED OPENING HEADER

**\*\* REFER TO DETAIL D/SD2.0 FOR TYPICAL FLITCH BEAM CONNECTIONS**  
**\*\* REFER TO DETAIL E/SD2.0 FOR TYPICAL STEEL BEAM CONNECTIONS**  
**\*\* FOR FLUSH TOP BEAMS PROVIDE 2X STACKED PLATES BENEATH BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3" x 0.120" NAILS @ 8" O.C.**  
**\*\* FOR FLUSH BOTTOM BEAMS PROVIDE 2X STACKED PLATES ATOP BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3" x 0.120" NAILS @ 8" O.C.**



**MULHERN+KULL**  
 REGISTERED STRUCTURAL ENGINEERING  
 3000 Bechtel Ave., Raleigh, NC 27607  
 P: 919.876.8888 F: 919.876.8889  
 M.L. #6-3025



MAX project number:  
126-21020


project mgr: JTR  
 drawn by: KL  
 issue date: 06-12-21

REVISIONS:  
 date: init:




FLOOR FRAMING PLANS  
 DRAYTON  
 RALEIGH, NC

LEFT HAND  
**S3.1T**



**2 PARTIAL 2ND FLOOR FRAMING PLAN**  
 SCALE: 1/8"=1'-0"  
 ELEVATION #5



**LEGEND**

- ▬ INTERIOR BEARING WALL
- ▬ BEARING WALL ABOVE
- ▬ BEAM / HEADER
- ▬ INDICATES SHEAR WALL & EXTENT
- ▬ EXTENT OF OVERFRAMING
- JL METAL HANGER
- \* INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
- ▶ INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.

REFER TO 50.0 FOR TYPICAL STRUCTURAL NOTES & SCHEDULES

SD2.0 & SD2.1 REFERS TO SD2.0J & SD2.1J FOR 1-JOIST FLOOR FRAMING OR SD2.0T & SD2.1T FOR TRUSS FLOOR FRAMING


SD2.1J/SD2.1T REFERS TO SD2.1JA/SD2.1TA FOR LVL/PSL/LSL BEAMS OR SD2.1JB/SD2.1TB FOR FLITCH BEAMS OR SD2.1JC/SD2.1TC FOR STEEL BEAMS

**MULHERN+KULCZYNSKI**  
RESIDENTIAL STRUCTURAL ENGINEERING  
300 Peninsula Ave. Building 4 - Asheville, NC 28806  
919.688.8888 - mulhern@mulhern-k.com  
N.C. #C-2625

**ENGINEERED BEAM MATERIAL SCHEDULE**

BEAM NUMBER	LVL OPTION	PSL OPTION	LSL OPTION	FLITCH OPTION	STEEL OPTION
001	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	W12x14 - F
002	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	W12x14 - F
003	(2) 3/4" x 18" - FB or (2) 3/4" x 20" - FB	3/4" x 18" - FB	N/A	(2) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - FB	W12x26 - F
004	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	W12x14 - F
005	(2) 3/4" x 11 1/2" - H cont.	3/4" x 11 1/2" - H cont.	(2) 3/4" x 11 1/2" - H cont.	(2) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - H cont.	N/A
005A	(2) 3/4" x 14" - H cont.	3/4" x 14" - H cont.	N/A	(2) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - H cont.	N/A
006	(1) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	W12x14 - F
007	(2) 3/4" x 11 1/2" - D	3/4" x 11 1/2" - D	(2) 3/4" x 11 1/2" - D	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - D	W10x12 - D
008	(2) 3/4" x 16" - H cont.	3/4" x 16" - H cont.	(2) 3/4" x 16" - H cont.	(2) 2x12 + (2) 3/4" x 10" STEEL FLITCH PLATES - H cont.	N/A
009	(2) 3/4" x 9" - F	3/4" x 9" - F	(2) 3/4" x 9" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - F	W6x10 - F
010	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	W12x14 - F
011	(2) 3/4" x 14" - F	3/4" x 14" - F	(2) 3/4" x 14" - F	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - FB	W12x14 - F
012	(2) 3/4" x 11 1/2" - D	3/4" x 11 1/2" - D	(2) 3/4" x 11 1/2" - D	(2) 2x12 + (1) 1/2" x 10" STEEL FLITCH PLATES - D	W10x12 - D

\*\* BEAM NOTATION:  
 - "F" INDICATES FLUSH BEAM  
 - "FT" INDICATES FLUSH TOP BEAM  
 - "FB" INDICATES FLUSH BOTTOM BEAM  
 - "D" INDICATES DROPPED BEAM  
 - "H" INDICATES DROPPED OPENING HEADER  
 \*\* REFER TO DETAIL D/SD2.0 FOR TYPICAL FLITCH BEAM CONNECTIONS  
 \*\* REFER TO DETAIL E/SD2.0 FOR TYPICAL STEEL BEAM CONNECTIONS  
 \*\* FOR FLUSH TOP BEAMS PROVIDE 2X STACKED PLATES BENEATH BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.  
 \*\* FOR FLUSH BOTTOM BEAMS PROVIDE 2X STACKED PLATES ATOP BEAM AS REQ'D. FASTEN PLATES IN SUCCESSION W/ (2) 3"x0.120" NAILS @ 8" O.C.



**5 PARTIAL SECOND FLOOR FRAMING PLAN  
 OPTIONAL EXT. BREAKFAST**  
 SCALE: 1/8"=1'-0" ELEV. #1 SHOWN - ALL ELEV. SIM.



OPTION FRAMING PLANS  
**DRAYTON**  
 RALEIGH, NC

sheet LEFT HAND  
**S5.0T**








REFER TO SO.O FOR  
TYPICAL STRUCTURAL NOTES  
& SCHEDULES

LEGEND	
• [Symbol]	INTERIOR BEARING WALL
• [Symbol]	BEARING WALL ABOVE
• [Symbol]	BEAM / HEADER
• [Symbol]	INDICATES SHEAR WALL & EXTENT
• [Symbol]	EXTENT OF OVERFRAMING
JL	METAL HANGER
• [Symbol]	INDICATES POST ABOVE. PROVIDE SOLID BLOCKING UNDER POST OR JAMB ABOVE.
▶ [Symbol]	INDICATES HOLD-DOWN OR STRAP. REFER TO SCHEDULE.




**MULHERN+KUL**  
RESIDENTIAL STRUCTURAL ENGINEERING  
3800 Southside Ave, Building 4 - Jackson, NC 28586  
919-455-8888 - mulhern@mulhernkull.com  
N.C. #3305



MJK project number:  
126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21


REVISIONS:	
date:	initial:



**3 PARTIAL ROOF FRAMING PLAN**  
SCALE: 1/8"=1'-0" ELEVATION #5  
ADD'L INFO SEE ELEV. 2

ROOF FRAMING PLANS  
DRAYTON  
RALEIGH, NC

LEFT HAND  
**S4.1**



**MULHERN+KULL**  
REGISTERED STRUCTURAL ENGINEERING  
3800 Middlebrook Building - Raleigh, NC 27608  
919.876.8888 - mulhern+kull.com  
N.C. #3-3025




M&K project number:  
**126-21020**  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21


REVISIONS:  
date: initial




FOUNDATION DETAILS  
DRAYTON  
RALEIGH, NC




**1 TYPICAL SLAB ON GRADE PERIMETER FOOTING**  
SCALE: 3/8"=1'-0"




**2 TYPICAL SLAB ON GRADE PERIMETER FOOTING**  
SCALE: 3/8"=1'-0" W/ BRICK VENEER




**3 TYPICAL MONOLITHIC INTERIOR GARAGE FOOTING**  
SCALE: 3/8"=1'-0"




**4 TYPICAL SLAB ON GRADE GARAGE PERIMETER FOOTING**  
SCALE: 3/8"=1'-0"




**5 TYPICAL SLAB ON GRADE GARAGE PERIMETER FOOTING**  
SCALE: 3/8"=1'-0" W/ BRICK VENEER




**6 TYPICAL SLAB ON GRADE GARAGE ENTRY @ PERIMETER FOOTING**  
SCALE: 3/8"=1'-0"




**7 TYPICAL SLAB ON GRADE GARAGE ENTRY @ PERIMETER FOOTING**  
SCALE: 3/8"=1'-0" W/ BRICK VENEER




**8 TYPICAL SLAB ON GRADE PERIMETER FOOTING @ PORCH/PATIO**  
SCALE: 3/8"=1'-0"




**9 TYPICAL SLAB ON GRADE PERIMETER FOOTING @ PORCH/PATIO**  
SCALE: 3/8"=1'-0" W/ BRICK VENEER



**10 TYPICAL FOOTING @ PORCH SLAB**  
SCALE: 3/8"=1'-0"




**11 TYPICAL THICKENED SLAB @ INTERIOR BEARING WALL**  
SCALE: 3/8"=1'-0"



**A TYPICAL CONTROL JOINT**  
SCALE: 3/8"=1'-0"  
LOCATE @ 15'-0" o.c. MAX OR CORNERS WHERE CRACKS ARE LIKELY TO DEVELOP

FILE: RH - Drayton - Structural DATE: 11/23/2021 12:45 PM



**MULHERN+KULL**  
RESIDENTIAL STRUCTURAL ENGINEERING  
3200 Middleburg Road, Raleigh, NC 27605  
919.876.8888 • mulhern+kull.com  
N.C. #0-3025




MAX project number:  
126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21

REVISIONS:  
date: initial




FRAMING DETAILS  
DRAYTON  
RALEIGH, NC


SHEET  
SD2.0J




**A1** TYPICAL SHEAR TRANSFER DETAIL @ ROOF  
SCALE: 3/8"=1'-0"  
HEEL HEIGHT LESS THAN 4 1/2"  
NO BLOCKING REQ'D




**A2** TYPICAL SHEAR TRANSFER DETAIL @ ROOF  
SCALE: 3/8"=1'-0"  
HEEL HEIGHT BETWEEN 4 1/2" - 16"  
BLOCKING REQ'D




**A3** TYPICAL SHEAR TRANSFER DETAIL @ RAISED HEEL TRUSS  
SCALE: 3/8"=1'-0"  
HEEL HEIGHT UP TO 48" MAX.




**B** TYPICAL GABLE END DETAIL  
SCALE: 3/8"=1'-0"




**C** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ EXTERIOR WALL  
SCALE: 3/8"=1'-0"




**D** TYPICAL FLITCH BEAM CONNECTION DETAIL  
SCALE: 3/4"=1'-0"




**E** TYPICAL STEEL BEAM CONNECTION DETAIL  
SCALE: 3/4"=1'-0"



**F1** TYPICAL HOLD DOWN INSTALLATION  
SCALE: N.T.S.




**F2** TYPICAL CMU FOUNDATION HOLD-DOWN INSTALLATION  
SCALE: N.T.S. (CORNER SHOWN - APPLICABLE TO ALL CONDITIONS)



**G** DECK CONNECTION DETAIL  
SCALE: 3/4"=1'-0"

FILE: RH - Drayton - Structurals DATE: 11/23/2021 12:47 PM






MULHERN+KUL...  
RESIDENTIAL STRUCTURAL ENGINEERING  
10755...  
N.C. #3025




MAX project number:  
126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21  
REVISIONS:  
date: initial




FRAMING DETAILS  
DRAYTON  
RALEIGH, NC




1 SHEAR TRANSFER DETAIL @ INTERIOR SHEARWALL BELOW  
SCALE: 3/4"=1'-0" PARALLEL FRAMING




2 SHEAR TRANSFER DETAIL @ INT. SHEARWALL ABOVE & BELOW  
SCALE: 3/4"=1'-0" EDGE OF FRAMING




3 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




4 DETAIL @ SHED ROOF  
SCALE: 3/8"=1'-0"




5 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




6 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




7 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"




8 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"




9 TYPICAL SHEAR TRANSFER DETAIL BETWEEN GARAGE BAYS  
SCALE: 3/4"=1'-0"




13 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




**MULHERN+KUL**  
RESIDENTIAL STRUCTURAL ENGINEERING  
3800 Bechtold Ave. Building 4 - Raleigh, NC 27608  
919.876.8888 - mulhernkull.com  
N.C. #3-3025




**1** SHEAR TRANSFER DETAIL @ INTERIOR SHEARWALL BELOW  
SCALE: 3/4"=1'-0"  
PARALLEL FRAMING




**2** SHEAR TRANSFER DETAIL @ INT. SHEARWALL ABOVE & BELOW  
SCALE: 3/4"=1'-0"  
EDGE OF FRAMING




**4** DETAIL @ SHED ROOF  
SCALE: 3/8"=1'-0"




**5** SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




**6** SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"



**7** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"



**8** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"



**9** TYPICAL SHEAR TRANSFER DETAIL BETWEEN GARAGE BAYS  
SCALE: 3/4"=1'-0"

FILE: RH - Drayton - Structurals DATE: 11/23/2021 12:48 PM

MAX project number:  
126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21


REVISIONS:  
date: initial




FRAMING DETAILS  
DRAYTON  
RALEIGH, NC

SHEET  
SD2.1BJ







**MULHERN+KUL**  
RESIDENTIAL STRUCTURAL ENGINEERING  
3800 Peachtree Dunwoody Ave., Suite 1000, Atlanta, GA 30328  
404.252.8888 • mulhernk.com  
N.C. #3-3025




**1** SHEAR TRANSFER DETAIL @ INTERIOR SHEARWALL BELOW  
SCALE: 3/4"=1'-0"  
PARALLEL FRAMING




**2** SHEAR TRANSFER DETAIL @ INT. SHEARWALL ABOVE & BELOW  
SCALE: 3/4"=1'-0"  
EDGE OF FRAMING




**4** DETAIL @ SHED ROOF  
SCALE: 3/8"=1'-0"




**5** SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




**6** SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"



**7** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"



**8** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"




**9** TYPICAL SHEAR TRANSFER DETAIL BETWEEN GARAGE BAYS  
SCALE: 3/4"=1'-0"

MAX project number: 126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21

REVISIONS:  
date: initial



FRAMING DETAILS  
DRAYTON  
RALEIGH, NC



**MULHERN+KUL**  
RESIDENTIAL STRUCTURAL ENGINEERING  
3200 Southway Ave. Raleigh, NC 27607  
919.876.8888 • mulhernk.com  
N.C. #0-3025




M&K project number:  
**126-21020**  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21

REVISIONS:  
date: initial




FRAMING DETAILS  
**DRAYTON**  
RALEIGH, NC


SHEET  
**SD2.0T**




**A1** TYPICAL SHEAR TRANSFER DETAIL @ ROOF  
SCALE: 3/8"=1'-0"  
HEEL HEIGHT LESS THAN 4 1/2"  
NO BLOCKING REQ'D




**A2** TYPICAL SHEAR TRANSFER DETAIL @ ROOF  
SCALE: 3/8"=1'-0"  
HEEL HEIGHT BETWEEN 4 1/2" - 16"  
BLOCKING REQ'D




**A3** TYPICAL SHEAR TRANSFER DETAIL @ RAISED HEEL TRUSS  
SCALE: 3/8"=1'-0"  
HEEL HEIGHT UP TO 48" MAX.




**B** TYPICAL GABLE END DETAIL  
SCALE: 3/8"=1'-0"




**C1** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ EXTERIOR WALL  
SCALE: 3/8"=1'-0"  
PARALLEL TRUSS




**C2** TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ EXTERIOR WALL  
SCALE: 3/8"=1'-0"  
PERPENDICULAR TRUSS




**D** TYPICAL FLITCH BEAM CONNECTION DETAIL  
SCALE: 3/4"=1'-0"



**E** TYPICAL STEEL BEAM CONNECTION DETAIL  
SCALE: 3/4"=1'-0"



**F1** TYPICAL HOLD DOWN INSTALLATION  
SCALE: N.T.S.




**F2** TYPICAL CMU FOUNDATION HOLD-DOWN INSTALLATION  
SCALE: N.T.S.  
(CORNER SHOWN - APPLICABLE TO ALL CONDITIONS)









MULHERN+KULL  
RESIDENTIAL STRUCTURAL ENGINEERING  
10000 W. 11th St., Suite 100  
Charlotte, NC 28203  
Tel: 704-305-3025




MAX project number:  
126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21

REVISIONS:  
date: initial




FRAMING DETAILS  
DRAYTON  
RALEIGH, NC


Sheet:  
SD2.1BT




1 SHEAR TRANSFER DETAIL @ INTERIOR SHEARWALL BELOW  
SCALE: 3/4"=1'-0" PARALLEL FRAMING




2 SHEAR TRANSFER DETAIL @ INT. SHEARWALL ABOVE & BELOW  
SCALE: 3/4"=1'-0" EDGE OF FRAMING




3 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




4 DETAIL @ SHED ROOF  
SCALE: 3/8"=1'-0"




5 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




6 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




7 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"



8 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"




9 TYPICAL SHEAR TRANSFER DETAIL BETWEEN GARAGE BAYS  
SCALE: 3/4"=1'-0"




13 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"


FILE: RH - Drayton - Structurals DATE: 11/23/2021 12:48 PM




1 SHEAR TRANSFER DETAIL @ INTERIOR SHEARWALL BELOW  
SCALE: 3/4"=1'-0"  
PARALLEL FRAMING




2 SHEAR TRANSFER DETAIL @ INT. SHEARWALL ABOVE & BELOW  
SCALE: 3/4"=1'-0"  
EDGE OF FRAMING




3 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




4 DETAIL @ SHED ROOF  
SCALE: 3/8"=1'-0"




5 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




6 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"




7 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"



8 TYPICAL SHEAR TRANSFER DETAIL BETWEEN FLOORS @ INTERIOR WALL  
SCALE: 3/4"=1'-0"



9 TYPICAL SHEAR TRANSFER DETAIL BETWEEN GARAGE BAYS  
SCALE: 3/4"=1'-0"



13 SHEAR TRANSFER DETAIL @ EXTERIOR SHEARWALL ABOVE  
SCALE: 3/4"=1'-0"

MULHERN+KULP  
RESIDENTIAL STRUCTURAL ENGINEERING  
10000 W. HARRIS LANE, SUITE 100, RALEIGH, NC 27617  
TEL: 919-305-3025


M&K project number: 126-21020  
project mgr: JTR  
drawn by: KL  
issue date: 06-12-21  
REVISIONS:  
date: initial



FRAMING DETAILS  
DRAYTON  
RALEIGH, NC

SD2.1CT






**MULHERN+KUL**  
 RESIDENTIAL STRUCTURAL ENGINEERING  
 3800 Shallowford Ave., Raleigh, NC 27609  
 919.876.8888 • mulhern@mulhernkull.com  
 N.C. Lic. #E-3025

MAX project number:  
 126-21020  
 project mgr: JTR  
 drawn by: KL  
 issue date: 06-12-21




FRAMING DETAILS  
 DRAYTON  
 RALEIGH, NC


SD2.2




**OUTSIDE ELEVATION**




**SECTION A-A THROUGH PIER**




**OUTSIDE ELEVATION**




**SECTION A-A THROUGH PIER**




**INSIDE ELEVATION**



**PLAN VIEW OF CORNER DETAIL**



**INSIDE ELEVATION**



**PLAN VIEW OF CORNER DETAIL**


**1** TWO SIDED GARAGE PORTAL FRAME BRACING ELEVATION ON CONCRETE STEM  
 SCALE: N.T.S.

**2** TWO SIDED GARAGE PORTAL FRAME BRACING ELEVATION ON CMU STEM  
 SCALE: N.T.S.

ALTERNATIVES TO 1/2" DIA. ANCHOR BOLT:  
 1) 1/2" DIA. x 6" LONG SIMPSON TITEN HD  
 2) 1/2" DIA. THREADED ROD EPOXY SET  
 W/ 4 1/2" EMBED. (MIN) UTILIZING HILTI HY200 EPOXY ANCHORING SYSTEM (OR EQUAL)

ALTERNATIVE TO 1/2" DIA. ANCHOR BOLT:  
 1) 1/2" DIA. THREADED ROD EPOXY SET  
 W/ 4 1/2" EMBED. (MIN) UTILIZING HILTI HY200 EPOXY ANCHORING SYSTEM (OR EQUAL)

FILE: RH - Drayton - Structural DATE: 11/23/2021 12:49 PM




**MULHERN+KUL**  
 RESIDENTIAL STRUCTURAL ENGINEERING  
 3800 Southside Ave. Building 4 - Jackson, NC 28586  
 919-455-8888 - mulhern@mulhernkull.com  
 N.C. #33025




M&K project number:  
 126-21020  
 project mgr: JTR  
 drawn by: KL  
 issue date: 06-12-21

REVISIONS:	
date:	initial:



**TYPICAL CONNECTION  
 DETAIL @ 2nd FLOOR DECK**



**TYPICAL PORCH  
 POST CONNECTION DETAIL**

SCALE: NONE  
 SLAB ON GRADE SHOWN (S.M. @ GRAVE & BSMT.)


FRAMING DETAILS  
 DRAYTON  
 RALEIGH, NC

**SD3.0**





Truss Connector Total List		
Qty	Product	Manuf
19	HTU26	Simpson
1	HTU26-2	Simpson
4	LUS26	Simpson



**ROOF LAYOUT**  
DRAWING SCALE : NTS

PROJECT NUMBER <b>22060002</b>
SHEET NUMBER <b>1 / 1</b>

REVISIONS	
DATE	BY
6-6-22	ND

<b>DRB GROUP</b>
<b>DRAYTON 5 - 77 FARM AT NEILLS CREEK</b>
<b>ROOF TRUSS LAYOUT</b>

