


Job 72274660	Truss F200	Truss Type Truss	Qty 1	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:22

Page: 1

ID:wWHL3JJHSrPsRLF_S9UFi8ztVLu-5REdmMPRA?ZknlE90JYJuyr4?1Bw32IRtVUIhqz5kyR



Loading	(psf)	Spacing	1-7-3	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.64	Vert(LL)	-0.29	16-17	>803	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.76	Vert(CT)	-0.41	16-17	>584	360	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.51	Horz(CT)	0.07	12	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 101 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS (lb/size) 12=863/0-3-8, (min. 0-1-8), 20=863/0-3-8, (min. 0-1-8)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-2224/0, 3-4=-3073/0, 4-5=-3515/0, 5-6=-3515/0, 6-7=-3515/0, 7-8=-3515/0, 8-9=-3070/0, 9-10=-2224/0
 BOT CHORD 19-20=0/1666, 18-19=0/2752, 17-18=0/3373, 16-17=0/3515, 15-16=0/3375, 14-15=0/2752, 13-14=0/2752, 12-13=0/1666
 WEBS 7-16=-275/25, 2-20=-1829/0, 2-19=0/776, 3-19=-735/0, 3-18=0/447, 4-18=-417/0, 4-17=-122/493, 10-12=-1829/0, 10-13=0/777, 9-13=-733/0, 9-15=0/443, 8-15=-427/0, 8-16=-118/511

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) All plates are 3x3 MT20 unless otherwise indicated.
 - 4) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72274660	Truss F201	Truss Type Truss	Qty 7	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:23

Page: 1

ID: PirjHfKvD9Xj3VqA0s?UFLztVLT-Zdo?ziQ3KHbOvpLZ03YRAOB8QWmoUWa69DIDGz5kyQ



Scale = 1:56.5

Plate Offsets (X, Y):	[17:0-2-0,Edge], [19:0-1-8,Edge], [28:0-2-0,Edge]											
Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.87	Vert(LL)	-0.28	25-26	>860	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.81	Vert(CT)	-0.38	25-26	>626	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.54	Horz(CT)	0.06	20	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 141 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.1(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing, Except:
WEBS	2x4 SP No.3(flat)		6-0-0 oc bracing: 19-20,18-19,17-18.
OTHERS	2x4 SP No.3(flat)		

REACTIONS	(lb/size)	17=163/0-3-8, (min. 0-1-8), 20=1481/0-3-8, (min. 0-1-8), 28=786/0-3-8, (min. 0-1-8)
	Max Uplift	17=-74 (LC 3)
	Max Grav	17=282 (LC 4), 20=1481 (LC 1), 28=795 (LC 10)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-2005/0, 3-4=-2724/0, 4-5=-2955/0, 5-6=-2955/0, 6-7=-2955/0, 7-8=-2318/0, 8-9=-1344/0, 9-10=-1344/0, 10-11=0/1272, 11-12=0/1267, 12-13=-360/370, 13-14=-360/370, 14-15=-360/370
BOT CHORD	27-28=0/1518, 26-27=0/2466, 25-26=0/2942, 24-25=0/2955, 23-24=0/2705, 22-23=0/1941, 21-22=0/1941, 20-21=0/708, 19-20=-792/44, 18-19=-370/360, 17-18=-113/260
WEBS	6-24=-334/0, 13-19=-335/0, 15-17=-343/149, 15-18=-350/136, 2-28=-1666/0, 2-27=0/677, 3-27=-641/0, 3-26=0/360, 4-26=-303/0, 4-25=-239/319, 10-20=-1953/0, 10-21=0/904, 8-21=-853/0, 8-23=0/544, 7-23=-563/0, 7-24=0/628, 12-20=-742/0, 12-19=0/727

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - All plates are 3x3 MT20 unless otherwise indicated.
 - Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 74 lb uplift at joint 17.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-0-0 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - CAUTION, Do not erect truss backwards.



Job 72274660	Truss F202	Truss Type Truss	Qty 1	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:23

Page: 1

ID:tuP5U_LXzTfahfPMaaWjnZztVLs-Zdo?ziQ3KlhbOvpLZ03YRAOBrQWDoUMa69DIDGz5kyQ




Plate Offsets (X, Y): [18:0-2-0,Edge], [32:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.89	Vert(LL)	-0.27	29-30	>879	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.82	Vert(CT)	-0.37	29-30	>639	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.55	Horz(CT)	0.05	24	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 147 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS All bearings 0-3-8.
 (lb) - Max Uplift All uplift 100 (lb) or less at joint(s) except 18=319 (LC 3)
 Max Grav All reactions 250 (lb) or less at joint(s) 18 except 21=597 (LC 14), 24=1290 (LC 13), 32=770 (LC 14)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
 TOP CHORD 2-3=-1922/0, 3-4=-2593/0, 4-5=-2744/0, 5-6=-2744/0, 6-7=-2744/0, 7-8=-2033/0, 8-9=-1008/0, 9-10=-1008/0, 10-11=0/1501, 11-12=0/1498, 12-13=0/1205, 13-14=0/1045, 14-15=0/1045, 15-16=0/488
 BOT CHORD 31-32=0/1462, 30-31=0/2358, 29-30=0/2780, 28-29=0/2744, 27-28=0/2452, 26-27=0/1630, 25-26=0/1630, 24-25=0/351, 23-24=-1205/0, 22-23=-1205/0, 21-22=-1205/0, 20-21=-488/0, 19-20=-488/0, 18-19=-488/0
 WEBS 6-28=-342/0, 13-21=-136/268, 12-24=-502/0, 15-21=-821/0, 16-18=0/640, 15-20=0/254, 2-32=-1605/0, 2-31=0/639, 3-31=-606/0, 3-30=0/327, 4-30=-265/0, 4-29=-256/282, 10-24=-1996/0, 10-25=0/918, 8-25=-871/0, 8-27=0/564, 7-27=-588/0, 7-28=0/644

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x3 MT20 unless otherwise indicated.
 - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 318 lb uplift at joint 18.
 - 4) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



Job 72274660	Truss F203	Truss Type Truss	Qty 1	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:24

Page: 1

ID:tuP5U_LXzTfahfPMaaWjnZztVLs-2qMNA2Qi5cpR03NX7kanzNxMNqrlXxxkKpzsliz5kyP




Plate Offsets (X, Y): [15:0-2-0,Edge], [26:0-2-0,Edge]

Loading	(psf)	Spacing	1-7-3	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.84	Vert(LL)	-0.28	23-24	>850	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.80	Vert(CT)	-0.38	23-24	>619	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.53	Horz(CT)	0.06	18	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 126 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 2-2-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing, Except: 6-0-0 oc bracing: 17-18,16-17,15-16.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS	(lb/size)
	15=-43/0-3-6, (min. 0-1-8), 18=1364/0-3-8, (min. 0-1-8), 26=805/0-3-8, (min. 0-1-8)
Max Uplift	15=-183 (LC 3)
Max Grav	15=129 (LC 4), 18=1364 (LC 1), 26=808 (LC 10)

FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD	2-3=-2045/0, 3-4=-2790/0, 4-5=-3060/0, 5-6=-3060/0, 6-7=-3060/0, 7-8=-2459/0, 8-9=-1511/0, 9-10=-1511/0, 10-11=0/930, 11-12=0/927, 12-13=-53/399
BOT CHORD	25-26=0/1546, 24-25=0/2519, 23-24=0/3023, 22-23=0/3060, 21-22=0/2831, 20-21=0/2093, 19-20=0/2093, 18-19=0/894, 17-18=-399/53, 16-17=-399/53, 15-16=-399/53
WEBS	6-22=-316/0, 12-18=-797/0, 13-15=-66/526, 2-26=-1697/0, 2-25=0/695, 3-25=-659/0, 3-24=0/376, 4-24=-324/0, 4-23=-203/365, 10-18=-1927/0, 10-19=0/867, 8-19=-818/0, 8-21=0/517, 7-21=-526/0, 7-22=0/591

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x3 MT20 unless otherwise indicated.
 - 3) Provide mechanical connection (by others) of truss to bearing plate capable of withstanding 183 lb uplift at joint 15.
 - 4) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 5) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 6) CAUTION, Do not erect truss backwards.




Job 72274660	Truss F205	Truss Type Truss	Qty 2	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:24

Page: 1

ID:L4zUiKM9kmmRlp_Z7H2yKmtzVLR-2qMNA2Qi5cpR03NX7kantzNRRNqvVX?qtKpzsliz5kyP



Scale = 1:51.3

Plate Offsets (X, Y):		[17:0-2-0,Edge], [27:0-1-8,Edge], [28:0-2-0,Edge]										
Loading	(psf)	Spacing	1-7-3	CSI		DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.52	Vert(LL)	-0.12	27-28	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.56	Vert(CT)	-0.19	27-28	>773	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.28	Horz(CT)	0.02	17	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 127 lb	FT = 20%F, 11%E

LUMBER
TOP CHORD 2x4 SP No.2(flat)
BOT CHORD 2x4 SP No.2(flat)
WEBS 2x4 SP No.3(flat)
OTHERS 2x4 SP No.3(flat)

BRACING
TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD Rigid ceiling directly applied or 6-0-0 oc bracing.

REACTIONS All bearings 0-3-8.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 17 except 20=532 (LC 11), 24=943 (LC 16), 28=516 (LC 14)

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.
TOP CHORD 2-3=-1259/0, 3-4=-1259/0, 4-5=-1259/0, 5-6=-692/0, 6-7=0/473, 7-8=0/473, 8-9=0/473, 9-10=-381/74, 10-11=-381/74, 11-12=-381/74
BOT CHORD 27-28=0/907, 26-27=0/1259, 25-26=0/1040, 24-25=0/334, 21-22=-74/381
WEBS 6-24=-808/0, 6-25=0/514, 5-25=-509/0, 5-26=0/421, 9-24=-458/0, 9-22=0/356, 12-20=-368/0, 14-20=-336/0, 2-28=-994/0, 2-27=0/389

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are 3x3 MT20 unless otherwise indicated.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.
 - 5) CAUTION, Do not erect truss backwards.




Job 72274660	Truss F206	Truss Type Truss	Qty 12	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	-----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:25

Page: 1

ID:L4zUikM9kmmRlp_Z7H2yKmntvLr-2qMNA2Qi5cpR03NX7kanzNxPjqrSXyjkKpzsliz5kyP



Scale = 1:48.1

Plate Offsets (X, Y):	[16:0-1-8,Edge], [17:0-1-8,Edge]
-----------------------	----------------------------------

Loading	(psf)	Spacing	1-4-0	CSI	DEFLL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	0.69	Vert(LL)	-0.39	17	>686	480	MT18HS 244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.82	Vert(CT)	-0.53	17-18	>498	360	MT20 244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.48	Horz(CT)	0.08	12	n/a	n/a	
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 111 lb FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 5-10-1 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS	(lb/size)	12=809/ Mechanical, (min. 0-1-8), 20=809/0-3-8, (min. 0-1-8)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-2135/0, 3-4=-3038/0, 4-5=-3705/0, 5-6=-3705/0, 6-7=-3705/0, 7-8=-3030/0, 8-9=-3030/0, 9-10=-2137/0	
BOT CHORD	19-20=0/1580, 18-19=0/2668, 17-18=0/3382, 16-17=0/3705, 15-16=0/3376, 14-15=0/3376, 13-14=0/2668, 12-13=0/1581	
WEBS	2-20=-1736/0, 2-19=0/771, 3-19=-741/0, 3-18=0/515, 4-18=-479/0, 4-17=-38/642, 10-12=-1736/0, 10-13=0/774, 9-13=-739/0, 9-14=0/503, 7-14=-481/0, 7-16=-26/643	

- NOTES**
- 1) Unbalanced floor live loads have been considered for this design.
 - 2) All plates are MT20 plates unless otherwise indicated.
 - 3) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 4) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



Job 72274660	Truss F207	Truss Type Truss	Qty 5	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:25

Page: 1

ID:L4zUiKM9kmmRlp_Z7H2yKmtzVLR-W0wOORKswxleDyjhr50WbTZJEBhGPotZTiPi9z5kyO




Plate Offsets (X, Y): [16:0-1-8,Edge], [17:0-1-8,Edge]

Loading	(psf)	Spacing	1-4-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.70	Vert(LL)	-0.40	16-17	>669	480	MT18HS	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.82	Vert(CT)	-0.55	16-17	>488	360	MT20	244/190
BCLL	0.0	Rep Stress Incr	YES	WB	0.49	Horz(CT)	0.09	12	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH								
											Weight: 112 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 5-9-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.1(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS	(lb/size)	12=819/0-3-8, (min. 0-1-8), 20=819/0-3-8, (min. 0-1-8)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-2170/0, 3-4=-3092/0, 4-5=-3805/0, 5-6=-3805/0, 6-7=-3805/0, 7-8=-3091/0, 8-9=-3091/0, 9-10=-2170/0	
BOT CHORD	19-20=0/1604, 18-19=0/2713, 17-18=0/3448, 16-17=0/3805, 15-16=0/3448, 14-15=0/3448, 13-14=0/2713, 12-13=0/1604	
WEBS	2-20=-1761/0, 2-19=0/787, 3-19=-755/0, 3-18=0/527, 4-18=-496/0, 4-17=-23/677, 10-12=-1761/0, 10-13=0/787, 9-13=-755/0, 9-14=0/526, 7-14=-496/0, 7-16=-21/677	

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - All plates are MT20 plates unless otherwise indicated.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.



Job 72274660	Truss F208	Truss Type Truss	Qty 2	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:25

Page: 1

ID:L4zUiKM9kmmRlp_Z7H2yKmztVLR-W0wIOORKswxleDyjhR50WbTdrEERGSxtZTiPI9z5kyO




Plate Offsets (X, Y): [9:0-2-0,Edge], [14:0-2-0,Edge]

Loading	(psf)	Spacing	1-4-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.41	Vert(LL)	-0.11	12-13	>999	480	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.58	Vert(CT)	-0.14	12-13	>999	360		
BCLL	0.0	Rep Stress Incr	YES	WB	0.29	Horz(CT)	0.03	9	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-SH							Weight: 74 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS	(lb/size)	9=524/ Mechanical, (min. 0-1-8), 14=524/0-3-8, (min. 0-1-8)
FORCES	(lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.	
TOP CHORD	2-3=-1228/0, 3-4=-1552/0, 4-5=-1552/0, 5-6=-1552/0, 6-7=-920/0	
BOT CHORD	13-14=0/970, 12-13=0/1455, 11-12=0/1552, 10-11=0/1257, 9-10=0/563	
WEBS	2-14=-1064/0, 2-13=0/359, 3-13=-316/0, 3-12=-39/304, 7-9=-748/0, 7-10=0/496, 6-10=-469/0, 6-11=0/454	

- NOTES**
- Unbalanced floor live loads have been considered for this design.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.




Job 72274660	Truss K200	Truss Type Truss	Qty 1	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:25

Page: 1

ID:L4zUiKM9kmmRlp_Z7H2yKmztVLR-W0wOORkswxleDyjhR50WbTi?ENLGW?tZTiPI9z5kyO



Scale = 1:48.1

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-R						Weight: 98 lb	FT = 20%F, 11%E

LUMBER	BRACING
TOP CHORD 2x4 SP No.2(flat)	TOP CHORD Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD 2x4 SP No.2(flat)	BOT CHORD Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS 2x4 SP No.3(flat)	
OTHERS 2x4 SP No.3(flat)	

REACTIONS All bearings 22-5-0.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 20, 21, 22, 23, 24, 25, 26, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72274660	Truss K201	Truss Type Truss	Qty 1	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:25

Page: 1

ID:pHXsvgNnV4vIwzZlh?ZBs_ztVLq-W0wOORkswxleDjyhR50WbTi?ENLgW?tZTiP9z5kyO



Scale = 1:36.5

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP	
TCLL	40.0	Plate Grip DOL	1.00	TC	0.08	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	0.01	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	0.03	Horiz(TL)	n/a	-	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-R							Weight: 65 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS All bearings 14-8-0.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- 1) All plates are 1.5x3 MT20 unless otherwise indicated.
 - 2) Gable requires continuous bottom chord bearing.
 - 3) Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - 4) Gable studs spaced at 1-4-0 oc.
 - 5) This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - 6) Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.




Job 72274660	Truss K202	Truss Type Truss	Qty 1	Ply 1	PRO BLDRS / SMITHFIELD PLAN 2ND FL Job Reference (optional)
-----------------	---------------	---------------------	----------	----------	--

UFP Mid Atlantic LLC, 5631 S. NC 62, Burlington, NC, Micah Clayton

Run: 8.51 S Oct 22 2021 Print: 8.510 S Oct 22 2021 MiTek Industries, Inc. Thu Jun 16 10:53:25

Page: 1

ID:19M26uvPLEN1KWFa8389aKzChMs-W0wIOORkswxleDjhr50WbTieEN8GWxtZTI9z5kyO



Scale = 1:26.9

Loading	(psf)	Spacing	2-0-0	CSI	DEFL	in	(loc)	l/defl	L/d	PLATES	GRIP
TCLL	40.0	Plate Grip DOL	1.00	TC	Vert(LL)	n/a	-	n/a	999	MT20	244/190
TCDL	10.0	Lumber DOL	1.00	BC	Vert(TL)	n/a	-	n/a	999		
BCLL	0.0	Rep Stress Incr	YES	WB	Horiz(TL)	0.00	8	n/a	n/a		
BCDL	5.0	Code	IRC2015/TPI2014	Matrix-R						Weight: 38 lb	FT = 20%F, 11%E

LUMBER		BRACING	
TOP CHORD	2x4 SP No.2(flat)	TOP CHORD	Structural wood sheathing directly applied or 6-0-0 oc purlins, except end verticals.
BOT CHORD	2x4 SP No.2(flat)	BOT CHORD	Rigid ceiling directly applied or 10-0-0 oc bracing.
WEBS	2x4 SP No.3(flat)		
OTHERS	2x4 SP No.3(flat)		

REACTIONS All bearings 8-3-8.
(lb) - Max Grav All reactions 250 (lb) or less at joint(s) 8, 9, 10, 11, 12, 13, 14

FORCES (lb) - Max. Comp./Max. Ten. - All forces 250 (lb) or less except when shown.

- NOTES**
- All plates are 1.5x3 MT20 unless otherwise indicated.
 - Gable requires continuous bottom chord bearing.
 - Truss to be fully sheathed from one face or securely braced against lateral movement (i.e. diagonal web).
 - Gable studs spaced at 1-4-0 oc.
 - This truss is designed in accordance with the 2015 International Residential Code sections R502.11.1 and R802.10.2 and referenced standard ANSI/TPI 1.
 - Recommend 2x6 strongbacks, on edge, spaced at 10-00-00 oc and fastened to each truss with 3-10d (0.131" X 3") nails. Strongbacks to be attached to walls at their outer ends or restrained by other means.



This design is based upon parameters shown, and is for an individual building component to be installed and loaded vertically. Applicability of design parameters and proper incorporation of component is responsibility of the Building Designer. Building Designer shall verify all design information on this sheet for conformance with conditions and requirements of the specific building and governing codes and ordinances. Building Designer accepts responsibility for the correctness or accuracy of the design information as it may relate to a specific building. Certification is valid only when truss is fabricated by a UFPI plant. Bracing shown is for lateral support of truss members only and does not replace erection and permanent bracing. Refer to Building Component Safety Information (BCSI) for general guidance regarding storage, erection and bracing available from SBCA and Truss Plate Institute.

