




**FRONT ELEVATION**

Scale: 1/4" = 1'0"

9'0" CEILING HEIGHT FIRST FLOOR  
7'6" Header Height 1st Floor  
8'0" CEILING HEIGHT SECOND FLOOR  
7'0" Header height 2nd Floor  
FRAME WINDOWS TO HEADER HEIGHT



**LEFT ELEVATION**

Scale: 1/8" = 1'0"




**RIGHT ELEVATION**

Scale: 1/8" = 1'0"





**REAR ELEVATION**

Scale: 1/8" = 1'0"



**FOUNDATION PLAN**  
Scale: 1/4" = 1'0"



1. 15# FELT UNDERLAYMENT UNDER COMPOSITION SHINGLES.
2. ROOF DECKING.
3. 2 X RAFTERS / ENGINEERED TRUSSES
4. DOUBLE TOP PLATE.
5. 2 X 4 RETURN.
6. 3/4" FASCIA OR PVC TRIM COIL
7. 2 X FASCIA
8. 1/4" PLYWOOD OR VINYL SOFFIT
9. 1 X FREIZE BOARD (TO BE USED WITH BRICK VENEERS)
10. INSULATION BOARD OR HOUSE WRAP
11. AIR SPACE.
12. BRICK WITH BRICK TIES PER MANUFACTURER'S SPECIFICATIONS.
13. 1/2" X 12" ANCHOR BOLTS, 6'-0" O.C., 12" FROM CORNERS.
14. FLASHING WITH WEEP HOLES @ 48" O.C.
15. FINISHED GRADE.
16. FOOTING
17. COMPACTED EARTH FILL.
18. 6 MIL VAPOR BARRIER
19. 4" CONCRETE SLAB, 3,000 P.S.I. WITH 6" X 6" 10 GA. X 10 GA. WELDED WIRE FABRIC.
20. 1/2" GYPSUM BOARD.

## EXTERIOR WALL SECTION

### FOUNDATION NOTES:

ALL FOOTINGS SHALL BEAR ON ORIGINAL UNDISTURBED SOIL  
THE 28 DAY COMPRESSIVE STRENGTH OF ALL FOOTINGS IS 3000 PSI

PROVIDE WATER PROOFING AND PERIMTER DRAINS AS REQUIRED

FOOTING WIDTHS ARE BASED ON A LOAD BEARING SOIL CAPACITY OF 2000 PSI

PROVIDE 6 MIL POLY VAPOR BARRIER TO COVER GROUND IN CRAWL SPACE AND GROUND UNDER POURED CONCRETE

ALL ANCHOR BOLTS TO BE 1/2" X 12" LONG. ANCHOR BOLTS SHALL BE SPACED AT A MAXIMUM OF 6' ON CENTER AND NO MORE THEN 1' FROM EACH CORNER

### GENERAL FRAMING NOTES:

ALL LUMBER IN CONTACT WITH CONCRETE OR MASONRY SHALLE BE PRESSURE TREATED

FRAMING LUMBER SHALL BE SYP #2 GRADE AND / OR SPRUCE PINE FIR #1 AND / OR KILN DRIED

WHERE PRE-ENGINEERED JOISTS AND TRUSSES ARE USED, MANUFACTURER SHALL PROVIDE DRAWINGS / SCHEMATICS, WHICH SHALL BEAR OF A N.C. ENGINEER

STUDS AND JOISTS SHALL NOT BE CUT TO INSTALL PLUMBING OR WIRING WITHOUT ADDING METAL OR WOOD SIDE PANELS TO STRENGTHEN MEMBER TO ITS ORIGINAL CAPACITY

NAIL MULTIPLE MEMBERS WITH 2 ROWS OF 16d NAILS STAGGERED 32" O.C. AND USE 3 X 16d NAILS 2" IN AT EACH END.


NAIL FLOOR JOISTS TO SILL PLATE WITH WITH 8d TOE NAILS

ALL EXPOSED FRAMING ON PORCHES OR DECKS SHALL BE PRESSURE TREATED


PROVIDE WATERPROOFING AND DRAINS AS REQUIRED

ALL FRAMING TO BE 16" O.C. WALL FRAMING DIMENSIONS ARE BASED ON 2X4 OR 2X6 EXTERIOR WALLS AND 2X4 INTERIOR WALLS. DOULBE / TRIPLE JACK STUDS AS NECESSARY UNDER HEADERS AS REQUIRED

LVLS TO BE SIZED BY OTHERS (TRUSS MANUFACTURER)



LUG FOOTING



STAIR DETAIL

PLAN:  
Roark 2.0

SHEET TITLE:  
DETAIL SHEETS


PROJECT ADDRESS:  
Liberty Meadows Lot 1

DESIGNED BY:  
Precision Custom Homes  
Raeferd, NC  
Shaun@PrecisionCustomHomesNC.com

DATE:  
7/19/22

SCALE:  
1/4" = 1'

SHEET:  
A-3



| AREA SCHEDULE    |          |
|------------------|----------|
| NAME             | AREA     |
| 1st FLOOR AREA   | 1,185 SF |
| 2nd FLOOR AREA   | 1305 SF  |
| GARAGE           | 418 SF   |
| FRONT PORCH      | 75 SF    |
| REAR PORCH       | 120 SF   |
| TOTAL HEATED     | 2490 SF  |
| TOTAL UNDER ROOF | 3103 SF  |

**1st Floor**  
Scale: 1/4" = 1'0"

SHEET TITLE:  
**1st FLOOR**


PROJECT ADDRESS:  
Liberty Meadows Lot 1

DESIGNED BY:  
Precision Custom Homes  
Raeferd, NC  
Shaun@PrecisionCustomHomesNC.com

DATE:  
7/19/22

SCALE:  
1/4" = 1'

SHEET:  
**A-4**



| AREA SCHEDULE    |          |
|------------------|----------|
| NAME             | AREA     |
| 1st FLOOR AREA   | 1,185 SF |
| 2nd FLOOR AREA   | 1,305 SF |
| GARAGE           | 418 SF   |
| FRONT PORCH      | 75 SF    |
| REAR PORCH       | 120 SF   |
| TOTAL HEATED     | 2490 SF  |
| TOTAL UNDER ROOF | 3103 SF  |

**2nd Floor**  
Scale: 1/4" = 1'0"

SHEET TITLE:  
**2nd FLOOR**

PROJECT ADDRESS:  
**Liberty Meadows Lot 1**

DESIGNED BY:  
Precision Custom Homes  
RaeFord, NC  
Shaun@PrecisionCustomHomesNC.com

DATE:  
7/19/22

SCALE:  
1/4" = 1'

SHEET:  
**A-5**