



Products				
PlotID	Length	Product	Plies	Net Qty
FJ-27	27' 10"	14" BCI@ 4500s-1.8	1	7
FJ-27-2	27' 10"	14" BCI@ 4500s-1.8	2	2
FJ-19	19' 6 1/4"	14" BCI@ 4500s-1.8	1	2
FJ-18	18' 3 1/4"	14" BCI@ 4500s-1.8	1	2
FJ-15	15' 7"	14" BCI@ 4500s-1.8	1	1
FJ-15	15' 3 3/4"	14" BCI@ 4500s-1.8	1	5
FJ-15	15' 3 1/2"	14" BCI@ 4500s-1.8	1	3
FJ-12	12' 1 1/4"	14" BCI@ 4500s-1.8	1	9
FJ-8A	8' 4 3/4"	14" BCI@ 4500s-1.8	1	1
FJ-4	4' 0"	14" BCI@ 4500s-1.8	1	1
FJ-3	3' 6 3/4"	14" BCI@ 4500s-1.8	1	1
FB1-3	18' 0"	1-3/4" x 14" VERSA-LAM@ 2.0 3100 SP	3	3
Rim1	12' 0"	1" x 14" BC RIM BOARD OSB	1	11
Bk1	2' 0"	14" BCI@ 4500s-1.8	1	9

Wall Framing				
PlotID	Length	Product	Plies	Net Qty
Hdr1	8' 0"	1-3/4" x 9-1/4" VERSA-LAM@ 2.0 3100 SP	2	2

Hangers			
PlotID	Qty	Manuf	Product
H1	24	Simpson	IUS 1.81/14

Builders FirstSource
 Boise Cascade
 Engineered Wood Products
 www.BLDR.com
 1135 Robeson St.
 Fayetteville, NC 28305
 V (910) 485-1111
 F (910) 485-6475
 7601 BOEING DRIVE
 GREENSBORO, NC 27409
 V: 336.884.5454
 3189 NC HIGHWAY5
 ABERDEEN NC 28315
 V: 910.944.2516

This layout and associated materials list has been prepared based on project plans and/or information provided to Builders FirstSource (BFS). It remains the responsibility of the builder, architect, designer, or other responsible persons to review this information to assure that it is appropriate, accurate, complete and complies with applicable building codes.

- GENERAL NOTES
- 1.) READ THE INSTALLATION GUIDE BEFORE FRAMING.
 - 2.) ALL WALL SHOWN ARE LOAD BEARING UNLESS NOTES OTHERWISE. WALLS NOT SHOWN HAVE BEEN CONSIDERED NON-LOAD BEARING.
 - 3.) UNLESS STATED OTHERWISE ALL CEILING & BEARING WALLS SUPPORTED BY FOUNDATION.
 - 4.) CONTACT YOUR LOCAL BUILDERS FIRSTSOURCE LOCATION BEFORE MAKING ANY ALTERATION & ADJUSTMENTS. FAILURE MAY RESULT IN COSTLY REPAIRS.

H & H HOMES
ENGAGE-C GL
 2nd FLOOR EWP PLACEMENT PLAN
 Builders FirstSource, Central Carolina Markets
 DRAWN BY: LEE ATKINS
 DATE: 3-20-18
 SCALE: NTS
 JOB #

MINIMUM DESIGN DATA
 LIVE LOAD 40 PSF
 DEAD LOAD 10 PSF
 TOTAL LOAD 50 PSF
 STRESS DURATION = 100%
 DEFLECTION CRITERIA
 L/480 (MINIMUM)
 ARCHITECTURAL PLAN DATE
 11-16-17
 REVISED ARCH. PLAN DATE
 XX-XX-XX
 SEALED PLAN DATE
 12-22-17
Sheet
1 of 1