



	HUS410	USP	19	NA	16d/3-1/2"	16d/3-1/2"
	MSH422	USP	3	Varies	10d/3"	10d/3"

Products					
PlotID	Length	Product	Plies	Net Qty	Fab Type
DB1	14-0-0	1-3/4"x 9-1/4" LVL Kerto-S	2	2	FF
DB2	4-0-0	1-3/4"x 9-1/4" LVL Kerto-S	2	2	FF
FB2	16-0-0	1-3/4"x 14" LVL Kerto-S	1	1	FF
Side GDH	22-0-0	1-3/4"x 18" LVL Kerto-S	3	6	FF
FB1(Top Flush)	21-0-0	1-3/4"x 23-7/8" LVL Kerto-S	3	3	FF

= Indicates Left End of Truss
 (Reference Engineered Truss Drawing)
 Do NOT Erect Truss Backwards

Truss Placement Plan
 SCALE: 1/4"=1'

LOAD CHART FOR JACK STUDS
 (BASED ON TABLES R502.5(1) & (2))
 NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADERS/GIRDS

END REACTION (UP TO) (LB)	END REACTION (UP TO) (LB)	END REACTION (UP TO) (LB)
1700	2550	3400
3400	5100	6800
5100	7650	10200
6800	10200	13600
8500	12750	17000
10200	15300	
11900		
13600		
15300		

BUILDER	A & G
JOB NAME	Lot 45 Liberty Meadows
PLAN	Aiken 2nd Floor Trusses
SEAL DATE	06/11/2020
QUOTE #	Quote #
JOB #	J0622-3391

CITY / CO.	Cumberland County/Fayetteville
ADDRESS	Liberty Meadows
MODEL	Open Web
DATE REV.	07/26/22
DRAWN BY	Marshall Naylor
SALES REP.	Marshall Naylor

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY.
 These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature: Marshall Naylor
 Marshall Naylor

ROOF & FLOOR TRUSSES & BEAMS

Reilly Road Industrial Park
 Fayetteville, N.C. 28309
 Phone: (910) 864-8787
 Fax: (910) 864-4444