Harnett County Department of Public Health

Improvement Permit

A building permit cannot be issued with only an Improvement Permit

PROPERTY LOCATION: 93 Bonnie Girl Ct (SR 1253)

ISSUED TO: Smith Douglas Homes	PROPERTY LOCATION: 93 BOTTING		
	subdivision Duncans Cros		LOT # 73
NEW REPAIR EXPANSION	Site Improvements re	quired prior to Construction Auth	norization Issuance:
Type of Structure: 50'x54' SFD			
Proposed Wastewater System Type: 25% reduction			
Projected Daily Flow: 480 GPD			
Number of bedrooms: 4 Number of Occupants: 8	max		
Basement Yes No			
	d on final location and elevations of facilities	(*)	
Type of Water Supply: Community Public W		Permit valid for:	▼ Five years
Permit conditions:			☐ No expiration
remit conditions.			no expiration
1, 1/			
hat wind from home Male Man	PEHS Date: 09-06-22	CEC A	TTACHED SITE SVETCH
Authorized State Agent:: Mal W			ATTACHED SITE SKETCH
The issuance of this permit by the Health Department in no way guarantees the issite is subject to revocation if the site plan, plat, or the intended use changes. The			
the Laws and Rules for Sewage Treatment and Disposal and to conditions of this		and are the beam a surject	to companie and the providence
30.3 CHRONOCH (Kornovicatoria pelena 💆 presa tespera (1975). Dapa 🕻 (1976). Sectoria (1975). Sectoria (1975).	COSSIS DAZE BE		
	Commenter Analysis and		
	Construction Authorization		
	(Required for Building Permit)		
The construction and installation requirements of Rules .1950, .1952, .1954, .1955		into this permit and shall be met. Syste	ems shall be installed in accordance
with the attached system layout.	1 (2000) 1		
0 111 5 1 11			
ISSUED TO: Smith Douglas Homes	PROPERTY LOCATION: 93 B		
	SUBDIVISION Duncans (Crossing	LOT # <u>73</u>
Facility Type: 50'x54' SFD	New ☐ Expansion ☐ Repair		
Basement? Yes No Basement Fixtures?			
	163 🔀 110	(Initial) Wassesser Flan	v: 480 GPD
Type of Wastewater System** 25% reduction			
		(Initial) Wastewater Flow	v. <u>400</u> GFD
(See note below, if applicable)		(Initial) Wastewater Flow	y. 400 GFD
(See note below, if applicable) 25% reduction	(Repair)	(initial) wastewater riow	4. 400 GFD
25% reduction	,	(initial) wastewater riow	V. 400
25% reduction Installation Requirements/Conditions Number	er of trenches 5		
25% reduction Installation Requirements/Conditions Numb	er of trenches 5 length of each trench 60 feet	Trench Spacing: 9	Feet on Center
25% reduction Installation Requirements/Conditions Numb	er of trenches 5 length of each trench 60 feet hes shall be installed on contour at a	Trench Spacing: 9 Soil Cover: 6	Feet on Center _inches
25% reduction Installation Requirements/Conditions Numb	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover sha	Feet on Center inches Il not exceed
25% reduction Installation Requirements/Conditions Numb	er of trenches 5 length of each trench 60 feet hes shall be installed on contour at a	Trench Spacing: 9 Soil Cover: 6	Feet on Center inches Il not exceed
25% reduction	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover sha	Feet on Center inches Il not exceed
25% reduction Installation Requirements/Conditions Number	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover sha	Feet on Center inches Il not exceed ottom)
25% reduction	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shal 36" above the trench b	Feet on Center inches Il not exceed ottom) inches below pipe
25% reduction	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover sha	Feet on Centerinches not exceed ottom) inches below pipe inches above pipe
25% reduction Installation Requirements/Conditions Number	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shal 36" above the trench b	Feet on Center inches Il not exceed ottom) inches below pipe
25% reduction	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4"	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shal 36" above the trench b	Feet on Centerinches not exceed ottom) inches below pipe inches above pipe
25% reduction Installation Requirements/Conditions Number	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4" directions)	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench be Aggregate Depth:	Feet on Centerinches not exceed ottom) inches below pipe inches above pipe
25% reduction Installation Requirements/Conditions Numb Septic Tank Size 1000 gallons Exact Pump Tank Size gallons Trenc Maxim (Trend in all Pump Requirements: ft. TDH vs. GPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10F	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches th bottoms shall be level to +/-1/4" directions)	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench be Aggregate Depth:	Feet on Centerinches not exceed ottom) inches below pipe inches above pipe
25% reduction Installation Requirements/Conditions Number	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches th bottoms shall be level to +/-1/4" directions)	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench be Aggregate Depth:	Feet on Centerinches not exceed ottom) inches below pipe inches above pipe
25% reduction	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches th bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA.	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shai 36" above the trench b Aggregate Depth:	Feet on Centerinches not exceed ottom) inches below pipe inches above pipe inches total
25% reduction Installation Requirements/Conditions Numb Septic Tank Size 1000 gallons Exact Pump Tank Size gallons Trenc Maxim (Trend in all Pump Requirements: ft. TDH vs. GPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10F	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches th bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA.	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shai 36" above the trench b Aggregate Depth:	Feet on Centerinches not exceed ottom) inches below pipe inches above pipe inches total
25% reduction Installation Requirements/Conditions Number Septic Tank Size 1000 gallons Exact Pump Tank Size gallons Trench Maxim (Trench In all Pump Requirements: ft. TDH vs. GPM GPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10F NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN IN **If applicable: understand the system type specified is different formula different formula ft. TDH vs. GPM Conditions: water formula ft. TDH vs. GPM GPM	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches th bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA.	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shal 36" above the trench b Aggregate Depth: REPAIR AREA.	Feet on Centerinches not exceed ottom) inches below pipe inches above pipe inches total
25% reduction Installation Requirements/Conditions Number Septic Tank Size 1000 gallons Exact Pump Tank Size gallons Trench Maxim (Trench In all Pump Requirements: ft. TDH vs. GPM GPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10F NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN IN **If applicable: understand the system type specified is different forms different forms ft. TDH vs. GPM Owner/Legal Representative Signature: Conditions ft. TDH vs. Conditi	length of each trench 60 feet thes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA. Everent from the type specified on the application	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shal 36" above the trench b Aggregate Depth: REPAIR AREA.	Feet on Centerinches Il not exceed ottom) inches below pipe inches above pipe inches total
25% reduction Installation Requirements/Conditions Number	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA. Everent from the type specified on the application and the intended use changes. The Construction Authorization shall not the intended use changes.	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shail 36" above the trench be aggregate Depth: REPAIR AREA. Date: Date:	Feet on Centerinches Il not exceed ottom) inches below pipe inches above pipe inches total of this permit.
25% reduction Installation Requirements/Conditions Number Septic Tank Size 1000 gallons Exact Pump Tank Size gallons Trench Maxim (Trench In all Pump Requirements: ft. TDH vs. GPM GPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10F NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN IN **If applicable: understand the system type specified is different forms different forms ft. TDH vs. GPM Owner/Legal Representative Signature: Conditions ft. TDH vs. Conditi	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA. Everent from the type specified on the application and the intended use changes. The Construction Authorization shall not the intended use changes.	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shail 36" above the trench be aggregate Depth: REPAIR AREA. Date: Date:	Feet on Centerinches Il not exceed ottom) inches below pipe inches above pipe inches total
25% reduction Installation Requirements/Conditions Number	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA. Everent from the type specified on the application and the intended use changes. The Construction Authorization shall not the intended use changes.	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shail 36" above the trench be aggregate Depth: REPAIR AREA. Date: Date:	Feet on Centerinches Il not exceed ottom) inches below pipe inches above pipe inches total of this permit.
Installation Requirements/Conditions Septic Tank Size 1000 gallons Pump Tank Size gallons Pump Tank Size gallons Frence Maxim (Trending in all pump Requirements: ft. TDH vs. GPM Conditions: WATER LINES (INCLUDING IRRIGATION) MUST BE 10FN NO UTILITIES ALLOWED IN INITIAL OR REPAIR DRAIN IN the state of the system type specified is different to revocation if the site plan, plat, or the Construction Authorization is subject to revocation if the site plan, plat, or the Construction Authorization is subject to compliance with the provisions of the Laws	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA. Everent from the type specified on the application and Rules for Sewage Treatment and Disposal and to the conditions.	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench be above the specifications of this permit.	Feet on Centerinches Il not exceed ottom) inches below pipe inches above pipe inches total of this permit.
25% reduction Installation Requirements/Conditions Number	length of each trench 60 feet hes shall be installed on contour at a num Trench Depth of: 18-24 inches the bottoms shall be level to +/-1/4" directions) T. FROM ANY PART OF SEPTIC SYSTEM OR FIELD AREA. Everent from the type specified on the application and Rules for Sewage Treatment and Disposal and to the conditions.	Trench Spacing: 9 Soil Cover: 6 (Maximum soil cover shall 36" above the trench be above the trench be appropriate to be transferred when there is a change it tions of this permit.	Feet on Centerinches Il not exceed ottom) inches below pipe inches above pipe inches total of this permit.

Harnett County Department of Public Health Site Sketch

Property Location: 93 Bonnie Girl C	Ct (SR 1253)	
Issued To: Smith Douglas Homes		Lot # 73
Authorized State Agent: Man	LA REHY	Date: 09-06-22

