

Connector Information Nail Information Supported Manuf | Qty Product Truss Header Member HJC26 USP 10d/3" 16d/3-1/2" 3 Varies HUS26 USP 16d/3-1/2" 16d/3-1/2" USP THD28-2 Varies 16d/3-1/2" 10d/3"

All Truss Reactions are Less than 3,000 lbs. Unless Noted Otherwise.

-- Denotes Reaction Greater than 3,000 lbs.

Truss Placement Plan SCALE: 3/16" = 1'

Beam Legend					
PlotID	Length	Product	Plies	Net Qty	Fab Type
GDH	23' 0"	1-3/4"x 11-7/8" LVL Kerto-S	2	2	FF

соттесн **ROOF & FLOOR TRUSSES & BEAMS** 

> Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444

tearing reactions less than or equal to 3000# are eemed to comply with the prescriptive Code equirements. The contractor shall refer to the ttached Tables (derived from the prescriptive Code equirements) to determine the minimum foundatic ize and number of wood studs required to support eactions greater than 3000# but not greater than 5000#. A registered design professional shall be etained to design the support system for any eaction that exceeds those specified in the attache ables. A registered design professional shall be etained to design the support system for all eactions that exceed 15000#.

**Curtis Quick** 

Curtis Quick

LOAD CHART FOR JACK STUDS

Lillington / Harnett Anthony Williams Lot 162 Ballard Curtis Quick 09/20/22 DRAWN BY SALES REP. CI TY / CO. Watermark Homes Ballard

SEAL DATE **BUILDER** QUOTE JOB THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

11/4/20

Lot

NAME

Quote

J0922-4792

▲ = Denotes Left End of Truss (Reference Engineered Truss Drawing) Do Not Erect Trusses Backwards