



**Front Elevation**  
Scale: 1/4" = 1'0"

**NOTICE TO CONTRACTOR**  
All construction must comply with current NC Building Codes and is subject to field inspection and verification.


**APPROVED**  
Limited building only review  
Permit holder responsible for full compliance with the code

11/30/2022






**Rear Elevation**  
Scale: 1/4" = 1'0"



**Left Elevation**  
Scale: 1/4" = 1'0"



**Right Elevation**  
Scale: 1/4" = 1'0"

DATE: Thursday, October 6, 2022  
REVISED  
DRAWING#

SCALE: 1/4"  
DRAWN BY  
APPROVED

**The Cypress Ely.A**


BBH-2052




Optional Stone Or Brick  
**Front Elevation**  
 Scale: 1/4" = 1'0"



**Rear Elevation**  
 Scale: 1/4" = 1'0"



**Left Elevation**  
 Scale: 1/4" = 1'0"




**Right Elevation**  
 Scale: 1/4" = 1'0"

DATE: Thursday, October 6, 2022  
 REVISED  
 DRAWING#

SCALE: 1/4"  
 DRAWN BY  
 APPROVED

**The Cypress EIV.B**


BBH-2052



# First Floor Plan

Scale: 1/4" = 1'-0"

## Kitchen Cabinets



| FIRST FLOOR OPENING SCHEDULE |               |       |       |
|------------------------------|---------------|-------|-------|
| PRODUCT CODE                 | SIZE          | HINGE | COUNT |
| 36X80 COLONIAL A             | 3'-0"         | L     | 1     |
| 7X16 GARAGE DOOR             | 16'-0"        | U     | 1     |
| 72X80 SLIDING FRENCH 2       | 6'-0"         | NL    | 1     |
| 20 colonial                  | 2'-0"         | R     | 1     |
| 20 colonial                  | 2'-0"         | L     | 1     |
| 30 doublehung colonial       | 3'-0"         | LR    | 1     |
| 32X80 COLONIAL A 1           | 2'-8"         | L     | 1     |
| 24X24 CASEMENT 1             | 2'-0" x 2'-0" | N     | 2     |
| 28x52 Twin                   | 5'-4" x 5'-2" | NA    | 1     |
| 28x52 twin                   | 5'-4" x 5'-2" | NA    | 1     |
| 28x32 single                 | 2'-8" x 3'-2" | N     | 1     |

## Areas


|              |      |
|--------------|------|
| First Floor  | 929  |
| Second Floor | 1270 |
| =====        |      |
| Total Heated | 2199 |
| Garage       | 413  |
| Porch        | 69   |

DATE: Thursday, October 6, 2022  
 REVISED  
 DRAWING#

SCALE: 1/4"  
 DRAWN BY  
 APPROVED

The Cypress


BBH-2052




## Second Floor Plan

Scale: 1/4" = 1'-0"

### Master Bath Cabinets



### Hall Bath Cabinets




| SECOND FLOOR OPENING SCHEDULE |               |       |       |
|-------------------------------|---------------|-------|-------|
| PRODUCT CODE                  | SIZE          | HINGE | COUNT |
| 2-0 Door Unit                 | 2'-0"         | L     | 1     |
| 20 cased opening              | 2'-0"         | N     | 2     |
| 20 colonial                   | 2'-0"         | L     | 3     |
| 26 colonial                   | 2'-6"         | R     | 4     |
| 3-0 Doublehung Door Unit      | 4'-0"         | LR    | 3     |
| 28 colonial                   | 2'-8"         | L     | 1     |
| 20x32 single                  | 2'-0" x 3'-2" | N     | 1     |
| 28x52 Twin                    | 5'-4" x 5'-2" | NA    | 1     |
| 28x52 single                  | 2'-8" x 5'-2" | N     | 4     |

DATE: Thursday, October 6, 2022  
 REVISED  
 DRAWING#



SCALE: 1/4"  
 DRAWN BY  
 APPROVED

The Cypress


BBH-2052




**Foundation Plan**  
 Scale: 1/4" = 1'-0"




|                                 |          |          |
|---------------------------------|----------|----------|
| DATE: Thursday, October 6, 2022 | REVISED  | DRAWING# |
| SCALE: 1/4"                     | DRAWN BY | APPROVED |
| <b>The Cypress</b>              |          |          |
| BBH-2052                        |          |          |



**Foundation Plan**  
 Scale: 1/4" = 1'-0"



**TURN-DOWN  
FOOTING DETAIL**




**INTEGRAL SLAB FOOTING  
DETAIL AT BEARING WALL**

DATE: Thursday, October 6, 2022  
 REVISIONS  
 DRAWING#

SCALE: 1/4"  
 DRAWN BY  
 APPROVED


**The Cypress**

BBH-2052




# Foundation Plan

Scale: 1/4" = 1'-0"



STEM WALL FOOTING DETAIL



LUG FOOTING DETAIL

DATE: Thursday, October 6, 2022  
 REVISIONS  
 DRAWING#

SCALE: 1/4"  
 DRAWN BY  
 APPROVED

The Cypress

BBH-2052



# ROOF & FLOOR TRUSSES & BEAMS

Reilly Road Industrial Park  
Fayetteville, N.C. 28309  
Phone: (910) 864-8787  
Fax: (910) 864-4444

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables ( derived from the prescriptive Code requirements ) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.


Signature **David Landry**

**David Landry**

### LOAD CHART FOR JACK STUDS

(BASED ON TABLES R502.5(1) & (b))  
NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADER/GIRDER

| END REACTION (UP TO) | REQ. D. STUDS FOR (1) 1/2" HEADER | END REACTION (UP TO) | REQ. D. STUDS FOR (1) 1/2" HEADER | END REACTION (UP TO) | REQ. D. STUDS FOR (1) 1/2" HEADER |
|----------------------|-----------------------------------|----------------------|-----------------------------------|----------------------|-----------------------------------|
| 1700                 | 1                                 | 2550                 | 1                                 | 3400                 | 1                                 |
| 3400                 | 2                                 | 5100                 | 2                                 | 6800                 | 2                                 |
| 5100                 | 3                                 | 7650                 | 3                                 | 10200                | 3                                 |
| 6800                 | 4                                 | 10200                | 4                                 | 13600                | 4                                 |
| 8500                 | 5                                 | 12750                | 5                                 | 17000                | 5                                 |
| 10200                | 6                                 | 15300                | 6                                 |                      |                                   |
| 11900                | 7                                 |                      |                                   |                      |                                   |
| 13600                | 8                                 |                      |                                   |                      |                                   |
| 15300                | 9                                 |                      |                                   |                      |                                   |



| BUILDER                    | CITY / CO. | Harnett Co. / Harnett |
|----------------------------|------------|-----------------------|
| Benjamin Stout Real Estate | ADDRESS    | 61 Solomon Drive      |
| JOB NAME                   | MODEL      | I-Joists Over Crawl   |
| PLAN                       | DATE REV.  | 11/21/22              |
| SEAL DATE                  | DRAWN BY   | David Landry          |
| QUOTE #                    | SALES REP. | Marshall Naylor       |
| JOB #                      |            | J1122-5794            |

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

▲ = Indicates Left End of Truss  
(Reference Engineered Truss Drawing)  
Do NOT Erect Truss Backwards





**ROOF & FLOOR TRUSSES & BEAMS**

Reilly Road Industrial Park  
 Fayetteville, N.C. 28309  
 Phone: (910) 864-8787  
 Fax: (910) 864-4444


Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables ( derived from the prescriptive Code requirements ) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature **David Landry**  
 David Landry

**LOAD CHART FOR JACK STUDS**

(BASED ON TABLES R502.5(1) & (b))  
 NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADER/GIRDER

| END REACTION (UP TO) | REQ. D. STUDS FOR (1) FLY HEADER | END REACTION (UP TO) | REQ. D. STUDS FOR (1) FLY HEADER | END REACTION (UP TO) | REQ. D. STUDS FOR (1) FLY HEADER |
|----------------------|----------------------------------|----------------------|----------------------------------|----------------------|----------------------------------|
| 1700                 | 1                                | 2550                 | 1                                | 3400                 | 1                                |
| 3400                 | 2                                | 5100                 | 2                                | 6800                 | 2                                |
| 5100                 | 3                                | 7650                 | 3                                | 10200                | 3                                |
| 6800                 | 4                                | 10200                | 4                                | 13600                | 4                                |
| 8500                 | 5                                | 12750                | 5                                | 17000                | 5                                |
| 10200                | 6                                | 15300                | 6                                |                      |                                  |
| 11900                | 7                                |                      |                                  |                      |                                  |
| 13600                | 8                                |                      |                                  |                      |                                  |
| 15300                | 9                                |                      |                                  |                      |                                  |



| Products |        |                            |       |         |          |
|----------|--------|----------------------------|-------|---------|----------|
| PlotID   | Length | Product                    | Plies | Net Qty | Fab Type |
| BM1      | 4' 0"  | 1-3/4"x 16" LVL Kerto-S    | 2     | 2       | FF       |
| BM2      | 7' 0"  | 1-3/4"x 9-1/4" LVL Kerto-S | 2     | 4       | FF       |
| GDH      | 20' 0" | 1-3/4"x 18" LVL Kerto-S    | 2     | 2       | FF       |

**1 Truss Placement Plan**  
 Scale: 1/4"=1'

**All Walls Shown Are Considered Load Bearing**

- Dimension Notes**
1. All exterior wall to wall dimensions are to face of sheathing unless noted otherwise
  2. All interior wall dimensions are to face of frame wall unless noted otherwise
  3. All exterior wall to truss dimensions are to face of frame wall unless noted otherwise

| Connector Information |         |       |     |                  | Nail Information |            |
|-----------------------|---------|-------|-----|------------------|------------------|------------|
| Sym                   | Product | Manuf | Qty | Supported Member | Header           | Truss      |
| ●                     | MSH422  | USP   | 4   | Varies           | 10d/3"           | 10d/3"     |
| ●                     | HUS410  | USP   | 2   | NA               | 16d/3-1/2"       | 16d/3-1/2" |

- Plumbing Drop Notes**
1. Plumbing drop locations shown are NOT exact.
  2. Contractor to verify ALL plumbing drop locations prior to setting Floor Trusses.
  3. Adjust spacing as needed not to exceed 24"oc.

|           |                            |            |                       |
|-----------|----------------------------|------------|-----------------------|
| BUILDER   | Benjamin Stout Real Estate | CITY / CO. | Harnett Co. / Harnett |
| JOB NAME  | Lot 53 Liberty Meadows     | ADDRESS    | 61 Solomon Drive      |
| PLAN      | Cypress / 2GRF, CP         | MODEL      | Floor                 |
| SEAL DATE | N/A                        | DATE REV.  | 11/21/22              |
| QUOTE #   |                            | DRAWN BY   | David Landry          |
| JOB #     | J1122-5793                 | SALES REP. | Marshall Naylor       |

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

**▲ = Indicates Left End of Truss**  
 (Reference Engineered Truss Drawing)  
 Do NOT Erect Truss Backwards



**ROOF & FLOOR TRUSSES & BEAMS**

Reilly Road Industrial Park  
 Fayetteville, N.C. 28309  
 Phone: (910) 864-8787  
 Fax: (910) 864-4444

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables ( derived from the prescriptive Code requirements ) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.


Signature David Landry  
 David Landry

**LOAD CHART FOR JACK STUDS**

(BASED ON TABLES R502.5(1) & (b))

NUMBER OF JACK STUDS REQUIRED @ EA END OF HEADER/GIRDER

| END REACTION (UP TO) | REQ. STUDS FOR (1) 1" X 4" HEADER | END REACTION (UP TO) | REQ. STUDS FOR (1) 1" X 4" HEADER | END REACTION (UP TO) | REQ. STUDS FOR (1) 1" X 4" HEADER |
|----------------------|-----------------------------------|----------------------|-----------------------------------|----------------------|-----------------------------------|
| 1700                 | 1                                 | 2550                 | 1                                 | 3400                 | 1                                 |
| 3400                 | 2                                 | 5100                 | 2                                 | 6800                 | 2                                 |
| 5100                 | 3                                 | 7650                 | 3                                 | 10200                | 3                                 |
| 6800                 | 4                                 | 10200                | 4                                 | 13600                | 4                                 |
| 8500                 | 5                                 | 12750                | 5                                 | 17000                | 5                                 |
| 10200                | 6                                 | 15300                | 6                                 |                      |                                   |
| 11900                | 7                                 |                      |                                   |                      |                                   |
| 13600                | 8                                 |                      |                                   |                      |                                   |
| 15300                | 9                                 |                      |                                   |                      |                                   |



| Products |        |                            |       |         |          |
|----------|--------|----------------------------|-------|---------|----------|
| PlotID   | Length | Product                    | Plies | Net Qty | Fab Type |
| BM1      | 4' 0"  | 1-3/4"x 16" LVL Kerto-S    | 2     | 2       | FF       |
| BM2      | 7' 0"  | 1-3/4"x 9-1/4" LVL Kerto-S | 2     | 4       | FF       |
| GDH      | 20' 0" | 1-3/4"x 18" LVL Kerto-S    | 2     | 2       | FF       |

| Products |        |              |       |         |          |
|----------|--------|--------------|-------|---------|----------|
| PlotID   | Length | Product      | Plies | Net Qty | Fab Type |
| BM3      | 8' 0"  | 2x12 SP No.2 | 2     | 2       | FF       |

1 Truss Placement Plan  
 Scale: 1/4"=1'

All Walls Shown Are Considered Load Bearing

Roof Area = 2132.88 sq.ft.  
 Ridge Line = 71.68 ft.  
 Hip Line = 0 ft.  
 Horiz. OH = 141.34 ft.  
 Raked OH = 188.84 ft.  
 Decking = 73 sheets

| Hatch Legend |                 |
|--------------|-----------------|
|              | Padded HVAC     |
|              | Tray Ceiling    |
|              | 2nd Floor Walls |
|              | Drop Beam       |

Dimension Notes

- All exterior wall to wall dimensions are to face of sheathing unless noted otherwise
- All interior wall dimensions are to face of frame wall unless noted otherwise
- All exterior wall to truss dimensions are to face of frame wall unless noted otherwise

| BUILDER                    | CITY / CO. | Harnett Co. / Harnett |
|----------------------------|------------|-----------------------|
| Benjamin Stout Real Estate | ADDRESS    | 61 Solomon Drive      |
| JOB NAME                   | MODEL      | Roof                  |
| PLAN                       | DATE REV.  | 11/21/22              |
| SEAL DATE                  | DRAWN BY   | David Landry          |
| QUOTE #                    | SALES REP. | Marshall Naylor       |
| JOB #                      |            | J1122-5792            |

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSI-B1 and BCSI-B3 provided with the truss delivery package or online @ sbcindustry.com

= Indicates Left End of Truss  
 (Reference Engineered Truss Drawing)  
 Do NOT Erect Truss Backwards