


55  
 ALL BE PERFORMED IN ACCORDANCE WITH ALL APPLICABLE STATE AND LOCAL CODES AND REGULATIONS. SHALL THOROUGHLY REVIEW ALL SHEETS IN PLAN SET AND SHALL BE RESPONSIBLE FOR OBTAINING ALL NECESSARY PERMITS AND ORDINANCES BEFORE BEGINNING CONSTRUCTION. CONTRACTOR SHALL ASSUME RESPONSIBILITY FOR JUSTIFICATION AND/OR CORRECTION BEFORE WITH WORK. CONTRACTORS SHALL ASSUME RESPONSIBILITY THAT ARE NOT REPORTED PRIOR TO CONSTRUCTION. ALL WORK SHOULD BE READ ON LOCAL CODES AND REGULATIONS AND SHOULD BE COMPLETED PRIOR TO BUILDING WITH ALL PERMITS.




**HALES FARM - LOT 3**  
 10434 NC 27 WEST  
 LILLINGTON, NC 27546


PLANS DESIGNED TO THE  
 2018 NORTH CAROLINA STATE  
 RESIDENTIAL BUILDING CODE.




**FRONT ELEVATION - C**  
 SCALE: 1/4" = 1'-0"



**LEFT ELEVATION**  
 SCALE: 1/8" = 1'-0"




**REAR ELEVATION**  
 SCALE: 1/8" = 1'-0"



**RIGHT ELEVATION**  
 SCALE: 1/8" = 1'-0"

SCALE NOTE: 1/8" PRINTS ARE TO SCALE EXCEPT 1/4" PRINTS ARE NOT TO SCALE



**RENAISSANCE**  
 RESIDENTIAL DESIGN, INC.  
 1019 LEXINGTON  
 FAYETTEVILLE, NC 27802

**WEAVER HOMES**  
 350 Wagoner Drive • Fayetteville, NC 28303  
 910.630.2100 • 800.892.2190  
 www.weaver-homes.com


**WEAVER HOMES**  
 CAROLINA COLLECTION  
 MAGNOLIA-II DRIVE LEFT

DATE: FEBRUARY 19, 2021  
 SCALE: 1/4" = 1'-0"  
 DRAWN BY: WWT  
 ENGINEERED BY:  
 REVIEWED BY:



C - ELEVATIONS  
 A-3

PRICES, PROMOTIONS, INCENTIVES, FEATURES, OPTIONS, FINISHES, ELEVATIONS, MATERIALS, AND DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. SQUARE FOOTAGE AND DIMENSIONS ARE ESTIMATED AND MAY VARY FROM ACTUAL CONSTRUCTION. ACTUAL POSITION OF HOUSE ON LOT WILL BE DETERMINED BY THE SITE PLAN AND PLAT. ALL DIMENSIONS AND FINISHES ARE TO BE PERFORMED BY ARTIST CONCEPTS. FLOOR PLANS ARE THE COPYRIGHTED PROPERTY OF WEAVER HOMES AND ARE TO BE USED STRICTLY FOR THE ADVANTAGE OR DISPLAY OF THE PLANS IS STRICTLY PROHIBITED. SEE NEW HOME SALES CONSULTANT FOR COMPLETE DETAILS. COPYRIGHT © 2021 WEAVER HOMES

**FRONT PORCH AND DINING ROOM WINDOW ELEVATION B**



**OPTIONAL FAMILY ROOM WITH ALTERNATE FIREPLACE LOCATION AND BUILT-INS**



SQUARE FOOTAGE (SF)	
1st FLOOR:	581 SQ. FT.
2nd FLOOR:	1471 SQ. FT.
TOTAL:	1828 SQ. FT.
GARAGE:	539 SQ. FT.
FRONT PORCH (ELEV. A-C):	25 SQ. FT.
FRONT PORCH (ELEV. B):	100 SQ. FT.
5th FLOOR PATIO:	100 SQ. FT.
OPT. REAR PORCH:	100 SQ. FT.

SCALE NOTE: 1/8" = 1'-0"  
TO SCALE AS NOTED.  
11x17 PRINTS ARE NOT TO SCALE

DATE: FEBRUARY 19, 2011  
SCALE: 1/4" = 1'-0"  
DRAWN BY: WHT  
ENGINEERED BY:  
REVIEWED BY:

**WEAVER HOMES  
CAROLINA COLLECTION  
MAGNOLIA-II DRIVE LEFT**

PRICES, PROMOTIONS, INCENTIVES, FEATURES, OPTIONS, FLOORING, FINISHES, MATERIALS, WATER, AND UTILITIES ARE SUBJECT TO CHANGE WITHOUT NOTICE. SQUARE FOOTAGE AND DIMENSIONS ARE ESTIMATED AND MAY VARY IN ACTUAL CONSTRUCTION. ACTUAL POSITION OF HOUSE ON LOT WILL BE DETERMINED BY THE SITE PLAN AND PROFESSIONAL FLOOR PLANS AND ELEVATIONS. PHOTOGRAPHS AND ARTIST CONCEPTIONS OF FLOOR PLANS ARE THE COPYRIGHTED PROPERTY OF WEAVER HOMES AND ARE NOT TO BE REPRODUCED OR ADAPTED OR COPIED IN ANY MANNER WITHOUT THE WRITTEN PERMISSION AND CONSENT OF WEAVER HOMES. © 2011 WEAVER HOMES

**WEAVER HOMES**  
350 Waggoner Drive • Fayetteville, NC 28303  
910.669.2100 • 800.862.2100  
www.weaver-homes.com


The art of redefining your vision into reality.  
RENAISSANCE RESIDENTIAL DESIGN, INC.  
10000 W. WILSON ROAD  
SUITE 100  
DURHAM, NC 27715  
919.487.1111  
www.renaissanceid.com

**RENAISSANCE**  
RESIDENTIAL DESIGN, INC.  
RALEIGH, NC 27612  
www.renaissanceid.com







**FRONT PORCH AND DINING ROOM WINDOW ELEVATIONS**



**OPTIONAL FAMILY ROOM WITH ALTERNATE FIREPLACE LOCATION AND BUILT-INS**




**ELECTRICAL LAYOUT NOTES:**  
 1) BLOCK AND WIRE FOR ALL CEILING FANS PER PLAN  
 2) VANT LIGHTS TO BE SET @ 8'0\"/>

**ELECTRICAL LEGEND**

- 100 V OUTLET
- 100 V GFI OUTLET
- 100 V SWITCHED OUTLET
- 4-FLX
- COUNTER OR FLOOR HOUNDED
- LEATHERNEED
- 200 V OUTLET
- 200 V DEDICATED CIRCUIT
- SPECIAL PURPOSE (240 V, ETC)
- WALL HOUNT LIGHT
- CEILING HOUNT LIGHT
- PERJANT LIGHT
- RECESSED CAN LIGHT
- TRN CAN LIGHT
- ETERNAL LIGHT
- FLUORESCENT LIGHT
- UNDERCABINET LIGHT
- FLOOD LIGHT
- SWITCH
- DIFFER SWITCH
- TELEPHONE
- DATA
- TELEPHONE AND DATA
- TV CONNECTION
- TV/DATA
- CIRCUIT FOR COMPONENT WIRING
- BREAKER
- 100 V BROCK / CH DETECTOR
- 100 V BROCK DETECTOR
- EXHAUST FAN
- LOW VOLTAGE PANEL
- ALERT PANEL
- CEILING FAN
- CEILING FAN W/ LIGHT

SCALE NOTE: 1/8\"/>




**RENAISSANCE**  
 RESIDENTIAL DESIGN, INC.  
 BALDWIN, NC 27012  
 WWW.RENAISSANCE-RESIDENTIAL.COM

**WEAVER HOMES**  
 150 Weaver Drive • Fayetteville, NC 28403  
 910.620.2100 • Fax: 910.620.1910  
 www.weaverhomes.com

PRICES, PROMOTIONS, INCENTIVES, FEATURES, OPTIONS, FLOOR PLANS, ELEVATIONS, FINISHES, MATERIALS AND DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. SQUARE FOOTAGE AND DIMENSIONS ARE ESTIMATED AND NOT GUARANTEED. CONSTRUCTION ACTUAL. PORTION OF HOUSE ON LOT WILL BE DETERMINED BY THE SITE PLAN AND ZONING REGULATIONS AND ALL ELECTRICAL REQUIREMENTS ARE THE RESPONSIBILITY OF THE HOMEOWNER. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE ADAPTATION OR DISPLAY OF THE PLANS IN STRICT COMPLIANCE WITH ALL APPLICABLE CODES AND REGULATIONS. SEE NEW YORK BUILDING CODES AND REGULATIONS FOR DETAILS. COPYRIGHT © 2010 WEAVER HOMES

**WEAVER HOMES**  
 CAROLINA COLLECTION  
 MAGNOLIA-II DRIVE LEFT

DATE: FEBRUARY 19, 2011  
 REV.  
 SCALE: 1/4" = 1'-0"  
 DRAWN BY: WJL  
 ENGINEERED BY:  
 REVIEWED BY:  
 FIRST FLOOR ELECTRICAL PLAN  
 E-1




**ELECTRICAL LAYOUT NOTES:**  
 1) BLOCK AND LINE FOR ALL  
 CEILING FANS PER PLAN  
 2) VANTY LIGHTS TO BE SET  
 @ 8'0" AFF. (TYP)  
 3) ADDITIONAL EXISTING OUTLETS  
 ARE TO BE  
 LOCATED BY ELECTRICIAN  
 4) PLACE SWITCHES 6" MIN FROM  
 ROOM OPENING.

**ELECTRICAL LEGEND**

- 120 V OUTLET
- 120 V GFI OUTLET
- 120 V SWITCHED OUTLET
- 120 V DEDICATED OUTLET
- 4 PLEX
- COUNTER ON FLOOR MOUNTED
- COUNTER ON FLOOR MOUNTED 120V GFI
- LEANER/FREED
- 220 V OUTLET
- 120 V DEDICATED CIRCUIT
- SPECIAL FUNCTION (240 V, 5T/C)
- WALL MOUNT LIGHT
- CEILING MOUNT LIGHT
- RECESSED CAN LIGHT
- MINI CAN LIGHT
- ETHERNET LIGHT
- FLOODESCENT LIGHT
- UNDER-CABINET LIGHT
- FLOOD LIGHT
- SWITCH
- DIMMER SWITCH
- ▲ TELEPHONE
- ▲ DATA
- ▲ TELEPHONE AND DATA
- TV TV CONNECTION
- TV TV DATA
- CONDUIT FOR COMPONENT WIRING
- BREAKER
- 120 V BRN/BL CO DETECTOR
- EXHAUST FAN
- LOW VOLTAGE PANEL
- ALARM PANEL
- CEILING FAN
- CEILING FAN W/ LIGHT

SCALE NOTE: 1/8" = 1'-0" PRINTS ARE  
 TO SCALE UNLESS NOTED  
 1/4" = 1'-0" PRINTS ARE NOT TO SCALE



**RENAISSANCE**  
 RESIDENTIAL DESIGN, INC.  
 10100 W. 10TH AVENUE  
 SUITE 100  
 DENVER, CO 80231  
 (303) 441-4444  
 WWW.RENAISSANCEDENVER.COM

THIS SET OF PRINTS IS THE PROPERTY OF RENAISSANCE RESIDENTIAL DESIGN, INC. AND IS TO BE USED ONLY FOR THE PROJECT AND SITE SPECIFICALLY IDENTIFIED. IT IS NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF RENAISSANCE RESIDENTIAL DESIGN, INC.

**WEAVER HOMES**  
 3000 Weaver Drive • Fayetteville, NC 28404  
 910.439.2100 • 910.439.2101  
 www.weaverhomes.com

PLEASE PROMOTIONS, INCENTIVES, FEATURES, OPTIONS, AND DISCOUNTS ARE SUBJECT TO CHANGE WITHOUT NOTICE. WE ADOPT THE LATEST CODES AND REGULATIONS. THE CONTRACTOR AND ARCHITECT SHALL BE RESPONSIBLE FOR VERIFYING THE ACTUAL CONDITIONS OF THE PROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THE ACTUAL CONDITIONS OF THE PROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THE ACTUAL CONDITIONS OF THE PROJECT. THE CONTRACTOR SHALL BE RESPONSIBLE FOR VERIFYING THE ACTUAL CONDITIONS OF THE PROJECT.


**WEAVER HOMES**  
 CAROLINA COLLECTION  
 MAGNOLIA-II DRIVE LEFT

DATE: FEBRUARY 13, 2011  
 REV.  
 SCALE: 1/8" = 1'-0"  
 DRAWN BY: JTB  
 CHECKED BY: JTB  
 APPROVED BY: JTB  
 SECOND FLOOR ELECTRICAL PLAN  
**E-2**






~~FRONT PORCH AND DINING  
ROOF LINEN/POW ELEVATION B~~



OPTIONAL FAMILY ROOM  
WITH ALTERNATE FIREPLACE  
LOCATION AND BUILT-INS



PACK PORCH BEAM OUT TO 8\"/>
 WIDTH (TYP. W/ COVERED  
PORCH OPTION)


- STRUCTURAL NOTES:**
1. ALL FRAMING LUMBER TO BE SPC #2 (UNO). ALL TREATED LUMBER TO BE SPC #2 (UNO).
  2. ALL LOAD BEARING HEADERS TO BE (2) 2 x 6 (UNO).
  3. WINDOW AND DOOR HEADERS TO BE SUPPORTED W/ (1) JACK STUD AND (1) KING STUD EA. END (UNO). SEE TABLE R602.7.5 FOR ADDITIONAL KING STUD REQUIREMENTS.
  4. SQUARE BRONTE JOINT LIONS WHICH REQUIRE SOLID BLOCKING TO GIRDER OR (OR EQUAL) AND 6 x 6 POSTS W/ ABRAID POST BASES (OR EQUAL) (UNO). ALL 4 x 4 AND 6 x 6 POSTS TO BE INSTALLED WITH 700 LB CAPACITY UPLIFT CONNECTORS AT TOP (UNO).
  5. ALL 4 x 4 POSTS SHALL BE ANCHORED TO SLABS W/ SIMPSON ABRAID POST BASES (OR EQUAL) AND 6 x 6 POSTS TO BE INSTALLED WITH 700 LB CAPACITY UPLIFT CONNECTORS AT TOP (UNO).
  6. (2) METAL ANGLES USING 2\"/>

**BRACE WALL PANEL NOTES:**

EXTERIOR WALLS: ALL EXTERIOR WALLS TO BE SHEATHED WITH GS-WS9 OR GS-SS9 IN ACCORDANCE WITH SECTION R602.10.3 UNLESS NOTED OTHERWISE.

REQUIRED LENGTH OF BRACING: REQUIRED BRACE WALL LENGTH FOR EACH SIDE OF THE CIRCUMSCRIBED RECTANGLE ARE AND GS-SS9 INTERPOLATED PER TABLE R602.10.1. METHODS OF CONNECTION SHALL BE AS SHOWN IN THIS PLAN. METHOD PF CONTRIBUTES 1.5 TIMES ITS ACTUAL LENGTH.

GYPSUM: ALL INTERIOR SIDES OF EXTERIOR WALLS AND BOTH SIDES OF INTERIOR WALLS TO HAVE 1/2\"/>



SCALE NOTE: 1/8x24 PRINTS ARE  
TO SCALE AS NOTED.  
11x17 PRINTS ARE NOT TO SCALE


DATE: FEBRUARY 19, 2021  
REV: \_\_\_\_\_  
SCALE: 1/4\"/>

WEAVER HOMES  
CAROLINA COLLECTION  
MAGNOLIA-II DRIVE LEFT

PRICES, PROMOTIONS, INCENTIVES, FEES, OPTIONS, PERMITS, AND REGULATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. WE ADOPT THE LATEST EDITIONS OF ALL CODES AND STANDARDS. ALL DIMENSIONS ARE ESTIMATED AND MAY VARY BY ACTUAL CONSTRUCTION. ACTUAL POSITIONS OF ROOF, FLOOR, AND FINISH FLOOR ARE ESTIMATED AND MAY VARY BY ACTUAL CONSTRUCTION. ALL DIMENSIONS ARE ESTIMATED AND MAY VARY BY ACTUAL CONSTRUCTION. ALL DIMENSIONS ARE ESTIMATED AND MAY VARY BY ACTUAL CONSTRUCTION. ALL DIMENSIONS ARE ESTIMATED AND MAY VARY BY ACTUAL CONSTRUCTION.

**WEAVER HOMES**  
350 Wagner Drive - Fayetteville, NC 28303  
910.438.1616  
www.weaver-homes.com

**RENAISSANCE**  
RESIDENTIAL DESIGN, INC.  
RALEIGH, NC 27612  
www.renaissance.com









TABLE REQ. 7.5  
MINIMUM NUMBER PER FOOT HEIGHT STUDS  
AT EACH END OF HEADERS IN EXTERIOR WALLS

HEADER SPAN (FEET)	MAXIMUM STUD SPACING (INCHES) (SEE TABLE REQ. 2.5)			
	16	24	32	48
UP TO 3'	1	1	1	1
4'	2	2	2	2
8'	3	3	3	3
12'	5	5	5	5
16'	6	6	6	6

- STRUCTURAL NOTES:**
1. ALL FRAMING LUMBER TO BE SPF #2 #2 (UNO). ALL TREATED LUMBER TO BE SYP #2 (UNO).
  2. ALL LOAD BEARING HEADERS TO BE (2) 2 x 6 (UNO).
  3. WINDOW AND DOOR HEADERS TO BE SUPPORTED W/ (1) JACK STUD AND (1) KING STUD EA. END (UNO.). SEE TABLE REQ. 7.5 FOR ADDITIONAL KING STUD REQUIREMENTS.
  4. SQUARES DENOTE POINT LOADS WHICH REQUIRE SOLID BLOCKING TO GIRDER OR FOUNDATION. ALL SQUARES TO BE (2) STUDS (UNO).
- DSP - DOUBLE STUD POCKET  
TSP - TRIPLE STUD POCKET

SCALE NOTE: 1/8"24 PRINTS ARE TO SCALE AS NOTED.  
11x17 PRINTS ARE NOT TO SCALE



**RENAISSANCE**  
RESIDENTIAL DESIGN, INC.  
1000 S. W. 10th Street  
FALMOUTH, NC 27512  
WWW.RENAISSANCECDM.COM

The art of transforming your vision into reality.  
RENAISSANCE RESIDENTIAL DESIGN, INC.  
ARCHITECTURE TO CONCEPTS  
CONCEPTS TO PERMITS  
PERMITS TO CONSTRUCTION  
CONSTRUCTION TO COMPLETION  
RESIDENTIAL DESIGN, INC. IS AN  
EQUAL OPPORTUNITY AFFIRMATIVE  
EMPLOYER.  
RENAISSANCE RESIDENTIAL DESIGN, INC.  
IS AN EQUAL OPPORTUNITY AFFIRMATIVE  
EMPLOYER.  
RENAISSANCE RESIDENTIAL DESIGN, INC.  
IS AN EQUAL OPPORTUNITY AFFIRMATIVE  
EMPLOYER.

**WEAVER**  
HOMES  
350 Wagoner Drive • Fayetteville, NC 28303  
910.602.2100 • 800.892.2190  
www.weaver-homes.com

PRICES, PROMOTIONS, INCENTIVES, FEATURES, OPTIONS,  
FLOOR PLANS, ELEVATIONS, FINISHING MATERIALS AND  
DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE.  
SQUARE FOOTAGE AND DIMENSIONS ARE ESTIMATED AND  
BASED UPON FACTUAL CONSTRUCTION. ACTUAL FOOTING OF  
HOUSE ON LOT WILL BE DETERMINED BY THE SITE PLAN AND  
ZONING AND FLOOR PLANS AND ELEVATION REQUIREMENTS ARE  
ARTIST CONCEPTS. FLOOR PLANS ARE THE COPYRIGHTED  
PROPERTY OF WEAVER HOMES AND USE, REPRODUCTION,  
ADAPTATION OR DISPLAY OF THE PLANS IS STRICTLY  
PROHIBITED. SEE NEW HOME SALES CONTRACT FOR  
CURRENT DETAILS. COPYRIGHT © 2019 WEAVER HOMES


**WEAVER HOMES**  
CAROLINA COLLECTION  
MAGNOLIA-II DRIVE LEFT

DATE: FEBRUARY 19, 2021  
REV.  
SCALE: 1/8" = 1'-0"  
DRAWN BY: WJG  
ENGINEERED BY:  
REVIEWED BY:

ATTIC FLOOR  
FRAMING PLAN  
S-3



**ELEVATION C**




2 X 6 RAFTERS @ 16" O.C. NOTE: NOT TO SCALE. COVERED PORCH ON OPT. FAMILY ROOM

**ATTIC VENT CALCULATION:**  
 100 SQ. FT. OF ATTIC DIVIDED BY 150 REQUIRES 0.7 SQ. FT. OF NET FREE VENTILATING AREA (MIN.).

(COVERED PORCH (PATIO STD.))

**ATTIC VENT CALCULATION:**  
 1250 SQ. FT. OF ATTIC DIVIDED BY 150 REQUIRES 8.3 SQ. FT. OF NET FREE VENTILATING AREA (MIN.).

- STRUCTURAL NOTES:**
1. ALL TRIMMING LUMBER TO BE #2 SPF (UNCO).
  2. HIP BRACES ARE TO BE SPACED A MIN. OF 8'-0" MULTS @ 16" O.C. (TYP).
  3. STICK FRAME OVER-FRAMED ROOF SECTIONS WITH 2 X 6 RAFTERS @ 16" O.C. (TYP).
  4. WITH SHEARON H/24 HURRICANE TIES @ 24" FASTEN FLAT WALLS TO RAFTERS OR TRUSSES.
  5. REFER TO SECTION R802.11 OF THE 2018 IRC FOR REQUIRED UPLIFT RESISTANCE AT RAFTERS AND TRUSSES.



**RENAISSANCE**  
 RESIDENTIAL DESIGN, INC.  
 RALEIGH, NC 27612  
 WWW.RENDESIGN.COM


**WEAVER HOMES**  
 350 Wagoner Drive Fayetteville, NC 28303  
 910.601.0100 • Fax: 910.212.9100  
 www.weaver-homes.com

PRICES, PROMOTIONS, INCENTIVES, FEATURES, OPTIONS, FLOOR PLANS, AND SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. SOME FOOTINGS AND DIMENSIONS ARE ESTIMATED AND NOT TO SCALE. CONSTRUCTION ACTUAL POSITION OF HOUSE ON LOT WILL BE DETERMINED BY THE SITE PLAN AND FIELD PLAN. FLOOR PLANS AND ELEVATIONS REPRESENT THE ARTIST CONCEPTUAL FLOOR PLANS AND ARE THE COPYRIGHTED PROPERTY OF WEAVER HOMES. ANY USE, REPRODUCTION, ADAPTATION OR DISPLAY OF THE PLANS IS STRICTLY PROHIBITED. SEE HOW HOMES ONLINE WITH THE CURRENT DETAILS. COPYRIGHT © 2018 WEAVER HOMES


**WEAVER HOMES**  
 CAROLINA COLLECTION  
 MAGNOLIA-II DRIVE LEFT

DATE: FEBRUARY 19, 2018  
 SCALE: 1/4" = 1'-0"  
 DRAWN BY: WFT  
 ENGINEERED BY:  
 REVIEWED BY:


ROOF PLAN  
 ELEVATION - C  
 S4



**WALL SECTION W/ SLAB  
W/ STD. SIDING SHOWN (NTS)**



**WALL SECTION W/ CRAWL SPACE  
W/ STD. SIDING SHOWN (NTS)**



**RENAISSANCE**  
RESIDENTIAL DESIGN, INC.  
WALTON, NC 27157  
(919) 844-1212  
WWW.RENAISSANCEDSIGN.COM

THESE ARCHITECTURAL DRAWINGS ARE THE PROPERTY OF RENAISSANCE RESIDENTIAL DESIGN, INC. AND ARE NOT TO BE REPRODUCED, COPIED, OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE WRITTEN PERMISSION OF RENAISSANCE RESIDENTIAL DESIGN, INC. ANY UNAUTHORIZED USE OF THESE DRAWINGS IS STRICTLY PROHIBITED AND WILL BE PROSECUTED TO THE FULL EXTENT OF THE LAW.


**WEAVER**  
HOMES  
350 Wagoner Drive • Fayetteville, NC 28303  
910.670.2100 • 800.862.2100  
www.weaverhomes.com

PRICES, PROMOTIONS, INCENTIVES, FEATURES, OPTIONS, FLOOR PLANS, MATERIALS, FINISHES, MATERIALS AND DIMENSIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE. SQUARE FOOTAGE AND DIMENSIONS ARE ESTIMATED AND MAY VARY IN ACTUAL CONSTRUCTION. ACTUAL POSITION OF HOUSE OR LOT WILL BE DETERMINED BY THE SITE PLAN AND PLOT PLAN. ALL DIMENSIONS AND RELATIONS REFER TO THE CENTER OF GRAVITY UNLESS OTHERWISE SPECIFIED. THE ABOVE CONSTRUCTION FLOOR PLANS ARE THE COPYRIGHTED PROPERTY OF WEAVER HOMES. ANY USE, REPRODUCTION, ADAPTATION OR COPIY OF THE PLANS IS STRICTLY PROHIBITED. SEE NEW HOME SELLER'S GUIDE FOR CURRENT DETAILS. COPYRIGHT © 2020 WEAVER HOMES

**WEAVER HOMES**  
CAROLINA COLLECTION  
MAGNOLIA-II DRIVE LEFT

DATE: FEBRUARY 19, 2021  
REV.  
SCALE: 1/4" = 1'-0"  
DRAWN BY: WFT  
ENGINEERED BY:  
REVIEWED BY:  
TYPICAL WALL SECTIONS  
D-1





### Truss Placement Plan SCALE: NTS

▲ = Denotes Left End of Truss  
(Reference Engineered Truss Drawing)

All Truss Reactions are Less  
than 3,000 lbs. Unless Noted Otherwise.

○ -- Denotes Reaction Greater than 3,000 lbs.  
Reaction / # of Studs

Connector Information				Nail Information		
Sym	Product	Manuf	Qty	Supported Member	Header	Truss
●	HUS410	USP	10	NA	16d/3-1/2"	16d/3-1/2"
●	THD410	USP	7	NA	16d/3-1/2"	10d/3"

Products					
PlotID	Length	Product	Plies	Net Qty	Fab Type
GDH (Dropped)	20' 0"	1-3/4"x 11-7/8" LVL Kerto-S	2	2	FF
BM1 (Flush)	15' 0"	1-3/4"x 16" LVL Kerto-S	2	2	FF
BM2 (Flush)	11' 0"	1-3/4"x 16" LVL Kerto-S	2	2	FF

#### LOAD CHART FOR JACK STUDS

LOAD REACTION (UP TO 10' SPAN)	MEMBER SIZE	LOAD REACTION (UP TO 10' SPAN)	MEMBER SIZE
1700	1	2550	1
3400	2	5100	2
5100	3	7650	3
6800	4	10200	4
8500	5	12750	5
10200	6	15300	6
11900	7		
13600	8		
15300	9		


BUILDER	Weaver Development	CITY / CO.	Lillington / Harnett
JOB NAME	Lot 4 Hales Farm	ADDRESS	NC 27 West
PLAN	Magnolia II "C"	MODEL	Floor
SEAL DATE	Seal Date	DATE REV.	/ /
QUOTE #	Quote #	DRAWN BY	Christine Shivy
JOB #	J0822-4191	SALES REP.	Lenny Norris

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSH-B1 and BCSH-B3 provided with the truss delivery package or online @ sbcindustry.com

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature Christine Shivy  
Christine Shivy

**comtech**  
ROOF & FLOOR  
TRUSSES & BEAMS  
Reilly Road Industrial Park  
Fayetteville, N.C. 28309  
Phone: (910) 864-8787  
Fax: (910) 864-4444



### Truss Placement Plan SCALE: NTS

▲ = Denotes Left End of Truss  
(Reference Engineered Truss Drawing)

All Truss Reactions are Less than 3,000 lbs. Unless Noted Otherwise.

○ -- Denotes Reaction Greater than 3,000 lbs. Reaction / # of Studs

Connector Information				Nail Information		
Sym	Product	Manuf	Qty	Supported Member	Header	Truss
●	HUS410	USP	10	NA	16d/3-1/2"	16d/3-1/2"
●	THD410	USP	7	NA	16d/3-1/2"	10d/3"

Products					
PlotID	Length	Product	Plies	Net Qty	Fab Type
GDH (Dropped)	20' 0"	1-3/4"x 11-7/8" LVL Kerto-S	2	2	FF
BM1 (Flush)	15' 0"	1-3/4"x 16" LVL Kerto-S	2	2	FF
BM2 (Flush)	11' 0"	1-3/4"x 16" LVL Kerto-S	2	2	FF

**LOAD CHART FOR JACK STUDS**

IRIS ACTION (UP TO 1000 LBS)	IRIS ACTION (UP TO 2000 LBS)	IRIS ACTION (UP TO 3000 LBS)
1700 1	2550 1	3400 1
3400 2	5100 2	6500 2
5100 3	7650 3	10500 3
6800 4	13200 4	13500 4
8500 5	12750 5	17000 5
10200 6	15300 6	
11900 7		
13600 8		
15300 9		

BUILDER	Weaver Development	CITY / CO.	Lillington / Harnett
JOB NAME	Lot 4 Hales Farm	ADDRESS	NC 27 West
PLAN	Magnolia II "C"	MODEL	Floor
SEAL DATE	Seal Date	DATE REV.	/ /
QUOTE #	Quote #	DRAWN BY	Christine Shivy
JOB #	J0822-4191	SALES REP.	Lenny Norris


THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSH-B1 and BCSH-B3 provided with the truss delivery package or online @ sbcindustry.com

Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.

Signature: Christine Shivy  
Christine Shivy

**ROOF & FLOOR TRUSSES & BEAMS**  
Reilly Road Industrial Park  
Fayetteville, N.C. 28309  
Phone: (910) 864-8787  
Fax: (910) 864-4444






Connector Information					Nail Information	
Sym	Product	Manuf	Qty	Supported Member	Header	Truss
■	JUS24	USP	7	NA	10d/3"	10d/3"

▲ = Denotes Left End of Truss  
(Reference Engineered Truss Drawing)

### Truss Placement Plan SCALE: NTS



All Truss Reactions are Less than 3,000 lbs. Unless Noted Otherwise.  
-- Denotes Reaction Greater than 3,000 lbs. Reaction / # of Studs


#### LOAD CHART FOR JACK STUDS

REACTION (LBS)	SPACING (IN)	NO. OF STUDS	REACTION (LBS)	SPACING (IN)	NO. OF STUDS
1700	1	2550	1	3400	1
3400	2	5100	2	6500	2
5100	3	7650	3	10000	3
6800	4	10200	4	13500	4
8500	5	12750	5	17000	5
10200	6	15300	6		
11900	7				
13600	8				
15300	9				

BUILDER	Weaver Development	CITY / CO.	Lillington / Harnett
JOB NAME	Lot 4 Hales Farm	ADDRESS	NC 27 West
PLAN	Magnolia II "C"	MODEL	Roof
SEAL DATE	Seal Date	DATE REV.	/ /
QUOTE #		DRAWN BY	Christine Shivy
JOB #	J0822-4190	SALES REP.	Lenny Norris

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSH-B1 and BCSH-B3 provided with the truss delivery package or online @ sbcindustry.com	
Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.	
Signature	<u>Christine Shivy</u> Christine Shivy


<b>ROOF &amp; FLOOR TRUSSES &amp; BEAMS</b>	
Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444	



Connector Information					Nail Information	
Sym	Product	Manuf	Qty	Supported Member	Header	Truss
■	JUS24	USP	7	NA	10d/3"	10d/3"

▲ = Denotes Left End of Truss  
(Reference Engineered Truss Drawing)

### Truss Placement Plan SCALE: NTS



-- Denotes Reaction Greater than 3,000 lbs.  
Reaction / # of Studs

All Truss Reactions are Less than 3,000 lbs. Unless Noted Otherwise.

#### LOAD CHART FOR JACK STUDS

MEMBER SIZE (L x W)	SPACING (ft)	MAX. LOAD (lbs)
1700	1	2550
3400	2	5100
5100	3	7650
6800	4	10200
8500	5	12750
10200	6	15300
11900	7	
13600	8	
15300	9	

BUILDER	Weaver Development	CITY / CO.	Lillington / Harnett
JOB NAME	Lot 4 Hales Farm	ADDRESS	NC 27 West
PLAN	Magnolia II "C"	MODEL	Roof
SEAL DATE	Seal Date	DATE REV.	/ /
QUOTE #		DRAWN BY	Christine Shivy
JOB #	J0822-4190	SALES REP.	Lenny Norris



THIS IS A TRUSS PLACEMENT DIAGRAM ONLY. These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the truss support structure including headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult BCSH-B1 and BCSH-B3 provided with the truss delivery package or online @ sbcindustry.com	
Bearing reactions less than or equal to 3000# are deemed to comply with the prescriptive Code requirements. The contractor shall refer to the attached Tables (derived from the prescriptive Code requirements) to determine the minimum foundation size and number of wood studs required to support reactions greater than 3000# but not greater than 15000#. A registered design professional shall be retained to design the support system for any reaction that exceeds those specified in the attached Tables. A registered design professional shall be retained to design the support system for all reactions that exceed 15000#.	
Signature	<u>Christine Shivy</u> Christine Shivy

<b>ROOF &amp; FLOOR TRUSSES &amp; BEAMS</b>	
Reilly Road Industrial Park Fayetteville, N.C. 28309 Phone: (910) 864-8787 Fax: (910) 864-4444	



**BM1 Kerto-S LVL 1.750" X 16.000" 2-Ply - PASSED**

Level: Level



**Member Information**

Type:	Girder
Plies:	2
Moisture Condition:	Dry
Deflection LL:	480
Deflection TL:	360
Importance:	Normal - II
Temperature:	Temp <= 100°F

Application:	Floor
Design Method:	ASD
Building Code:	IBC/IRC 2015
Load Sharing:	No
Deck:	Not Checked

**Reactions UNPATTERNED Ib (Uplift)**

Brg	Direction	Live	Dead	Snow	Wind	Const
1	Vertical	296	4522	577	0	0
2	Vertical	298	4548	580	0	0

**Bearings**

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - Hanger	3.000"	Vert	59%	4522 / 655	5177	L	D+0.75(L+S)
2 - SPF	3.500"	Vert	100%	4548 / 658	5206	L	D+0.75(L+S)

**Analysis Results**

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	15931 ft-lb	7'4 3/4"	31109 ft-lb	0.512 (51%)	D	Uniform
Unbraced	18237 ft-lb	7'4 3/4"	18273 ft-lb	0.998 (100%)	D+0.75(L+S) L	
Shear	3695 lb	1'7"	10752 lb	0.344 (34%)	D	Uniform
LL Defl inch	0.041 (L/4231)	7'4 13/16"	0.361 (L/480)	0.113 (11%)	0.75(L+S) L	
TL Defl inch	0.324 (L/535)	7'4 13/16"	0.481 (L/360)	0.673 (67%)	D+0.75(L+S) L	

**Design Notes**

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Fasten all plies using 3 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 3 Refer to last page of calculations for fasteners required for specified loads.
- 4 Fill all hanger nailing holes.
- 5 Girders are designed to be supported on the bottom edge only.
- 6 Top loads must be supported equally by all plies.
- 7 Top must be laterally braced at a maximum of 6'5 1/8" o.c.
- 8 Bottom must be laterally braced at end bearings.
- 9 Lateral slenderness ratio based on single ply width.

ID	Load Type	Location	Trib Width	Side	Dead 0.9	Live 1	Snow 1.15	Wind 1.6	Const. 1.25	Comments
1	Uniform			Top	125 PLF	0 PLF	0 PLF	0 PLF	0 PLF	Exterior Wall
2	Uniform			Near Face	78 PLF	0 PLF	78 PLF	0 PLF	0 PLF	M1
3	Uniform			Far Face	15 PLF	40 PLF	0 PLF	0 PLF	0 PLF	Floor Load

Continued on page 2...

**Notes**

Calculated Structural Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 11/3/2024

**Manufacturer Info**


Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
[www.metsawood.com/us](http://www.metsawood.com/us)

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS



**BM1 Kerto-S LVL 1.750" X 16.000" 2-Ply - PASSED**

Level: Level



...Continued from page 1

ID	Load Type	Location	Trib Width	Side	Dead 0.9	Live 1	Snow 1.15	Wind 1.6	Const. 1.25	Comments
4	Uniform			Top	130 PLF	0 PLF	0 PLF	0 PLF	0 PLF	Exterior Load
5	Uniform			Top	251 PLF	0 PLF	0 PLF	0 PLF	0 PLF	A1GE
	Self Weight				12 PLF					

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 11/3/2024

**Manufacturer Info**

Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
[www.metsawood.com/us](http://www.metsawood.com/us)

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS






Client: Weaver Development  
 Project: Magnolia-II Elev. C  
 Address: Magnolia-II Elev. C

Date: 4/13/2022  
 Input by: Christine Shivy  
 Job Name: Magnolia-II Elev. C  
 Project #:

**BM2 Kerto-S LVL 1.750" X 16.000" 2-Ply - PASSED**

Level: Level



**Member Information**

Type:	Girder	Application:	Floor
Plies:	2	Design Method:	ASD
Moisture Condition:	Dry	Building Code:	IBC/IRC 2015
Deflection LL:	480	Load Sharing:	No
Deflection TL:	360	Deck:	Not Checked
Importance:	Normal - II		
Temperature:	Temp <= 100°F		

**Reactions UNPATTERNED lb (Uplift)**

Brg	Direction	Live	Dead	Snow	Wind	Const
1	Vertical	3389	1200	0	0	0
2	Vertical	3389	1200	0	0	0

**Bearings**

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF	3.500"	Vert	88%	1200 / 3389	4589	L	D+L
2 - SPF	3.500"	Vert	88%	1200 / 3389	4589	L	D+L

**Analysis Results**

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	11397 ft-lb	5'4 3/4"	34565 ft-lb	0.330 (33%)	D+L	L
Unbraced	11397 ft-lb	5'4 3/4"	11764 ft-lb	0.969 (97%)	D+L	L
Shear	4341 lb	1'7 1/2"	11947 lb	0.363 (36%)	D+L	L
LL Defl inch	0.085 (L/1457)	5'4 3/4"	0.259 (L/480)	0.329 (33%)	L	L
TL Defl inch	0.115 (L/1076)	5'4 3/4"	0.345 (L/360)	0.335 (33%)	D+L	L

**Design Notes**

- 1 Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- 2 Fasten all plies using 3 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- 3 Refer to last page of calculations for fasteners required for specified loads.
- 4 Girders are designed to be supported on the bottom edge only.
- 5 Top must be laterally braced at end bearings.
- 6 Bottom must be laterally braced at end bearings.
- 7 Lateral slenderness ratio based on single ply width.

ID	Load Type	Location	Trib Width	Side	Dead 0.9	Live 1	Snow 1.15	Wind 1.6	Const. 1.25	Comments
1	Uniform			Far Face	89 PLF	267 PLF	0 PLF	0 PLF	0 PLF	F4
2	Uniform			Near Face	121 PLF	361 PLF	0 PLF	0 PLF	0 PLF	F2
	Self Weight				12 PLF					

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

1. Dry service conditions, unless noted otherwise
2. LVL not to be treated with fire retardant or corrosive

chemicals

**Handling & Installation**

1. LVL beams must not be cut or drilled
2. Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
3. Damaged Beams must not be used
4. Design assumes top edge is laterally restrained
5. Provide lateral support at bearing points to avoid lateral displacement and rotation

6. For flat roofs provide proper drainage to prevent ponding

This design is valid until 11/3/2024

**Manufacturer Info**

Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
[www.metsawood.com/us](http://www.metsawood.com/us)

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS








Client: Weaver Development  
 Project: Magnolia-II Elev. C  
 Address: Magnolia-II Elev. C

Date: 4/13/2022  
 Input by: Christine Shivy  
 Job Name: Magnolia-II Elev. C  
 Project #:

**GDH Kerto-S LVL 1.750" X 11.875" 2-Ply - PASSED**

Level: Level



**Member Information**

Type:	Girder	Application:	Floor
Plies:	2	Design Method:	ASD
Moisture Condition:	Dry	Building Code:	IBC/IRC 2015
Deflection LL:	480	Load Sharing:	No
Deflection TL:	360	Deck:	Not Checked
Importance:	Normal - II		
Temperature:	Temp <= 100°F		

**Reactions UNPATTERNED lb (Uplift)**

Brg	Direction	Live	Dead	Snow	Wind	Const
1	Vertical	0	2098	337	0	0
2	Vertical	0	2098	337	0	0

**Bearings**

Bearing	Length	Dir.	Cap.	React D/L lb	Total	Ld. Case	Ld. Comb.
1 - SPF End Grain	3.500"	Vert	24%	2098 / 337	2434	L	D+S
2 - SPF End Grain	3.500"	Vert	24%	2098 / 337	2434	L	D+S

**Analysis Results**

Analysis	Actual	Location	Allowed	Capacity	Comb.	Case
Moment	8354 ft-lb	8'5"	17919 ft-lb	0.466 (47%)	D	Uniform
Unbraced	9694 ft-lb	8'5"	9704 ft-lb	0.999 (100%)	D+S	L
Shear	1788 lb	1'3 3/8"	7980 lb	0.224 (22%)	D	Uniform
LL Defl inch	0.070 (L/2809)	8'5 1/16"	0.409 (L/480)	0.171 (17%)	S	L
TL Defl inch	0.506 (L/388)	8'5 1/16"	0.546 (L/360)	0.927 (93%)	D+S	L

**Design Notes**

- Provide support to prevent lateral movement and rotation at the end bearings. Lateral support may also be required at the interior bearings by the building code.
- Fasten all plies using 2 rows of 10d Box nails (.128x3") at 12" o.c. Maximum end distance not to exceed 6".
- Refer to last page of calculations for fasteners required for specified loads.
- Girders are designed to be supported on the bottom edge only.
- Top loads must be supported equally by all plies.
- Top must be laterally braced at a maximum of 9'6 3/4" o.c.
- Bottom must be laterally braced at end bearings.
- Lateral slenderness ratio based on single ply width.

ID	Load Type	Location	Trib Width	Side	Dead 0.9	Live 1	Snow 1.15	Wind 1.6	Const. 1.25	Comments
1	Uniform			Top	200 PLF	0 PLF	0 PLF	0 PLF	0 PLF	Exterior Loads
2	Uniform			Top	40 PLF	0 PLF	40 PLF	0 PLF	0 PLF	2'-0" Gable End
	Self Weight				9 PLF					

**Notes**

Calculated Structured Designs is responsible only of the structural adequacy of this component based on the design criteria and loadings shown. It is the responsibility of the customer and/or the contractor to ensure the component suitability of the intended application, and to verify the dimensions and loads.

**Lumber**

- Dry service conditions, unless noted otherwise
- LVL not to be treated with fire retardant or corrosive chemicals

chemicals

**Handling & Installation**

- LVL beams must not be cut or drilled
- Refer to manufacturer's product information regarding installation requirements, multi-ply fastening details, beam strength values, and code approvals
- Damaged Beams must not be used
- Design assumes top edge is laterally restrained

- For flat roofs provide proper drainage to prevent ponding

This design is valid until 11/3/2024

**Manufacturer Info**

Metsä Wood  
 301 Merritt 7 Building, 2nd Floor  
 Norwalk, CT 06851  
 (800) 622-5850  
[www.metsawood.com/us](http://www.metsawood.com/us)

Comtech, Inc.  
 1001 S. Reilly Road, Suite #639  
 Fayetteville, NC  
 USA  
 28314  
 910-864-TRUS

