



TRUSSES TO BE DESIGNED AT 24" ON CENTER

TRUSS LAYOUT DIMENSIONS AT PULL DOWN ATTIC ACCESS

240-00 2-00-00

Truss Connector List				
QTY	PROD	VENDOR		
12	HUS26	SIMPSON		
1	LUS26	SIMPSON		
1	HUS28	SIMPSON		
2 Sets	TBE4	SIMPSON		



DEDICATED TO QUALITY AND EXCELLENCE 200 EMMETT ROAD DUNN, NORTH CAROLINA 28334 PHONE: 910-892-8400 FAX: 910-892-8384

181 BIRCHWOOD KB HOME	ay GOR	ORDER: 32273	SHIP DATE: 2022
	w/MB Tra	P.O. NUMBER: PO #	REV: 1/19/22
	.2723 "D"	SCALE	PRINT DATE: 7/12/22
CUSTOMER:	MODEL: 237.	SCALE: NOT TO S	DRAWN BY: JRH
		237.2723 "	KB HOME 237.2723 "D" w/MB Tray G(OT TO SCALE P.O. NUMBER: ORDER: ORDER

TOP LIVE: 20 PSF

TOP DEAD: 10 PSF

BOTM DEAD: 10 PSF

WIND SPD: 120 MPH

GENERAL NOTES:

DO NOT CUT OR MODIFY TRUSSES.

TRUSSES ARE SPACED 24" ON CENTER UNLESS NOTED OTHERWISE.

REFER TO THE INDIVIDUAL TRUSS DESIGN DRAWINGS FOR THE LOCATION OF LATERAL BRACING AND MULTI-PLY CONNECTION REQUIREMENTS.

PER ANSI TPI 1-2002 THE TRUSS ENGINEER IS RESPONSIBLE FOR TRUSS TO TRUSS CONNECTIONS AND TRUSS PLY TO PLY CONNECTIONS. THIS TRUSS PLACEMENT PLAN RECCOMENDS TRUSS TO BEARING CONNECTIONS AND TRUSS TO BEAM CONNECTIONS WHICH SHALL BE REVIEWED BY THE BUILDING DESIGNER. IT IS THE RESPONSIBILITY OF THE BUILDING DESIGNER TO RESOLVE ALL ROOF FORCES ADEQUATELY TO THE FOUNDATION.